

Spectral GNNs vs GATs

When attention is (not all you need) the "only" option

Jorge Luiz Franco

UNDERGRADUATE PROGRAM IN COMPUTER SCIENCE

Advisor: Prof. Filipe Alves Neto Verri, Ph.D.

Universidade de São Paulo - ICMC

June 17, 2024

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

Motivation

- Graph machine learning can be tracked backwards to the problem of ‘learning’ on data that is inherently a graph [4, 2] or can be modeled as a graph [6, 7]
- Variety of tasks: node/edge classification, link prediction, graph partitioning, which rely on learning representations from graph-structured data.
- Techniques were most developed by complex networks researchers.
- **Last decade:** significant shift towards the merging of three main communities: graph signal processing, deep learning and complex nets.

GraphML paradigms Overview

- Three main learning paradigms: supervised, unsupervised, and semi-supervised learning
- We are interested on the (semi-)supervised learning paradigm, which encompasses a variety of techniques designed to leverage learning to (partially-)labeled data [5, 1]
- Focus in the subset of graph elements (nodes, edges, graph structure) prediction(classification/regression) methods.
- Consider the division of the field into traditional graph learning: topological graph measures into tabular ML algorithms [3, 4], and deep graph learning

Introduction to Last-Mile Delivery Drones

Figure: Drones Congestion
in a high-traffic Last Mile
Delivery context.

Source: [?]



Introduction to Last-Mile Delivery Drones

Last Mile Delivery Drones (LMDD)

- Heterogeneous research area:
 - Combining drones and trucks.
 - Linear integer modeling.
 - Fuzzy logic for uncertainties.
 - Multi-objective optimization.
 - Exclusive drone-based solutions.
- **Complex Systems Decentralized Approach:**
 - Tradable permit model for multi-agent airspace use [?].

Related Work and Centralized Control

- **Necessity of Air Traffic Management:**
 - Most centralized models don't address collision avoidance [?].
 - Ensuring optimal path planning and efficient airspace control.
- **Centralized Control and UTM:**
 - **Centralized Control:**
 - Federal Aviation Administration (FAA) and NASA's Unmanned Aircraft System Traffic Management (UTM) [?].
 - Ensures organized, legislative-backed airspace control.
 - **Decentralized Models:**
 - Novel but complex in scalability and regulatory compliance.

Proposed Approach

- **Aispace Control and MAPF Approach:**
 - Multi-Agent Path Finding (MAPF) is a solution for addressing spatial characteristics and collision avoidance.
- **Proposed Strategy:**
 - Employing MAPF strategy for Last Mile Delivery Drone problem.
 - Three approaches: MILP, heuristic and hybrid.
 - Use of prioritized planning [?] and conflict-based search [?] to manage computational complexity in the heuristic.
 - Comparing the MILP with the heuristic.
 - Qualitative comparison between centralized and decentralized approaches.

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

LMDD as MAPF

- Tasks for each agent (drone) described by tuples:

$$\text{task}_i := \{(x_{\text{start}_i}, y_{\text{start}_i}), (x_{\text{goal}_i}, y_{\text{goal}_i})\}, \forall \text{ drone } d_i$$

- Grid bounds: $x \leq X, y \leq Y$.
- Goal: find paths P_{d_i} making the path length as short as possible.

Path Planning and Constraints

- Drones limited to four principal movements: upward $(x, y + 1)$, downward $(x, y - 1)$, rightward $(x + 1, y)$, and leftward $(x - 1, y)$.
- Adjacency: (x_1, y_1) is adjacent to $(x_2, y_2) \iff |x_2 - x_1| + |y_2 - y_1| = 1$.
- New decision variable: t_{begin} (arrival time).

LMDD Goals

- Given time T , minimize the sum of distances of all drones.
- Allow drones to wait in cells and choose entry time.
- Non-weighted distances make the problem easier than standard MAPF.

Network Flow Problem

- MAPF is equivalent to multi-commodity minimum cost maximum flow problem [?].
- Visualized as Network Flow problem.
- The number of drones is a max flow in the time-expanded net

MAPF as Network Flow Problem

- Transformation into a time-expanded network [?].





Figure: Time-expanded network representation (sourced from [?])

Multi-Commodity Flow Formulation

- Each drone is a separate commodity flowing from start to goal node.
- Ensuring each drone reaches its goal within a given time horizon T .




Figure: Equivalence of MAPF to multi-commodity network flow (sourced from [?])

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

MILP Model - Graph Modelling


- Proposal of a Mixed-Integer Linear Programming (MILP) model to solve the problem.
- Graph construction representing spatio-temporal permits shared by the drones.
- Modeled as a directed graph (digraph) $G = (V, A)$.
- V : set of nodes representing airspace and virtual drone locations.
- A : set of directed arcs representing permitted transitions between nodes.

MILP Model - Virtual Nodes

- Source node b_k : Starting point of drone k 's mission.
- Sink node e_k : Ending point of drone k 's mission.
- Focus on spatial topology, omitting temporal component.

Figure: Graph modelling.

Source: The authors.



MILP Model - Parameters

- T : Maximum time allowed for the mission.
- b_k : Initial virtual vertex representing the initial position of drone k .
- e_k : Final virtual vertex representing the final position of drone k .
- \mathcal{R} : Set of drones.
- \mathcal{G} : Digraph $(\mathcal{V}, \mathcal{A})$ representing the airspace.
- \mathcal{V} : Set of vertices of \mathcal{G} .
- $\mathcal{B} \subset \mathcal{V}$: Set of initial virtual vertices b_k .
- $\mathcal{E} \subset \mathcal{V}$: Set of final virtual vertices e_k .
- \mathcal{S} : Set $\mathcal{V} \setminus (\mathcal{B} \cup \mathcal{E})$.
- \mathcal{A} : Set of arcs $(i, j) \in \mathcal{A}$ of \mathcal{G} .

MILP Model - Variables

- Decision Variables:
 - $x_{i,j,t}^k = 1 \iff$ drone k jumps from i to j at time t .
- Indices:
 - k : Drone $\implies k \in \mathcal{R}$.
 - t : Time $\implies 1 \leq t \leq T$.
 - i, j, l : Vertices $\implies i, j, l \in \mathcal{V}$.

MILP Model - Objective Function

- Minimize the total sum of the number of drone movements:

$$\min \sum_{k \in \mathcal{R}} \sum_{t=1}^T \sum_{(i,j) \in \mathcal{A}: j \notin (\mathcal{E} \cup \mathcal{B})} x_{i,j,t}^k$$

- Minimize the total number of drone movements, counting $n - 1$ jumps for each drone that performs n jumps.

MILP Model - Constraints

- Ensure each drone starts its mission:

$$\sum_{t=1}^T \sum_{j \in \mathcal{S}} x_{b_k, j, t}^k = 1, \quad \forall k \in \mathcal{R}$$

- Flow conservation:

$$\sum_{j \in \mathcal{V}} x_{i, j, t-1}^k = \sum_{l \in \mathcal{V}} x_{j, l, t}^k, \quad \forall j \in \mathcal{V}, \forall k \in \mathcal{R}, \forall t \in \{2, \dots, T\}$$

MILP Model - Constraints (Cont.)

- Border condition at time $t = 0$:

$$x_{i,j,0}^k = \begin{cases} 1, & \text{if } i = b_k \wedge j = b_k, \\ 0, & \text{otherwise.} \end{cases} \quad \forall k \in \mathcal{R}, \forall (i,j) \in A$$

- Mutual exclusion of vertex occupation:

$$\sum_{k \in \mathcal{R}} \sum_{j \in \mathcal{V}} x_{i,j,t}^k \leq 1, \quad \forall j \in \mathcal{V}, \forall t \in \{1, \dots, T\}$$

MILP Model - Mission Accomplishment

- Ensure each drone completes its mission:

$$\sum_{t=1}^T \sum_{i \in \mathcal{S}} x_{i,e_k,t}^k \geq 1, \quad \forall k \in \mathcal{R}$$

Heuristic Approach

- Utilize distance measure as heuristic metric [?].
- Organize drones in ascending order (prioritized planning) based on start and end points.
- Employ iterative Breadth-First Search (BFS) on temporal graph.
- Dynamic constraints update of occupied positions (conflict-based search).
- Combine heuristic sorting and iterative BFS for efficient path planning and adaptability.

Algorithm Notation

Table: Notation used in the Algorithm.

Notation	Definition
\mathcal{V}	Set of vertices in the graph : (i, j, t)
\mathcal{E}	Set of edges
\mathcal{D}	Set of drones
\mathcal{S}	Set of already scheduled vertices
$\mathcal{P}_d \subseteq \mathcal{V}$	Path of drone d
$\mathcal{G} = (\mathcal{V}, \mathcal{E})$	Temporal Graph

Heuristic Algorithm Steps

- ① **Drones Sorting:** Ascending sort using Euclidean Distance.

$$\mathcal{D}_{\text{sorted}} = \text{sort}(\mathcal{D}, \text{heuristic}) \quad (1)$$

- ② **Path for Each Drone:** Compute path P_d using BFS on graph \mathcal{G} .


$$\forall d \in \mathcal{D}_{\text{sorted}} : \quad \mathcal{P}_d = \text{BFS}(\mathcal{G}, d) \quad (2)$$

- ③ **Constraints Update:** Update set of already scheduled vertices \mathcal{S} .

$$\mathcal{S} = \mathcal{S} \cup \bigcup_{d \in \mathcal{D}_{\text{sorted}}} \mathcal{P}_d \quad (3)$$


Algorithm Visualization

Figure: Algorithm visualization.
Source: The authors.



Complexity Analysis and Boundedness

- Worst-case complexity: $\mathcal{O}((N + M)KNM \log((N + M)KNM))$.
- Approximation: $\mathcal{O}(N^3 K \log(N^3 K))$ for square grids.



Hybrid Methodology

- **Heuristic Solution Generation**

- Quickly generates an initial feasible solution.
- Determines a plausible time horizon $T_{\text{heuristic}}$.

- **MILP Model Refinement**

- Uses $T_{\text{heuristic}}$ and initial feasible solution from heuristic.
- Refines the solution to ensure global optimality.

- **Advantages**

- Combines computational speed with solution accuracy.
- Skips multiple iterations to determine T , reducing computational expense.

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

Results




Figure: Exact Model Objective. Source: The authors.

Results




Figure: Heuristic Objective. Source: The authors.

Results




Figure: Heuristic Routing Time (T) corresponding to Figure ???. Source: The authors.

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

Conclusion

Advancements


- Addressing the Last Mile Delivery Drones problem through a MAPF approach ;
- Ensuring collision avoidance and efficient airspace control.
- Significant advancement over previous algorithms with guaranteed finite and bounded polynomial time convergence for the heuristic

Limitations

- Does not address real world problems like energy, fuel and speed of the drones;
- The experiment using binary search to find the T for the MILP in $\mathcal{O}(\log(T))$ is not conducted;
- Small grid sizes in experiments;

Future Works

Figure: Tradable Permit Model in the Decentralized LMDD.
Source: [?]



Future Works

Decentralized Model from [?]

- naive agents
- greedy random choices

Decentralized Model with Intelligence

- Reinforcement Learning
- Graph Dynamical System
 - Complex Networks
 - Graph Neural Networks

Summary

Introduction

Problem Description

Materials and Methods

Results

Conclusion and Future Works

References

References I

-  D. R. AMANCIO, C. H. COMIN, D. CASANOVA, G. TRAVIESO, O. M. BRUNO, F. A. RODRIGUES, AND L. DA FONTOURA COSTA, *A systematic comparison of supervised classifiers*, PLOS ONE, 9 (2014), pp. 1–14.
-  I. CHAMI, S. ABU-EL-HAIJA, B. PEROZZI, C. RÂO, AND K. MURPHY, *Machine learning on graphs: A model and comprehensive taxonomy*, Journal of Machine Learning Research, 23 (2022), pp. 1–64.
-  L. D. F. COSTA, *Characterization of complex networks: A survey of measurements*, Advances in physics, 56 (2007), pp. 167–242.
-  T. SILVA AND L. ZHAO, *Machine Learning in Complex Networks*, Springer International Publishing, 2016.

References II

-  F. A. N. VERRI, P. R. UARIO, AND L. ZHAO, *Advantages of edge-centric collective dynamics in machine learning tasks*, Journal of Applied Nonlinear Dynamics, 7 (2018), pp. 269–285.
-  F. A. N. VERRI AND L. ZHAO, *High level data classification based on network entropy*, in The 2013 International Joint Conference on Neural Networks (IJCNN), 2013, pp. 1–5.
-  J. YOU, X. MA, Y. DING, M. J. KOCHENDERFER, AND J. LESKOVEC, *Handling missing data with graph representation learning*, Advances in Neural Information Processing Systems, 33 (2020), pp. 19075–19087.