Status	Finished
Started	Sunday, 11 October 2026, 6:31 PM
Completed	Sunday, 11 October 2026, 6:39 PM
Duration	8 mins 21 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3,3,2,1)

b. (1,2,3)(4,5,6)

c. Error

d. (1,2,3,4,5,6) ✓

Question **2**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. 2

b. 117 ✓

c. 100

d. Error

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

- a. i,iii ✓
- b. iii,iv
- c. ii,iv
- d. i,ii

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

- a. {0,0,9}
- b. {9}
- c. {0,9} ✓
- d. It will throw an error as there are two 0 while creating the set.

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

c. Name Error

d. TypeError: update() doesn't allow list as a argument.

Question **6**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,1}

b. {}

c. {3} ✓

d. {2,5,3,1}

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. (12)

b. Error ✓

c. 12

d. (55,78,64,25)

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. (3,14,25)

b. Error

c. (58,47,36,25)

d. (36, 25, 14) ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Error

b. Computer

c. () ✓

d. (Computer)

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following is a Python tuple?

- a. (1,4,5,6,7) ✓
- b. [1,2,3,4]
- c. {1,3,8,9,41}
- d. ("Wonder")

Question **11**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

- a. True
- b. Error
- c. False ✓
- d. Error

Question **12**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

- a. None of these
- b. A tuple maintains the order of items ✓
- c. We can change the tuple once created
- d. A tuple is unordered

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

- a. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓
- b. (30, 40, 50)(40, 50, 60, 70, 80)
- c. (10, 20, 30, 40) (40, 50, 60, 70, 80)
- d. (30, 40, 50) (10, 20, 30, 40)

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

- a. tupl.append(2)
- b. tupl.sort()
- c. tupl[1]=2
- d. tupl1=tupl+tupl ✓

Question **15**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (55, 44, 33, 22, 11)
x = [t1[i] for i in range(0, len(t1), 2)]
print(x)
```

- a. [(55,33,11)]
- b. [55, 33, 11] ✓
- c. ([55,33,11])
- d. (55,33,11)