

Bar Bending Schedule (BBS) Report

Generated on 05-May-2026 06:29 | Element: **Beam** | Standards: IS 456:2000, IS 2502:1963

1. Input Parameters

Parameter	Value	Parameter	Value
Element	beam	Width (mm)	300
Depth (mm)	450	Length (mm)	6000
Cover (mm)	25	Main Bar Dia (mm)	16
Main Bar Qty	4	Stirrup Dia (mm)	8
Stirrup Spacing (mm)	150	Hook Type	135°
Lap Length (mm)	0		

2. Bar Bending Schedule

Bar Mark	Description	Dia (mm)	Shape	Cutting Len (mm)	Qty	Total Len (m)	Unit Wt (kg/m)	Total Wt (kg)
M1	Main Bar (Beam)	16.0	Straight w/ hooks	6270.0	4	25.08	1.58	39.63
S1	Stirrup / Tie	8.0	Rect. closed (135° hook)	1332.0	40	53.28	0.395	21.05
TOTAL						78.36		60.68

3. Final Steel Order (with 5% wastage, 12 m rods)

Dia (mm)	Net Length (m)	Net Weight (kg)	Wastage %	Order Length (m)	Order Weight (kg)	12 m Rods
8.0	53.28	21.05	5%	55.94	22.1	5
16.0	25.08	39.63	5%	26.33	41.61	3
GRAND TOTAL				82.28	63.71	

This report is auto-generated. Verify against site drawings before fabrication. Hook lengths and bend deductions follow IS 2502.