

Bar Bending Schedule (BBS) Report

Generated on 05-May-2026 07:44 | Element: **Column** | Standards: IS 456:2000, IS 2502:1963

1. Input Parameters

Parameter	Value	Parameter	Value
Element	Column	Width (mm)	300
Depth (mm)	300	Height (mm)	3000
Cover (mm)	40	Main Bar Dia (mm)	20
Main Bar Qty	6	Lateral Tie Dia (mm)	8
Lateral Tie Spacing (mm)	200	Hook Type	135°
Lap Length (mm)	0		

2. Bar Bending Schedule

Bar Mark	Element	Description	Dia (mm)	Shape	Cutting Len (mm)	Qty	Total Len (m)	Unit Wt (kg/m)	Total Wt (kg)
M1	Column	Main Vertical Bar	20.0	Straight w/ lap	3920.0	6	23.52	2.469	58.07
T1	Column	Lateral Tie	8.0	Rect. closed (135° hook)	976.0	16	15.616	0.395	6.17
TOTAL							39.14		64.24

3. Final Steel Order (with 5% wastage, 12 m rods)

Dia (mm)	Net Length (m)	Net Weight (kg)	Wastage %	Order Length (m)	Order Weight (kg)	12 m Rods
8.0	15.62	6.17	5%	16.4	6.48	2
20.0	23.52	58.07	5%	24.7	60.97	3
GRAND TOTAL				41.1	67.45	

✓ **Engineering Verified** — Independent recalculation of total_length & weight per row passed.

This report is auto-generated. Verify against site drawings before fabrication. Hook lengths and bend deductions follow IS 2502.