



Little Piplup

Contest Teamnote
ICPC 2019 Internet Preliminary ver



Little Piplup

Gratus907(Wonseok Shin), Coffeetea(Jinje Han), DHdroid(Donghyun Son)

Contents

1 Settings	3	4.1 CCW	8	7.1.2 Knuth Optimization	16
1.1 C++	3	4.2 Point in polygon	8	7.2 Longest Increasing Subsequence	17
2 Data Structures	3	4.3 Length of Segment Union	8	7.3 Largest Sum Subarray	17
2.1 Segment Tree - Range Minimum	3	4.4 Closest Pair Problem	9	7.4 0-1 Knapsack	18
2.2 Segment Tree Lazy Propagation	3	4.5 Convex Hull (Graham Scan)	9	7.5 Longest Common Subsequence	18
2.3 Fenwick Tree	4	4.6 Intersection of Line Segment	11	7.6 Edit Distance	18
2.4 Disjoint Set Union (Union - Find)	5				
3 Mathematics	5	5 Graphs	11	8 String	19
3.1 Useful Mathematical Formula	5	5.1 Topological Sorting	11	8.1 KMP Algorithm	19
3.2 Binomial Coefficient	5	5.2 Lowest Common Ancestor	11	8.2 Manacher's Algorithm	19
3.3 Extended Euclidean Algorithm	6	5.3 MST Kruskal Algorithm	12	8.3 Trie	19
3.4 Fast Modulo Exponentiation	6	5.4 MST Prim Algorithm	12	8.4 Rabin-Karp Hashing	20
3.5 Modular Multiplicative Inverse	6	5.5 Dinic's Algorithm	13		
3.6 Miller-Rabin Primality Testing	6				
3.7 Pollard-Rho Factorization	7	6 Shortest Path	14	9 Miscellaneous	21
3.8 Euler Totient	7	6.1 Dijkstra	14	9.1 Binary and Ternary Search	21
3.9 Fast Fourier Transform	7	6.2 Bellman Ford	14	9.2 GCC Order Statistics Tree	21
4 Geometry	8	6.3 SPFA Algorithm	15	9.3 Useful Bitwise Functions in C++	21
		6.4 Floyd-Warshall	15	9.4 Prime numbers	21
				9.5 Time Complexity of Algorithms	22
		7 Dynamic	16	10 Checkpoints	23
		7.1 다이나믹 프로그래밍 최적화 기법	16	10.1 Debugging	23
		7.1.1 Convex Hull Trick	16	10.2 Thinking	23

1 Settings

1.1 C++

```
#include <bits/stdc++.h>
#pragma GCC optimize("O3")
#pragma GCC optimize("Ofast")
#pragma GCC target("avx,avx2,fma")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,tune=native")
#pragma GCC optimize("unroll-loops")
#define ll long long
#define eps 1e-7
#define all(x) ((x).begin()),((x).end())
#define usecppio ios::sync_with_stdio(0);cin.tie(0);cout.tie(0);
using namespace std;
using pii = pair<int, int>;
```

2 Data Structures

2.1 Segment Tree - Range Minimum

Range minimum, 0-based data.

```
struct Range_Minimum_Tree
{
    int n;
    vector<int> segtree;

    Range_Minimum_Tree(const vector<int> &data)
    {
        n = data.size();
        segtree.resize(4 * n);
        initialize(data, 0, n - 1, 1);
    }

    int initialize(const vector<int> &data, int l, int r, int node)
    {
        if (l == r)
            return segtree[node] = data[l];
        int mid = (l + r) / 2;
        int lmin = initialize(data, l, mid, node * 2);
        int rmin = initialize(data, mid + 1, r, node * 2 + 1);
        return segtree[node] = min(lmin, rmin);
    }
}
```

```
int minq(int l, int r, int node, int nodeleft, int noderight)
{
    if (r < nodeleft || noderight < l)
        return INT_MAX;
    if (l <= nodeleft && noderight <= r)
        return segtree[node];
    int mid = (nodeleft + noderight) / 2;
    return min(minq(l,r,node*2,nodeleft,mid),
               minq(l,r,node*2+1,mid+1,noderight));
}
```

2.2 Segment Tree Lazy Propagation

Lazy Propagation (Segment constant addition), 0-based data.

```
struct SegTree
{
    int n;
    vector <int> segtree;
    vector <int> lazy;

    SegTree()
    {
        n = 0;
    }

    SegTree(vector <int> &data)
    {
        n = data.size();
        segtree.resize(4*n);
        lazy.resize(4*n);
        init(data,1,0,n-1);
    }

    int init(vector <int> &data, int node, int l, int r)
    {
        if (l==r)
        {
            segtree[node] = data[l];
            return segtree[node];
        }
        int mid = (l+r)/2;
```

```

int ls = init(data,node*2,l,mid);
int rs = init(data,node*2+1,mid+1,r);
segtree[node] = (ls+rs);
return segtree[node];
}

void propagation(int node, int nl, int nr)
{
    if (lazy[node] != 0)
    {
        segtree[node] += (lazy[node] * (nr-nl+1));
        if (nl != nr)
        {
            lazy[node*2] += lazy[node];
            lazy[node*2+1] += lazy[node];
        }
        lazy[node] = 0;
    }
}

void range_upd(int s, int e, int k)
{
    return range_upd(s,e,k,1,0,n-1);
}

void range_upd(int s, int e, int k, int node, int nl, int nr)
{
    propagation(node,nl,nr);

    if (nr < s || nl > e)
        return;
    if (s <= nl && nr <= e)
    {
        lazy[node] += k;
        propagation(node,nl,nr);
        return;
    }
    int mid = (nl + nr)/2;
    range_upd(s,e,k,node*2,nl,mid);
    range_upd(s,e,k,node*2+1,mid+1,nr);
    segtree[node] = segtree[node*2] + segtree[node*2+1];
}

```

```

        return;
    }

    int sum(int s, int e)
    {
        return sum(s,e,1,0,n-1);
    }

    int sum(int s, int e, int node, int nl, int nr)
    {
        propagation(node,nl,nr);
        if (nr < s || nl > e)
            return 0;
        if (s <= nl && nr <= e)
        {
            return segtree[node];
        }
        int mid = (nl+nr)/2;
        return (sum(s,e,node*2,nl,mid) + sum(s,e,node*2+1,mid+1,nr));
    }
};

2.3 Fenwick Tree

struct Fenwick
{
    int n;
    int tree[MAXN];
    void init()
    {
        memset(tree,0,sizeof(tree));
    }
    int sum(int p)
    {
        int ret = 0;
        for (; p > 0; p -= p & -p)
            ret += tree[p];
        return ret;
    }
    void add (int p, int val)
    {
        for (; p <= n; p += p & -p)

```

```

        tree[p] += val;
    }
    void change (int p, int val)
    {
        int u = sum(p) - sum(p-1);
        add(p, val-u);
    }
}

```

2.4 Disjoint Set Union (Union - Find)

```

// Original Author : Ashishgup
struct Disjoint_Set_Union
{
    int parent[V], size[V];
    Disjoint_Set_Union(int N = V-1)
    {
        init(N);
    }
    void init(int N)
    {
        for(int i=1;i<=N;i++)
        {
            parent[i]=i;
            size[i]=1;
        }
    }
    int Find(int K)
    {
        while(K!=parent[K])
        {
            parent[K]=parent[parent[K]];
            K=parent[K];
        }
        return K;
    }
    int getSize(int K)
    {
        return size[Find(K)];
    }
    void unite(int x, int y)
    {

```

```

        int u=Find(x), v=Find(y);
        if(u==v)
            return;
        if(size[u]>size[v])
            swap(u, v);
        size[v]+=size[u];
        size[u] = 0;
        parent[u] = parent[v];
    }
} dsu;

```

3 Mathematics

3.1 Useful Mathematical Formula

- Catalan Number : Number of valid parentheses strings with n pairs

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

- Nim Game : Remember - XOR of all piles.
- Lucas Formula : $\binom{n}{m} \bmod p = \prod \binom{n_i}{m_i} \bmod p$
- Sum of divisors of n : About $n \log \log n$.
- 어떤 수열을 n 개의 증가하는 수열로 덮을 수 있다 \leftrightarrow longest decreasing subsequence 의 길이가 n 보다 작거나 같다. (Dilworth's Theorem)

3.2 Binomial Coefficient

If faster method is needed : use modulo inverse

```

int binomial(int n, int k)
{
    for (int i = 0; i <= n; ++i)
    {
        for (int j = 0; j <= min(i, k); ++j)
        {
            if (j == 0 || j == i)
                binom[i][j] = 1;
            else
                binom[i][j] = binom[i-1][j-1] + binom[i-1][j];
        }
    }
}

```

```

    return binom[n][k];
}

```

3.3 Extended Euclidean Algorithm

(x, y) such that $ax + by = \gcd(a, b) = d$.

```

int Extended_Euclidean(int a, int b, int & x, int & y)
{
    if (a == 0)
    {
        x = 0;
        y = 1;
        return b;
    }
    int x1, y1;
    int d = Extended_Euclidean(b % a, a, x1, y1);
    x = y1 - (b / a) * x1;
    y = x1;
    return d;
}

```

3.4 Fast Modulo Exponentiation

Calculating $x^y \bmod p$ in $\mathcal{O}(\log y)$ time.

```

ll modpow(ll x, ll y, ll p)
{
    ll res = 1;
    x = x % p;
    while (y > 0)
    {
        if (y & 1)
            res = (res*x) % p;
        y = y>>1;
        x = (x*x) % p;
    }
    return res;
}

```

3.5 Modular Multiplicative Inverse

```

ll modinv(ll x, ll p)
{
    return modpow(x, p-2, p);
}

```

3.6 Miller-Rabin Primality Testing

Base values of a chosen so that results are tested to be correct up to 10^{14} .

```

bool MRwitness(ll n, ll s, ll d, ll a)
{
    ll x = modpow(a, d, n);
    ll y = -1;

    while (s)
    {
        y = (x * x) % n;
        if (y == 1 && x != 1 && x != n-1)
            return false;
        x = y;
        s--;
    }
    return (y==1);
}

bool Miller_Rabin(ll n)
{
    if (n<2)
        return false;
    if (n == 2 || n == 3 || n == 5 || n == 7 ||
        n == 11 || n == 13 || n == 17)
        return true;
    if (n%2 == 0 || n%3 == 0 || n%5 == 0)
        return false;
    ll d = (n-1) / 2;
    ll s = 1;
    while (d%2==0)
    {
        d /= 2;
        s++;
    }
    int candidate[7] = {2,3,5,7,11,13,17};
    bool result = true;
    for (auto i : candidate)
    {
        result = result & MRwitness(n,s,d,i);
        if (!result)
            break;
    }
}

```

```

    }
    return result;
}

```

3.7 Pollard-Rho Factorization

```

ll PollardRho(ll n)
{
    srand (time(NULL));
    if (n==1)
        return n;
    if (n % 2 == 0)
        return 2;
    ll x = (rand()%(n-2))+2;
    ll y = x;
    ll c = (rand()%(n-1))+1;
    ll d = 1;
    while (d==1)
    {
        x = (modpow(x, 2, n) + c + n)%n;
        y = (modpow(y, 2, n) + c + n)%n;
        y = (modpow(y, 2, n) + c + n)%n;
        d = gcd(abs(x-y), n);
        if (d==n)
            return PollardRho(n);
    }
    return d;
}

```

3.8 Euler Totient

Calculating number of integers below n which is coprime with n .

```

ll euler_phi(ll n)
{
    ll p=2;
    ll ephi = n;
    while(p*p<=n)
    {
        if (n%p == 0)
            ephi = ephi/p * (p-1);
        while(n%p==0)
            n/=p;
        p++;
    }
}

```

```

    }
    if (n!=1)
    {
        ephi /= n;
        ephi *= (n-1);
    }
    return ephi;
}

```

3.9 Fast Fourier Transform

Compute $A(x) * B(x)$ in $O(n \log n)$ time.

Convolution 빠르게 구하기

$$c_j = \sum_{i=0}^j a_i b_{j-i}$$

```

#include <complex>
#define sz(v) ((int)(v).size())
#define all(v) (v).begin(),(v).end()
typedef complex<double> base;
typedef vector <int> vi;
void fft(vector <base> &a, bool invert)
{
    int n = sz(a);
    for (int i=1,j=0;i<n;i++)
    {
        int bit = n >> 1;
        for (;j>=bit;bit>>=1)
            j -= bit;
        j += bit;
        if (i < j)
            swap(a[i],a[j]);
    }
    for (int len=2;len<=n;len<<=1)
    {
        double ang = 2*M_PI/len*(invert?-1:1);
        base wlen(cos(ang),sin(ang));
        for (int i=0;i<n;i+=len)
        {
            base w(1);
            for (int j=0;j<len/2;j++)
            {
                base u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
            }
        }
    }
}

```

```

        a[i+j+len/2] = u-v;
        w *= wlen;
    }
}
if (invert)
    for (int i=0;i<n;i++)
        a[i] /= n;

}

void multiply(const vi &a,const vi &b, vi &res)
{
    vector<base> fa(all(a)), fb(all(b));
    int n = 1;
    while (n < max(sz(a),sz(b)))
        n <<= 1;
    fa.resize(n); fb.resize(n);
    fft(fa,false); fft(fb,false);
    for (int i=0;i<n;i++)
        fa[i] *= fb[i];
    fft(fa,true);
    res.resize(n);
    for (int i=0;i<n;i++)
        res[i] = int(fa[i].real()+
            (fa[i].real()>0?0.5:-0.5));
}

```

3.10 Berlekamp-Massey Algorithm

초항 $3k$ 개로 $k * k$ 행렬 전이를 갖는 문제를 선형점화식으로 변환 + Kitamasa method 를 이용한 $k^2 \log n$ 시간 계산. 초항만 몇개 구하고 guess_nth_term 쓰면 ok. 점화식을 알때는 get_nth로 키타마사만 쓰기.

Todo : FFT를 적용한 $k \log k \log n$ 키타마사 구현하기.

```

/*
    BerlekampMassey Algorithm Implementation :
    No touch unless absolutely necessary
    Implementation : Koosaga
*/
const int mod = 1000000007;
using lint = long long;
lint ipow(lint x, lint p){

```

```

    lint ret = 1, piv = x;
    while(p){
        if(p & 1) ret = ret * piv % mod;
        piv = piv * piv % mod;
        p >>= 1;
    }
    return ret;
}
vector<int> berlekamp_massey(vector<int> x){
    vector<int> ls, cur;
    int lf, ld;
    for(int i=0; i<x.size(); i++){
        lint t = 0;
        for(int j=0; j<cur.size(); j++){
            t = (t + 1ll * x[i-j-1] * cur[j]) % mod;
        }
        if((t - x[i]) % mod == 0) continue;
        if(cur.empty()){
            cur.resize(i+1);
            lf = i;
            ld = (t - x[i]) % mod;
            continue;
        }
        lint k = -(x[i] - t) * ipow(ld, mod - 2) % mod;
        vector<int> c(i-lf-1);
        c.push_back(k);
        for(auto &j : ls) c.push_back(-j * k % mod);
        if(c.size() < cur.size()) c.resize(cur.size());
        for(int j=0; j<cur.size(); j++){
            c[j] = (c[j] + cur[j]) % mod;
        }
        if(i-lf+(int)ls.size()>=(int)cur.size()){
            tie(ls, lf, ld) = make_tuple(cur, i, (t - x[i]) % mod);
        }
        cur = c;
    }
    for(auto &i : cur) i = (i % mod + mod) % mod;
    return cur;
}
int get_nth(vector<int> rec, vector<int> dp, lint n){
    int m = rec.size();
    vector<int> s(m), t(m);

```

```

s[0] = 1;
if(m != 1) t[1] = 1;
else t[0] = rec[0];
auto mul = [&rec](vector<int> v, vector<int> w){
    int m = v.size();
    vector<int> t(2 * m);
    for(int j=0; j<m; j++){
        for(int k=0; k<m; k++){
            t[j+k] += 111 * v[j] * w[k] % mod;
            if(t[j+k] >= mod) t[j+k] -= mod;
        }
    }
    for(int j=2*m-1; j>=m; j--){
        for(int k=1; k<=m; k++){
            t[j-k] += 111 * t[j] * rec[k-1] % mod;
            if(t[j-k] >= mod) t[j-k] -= mod;
        }
    }
    t.resize(m);
    return t;
};
while(n){
    if(n & 1) s = mul(s, t);
    t = mul(t, t);
    n >>= 1;
}
lint ret = 0;
for(int i=0; i<m; i++) ret += 111 * s[i] * dp[i] % mod;
return ret % mod;
}

int guess_nth_term(vector<int> x, lint n){
    if(n < x.size()) return x[n];
    vector<int> v = berlekamp_massey(x);
    if(v.empty()) return 0;
    return get_nth(v, x, n);
}

struct elem{int x, y, v;};
vector<int> get_min_poly(int n, vector<elem> M)
{
    // smallest poly P such that A^i = sum_{j < i} {A^j \times P_j}
    vector<int> rnd1, rnd2;
}

```

```

mt19937 rng(0x14004);
auto randint = [&rng](int lb, int ub){
    return uniform_int_distribution<int>(lb, ub)(rng);
};
for(int i=0; i<n; i++){
    rnd1.push_back(randint(1, mod - 1));
    rnd2.push_back(randint(1, mod - 1));
}
vector<int> gobs;
for(int i=0; i<2*n+2; i++){
    int tmp = 0;
    for(int j=0; j<n; j++){
        tmp += 111 * rnd2[j] * rnd1[j] % mod;
        if(tmp >= mod) tmp -= mod;
    }
    gobs.push_back(tmp);
    vector<int> nxt(n);
    for(auto &i : M){
        nxt[i.x] += 111 * i.v * rnd1[i.y] % mod;
        if(nxt[i.x] >= mod) nxt[i.x] -= mod;
    }
    rnd1 = nxt;
}
auto sol = berlekamp_massey(gobs);
reverse(sol.begin(), sol.end());
return sol;
}

lint det(int n, vector<elem> M){
    vector<int> rnd;
    mt19937 rng(0x14004);
    auto randint = [&rng](int lb, int ub){
        return uniform_int_distribution<int>(lb, ub)(rng);
    };
    for(int i=0; i<n; i++) rnd.push_back(randint(1, mod - 1));
    for(auto &i : M){
        i.v = 111 * i.v * rnd[i.y] % mod;
    }
    auto sol = get_min_poly(n, M)[0];
    if(n % 2 == 0) sol = mod - sol;
    for(auto &i : rnd) sol = 111 * sol * ipow(i, mod - 2) % mod;
    return sol;
}

```

4 Geometry

4.1 CCW

```
//Is 3 points Counterclockwise? 1 : -1
//0 : on same line
int CCW(Point a, Point b, Point c)
{
    int op = a.x*b.y + b.x*c.y + c.x*a.y;
    op -= (a.y*b.x + b.y*c.x + c.y*a.x);
    if (op > 0)
        return 1;
    else if (op == 0)
        return 0;
    else
        return -1;
}
```

4.2 Point in polygon

Returns boolean, if point is in the polygon (represented as vector of points).

```
// point in polygon test
inline double is_left(Point p0, Point p1, Point p2)
{
    return (p1.x - p0.x) * (p2.y - p0.y) - (p2.x - p0.x) * (p1.y - p0.y);
}
bool is_in_polygon(Point p, vector<Point>& poly)
{
    int wn = 0;
    for (int i = 0; i < poly.size(); ++i)
    {
        int ni = (i + 1 == poly.size()) ? 0 : i + 1;
        if (poly[i].y <= p.y)
        {
            if (poly[ni].y > p.y)
                if (is_left(poly[i], poly[ni], p) > 0)
                    ++wn;
        }
        else
        {
            if (poly[ni].y <= p.y)
                if (is_left(poly[i], poly[ni], p) < 0)
```

```
--wn;
    }
}
return wn != 0;
}



### 4.3 Length of Segment Union



Length of segment union, from vector of {start, end}.



```
//Src : e-maxx
int length_union(const vector<pair<int, int>> &a)
{
 int n = a.size();
 vector<pair<int, bool>> x(n*2);
 for (int i = 0; i < n; i++)
 {
 x[i*2] = {a[i].first, false};
 x[i*2+1] = {a[i].second, true};
 }

 sort(x.begin(), x.end());

 int result = 0;
 int c = 0;
 for (int i = 0; i < n * 2; i++)
 {
 if (i > 0 && x[i].first > x[i-1].first && c > 0)
 result += x[i].first - x[i-1].first;
 if (x[i].second)
 c--;
 else
 c++;
 }
 return result;
}

4.4 Closest Pair Problem

Requires : Points must be sorted with x-axis.
Runs in $\mathcal{O}(n \log^2 n)$


```
int dist (Point &p, Point &q)
{
    return (p.x-q.x)*(p.x-q.x) + (p.y-q.y)*(p.y-q.y);
```


```


```

```

bool compare(Point &p, Point &q)
{
    return (p.x < q.x);
}

bool ycompare(Point &p, Point &q)
{
    return (p.y < q.y);
}
Point pts[101010];

int closest_pair(Point p[], int n)
{
    if (n==2)
        return dist(p[0], p[1]);
    if (n==3)
    {
        return min(dist(p[0],p[1]),
                   min(dist(p[1],p[2]),dist(p[0],p[2])));
    }
    Point mid[n];
    int line = (p[n/2 - 1].x + p[n/2].x) / 2;
    int d = min(closest_pair(p, n/2), closest_pair(p + n/2, n - n/2));
    int pp = 0;
    for (int i = 0; i < n; i++)
    {
        int t = line - p[i].x;
        if (t*t < d)
        {
            mid[pp] = p[i];
            pp++;
        }
    }
    sort(mid,mid+pp,ycompare);
    for (int i = 0; i < pp - 1; i++)
        for (int j = i + 1; j < pp && mid[j].y - mid[i].y < d; j++)
            d = min(d, dist(mid[i], mid[j]));
    return d;
}

```

4.5 Convex Hull (Graham Scan)

```

// From GeeksforGeeks.
Point nextToTop(stack<Point> &S)
{
    Point p = S.top();
    S.pop();
    Point res = S.top();
    S.push(p);
    return res;
}

int swap(Point &p1, Point &p2)
{
    Point temp = p1;
    p1 = p2;
    p2 = temp;
}

int distSq(Point p1, Point p2)
{
    return (p1.x - p2.x)*(p1.x - p2.x) +
           (p1.y - p2.y)*(p1.y - p2.y);
}

int orientation(Point p, Point q, Point r) // Basically CCW
{
    int val = (q.y - p.y) * (r.x - q.x) -
              (q.x - p.x) * (r.y - q.y);

    if (val == 0) return 0; // colinear
    return (val > 0)? 1: 2; // clock or counterclock wise
}

int compare(const void *vp1, const void *vp2)
{
    Point *p1 = (Point *)vp1;
    Point *p2 = (Point *)vp2;

    // Find orientation
    int o = orientation(p0, *p1, *p2);
    if (o == 0)
        return (distSq(p0, *p2) >= distSq(p0, *p1))? -1 : 1;
}

```

```

    return (o == 2)? -1: 1;
}

// Prints convex hull of a set of n points.
void convexHull(Point points[], int n)
{
    // Find the bottommost point
    int ymin = points[0].y, min = 0;
    for (int i = 1; i < n; i++)
    {
        int y = points[i].y;
        if ((y < ymin) || (ymin == y &&
            points[i].x < points[min].x))
            ymin = points[i].y, min = i;
    }

    // Place the bottom-most point at first position
    swap(points[0], points[min]);

    // Sort n-1 points with respect to the first point.
    p0 = points[0];
    qsort(&points[1], n-1, sizeof(Point), compare);

    // If two or more points make same angle with p0,
    // Remove all but the one that is farthest from p0
    int m = 1;
    for (int i=1; i<n; i++)
    {
        while (i < n-1 && orientation(p0, points[i],
                                         points[i+1]) == 0)
            i++;
        points[m] = points[i];
        m++;
    }

    // If modified array of points has less than 3 points,
    // convex hull is not possible
    if (m < 3) return;

    // Create an empty stack and push first three points
}

```

```

// to it.
stack <Point> S;
S.push(points[0]);
S.push(points[1]);
S.push(points[2]);

// Process remaining n-3 points
for (int i = 3; i < m; i++)
{
    while (orientation(nextToTop(S), S.top(), points[i]) != 2)
        S.pop();
    S.push(points[i]);
}

// Now stack has the output points, print contents of stack
while (!S.empty())
{
    Point p = S.top();
    cout << "(" << p.x << ", " << p.y << ")" << endl;
    S.pop();
}

```

4.6 Intersection of Line Segment

```

//jason9319.tistory.com/358. modified
int isIntersect(Point a, Point b, Point c, Point d)
{
    int ab = ccw(a, b, c)*ccw(a, b, d);
    int cd = ccw(c, d, a)*ccw(c, d, b);
    if (ab == 0 && cd == 0)
    {
        if (a > b)swap(a, b);
        if (c > d)swap(c, d);
        return (c <= b&&a <= d);
    }
    return (ab <= 0 && cd <= 0);
}

```

5 Graphs

5.1 Topological Sorting

Topological sorting with dfs

```

vector <int> graph[V];
bool visited[V];
vector <int> sorted;

void dfs(int root)
{
    visited[root] = 1;
    for (auto it:graph[root])
    {
        if (!visited[it])
            dfs(it);
    }
    sorted.push_back(root);
}

int main()
{
    int n, m;
    scanf("%d%d",&n,&m);
    for (int i = 0; i<m; i++)
    {
        int small,big;
        scanf("%d%d",&small,&big);
        graph[small].push_back(big);
    }
    for (int i = 1; i<=n; i++)
        if (!visited[i])
            dfs(i);
    reverse(sorted.begin(),sorted.end()); // must reverse!
}

```

5.2 Lowest Common Ancestor

LCA Algorithm by sparse table.

minlen : (x, y) 사이를 잇는 간선 중 최소 길이 간선.

maxlen : (x, y) 사이를 잇는 간선 중 최대 길이 간선.

```

int n, k;
bool visited[101010];
int par[101010][21], maxedge[101010][21], minedge[101010][21];
int d[101010];
vector <pii> graph[101010]; // {destination, weight}
void dfs(int here,int depth) // run dfs(root,0)

```

```

{
    visited[here] = true;
    d[here] = depth;
    for (auto there : graph[here])
    {
        if (visited[there.first])
            continue;
        dfs(there.first, depth + 1);
        par[there.first][0] = here;
        maxedge[there.first][0] = there.second;
        minedge[there.first][0] = there.second;
    }
}

void precomputation()
{
    for (int i = 1; i<21; i++)
    {
        for (int j = 1; j<=n; j++)
        {
            par[j][i] = par[par[j][i-1]][i-1];
            maxedge[j][i] = max(maxedge[j][i - 1],
                                maxedge[par[j][i - 1]][i - 1]);
            minedge[j][i] = min(minedge[j][i - 1],
                                minedge[par[j][i - 1]][i - 1]);
        }
    }
}

pii lca(int x, int y)
{
    int maxlen = INT_MIN;
    int minlen = INT_MAX;
    if (d[x]>d[y])
        swap(x,y);
    for (int i = 20; i>=0; i--)
    {
        if (d[y]-d[x] >= (1<<i))
        {
            minlen = min(minlen,minedge[y][i]);
            maxlen = max(maxlen,maxedge[y][i]);
            y = par[y][i];
        }
    }
}
```

```

    }
}

if (x==y)
    return {minlen, maxlen};
for (int i = 20; i>=0; i--)
{
    if (par[x][i] != par[y][i])
    {
        minlen = min(minlen,min(minedge[x][i],minedge[y][i]));
        maxlen = max(maxlen,max(maxedge[x][i],maxedge[y][i]));
        x = par[x][i];
        y = par[y][i];
    }
}
minlen = min(minlen,min(minedge[x][0],minedge[y][0]));
maxlen = max(maxlen,max(maxedge[x][0],maxedge[y][0]));

int lca_point = par[x][0];
return {minlen,maxlen};
}

```

```

void tobedone()
{
    dfs(1,0);
    precomputation();
}

```

5.3 MST Kruskal Algorithm

Based on Union-Find implementation
 $\mathcal{O}(E \log E)$ if path-compressed Union Find.

```

int Kruskal()
{
    int mstlen = 0;
    sort(edgelist.begin(),edgelist.end());
    for (auto it:edgelist)
    {
        if (dsu.Find(it.s)==dsu.Find(it.e)) // Cycle Detection
            continue;
        else
        {
            dsu.unite(it.s,it.e);

```

```

            mstlen += it.w;
        }
    }
    return mstlen;
}

5.4 MST Prim Algorithm
vector <pii> Tree[101010];
// Note that we use {weight, destination} pair here.
// This is to use priority_queue!
bool visit[101010];
priority_queue <pii, vector<pii>, greater<pii>> pq;
void add(int i)
{
    visit[i] = true;
    for (auto it:Tree[i])
        pq.push(it);
}

int Prim(int start)
{
    int mstlen = 0;
    add(start);
    while(!pq.empty())
    {
        int cur = pq.top().second;
        int weight = pq.top().first;
        pq.pop();
        if (visit[cur])
            continue;
        else
        {
            mstlen+=weight;
            add(cur);
        }
    }
    return mstlen;
}
```

5.5 Dinic's Algorithm

```

struct Edge
{

```

```

int u, v;
ll cap, flow;
Edge() {}
Edge(int u, int v, ll cap): u(u), v(v), cap(cap), flow(0) {}
};

struct Dinic
{
    int N;
    vector<Edge> E;
    vector<vector<int>> g;
    vector<int> d, pt;

    Dinic(int N): N(N), E(0), g(N), d(N), pt(N) {}

    void AddEdge(int u, int v, ll cap)
    {
        if (u != v)
        {
            E.push_back(Edge(u, v, cap));
            g[u].push_back(E.size() - 1);
            E.push_back(Edge(v, u, 0));
            g[v].push_back(E.size() - 1);
        }
    }

    bool BFS(int S, int T)
    {
        queue<int> q({S});
        fill(d.begin(), d.end(), N + 1);
        d[S] = 0;
        while(!q.empty())
        {
            int u = q.front();
            q.pop();
            if (u == T) break;
            for (int k: g[u])
            {
                Edge &e = E[k];
                if (e.flow < e.cap && d[e.v] > d[e.u] + 1)
                {

```

```

                    d[e.v] = d[e.u] + 1;
                    q.push(e.v);
                }
            }
            return d[T] != N + 1;
        }

        ll DFS(int u, int T, ll flow = -1)
        {
            if (u == T || flow == 0) return flow;
            for (int &i = pt[u]; i < g[u].size(); i++)
            {
                Edge &e = E[g[u][i]];
                Edge &oe = E[g[u][i]^1];
                if (d[e.v] == d[e.u] + 1)
                {
                    ll amt = e.cap - e.flow;
                    if (flow != -1 && amt > flow) amt = flow;
                    if (ll pushed = DFS(e.v, T, amt))
                    {
                        e.flow += pushed;
                        oe.flow -= pushed;
                        return pushed;
                    }
                }
            }
            return 0;
        }

        ll MaxFlow(int S, int T)
        {
            ll total = 0;
            while (BFS(S, T))
            {
                fill(pt.begin(), pt.end(), 0);
                while (ll flow = DFS(S, T))
                    total += flow;
            }
            return total;
        };
    };
};
```

6 Shortest Path

모든 간선의 가중치를 필요할 때마다 0으로 잘 초기화했는지 확인하기.

6.1 Dijkstra

$\mathcal{O}(E \log V)$ Single-Start-Shortest-Path.
가중치에 음수 없는거 항상 확인하고 쓰기.

```
const int INF = 987654321;
const int MX = 105050;
struct Edge
{
    int dest, w;
    bool operator<(const Edge &p) const
    {
        return w > p.w;
    }
};

bool relax(Edge edge, int u, int dist[])
{
    bool flag = 0;
    int v = edge.dest, w = edge.w;
    if (dist[v] > dist[u] + w && (dist[u] != INF))
    {
        flag = true;
        dist[v] = dist[u]+w;
    }
    return flag;
}

int dijkstra(int dist[], int start, vector<Edge> graph[])
{
    fill(dist,dist+MX,INF);
    dist[start] = 0;
    priority_queue<Edge> pq;
    pq.push({start,0});
    while(!pq.empty())
    {
        Edge x = pq.top();
        int v = x.dest, w = x.w;
        pq.pop();
        if (w>dist[v])
            continue;
        for (auto ed : graph[v])
            if (relax(ed, v, dist))
                pq.push({ed.dest,dist[ed.dest]});
    }
}
```

```
for (auto ed : graph[v])
    if (relax(ed, v, dist))
        pq.push({ed.dest,dist[ed.dest]});
}
```

6.2 Bellman Ford

$\mathcal{O}(EV)$ Single-Start-Shortest-Path.
Not working for graph with minus cycle → must detect.

```
struct Edge
{
    int u, v, w;
};
vector <Edge> edgelist;
int V, E;
int dist[V+1];
bool relax_all_edge()
{
    bool flag = false;
    for (auto it:edgelist)
    {
        int u = it.u, v = it.v, w = it.w;
        if (dist[v] > dist[u] + w && (dist[u] != INF))
        {
            flag = true;
            dist[v] = dist[u]+w;
        }
    }
    return flag;
}
int bellman_ford()
{
    fill(dist,dist+V+2,INF);
    dist[1] = 0;
    for (int i = 0; i<V-1; i++)
    {
        relax_all_edge();
    }
    if (relax_all_edge())
        return -1;
    else
        return 0;
}
```

}

6.3 SPFA Algorithm

Average $\mathcal{O}(E)$, worst $\mathcal{O}(VE)$.

```

struct Edge
{
    int dest, w;
    bool operator<(const Edge &p) const
    {
        return w > p.w;
    }
};

bool inQ[100500];
int cycle[100500];
int spfa(int dist[], int start, vector<Edge> graph[])
{
    fill(dist, dist + MX, INF);

    queue<int> q;
    dist[start] = 0;
    inQ[start] = true;
    q.push(start);
    cycle[start]++;
    while (!q.empty())
    {
        int here = q.front();
        q.pop();
        inQ[here] = false;
        for (int i = 0; i < graph[here].size(); i++)
        {
            int next = graph[here][i].dest;
            int cost = graph[here][i].w;
            if (dist[next] > dist[here] + cost)
            {
                dist[next] = dist[here] + cost;
                if (!inQ[next])
                {
                    cycle[next]++;
                    if (cycle[next] >= graph->size())
                    {
                        printf("-1\n");
                        return 0;
                    }
                }
            }
        }
    }
}

```

```

        }
        q.push(next);
        inQ[next] = true;
    }
}

}

```

6.4 Floyd-Warshall

Works on adjacency matrix, in $\mathcal{O}(V^3)$.

```

int d[120][120];
int n;
void Floyd_Warshall()
{
    fill(d, d+sizeof(d), INF);
    //---Edges Here---//
    for (int i = 1; i<=n; i++)
        for (int j = 1; j<=n; j++)
            for (int k = 1; k<=n; k++)
                d[j][k] = MIN(d[j][k], d[j][i]+d[i][k]);
}

```

7 Dynamic

7.1 다이나믹 프로그래밍 최적화 기법

7.1.1 Convex Hull Trick

$dp[i] = \min_{j < i} (dp[j] + a[i]b[j])$ 이고, b 가 단조 감소하며, (현재 구현 기준) a 가 단조 증가할 때, 직선 $y = b[j]*x + dp[j]$ 들을 기준으로 해석해서 시간 복잡도를 줄인다.

```

ll A[100020];
ll B[100020];
ll dp[100020];
//dp[i] = dp[j]+A[i]*B[j];
typedef struct linear
{
    ll a,b;
    double xpos;
    linear(ll x=0, ll y=0, double z=0): a(x),b(y),xpos(z){}
    ll cal(ll n){return a*n+b;}
}linear;

```

```

double cross(linear l, linear m)
{
    return (double)(l.b-m.b)/(double)(m.a-l.a);
}
linear s[100020];
int main()
{
    ll n;
    scanf("%lld",&n);
    for(int i=0; i<n; i++)
        scanf("%lld",A+i);
    for(int i=0; i<n; i++)
        scanf("%lld",B+i);
    s[0]=linear(B[0],0,-1e18);
    ll fpos = 0, pt = 0;
    // pt: 스택의 맨 위 fpos: 대입할 직선 결정
    for(int i=1; i<n; i++)
    {
        // 시작할 위치가 A[i](좌표) 보다 처음으로 크거나 같아지는 순간
        while(s[fpos].xpos<A[i]&&fpos<=pt)
            fpos++;
        dp[i]=s[--fpos].cal(A[i]);
        linear newlin = linear(B[i],dp[i],0);
        while(pt>0&&cross(s[pt],newlin)<=s[pt].xpos)
        {
            if(pt==fpos)
                fpos--;
            pt--;
        }
        newlin.xpos = cross(s[pt],newlin);
        s[++pt] = newlin;
    }
    printf("%lld",dp[n-1]);
}

```

7.1.2 Knuth Optimization

dp 점화식이 다음 조건을 만족할 때, $O(n^3)$ 을 $O(n^2)$ 로 줄인다.

- $dp[i][j] = \min_{i < k < j} (dp[i][k] + dp[k][j]) + C[i][j]$
- $C[a][c] + C[b][d] \leq C[a][d] + C[b][c] \leq 2C[a][d]$ when $a \leq b \leq c \leq d$.

○ 때, $dp[i][j]$ 가 최소가 되는 k 는 $k_{(i,j-1)} \leq k_{(i,j)} \leq k_{(i+1,j)}$ 를 만족한다.

```

for(i = 1; i <= n; i++)
{
    dp[i][i] = 0;
    p[i][i] = i;
}

for(j = 2; j <= n; j++)
{
    for(i = 1; i <= n-j+1; i++){
        s = i, e = i+j-1;
        dp[s][e] = vMax;
        for(k = p[s][e-1]; k <= p[s+1][e]; k++)
        {
            if(dp[s][e] > dp[s][k] + dp[k+1][e])
            {
                dp[s][e] = dp[s][k] + dp[k+1][e];
                p[s][e] = k;
            }
        }
        dp[s][e] += cost[s][e];
    }
}

```

7.2 Longest Increasing Subsequence

Find LIS in $\mathcal{O}(n \log n)$ time.

```

vector <int> sequence;
vector <int> L;
int lis_len;
int position[BIG];
int lis[BIG];
int lis_pushed[BIG];
int n;
void FindLIS(vector <int> &seq)
{
    L.push_back(seq[0]);
    position[0] = 0;
    for (int i = 1; i <n; i++)
    {
        int u = L.size();
        if (seq[i] > L[u-1])
        {
            position[i] = u;
            lis[lis_len] = seq[i];
            lis_pushed[u] = 1;
            lis_len++;
        }
    }
}

```

```

        L.push_back(seq[i]);
    }
    else
    {
        int pos = lower_bound(L.begin(),L.end(),seq[i])-L.begin();
        L[pos] = seq[i];
        position[i] = pos;
    }
}
lis_len=L.size();
int lookingfor = lis_len-1;
for (int i = n-1; i>=0; i--)
{
    if (lis_pushed[position[i]]==0 && lookingfor == position[i])
    {
        lis[position[i]] = seq[i];
        lis_pushed[position[i]]=1;
        lookingfor--;
    }
}
}

Using multiset...
vector <int> sequence;
int n, lislen;
multiset<int> increase;

void find_lis()
{
    for (int i = 0; i<n; i++)
    {
        auto it = lower_bound(all(increase),sequence[i]);
        if (it == increase.begin())
            increase.insert(sequence[i]);
        else
        {
            --it;
            increase.erase(it);
            increase.insert(sequence[i]);
        }
    }
    lislen = increase.size();
}

```

}

7.3 Largest Sum Subarray

Computes sum of largest sum subarray in $\mathcal{O}(N)$

```

void consecsum(int n)
{
    dp[0] = number[0];
    for (int i = 1; i<n; i++)
        dp[i] = MAX(dp[i-1]+number[i],number[i]);
}

int maxsum(int n)
{
    consecsum(n);
    int max_sum=-INF;
    for (int i = 0; i<n; i++)
        dp[i] > max_sum ? max_sum = dp[i] : 0;
    return max_sum;
}

```

7.4 0-1 Knapsack

```

int dp[N][W];
int weight[N];
int value[N];
void knapsack()
{
    for (int i = 1; i<=n; i++)
    {
        for (int j = 0; j<=W; j++)
            dp[i][j] = dp[i-1][j];
        for (int j = weight[i]; j<=W; j++)
            dp[i][j] = max(dp[i][j], dp[i-1][j-weight[i]]+value[i]);
    }
}

```

7.5 Longest Common Subsequence

```

//input : two const char*
//output : their LCS, in c++ std::string type
string lcsf(const char *X,const char *Y)
{
    int m = (int)strlen(X);

```

```

int n = (int)strlen(Y);
int L[m+1][n+1];
for (int i=0; i<=m; i++)
{
    for (int j=0; j<=n; j++)
    {
        if (i == 0 || j == 0)
            L[i][j] = 0;
        else if (X[i-1] == Y[j-1])
            L[i][j] = L[i-1][j-1] + 1;
        else
            L[i][j] = max(L[i-1][j], L[i][j-1]);
    }
}
int index = L[m][n];

char lcsstring[index+1];
lcsstring[index] = 0;

int i = m, j = n;
while (i > 0 && j > 0)
{
    if (X[i-1] == Y[j-1])
    {
        lcsstring[index-1] = X[i-1];
        i--; j--; index--;
    }
    else if (L[i-1][j] > L[i][j-1])
        i--;
    else
        j--;
}
string lcsstr = lcsstring;
return lcsstr;
}

```

7.6 Edit Distance

```

int edit_dist[1010][1010];
int Editdist(string &s, string &t)
{
    int slen = s.length();

```

```

    int tlen = t.length();
    for (int i = 1; i<=slen; i++)
        edit_dist[i][0] = i;
    for (int i = 1; i<=tlen; i++)
        edit_dist[0][i] = i;
    for (int i = 1; i<=slen; i++)
    {
        for (int j = 1; j<=tlen; j++)
        {
            if (s[j-1]==t[i-1])
                edit_dist[j][i] = edit_dist[j-1][i-1];
            else
                edit_dist[j][i] = min(edit_dist[j-1][i]+1,
                                      min(edit_dist[j-1][i-1]+1,edit_dist[j][i-1]+1));
        }
    }
    return edit_dist[slen][tlen];
}

```

8 String

8.1 KMP Algorithm

P_i 배열의 정의 : $str[0]$ 부터 $str[i]$ 까지 중 접두사가 접미사와 같은 부분만큼의 길이.

```

// Original Author : bowbowbow (bowbowbow.tistory.com)
vector<int> getPi(string p)
{
    int j = 0;
    int plen = p.length();
    vector<int> pi;
    pi.resize(plen);
    for(int i = 1; i< plen; i++)
    {
        while((j > 0) && (p[i] != p[j]))
            j = pi[j-1];
        if(p[i] == p[j])
        {
            j++;
            pi[i] = j;
        }
    }
    return pi;
}

```

```

vector <int> kmp(string s, string p)
{
    vector<int> ans;
    auto pi = getPi(p);
    int slen = s.length(), plen = p.length(), j = 0;
    for(int i = 0 ; i < slen ; i++)
    {
        while(j>0 && s[i] != p[j])
            j = pi[j-1];
        if(s[i] == p[j])
        {
            if(j==plen-1)
            {
                ans.push_back(i-plen+1);
                j = pi[j];
            }
            else
                j++;
        }
    }
    return ans;
}

```

8.2 Manacher's Algorithm

$A[i] = i$ 번을 중심으로 하는 가장 긴 팰린드롬이 되는 반지름.

```

//original Author : Myungwoo (blog.myungwoo.kr)
int N,A[MAXN];
char S[MAXN];

void Manachers()
{
    int r = 0, p = 0;
    for (int i=1;i<=N;i++)
    {
        if (i <= r)
            A[i] = min(A[2*p-i],r-i);
        else
            A[i] = 0;
        while (i-A[i]-1 > 0 && i+A[i]+1 <= N
        && S[i-A[i]-1] == S[i+A[i]+1])
            A[i]++;
    }
}

```

```

        if (r < i+A[i])
            r = i+A[i], p = i;
    }
}

8.3 Trie
struct Trie
{
    int trie[NODE_MAX][CHAR_N];
    int nxt = 1;
    void insert(const char* s)
    {
        int k = 0;
        for (int i = 0; s[i]; i++)
        {
            int t = s[i] - 'a';
            if (!trie[k][t])
            {
                trie[k][t] = nxt;
                nxt++;
            }
            k = trie[k][t];
        }
        trie[k][26] = 1;
    }
    bool find(const char* s, bool exact = false)
    {
        int k = 0;
        for (int i = 0; s[i]; i++)
        {
            int t = s[i] - 'a';
            if (!trie[k][t])
                return false;
            k = trie[k][t];
        }
        if (exact)
        {
            return trie[k][26];
        }
        return true;
    };
}

```

8.4 Rabin-Karp Hashing

Hashmap[k]에, 길이가 len인 부분 문자열의 해시값이 k가 되는 시작점 인덱스 i를 push.

```
const ll MOD = BIG_PRIME;
int L;
char S[STR_LEN];
int safemod(int n)
{
    if(n >= 0)
        return n % MOD;
    return ((-n/MOD+1)*MOD + n) % MOD;
}
vector <int> hashmap[MOD];
void Rabin_Karp(int len)
{
    int Hash = 0;
    int pp = 1;
    for(int i=0; i<=L-len; i++)
    {
        if(i == 0)
        {
            for(int j = 0; j<len; j++)
            {
                Hash = safemod(Hash + S[len-j-1]*pp);
                if(j < len-1)
                    pp = safemod(pp*2);
            }
        }
        else
            Hash = safemod(2*(Hash - S[i-1]*pp) + S[len+i-1]);
        hashmap[Hash].push_back(i);
    }
    return;
}
```

9 Miscellaneous

9.1 Binary and Ternary Search

Preventing stupid mistakes by writing garbage instead of proper binary search.
상황에 따라 lo와 hi 중 어느 쪽이 답인지 달라짐.

```
while(lo+1 < hi)
{
    int mid = (lo+hi)/2;

    if(chk(mid))
        lo = mid;
    else
        hi = mid;
}
```

Ternary search

```
double ternary_search(double l, double r)
{
    double eps = 1e-9; //set the error limit here
    while (r - l > eps)
    {
        double m1 = l + (r - l) / 3;
        double m2 = r - (r - l) / 3;
        double f1 = f(m1); //evaluates the function at m1
        double f2 = f(m2); //evaluates the function at m2
        if (f1 < f2)
            l = m1;
        else
            r = m2;
    }
    return f(l); //return the maximum of f(x) in [l, r]
}
```

9.2 GCC Order Statistics Tree

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/detail/standard_policies.hpp>
typedef tree<int, null_type, less<int>, rb_tree_tag,
tree_order_statistics_node_update> ordered_set;

void test()
{
```

```

ordered_set X;
X.insert(1);
X.insert(2);
X.insert(4);
X.insert(8);
X.insert(16);

cout<<*X.find_by_order(1)<<endl; // 2
cout<<*X.find_by_order(2)<<endl; // 4
cout<<*X.find_by_order(4)<<endl; // 16
cout<<(end(X)==X.find_by_order(6))<<endl; // true

cout<<X.order_of_key(-5)<<endl; // 0
cout<<X.order_of_key(1)<<endl; // 0
cout<<X.order_of_key(3)<<endl; // 2
cout<<X.order_of_key(4)<<endl; // 2
cout<<X.order_of_key(400)<<endl; // 5
}

```

9.3 Useful Bitwise Functions in C++

```

int __builtin_clz(int x); // number of leading zero
int __builtin_ctz(int x); // number of trailing zero
int __builtin_clzll(ll x); // number of leading zero
int __builtin_ctzll(ll x); // number of trailing zero
int __builtin_popcount(int x); // number of 1-bits in x
int __builtin_popcountll(ll x); // number of 1-bits in x

lsb(n): (n & -n); // last bit (smallest)
floor(log2(n)): 31 - __builtin_clz(n | 1);
floor(log2(n)): 63 - __builtin_clzll(n | 1);

// compute next perm. ex) 00111, 01011, 01101, 01110, 10011, 10101...
ll next_perm(ll v)
{
    ll t = v | (v-1);
    return (t + 1) | (((~t & -~t) - 1) >> (__builtin_ctz(v) + 1));
}

```

9.4 Prime numbers

$< 10^k$	prime	$\# \text{ of prime}$
----------	-------	-----------------------

1	7	4	10	99999999967
2	97	25	11	99999999977
3	997	168	12	999999999989
4	9973	1229	13	999999999971
5	99991	9592	14	9999999999973
6	999983	78498	15	999999999999989
7	999991	664579	16	9999999999999937
8	99999989	5761455	17	9999999999999997
9	99999937	50847534	18	999999999999999989

9.5 Time Complexity of Algorithms

- Map, Set : $\log n$ 삽입 삭제 탐색, But very big constant
- PBDS-OST : $\log n$ 삽입 삭제 탐색, But very very big constant
- Segment Tree : $\log n$ change, $\log n$ query
- Lazy Propagation : $\log n$ segment addition
- Fenwick Tree : Same with Segtree but faster
- DSU : Inverse Ackermann merge
- GCD : $\log n$
- Binary Exponentiation : $\log b$
- Fast Fourier Transform : $n \log n$ 다항식 곱셈
- Closest Pair DnC : $n \log n$
- Graham Scan : $n \log n$
- Topological Sort : n
- LCA : Build time $n \log n$, 쿼리당 $\log n$
- Kruskal, Prim : $n \log n$
- Dijkstra : $E \log V$
- Bellman Ford : EV
- SPFA : EV 이지만 매우 빠름
- Floyd-Warshall : V^3
- Convex Hull Trick : $n^2 \rightarrow n$
- Knuth Opt : $n^3 \rightarrow n^2$

- Longest Increasing Subsequence : $n \log n$
- 0-1 Knapsack : $n w$
- Longest Common Subsequence : n^2
- Edit Distance : n^2
- KMP : $N + M$ pattern matching
- Manacher : N palindrome finding
- Trie : M insert, M erase, M search
- Binary, Ternary : $\log n$

10 Checkpoints

10.1 Debugging

- $10^5 * 10^5 \Rightarrow \text{OVERFLOW}$. 특히 for 문 안에서 $i * i < n$ 할 때 조심하기.
- If unsure with overflow, use `#define int long long` and stop caring.
- 행렬과 기하의 i, j 인덱스 조심. 헷갈리면 쓰면서 가기.
- Segment Tree, Trie, Fenwick 등 Struct 구현체 사용할 때는 항상 내부의 n 이 제대로 초기화되었는지 확인하기.
- Testcase가 여러 개인 문제는 항상 초기화 문제를 확인하기.
- iterator 주의 : `.end()` 는 항상 맨 끝 원소보다 하나 더 뒤의 iterator. `erase` 쓸 때는 iterator++ 관련된 문제들에 주의해야 한다.
- Memory Limit : Local variable은 int 10만개 정도까지만 사용. Global Variable의 경우 128MB면 대략 int 2000만 개까지는 잘 들어간다. long long은 절반. stack, queue, map, set 같은 특이한 컨테이너는 100만개를 잡으면 메모리가 벅枳지만 vector 100만개는 잡아도 된다.
- Array out of Bound : 배열의 길이는 충분한가? Vector `resize` 를 했다면 그것도 충분할까? 배열의 -1번에 접근한 적은 없는게 확실할까?
- Binary Search : 제대로 짠 게 맞을까? 1 차이 날 때 / $lo == hi$ 일 때 등등. Infinite loop 주의하기.
- Graph : 반례 유의하기. Connected라는 말이 없으면 Disconnected. Acyclic 하다는 말이 없으면 Cycle 넣기, 특히 $A \leftrightarrow B$ 그래프로 2개짜리 사이클 생각하기.
- Set과 map은 매우 느리다.

10.2 Thinking

- 모든 경우를 다 할 수 없나? 왜 안 되지? 시간 복잡도 잘 생각해 보기. 정해의 Target Complexity를 먼저 생각하고 주요 알고리즘들의 Complexity로 짜맞추기. 예를 들어, 쿼리가 30만개 들어온다면 한 쿼리를 적어도 $\log n$ 에 처리할 방법이 아무튼 있다는 뜻.
- 그 방법이 뭐지? xxxx한 일을 어떤 시간복잡도에 실행하는 적절한 자료구조가 있다면?
 - 필요한 게 정렬성이라면 힙이나 map을 쓸 수 있고
 - multiset / multimap도 사용할 수 있고.. 느리지만.
- 단조함수이며, 충분히 빠르게 검증가능한가 : Binary Search.

- 차원이 높은 문제 : 차원 내려서 생각하기. $3 \rightarrow 2$.
- 이 문제가 사실 그래프 관련 문제는 아닐까?
 - 만약 그렇다면, ‘간선’과 ‘정점’은 각각..?
 - 간선과 정점이 몇 개 정도 있는가?
- 이 문제에 Overlapping Subproblem이 보이나?
→ Dynamic Programming 을 적용.
- Directed Graph, 특히 Cycle에 관한 문제 : Topological Sorting? (ex : SNUPC 2019 kdh9949)
- 답의 상한이 Reasonable하게 작은가?
- output이 특정 수열/OX 형태 : 작은 예제를 Exhasutive Search. 모르는 무언가를 알기 위해서는 데이터가 필요하다.
- 그래프 문제에서, 어떤 “조건”이 들어갔을 때 → 이 문제를 “정점을 늘림으로써” 단순한 그래프 문제로 바꿀 수 있나? (ex : SNUPC 2018 달빛 여우) 이를테면, 훌짝성에 따라 점을 2배로 늘림으로써?
- DP도 마찬가지. 어떤 조건을 단순화하기 위해 상태의 수를 사이사이에 집어넣을 수 있나? (ex : SNUPC 2018 실버런)
- DP State를 어떻게 나타낼 것인가? 첫 i 개만을 이용한 답을 알면 $i + 1$ 개째가 들어왔을 때 빠르게 처리할 수 있을까?
- 더 큰 table에서 시작해서 줄여가기. 특히 Memory가 모자라면 Toggling으로 차원 하나 내릴 수 있는 경우도 상당히 많이 있다. 각 칸의 갱신 시간과 칸의 개수 찾기.
- Square root Decomposition : $O(n \log n)$ 이 생각나면 좋을 것 같지만 잘 생각나지 않고, 제한을 보니 $O(n\sqrt{n})$ 이면 될것도 같이 생겼을 때 생각해 보기. $O(\sqrt{n})$ 버킷 테크닉.
- 복잡도가 맞는데 왜인지 안 뚫리면 : 필요없는 long long을 사용하지 않았나? map이나 set iterator들을 보면서 상수 커팅. 간단한 함수들을 inlining. 재귀를 반복문으로. 특히 Set과 Map은 끔찍하게 느린다.
- 마지막 생각 : 조금 추하지만 해싱이나 Random 또는 bitset 을 이용한 $n^2/64$ 같은 걸로 뚫을 수 있나? 컴파일러를 믿고 10^8 의 몇 배 정도까지는 내 봐도 될 수도. 의외로 Naive한 문제가 많다.

미쳐 넣지 못한 것들

Ford-Fulkerson

```
#include<bits/stdc++.h>
using namespace std;

//시간복잡도: min( O(Ef), O(VE^2) )
#define n 1000 //점의 개수
int start, finish; //시작점, 끝점
int capacity[n][n], flow[n][n]; //각각 용량, 현재 유량

int Ford_Fulkerson(){
    int maxflow = 0;
    while(true) { //증가 경로가 없을 때까지 bfs 돌리기

        vector<int> parent(n, -1);
        queue<int> q;
        parent[start] = start;

        q.push(start);
        while(!q.empty() && parent[finish] == -1) {
            int here = q.front();
            q.pop();

            for (int next = 0 ; next < n ; ++next) {
                //용량이 남고, 미방문일 때
                if ( capacity[here][next] - flow[here][next]
                    > 0 && parent[next] == -1 ) {
                    parent[next] = here;
                    q.push(next);
                }
            }
        }
    }
}
```

```
}

if ( parent[finish] == -1 ) { //증가 경로가 없다
    break;
}

int amount = INT_MAX; //이 경로를 통해 증가할 유량 정
하기

for ( int p = finish ; p != start ; p = parent[p] ) {
    amount = min( capacity[ parent[p] ][p]
        - flow[ parent[p] ][p] , amount );
}

//정했으니 증가시키자
for ( int p = finish ; p != start ; p = parent[p] ) {
    flow[ parent[p] ][p] += amount;
    flow[p][ parent[p] ] -= amount;
}

//전체 유량에 더해주자
maxflow += amount;
}

return maxflow;
}
```

등록

- team079
- as54xhgu