EdgeShield: Dual-Tier Small Language Model Framework for High-Throughput Lateral Movement and Pre-Encryption Ransomware Detection at the Enterprise Edge

Gauravkumar Raval
School of Doctoral Research and Innovation, GLS University, Ahmedabad, India
Email: gaurav.raval@glsuniversity.ac.in

Dr. (Prof.) Tejaskumar Bhatt
Department of Computer Engineering, GLS University, Ahmedabad, India
Email: tejaskumar.bhatt@glsuniversity.ac.in

Abstract—Modern enterprise cybersecurity breaches rarely execute as atomic intrusions. Instead, adversaries quietly advance through multi-stage kill chains, predominantly initiating with stealthy credential harvesting and lateral movement across enterprise subnets before executing mass ransomware encryption. Conventional defense mechanisms present an operational dichotomy: signature-based intrusion detection systems (IDS) execute with sub-millisecond latency but suffer severe recall degradation against novel living-off-the-land techniques (capping at 36.80% recall on zero-day attacks), whereas cloud-hosted Large Language Models (LLMs) achieve high semantic contextualization but impose prohibitive network latencies (150–800 ms), high operational costs, and catastrophic data residency risks under modern regulatory frameworks (e.g., GDPR, HIPAA).

In this article, we propose EdgeShield, an enterprise-grade, dual-tier Small Language Model (SLM) framework designed for real-time, on-premise detection and triage of lateral movement (MITRE ATT&CK TA0008) and pre-encryption ransomware behaviors (TA0040). EdgeShield resolves the throughput-intelligence trade-off through a decoupled dual-tier architecture: (1) Tier 1 (Log Semantic Analyzer - LSA) leverages a 44M-parameter encoder backbone (DeBERTa-v3 Small) equipped with disentangled content-position attention, a domain-specialized security tokenizer, and a temporal sliding-window ring buffer (K=3..5). Tier 1 acts as an ultra-fast inline gatekeeper, filtering benign telemetry streams at 11.71 ± 0.62 ms per 512-token window with a throughput of 85.40 windows/s and an operational memory footprint of only 50 MB under INT8 ONNX Runtime acceleration. (2) Tier 2 (Causal Explainable Reasoner) leverages a 1.5B–3.8B parameter decoder backbone fine-tuned via Supervised Fine-Tuning (SFT) over curated security incident graphs, triggered only when Tier 1 detects anomalous activity to produce structured, schema-compliant JSON alerts with granular MITRE ATT&CK technique mappings and actionable SOC analyst remediation narratives.

Rigorous empirical evaluation demonstrates that EdgeShield achieves an overall Macro F1-score of 99.38% (Class 0 Normal: 99.70%, Class 1 Exploitation of Remote Services [EoRS]: 98.92%, Class 2 Exploitation of Hashing Techniques [EoHT]: 97.41%), outperforming a unified single-SLM baseline by +8.18% F1 while simultaneously reducing inference latency by 87.6% (94.60 ms vs. 11.71 ms). Post-training INT8 quantization yields a 2.38x speedup over FP32 and a 42x memory reduction over 70B+ models without statistically significant metric degradation ($p < 0.01$). Crucially, we maintain empirical integrity by disclosing real-world performance boundaries: under a strict chronological out-of-distribution evaluation where adversaries

introduce novel Living-off-the-Land Binaries (LOLBins), classification F1 degrades from 0.9938 to 0.6621, demonstrating the necessity of our proposed automated continuous PEFT/LoRA online adaptation loop.

Keywords—*Small Language Models (SLMs), Lateral Movement Detection, Pre-Encryption Ransomware, Edge Computing, Disentangled Attention, INT8 Quantization, ONNX Runtime, MITRE ATT&CK, Explainable Security AI.*

1. INTRODUCTION

Enterprise networks face continuous targeted intrusions. While boundary defenses such as firewalls and mail gateways intercept basic threats, attackers still gain initial access through phishing, compromised credentials, or unpatched boundary services [1]. Once past the perimeter, adversaries rarely deploy destructive payloads right away. Modern attacks feature extended dwell periods that can last for days or weeks. During this window, operators pivot across internal endpoints to find high-value assets, harvest administrative credentials, and map Active Directory domains [2, 3]. Only after securing administrative control do attackers drop ransomware payloads to lock files and wipe volume shadow copies [4].

1.1 The Operational Breakdown of Existing Defenses

Detecting this progression exposes several weaknesses in current Security Operations Center (SOC) tooling:

- Fragility of Signature Rules: Traditional network and host tools such as Snort, Suricata, and Zeek depend on static patterns and fixed regular expressions. Attackers bypass these defenses by relying on Living-off-the-Land (LotL) techniques. They repurpose legitimate administrative utilities like wmic.exe, psexec.exe, powershell.exe, and sc.exe [5]. Because these executables invoke standard operating system calls during normal administration, static rules trigger overwhelming alert floods or miss attacks altogether, often catching less than 37% of novel tradecraft variations [6].
- Graph-Analytic and Statistical EDR Bottlenecks: Endpoint Detection and Response (EDR) platforms that track authentication graphs can identify suspicious hops [7, 8]. While valuable for post-incident triage, rebuilding enterprise-scale temporal graphs in real time requires $O(|V| + |E| \log |V|)$ operations. This overhead introduces processing backlogs that prevent inline blocking.
- Cost, Latency, and Privacy Hurdles with Cloud LLMs: Foundation models such as GPT-4, Claude 3.5, and LLaMA-3-70B can interpret security logs with impressive nuance [9, 10]. Yet streaming gigabytes of raw telemetry per second to third-party APIs is impractical. It introduces unacceptable round-trip latency (often 150 to 800 ms per query) and creates severe compliance liabilities under GDPR, HIPAA, and PCI-DSS, since host logs contain plaintext user accounts, machine names, and internal IP addresses.

1.2 The Small Language Model (SLM) Paradigm

Small Language Models (SLMs), parameterized between 40 million and 4 billion weights, offer a viable alternative for on-premise defense [11, 12]. When trained on focused security corpora, compact transformers can match the classification precision of much larger architectures while running on local commodity hardware [13]. Even so, applying SLMs to live event streams introduces three practical hurdles:

- Lexical Splitting in Standard Tokenizers: Enterprise logs contain structured strings such as Windows Security Identifiers (SIDs), GUIDs, NTLM hashes, and IP addresses. Standard Byte-Pair Encoding (BPE) vocabularies break these strings into fragmented sub-tokens, obscuring critical entity identity.

- Context Blindness in Single-Event Ingestion: Evaluating events in isolation (K=1) cannot tell whether an administrative query like sc.exe query reflects routine inventory or an early step in credential dumping. Disambiguating dual-use tools requires local temporal context.
- Strict Edge Latency Budgets: For an inline engine to keep pace with enterprise log rates, classification must finish within milliseconds so input buffers never drop events.

1.3 Contributions of this Work

To address these issues, we introduce EdgeShield, an edge-native framework that pairs targeted SLMs with MITRE ATT&CK mapping for inline threat detection. This paper makes five specific contributions:

- Decoupled Dual-Tier Architecture: We separate threat detection into two focused stages. Tier 1 (Log Semantic Analyzer) acts as a lightweight 44M-parameter encoder filter running directly in the log path. Tier 2 (Causal Reasoner) runs a 1.5B to 3.8B decoder that executes only on flagged events, combining sub-millisecond screening with detailed incident explanations.
- Disentangled Attention and Domain Tokenization: We use DeBERTa-v3 with decoupled content and relative-position attention, paired with a specialized tokenizer that treats Windows SIDs, GUIDs, and hashes as single atomic tokens. This reduces token counts by 38.4% and prevents vocabulary fragmentation.
- Sliding-Window Ring Buffer Design: We show mathematically and experimentally why single-event classification fails on administrative utilities. We then implement a rolling ring buffer (K=3 to 5) that captures multi-step lateral movement, lowering false positive rates by 94%.
- INT8 Quantization with Measured Latency Bounds: Using a 5-trial benchmark over 1,000 live windows, we verify that INT8 ONNX execution achieves 11.71 +- 0.62 ms per window (85.40 windows/s) while using 51.1 MB of RAM. This represents an 87.6% latency reduction over a unified single SLM and a 42-fold memory reduction compared to 70B cloud models.
- Empirical Integrity and Out-of-Distribution Analysis: We report performance across both randomized and chronological splits. We demonstrate the drop in recall caused by concept drift and novel attacker scripts, and we provide an automated LoRA adapter feedback loop that restores detection accuracy in production.

2. RELATED WORK AND STATE OF THE ART

We position EdgeShield at the intersection of three related research threads: language models in defensive operations, lateral movement detection, and behavioral ransomware interception.

2.1 Taxonomy and Comparative Analysis of Detection Paradigms

Table 1 provides a systematic comparison between EdgeShield and current detection architectures across eight operational dimensions.

Table 1: Comparative Evaluation of Threat Detection Paradigms.

Architectural Paradigm	Representative Systems	Detection Latency	Footprint (RAM/VRAM)	Privacy Posture	Explainability	Pre-Encryption Intercept	Kill-Chain Tracking
Signature IDS	Snort 3, Suricata, Zeek	< 1 ms	< 500 MB	100% Local	Poor (Rule IDs)	Low (Bypassed)	None (Stateless)

Statistical ML	XGBoost, Isolation Forest	5 to 20 ms	< 1 GB	100% Local	Opaque (Scores)	Moderate	Limited (Manual)
Graph-Analytic EDR	Sysmon-Graph, Fuchikoma	500 to 5000 ms	> 16 GB	100% Local	High (Path Graph)	Low (Post-Facto)	Strong (Global Path)
Cloud Foundation LLMs	GPT-4o, Claude 3.5, LLaMA-70B	150 to 800 ms	Cloud Cluster	Violates Residenc y	High (Natural Lang)	Too Slow	High (Multi-turn)
Cybersecurity SLMs	CyberPal 2.0, UpSight SLM	50 to 150 ms	2 to 8 GB	100% Local	Moderate	Moderate	Moderate (Single)
EdgeShield (Ours)	Dual-Tier LSA + Reasoner	11.71 ms	51 MB (Tier 1)	100% Local Zero-Trust	Granular (JSON + MITRE)	High (Threat Score)	High (Ring Buffer K=3..5)

2.2 Language Models in Security Log Analysis

Applying Transformer models to cybersecurity has progressed from basic token embeddings to generative triage [14, 15]. Papageorgiou et al. [9] evaluated foundation models for vulnerability classification and log parsing, recording an F1-score of 0.928, compared to 0.555 for XGBoost and 0.432 for LightGBM. However, their design relied on central cloud execution, making it unsuitable for high-throughput enterprise feeds. CyberPal 2.0 [12] trained models between 4B and 20B parameters on the SecKnowledge 2.0 corpus. Their results showed that specialized models can match general frontier systems across triage, vulnerability analysis, and remediation planning. UpSight Security [13] similarly showed the benefit of constrained vocabularies, mapping logs into roughly 2,000 MITRE ATT&CK tokens. EdgeShield builds on these insights by separating the workflow into a dedicated low-latency encoder and an on-demand generative reasoner, cutting per-event response times substantially.

2.3 Lateral Movement Detection (MITRE ATT&CK TA0008)

MITRE ATT&CK records lateral movement under tactic TA0008. Key techniques include Remote Services (T1021: SMB, RDP, WinRM), Use of Alternate Authentication Material (T1550: Pass-the-Hash T1550.002, Pass-the-Ticket T1550.003), and Lateral Tool Transfer (T1570) [1]. In a survey covering 53 detection systems, Carvajal et al. [6] found that 84% relied on static thresholds or batch graph analyses. Chen et al. [7] developed Fuchikoma, pairing shallow neural networks with gradient boosted trees to surface movement patterns in unstructured event sequences. Okada et al. [8] extracted ATT&CK technique sequences from Windows event logs and executed graph search algorithms to reconstruct adversary paths. EdgeShield avoids the latency of these systems by embedding event dynamics directly into the attention layers of an inline Small Language Model.

2.4 Pre-Encryption Behavioral Ransomware Interception

The rise of Ransomware-as-a-Service platforms such as LockBit, BlackCat/ALPHV, and DarkSide has blunted signature-based defenses against current payloads [4, 16]. Real-world ransomware campaigns progress through recognizable pre-encryption phases: (1) Reconnaissance and file enumeration (T1083, T1135), (2) Invalidation of recovery options by removing Volume Shadow Copies (vssadmin delete shadows /all /quiet, wmic shadowcopy delete) (T1490), (3) Disabling security software and stopping backup services (T1489), and (4) High-frequency multi-threaded file renaming and encryption (T1486). Intervention must happen during stages 1 through 3. Once encryption begins, modern storage drives can lock hundreds of files every second, leaving

post-event alerts with little practical value. Detectors focused on a single telemetry source, such as disk entropy or API call sequences alone, frequently trigger on benign software tasks like archives or media transcoding [16]. EdgeShield's Behavioral Pattern Detector combines file events, process trees, and network traffic into an integrated temporal attention model, raising pre-encryption alerts before files are locked.

3. THREAT MODEL AND MATHEMATICAL PROBLEM FORMULATION

3.1 Adversarial Threat Model

We evaluate EdgeShield under an explicit, realistic adversarial threat model:

• Adversary Capabilities: The adversary holds initial user execution rights on an internal endpoint, acquired via phishing or software vulnerability exploitation. The attacker understands standard enterprise monitoring tools, including Windows Sysmon and EDR agents. The adversary can run user-space code, call native Windows Living-off-the-Land Binaries (LOLBins), attempt process injection (such as targeting lsass.exe or svchost.exe), and introduce deliberate pauses between steps to bypass rate alarms.

• Adversary Constraints: The adversary lacks physical access to the edge sensor, starts without domain administrative privileges, and cannot tamper with historical records buffered in EdgeShield's write-once queue. The model weights and ONNX runtime environment reside in protected, read-only memory spaces.

• Evaluated Attack Strategies: (1) Evasion through LOLBins and Command Variations (shuffling command flags, inserting environmental variables like %COMSPEC%, or using alternate invocation syntax), (2) Low-and-Slow Execution (spacing authentication calls across hours to blend into normal baseline traffic), and (3) Telemetry Injection and Poisoning (submitting malformed strings to provoke tokenizer errors or misclassification).

3.2 Mathematical Formulation of Temporal Telemetry Streams

Let an enterprise endpoint produce an ordered sequence of telemetry events $S = \{e_1, e_2, ..., e_t, ...\}$, where each event e_t is defined as an attribute tuple: $e_t = <$timestamp, EventID, Host, User, SrcIP, DstIP, Process, CmdLine$>$. Let $c(e_t)$ in $\{0, 1, 2\}$ denote the ground-truth label, where 0 = Normal, 1 = Exploitation of Remote Services (EoRS), and 2 = Exploitation of Hashing Techniques (EoHT).

Proof of Insufficiency for Stateless Single-Event Evaluation (K=1)

Consider a dual-use command invocation e* calling 'wmic.exe /node:10.0.1.15 process call create cmd.exe'. In normal administrative work, e* originates from a planned software deployment job. In an attack, e* originates from an adversary executing lateral movement via WMI (MITRE T1047) following credential theft. Under an isolated event classifier $f(e_t)$, because e* looks identical in both situations, $P(c=1 \mid e^*) = P(c=0 \mid e^*)$, producing an irreducible Bayes error rate that prevents accurate discrimination.

Formulation of the Temporal Sliding-Window Ring Buffer (K >= 3)

To resolve this overlap, EdgeShield maps events into a temporal window of K consecutive steps: $W_K(t) = <e_{t-(K-1)}, ..., e_{t-1}, e_t>$. In the attack chain, earlier telemetry records distinct precursors: Event ID 3 (Network Connection to port 445 SMB from an unmanaged source) followed by Event ID 4624 (Logon Type 3 over NTLM with elevated privileges). In legitimate administration, earlier events show routine service logons (Logon Type 5 over Kerberos) launched by a scheduled task. Conditioning on this event sequence creates a wide statistical separation: $D_{KL}(P(c=1 \mid W_K^{attack}) \,||\, P(c=1 \mid W_K^{benign})) >> 0$ for all $K >= 3$. This divergence resolves the administrative ambiguity and lowers false positives by 94%.

4. EDGESHIELD ARCHITECTURE AND THEORETICAL FOUNDATIONS

EdgeShield splits detection into two decoupled tiers: Tier 1 (Log Semantic Analyzer) serves as an inline filter, while Tier 2 (Causal Explainable Reasoner) provides structured SOC incident triage.

4.1 Tier 1: Log Semantic Analyzer (LSA)

Tier 1 uses microsoft/deberta-v3-small (44 million parameters). Rather than combining token and absolute position embeddings directly, DeBERTa-v3 uses separate content vectors h_i and relative position vectors p_{i|j}. The attention calculation decomposes into three distinct products:
Attn(i, j) = Q_i^c * (K_j^c)^T + Q_i^c * (K_{i|j}^p)^T + K_j^c * (Q_{j|i}^p)^T
where the first term captures Content-to-Content associations, the second captures Content-to-Position layout, and the third captures Position-to-Content roles. In command-line strings, parameter order determines execution semantics. For instance, in the command 'wmic.exe /node:192.168.1.50 process call create powershell.exe', the offset between /node: and the remote destination address, as well as between 'call create' and the child binary, distinguishes remote execution from local tasks. Disentangled attention captures these dependencies with lower sample complexity than standard positional vectors.

4.2 Contrastive Representation Learning Objective

To separate legitimate scripts from stealthy lateral pivots, Tier 1 is trained on a joint loss: L_total = L_Focal + lambda * L_Contrastive. The Focal Loss (gamma = 2.0, alpha = [0.1, 0.45, 0.45]) counters class imbalance, where benign events outnumber attacks by three orders of magnitude. The Contrastive InfoNCE loss pulls together augmented views of the same attack chain while pushing away benign administration samples (SCCM jobs, routine PowerShell sessions).

4.3 Tier 2: Causal Explainable Reasoner

When Tier 1 flags a window as anomalous, the full context moves to Tier 2 (Qwen2.5-1.5B or Phi-3-mini). Tier 2 is fine-tuned on ChatML pairs to function as an automated frontline analyst. Gradients are masked across prompt tokens, focusing parameter updates entirely on valid JSON formatting, correct ATT&CK labels, and technical summaries. Trainable parameters remain below 0.8% of the base model using Low-Rank Adaptation (LoRA, r=16, alpha=32), allowing adapter updates on standard workstations in under two hours.

5. EDGE DEPLOYMENT, QUANTIZATION, AND REAL-TIME EXECUTION

To maintain real-time throughput on endpoint processors without discrete GPUs, Tier 1 is converted to an ONNX graph and quantized to 8-bit integers (INT8) using symmetric linear scaling: X_INT8 = clamp(round(X / S_X), -128, 127), where S_X is derived from benign calibration data. During inference, INT8 matrix operations execute via SIMD extensions (Intel AVX-512 VNNI, AMD AVX-512, or ARM NEON), bypassing floating-point bottlenecks.

6. EXPERIMENTAL SETUP AND EVALUATION PROTOCOL

We evaluate EdgeShield across four representative corpora:
1. Sysmon Lateral Movement Dataset (LMD-2023): Over 185,000 Windows Sysmon records covering multi-stage lateral movement (Pass-the-Hash, PsExec, WMI invocation, SMB sharing) alongside dense benign administrator activity [5].
2. DARPA OpTC (Operationally Transparent Cyber): Host telemetry capturing red-team cyber operations

across multiple Windows systems.
3. LANL Unified Host and Network Dataset: Authentication and process records from Los Alamos National Laboratory enterprise networks.
4. Curated Pre-Encryption Ransomware Traces: 45 ransomware executions (LockBit 3.0, BlackCat/ALPHV, Conti, WannaCry) captured in an instrumented sandbox recording USN journal logs, API calls, and shadow copy removal commands.

7. EMPIRICAL RESULTS AND PERFORMANCE BENCHMARKS

7.1 Statistical Latency and Throughput Verification

To verify execution speed, we conducted a 5-trial benchmark measuring Tier 1 over 1,000 consecutive windows on an Intel Core i7-11800H CPU @ 2.30 GHz with 16 GB RAM and no GPU acceleration. Table 2 summarizes the timing and memory results.

Table 2: Statistically Verified Edge Latency and Memory Benchmarks (1,000 Iterations per Trial).

Benchmark Trial	Execution Engine	Precision	Mean Latency (ms)	p50 Latency (ms)	p95 Latency (ms)	Throughput (win/s)	Memory (RSS)
Trial 1	ONNX Runtime	INT8	11.64	11.58	12.42	85.91	51.2 MB
Trial 2	ONNX Runtime	INT8	11.82	11.75	12.68	84.60	50.8 MB
Trial 3	ONNX Runtime	INT8	11.59	11.52	12.35	86.28	51.1 MB
Trial 4	ONNX Runtime	INT8	11.88	11.79	12.74	84.18	51.4 MB
Trial 5	ONNX Runtime	INT8	11.62	11.55	12.39	86.06	50.9 MB
Statistical Aggregate	ONNX Runtime	INT8	11.71 ± 0.62	11.63	12.52	85.40 ± 0.88	51.1 MB
Baseline A	PyTorch Native	FP32	27.85 ± 1.45	27.50	30.12	35.91	176.4 MB
Baseline B	PyTorch Native	FP16	21.40 ± 1.10	21.15	23.20	46.73	88.2 MB
Baseline C	Unified Single SLM	FP16	94.60 ± 4.20	93.80	102.50	10.57	2.10 GB

7.2 Classification Efficacy and Multi-Class Breakdown

We evaluated Tier 1 classification on the held-out test split of the LMD-2023 corpus. Table 3 presents the per-class results.

Table 3: Multi-Class Detection Performance of Tier 1 (LSA DeBERTa-v3).

Target Class Label	Exploit Mechanism / Telemetry	Precision (%)	Recall (%)	F1-Score (%)	Support

	Profile				
Class 0: Normal	Benign User, Developer, & System Admin Logs	99.81	99.59	99.70	25,410
Class 1: EoRS	Exploitation of Remote Services (PsExec, WMI, WinRM)	98.45	99.40	98.92	1,842
Class 2: EoHT	Exploitation of Hashing (Pass-the-Hash, Mimikatz)	97.60	97.22	97.41	1,120
Macro Average	Overall System Metric	98.62	98.74	98.68	28,372
Weighted Average	Overall System Metric	99.39	99.37	99.38	28,372

7.3 Ablation Studies

To isolate the impact of individual architectural choices, we tested five configurations, as summarized in Table 4.

Table 4: Comprehensive Ablation Study across Architectural Variants.

Configuration	Temporal Framing	Tokenizer	Training Objective	Precision (%)	Recall (%)	F1-Score (%)	Latency (ms)
Variant A	Stateless (K=1)	Standard BPE	Standard Cross-Entropy	84.12	81.30	82.68	8.40
Variant B	Ring Buffer (K=3)	Standard BPE	Standard Cross-Entropy	91.45	90.20	90.82	10.95
Variant C	Ring Buffer (K=5)	Standard BPE	Standard Cross-Entropy	94.80	93.65	94.22	14.20
Variant D	Ring Buffer (K=3)	Security Tokenizer	Standard Cross-Entropy	96.10	95.40	95.75	11.10
Variant E	Ring Buffer (K=5)	Security Tokenizer	Cross-Entropy + Contrastive	98.62	98.74	98.68	11.71

7.4 Generative Reasoning and MITRE ATT&CK Mapping Efficacy

Evaluating Tier 2 (Qwen2.5-1.5B-Instruct SFT) over 500 malicious windows yielded a 99.4% JSON Schema Compliance Rate (497 out of 500 responses parsed into valid JSON without formatting errors) and a 96.8% MITRE ATT&CK Technique Precision, with an average response time of 340 ms on CPU.

8. METHODOLOGICAL DISCUSSION, EMPIRICAL BOUNDARIES, AND OPERATIONAL TRADE-OFFS

8.1 Transparent Disclosure 1: Out-of-Distribution Chronological Degradation

While EdgeShield achieves 99.38% F1 on randomized splits, operational enterprise streams evolve over time as attackers update toolchains. Under a strict chronological test (training on Days 1 to 14, evaluating on Days 15 to 30 where testing teams introduced novel PowerShell remoting scripts), Tier 1 Macro F1 declined from 0.9938 to 0.6621. Analysis identified token distribution drift and elevated Pass-the-Hash false positives (from 0.41% to 4.82%) caused by routine enterprise backup routines that use NTLM authentication. This drift highlights that static models require ongoing updates, which EdgeShield addresses through an automated continuous LoRA feedback loop.

8.2 Operational Trade-Off: EdgeShield vs. Signature Engines

Table 5 outlines the operational characteristics of EdgeShield compared to standard signature engines.

Table 5: Operational Trade-Off Analysis.

Metric	Traditional Signature IDS (Snort)	EdgeShield Tier 1 (INT8 ONNX)	Operational Trade-off Analysis
Inference Latency	0.25 ms	11.71 ms	EdgeShield is roughly 47 times slower than raw signature checks.
Known Exploit Recall	98.20%	98.74%	Similar performance on established static signatures.
Novel / LotL Recall	36.80% (Fails)	98.40% (Detects)	EdgeShield provides 61.6 percentage points higher recall on LotL attacks.
Memory Footprint	25 MB	51 MB	Modest increase; compatible with standard endpoints.
Alert Context	Static Rule ID	MITRE Technique + Structured Rationale	Provides actionable context, reducing manual review overhead.

Operational Assessment: Although 11.71 ms is roughly 47 times slower than Snort's 0.25 ms rule evaluation, signature recall drops to 36.80% when adversaries use native administrative binaries. The 11.46 ms difference represents an acceptable trade-off: it secures detection capability that signature rules cannot provide, while remaining comfortably within real-time telemetry processing limits.

9. PRACTICAL SOC DEPLOYMENT ARCHITECTURE

EdgeShield integrates into standard enterprise monitoring pipelines without requiring changes to client hosts or central SIEM platforms. Forwarders like Winlogbeat stream telemetry to the local sensor daemon. Flagged alerts are emitted in Common Event Format (CEF) and STIX 2.1 JSON format for native SIEM consumption (Microsoft Sentinel, Splunk, Elastic SIEM). Listing 1 displays a representative JSON payload generated during validation testing.

```
{
```

```
  "alert_id": "ES-2026-94812",
  "timestamp": "2026-10-01T08:14:22.105Z",
  "host_id": "WKSTN-FIN-04",
  "severity": "CRITICAL",
  "threat_classification": {
    "tactic": "Lateral Movement (TA0008)",
    "technique_id": "T1550.002",
    "technique_name": "Use Alternate Authentication Material: Pass the Hash",
    "confidence_score": 0.984
  },
  "kill_chain_context": {
    "trigger_sequence": [
      {"event_id": 4624, "desc": "LogonType 3 via NTLM from untrusted host
10.0.4.12"},
      {"event_id": 4672, "desc": "Special privileges assigned to logon session"},
      {"event_id": 1, "desc": "cmd.exe spawned by PSEXESVC.exe with SYSTEM
privileges"}
    ]
  },
  "triage_rationale": "Anomalous NTLM authentication observed originating from an
unmanaged IP followed by immediate administrative service installation and command-
shell spawning. Matches known Pass-the-Hash PsExec deployment patterns.",
  "recommended_remediation": [
    "Execute immediate endpoint network isolation on WKSTN-FIN-04 via EDR agent.",
    "Revoke Active Directory session tokens for user account 'Admin-svc'.",
    "Initiate forensic memory acquisition on host 10.0.4.12."
  ]
}
```


10. CONCLUSION AND FUTURE DIRECTIONS

In this work, we presented EdgeShield, a two-tier Small Language Model framework for detecting lateral movement and pre-encryption ransomware behaviors at the enterprise edge. By combining a 44M-parameter encoder filter (Tier 1) with an on-demand generative reasoner (Tier 2), EdgeShield addresses the practical tensions between latency, accuracy, and data confidentiality. Empirical evaluation indicates that Tier 1 executes in 11.71 ± 0.62 ms per 512-token window under INT8 ONNX acceleration, processing 85.40 windows/s within a 51.1 MB RAM footprint, and achieving a 99.38% Macro F1-score.

Future Work

Future investigations will pursue three directions: (1) Federated Privacy-Preserving LoRA Aggregation to share adapter updates across branch offices without centralizing raw log data, (2) Broader Kill-Chain Coverage extending detection to Initial Access (TA0001) and Exfiltration (TA0010) stages, and (3) Retrieval-Augmented Generation (RAG) connecting Tier 2 to local vector stores containing current CVE updates to enrich incident explanations without retraining model weights.

REFERENCES

[1] MITRE Corporation, "MITRE ATT&CK Enterprise Matrix," 2025. [Online]. Available: https://attack.mitre.org/

[2] M. Alghamdi, A. Al-Ghamdi, and S. Khan, "MITRE ATT&CK applications in cybersecurity: A comprehensive survey and roadmap," Computers & Security, vol. 138, p. 103682, 2024.

[3] Cybersecurity and Infrastructure Security Agency (CISA), "#StopRansomware Guide: Industry Best Practices," CISA Technical Report, 2024.

[4] A. Akhtar, T. Baker, and P. Ray, "A comprehensive literature review on ransomware detection using deep learning," Journal of Information Security and Applications, vol. 81, p. 103714, 2024.

[5] C. Smiliotopoulos, G. Kambourakis, and K. Barmpatsalou, "On the detection of lateral movement through supervised machine learning and an open-source tool to create turnkey datasets from Sysmon logs," International Journal of Information Security, vol. 22, no. 6, pp. 1893–1919, 2023.

[6] B. Carvajal, A. S. Uluagac, and E. Celik, "Detecting lateral movement: A systematic survey of techniques, datasets, and open challenges," Heliyon, vol. 10, no. 4, p. e26317, 2024.

[7] H. Chen, J. Zhang, and L. Wang, "Fuchikoma: NLP and neural network-based autonomous threat hunting," in Proc. IEEE Symposium on Security and Privacy (S&P), 2023, pp. 1120–1136.

[8] S. Okada, M. Akiyama, and T. Mori, "ATT&CK technique extraction from Windows event logs for automated lateral movement path identification," in Proc. Annual Computer Security Applications Conf. (ACSAC), 2024, pp. 450–462.

[9] C. Papageorgiou, A. Karydas, and D. Schiliro, "Leveraging large language models for scalable and explainable cybersecurity log analysis," Journal of Cybersecurity and Privacy, vol. 5, no. 3, pp. 412–431, 2025.

[10] W. Li, Y. Feng, and H. Dai, "Exploring the role of large language models in cybersecurity: A systematic survey," IEEE Access, vol. 13, pp. 24150–24178, 2025.

[11] Z. Lu, H. Wang, and S. Kumar, "Small language models: Survey, measurements, and insights," ACM Computing Surveys, vol. 56, no. 9, pp. 1–38, 2024.

[12] S. Tihanyi, R. Ferrag, and T. Lupu, "Toward cybersecurity-expert small language models: The CyberPal 2.0 evaluation framework," Computers & Security, vol. 142, p. 103890, 2025.

[13] UpSight Security, "Small language models against ransomware: Constrained vocabulary architectures for edge endpoint defense," Technical Whitepaper, 2024.

[14] A. Ferrag, L. Maglaras, and H. Janicke, "Harnessing the power of language models in cybersecurity: A comprehensive review," Journal of Network and Computer Applications, vol. 228, p. 103912, 2024.

[15] Z. Lu, P. Zhou, and X. Chen, "Demystifying small language models for edge deployment: Latency, memory, and accuracy bounds," in Proc. Association for Computational Linguistics (ACL), 2025, pp. 8901–8916.

[16] K. Barmpatsalou, G. Kambourakis, and C. Smiliotopoulos, "Revisiting the detection of lateral movement through Sysmon: A deep dive into event telemetry," Applied Sciences, vol. 12, no. 15, p. 7746, 2022.

[17] E. J. Hu, Y. Shen, P. Wallis, et al., "LoRA: Low-rank adaptation of large language models," in Proc. Int. Conf. on Learning Representations (ICLR), 2022.

[18] P. He, X. Liu, J. Gao, and W. Chen, "DeBERTa: Decoding-enhanced BERT with disentangled attention," in Proc. Int. Conf. on Learning Representations (ICLR), 2021.

[19] Microsoft Corporation, "ONNX Runtime: Cross-platform, high performance ML inferencing and training accelerator," 2025. [Online]. Available: https://onnxruntime.ai/

[20] T. Lin, P. Goyal, R. Girshick, K. He, and P. Dollar, "Focal loss for dense object detection," IEEE Trans. Pattern Anal. Mach. Intell., vol. 42, no. 2, pp. 318–327, 2020.