

Contents

1	Introduction	1
2	Matching Problems and Algorithms	2
2.1	Definitions	2
2.2	Maximum Bipartite Matching	3
2.3	The Stable Marriage Problem	13
3	Polyhedral Approaches to Matching Problems	18

List of Figures

List of Tables

Chapter 1

Introduction

Chapter 2

Matching Problems and Algorithms

2.1 Definitions

Let $G = (V, E)$ be an undirected graph with $|V| = n$ vertices and $|E| = m$ edges. We call G bipartite if we can partition its vertex set into two sets V_1, V_2 such that for each edge $u, v \in E$, $u \in V_1$ and $v \in V_2$. If every vertex of V_1 is adjacent to every vertex of V_2 and $|V_1| = n_1, |V_2| = n_2$, then we call G a complete bipartite graph and denote it by K_{n_1, n_2} . By a path, we mean a simple path, i.e., a path in which no vertex is repeated. The length of a path is the number of edges it contains.

From set theory, we recall that the symmetric difference of two sets A and B , denoted by $A \triangle B$, is the set of elements that belong to A or B but not both. Thus, $A \triangle B = (A \setminus B) \cup (B \setminus A) = (A \cup B) \setminus (A \cap B)$. Also, if we want to add an element x to set A , we shall use the shorthand $A + x := A \cup \{x\}$, and if we to remove it $A - x := A \setminus \{x\}$.

We write $T(n) = O(f(n))$ if and only if there exist positive constants c and n_0 such that $T(n) \leq cf(n)$ for all $n \geq n_0$. Most of the time, $T(n)$ will denote a bound on the worst-case running time of an algorithm defined on the positive integers. Similarly, we say that $T(n) = \Omega(f(n))$ if and only if there exist positive constants c and n_0 such that $T(n) \geq cf(n)$ for all $n \geq n_0$. Finally, we say that $T(n) = \Theta(f(n))$ if and only if $T(n) = O(f(n))$ and $T(n) = \Omega(f(n))$.

A matching of a graph $G = (V, E)$ is a subset of E such that each vertex is incident to at most one edge of the subset. The cardinality of a matching is the number of edges it contains. A vertex is called matched if it is incident to an edge of M . Otherwise, it is called unmatched or free. A matching is called maximal if no edge can be added without violating the matching property. A matching is maximum if no other matching has more edges. Clearly, every maximum matching is maximal (the converse is not always true). The following two definitions are fundamental in the study of matchings.

Definition 2.1.1. A path P in G with respect to a matching M is called alternating if its edges are alternatingly out of and in M .

Definition 2.1.2. A path P in G with respect to a matching M is called augmenting if it is alternating and its endpoints are free.

It is straightforward to see that every augmenting path has odd length. We will use the term M -augmenting whenever we want to emphasize the matching M .

2.2 Maximum Bipartite Matching

In this section, we present two famous algorithms for finding a maximum bipartite matching and prove their correctness.

The first algorithm is derived from a theorem of Berge [Ber57], previously observed by Petersen [Pet91].

Theorem 2.2.1. *Let $G = (V, E)$ be a graph and let M be a matching in G . Then M is maximum if and only if there is no M -augmenting path in G .*

Proof. Suppose that M is maximum. For the sake of contradiction, assume that there exists an M -augmenting path P with u and v as its endpoints in G . Then we can see that the matching $M' = M \triangle E(P)$ is a valid matching in G and satisfies $|M'| = |M| + 1$. Indeed, if we remove all edges of P that belong to M and add the remaining ones to M , we add one more edge to M in total (because P has odd length). The new matching is valid because u and v were free, and they were not incident to any matching edge, and every internal vertex of P remains incident to exactly one edge. All vertices outside P are unaffected. As a result, the new matching M' is valid and its cardinality is greater than that of M . This is a contradiction.

Now suppose that G does not contain any M -augmenting path and that a matching M' exists in G such that $|M'| > |M|$. Consider the graph $M_0 = M \triangle M'$. Each vertex in M_0 may be matched in both matchings or in either one. So, every vertex has degree at most 2. Hence, every component of M_0 is either a path or a cycle of even length (otherwise, there would exist a vertex that is incident to two edges in the same matching). Because M_0 has more edges of M' than of M , this also means that there exists a path P with more edges of M' than of M , and because the edges are alternating, P is an M -augmenting path, which contradicts our assumption that G does not contain any M -augmenting path. $\square$

Augmenting-Path Algorithm. Based on the theorem above, we can write an algorithm that will try to find an augmenting path, alternate its edges (this will increase the size of the current matching by one), and repeat the whole process until we can't find any augmenting path. $N(v)$ represents all the vertices u such that $\{v, u\} \in E(G)$.

Algorithm 2.1 Augmenting Path Algorithm

Require: Graph $G = (V, E)$, vertex v

Ensure: Array *matched* such that $matched[u] = v$ and $u \in V_2$ and $v \in V_1$ if and only if $\{u, v\} \in E(G)$ belongs to the matching

```
1: function DfsAugmentingPath(int  $v$ , bool visited[], int matched[])
2:   if visited[ $v$ ] then
3:     return FALSE;
4:   end if
5:   visited[ $v$ ]  $\leftarrow$  TRUE;
6:   for all  $u \in N(v)$  do
7:     if  $matched[u] = \emptyset$  or DfsAugmentingPath(matched[ $u$ ], visited, matched) then
8:       matched[ $u$ ]  $\leftarrow v$ ;
9:       return TRUE;
10:    end if
11:  end for
12:  return FALSE;
13: end function
```

Algorithm 2.1 is getting called from all vertices in the left part of bipartite graph (let's call it V_1). We will use an extra array called *visited* to track the vertices from V_1 that we have already visited across the path and we have to reset it to be false for all these vertices before the initial call. Array *matched* marks the matched vertices only from the right part of the bipartite graph (let's call it V_2). To get the edges of the matching, we simply take all the edges $\{v, matched[v]\}$ such that *matched*[v] is not empty and store them to set *matching*.

Algorithm 2.2 Maximum Bipartite Matching in $O(nm)$

Require: Bipartite graph $G = (V_1 \cup V_2, E)$

Ensure: Array *matching* that corresponds to the edges of the maximum matching

```
1: function MainAugmentingPath(int  $v$ , bool visited[], set matching)
2:   for all  $v \in V_2$  do
3:     matched[ $v$ ]  $\leftarrow \emptyset$ ;
4:   end for
5:   for all  $v \in V_1$  do
6:     for all  $u \in V_1$  do
7:       dist[ $i$ ]  $\leftarrow$  FALSE;
8:     end for
9:     DfsAugmentingPath( $v$ , visited, matched);
10:  end for
11:  matching  $\leftarrow \emptyset$ ;
12:  for all  $v \in V_2$  do
13:    if matched[ $v$ ]  $\neq \emptyset$  then
14:      matching  $\leftarrow matching \cup \{\{matched[v], v\}\}$ ;
15:    end if
16:  end for
17:  return matching;
18: end function
```

The idea is that if the initial call is from a free vertex, say v , and we cannot find another

free vertex u such that the edge $\{v, u\}$ exists, then we simply try to find a path (v, x, y) such that $\{v, x\}$ is not in the matching, but $\{x, y\}$ is, so we can start trying again from the vertex y , until we find a free vertex and then recursively alternate the path.

Lemma 2.2.2. *If we call [Algorithm 2.1](#) from a free vertex v and augmenting path with endpoint v exists, then it will return TRUE and alternate its edges.*

Proof. Suppose that a free vertex $u \in V_2$ exists such that $\{v, u\} \in E(G)$. Then from line 7 the algorithm successfully finds an augmenting path. Now suppose that such a vertex doesn't exist and $P = (v, v_1, v_2, \dots, u)$ any augmenting path with endpoint the vertex v . Since P is alternating, the edge $\{v, v_1\}$ does not belong to the matching, while $\{v_1, v_2\}$ does. Because the algorithm checks all neighbors of v (line 6), it will eventually examine v_1 (assuming that all the other neighbors - if they exist - return false), and line 7 does a recursive call for $matched[v_1] = v_2$ (note that v_2 is impossible to be visited, otherwise an alternative path $(v, \dots, v_2)$ exists and the algorithm would have already found another augmenting path from that recursive call to u or to another free vertex). Repeating the same argument along P , the algorithm eventually reaches the free vertex $u \in V_2$, where line 7 is true since $matched[u] = \emptyset$. The recursive calls then return TRUE and update the array $matched$ accordingly, thus alternating the edges of P . $\square$

From this, we get the following remark.

Remark 2.2.3. *After an initial call of [Algorithm 2.1](#) from a free vertex $v \in V_1$, the only vertices that can become matched are v and one free vertex of V_2 . If no augmenting path is found, then the matching remains unchanged.*

Then, we can prove the following lemma.

Lemma 2.2.4. *Every initial call to [Algorithm 2.1](#) from [Algorithm 2.2](#) takes a free vertex as parameter.*

Proof. This is obviously true in the first iteration. Assume that we are at iteration i , and that the statement holds for all previous iterations. Let v be the vertex from which we are about to initially call [Algorithm 2.1](#). If v is free, then we are done. If it is not, v must have become matched during some previous iteration. However, by [Remark 2.2.3](#), in each iteration the only vertex of V_1 that can become matched is the vertex from which [Algorithm 2.1](#) was initially called. Since [Algorithm 2.1](#) has never been initially called from v before iteration i , the vertex v could not have become matched earlier. $\square$

The output of the [Algorithm 2.2](#) (set matching) is always a valid matching. Since the algorithm initializes with an empty matching and only updates it by alternating edges along valid augmenting paths starting from free vertices ([Lemma 2.2.2](#)), the maintained set of edges is always a valid matching. Now we have to prove that it is maximum.

Theorem 2.2.5. *[Algorithm 2.2](#) returns a maximum matching.*

Proof. Let $v_1, v_2, \dots, v_k$ be the vertices of V_1 in the order in which [Algorithm 2.2](#) processes them. For each $i \in \{0, 1, \dots, k\}$, let M_i be the matching after the first i iterations of the algorithm, with $M_0 = \emptyset$. Also, let G_i be the subgraph of G induced by the vertex set

$$\{v_1, v_2, \dots, v_i\} \cup V_2.$$

We will prove by induction on i that M_i is a maximum matching of G_i .

For $i = 0$, the graph G_0 has no vertices in V_1 , so the empty matching M_0 is trivially maximum.

Now assume that M_i is a maximum matching of G_i , and consider iteration $i + 1$, where the algorithm processes the vertex v_{i+1} . By [Lemma 2.2.4](#), the initial call to [Algorithm 2.1](#) is made from a free vertex. We consider two cases.

Case 1: $DfsAugmentingPath(v_{i+1})$ ([Algorithm 2.1](#) with parameter the vertex v_{i+1}) returns TRUE. Then, by [Lemma 2.2.2](#), the algorithm finds an augmenting path in G_{i+1} with endpoint v_{i+1} and alternates its edges. Therefore,

$$|M_{i+1}| = |M_i| + 1.$$

On the other hand, any matching of G_{i+1} can use at most one edge incident to the new vertex v_{i+1} . Hence, by removing that edge if it exists, we obtain a matching of G_i , and therefore every matching of G_{i+1} has size at most $|M_i| + 1$. Since M_i is maximum in G_i , it follows that M_{i+1} is a maximum matching of G_{i+1} .

Case 2: $DfsAugmentingPath(v_{i+1})$ returns FALSE. Then, again by [Lemma 2.2.2](#), there is no M_i -augmenting path in G_{i+1} with endpoint v_{i+1} . Since M_i is maximum in G_i , [Theorem 2.2.1](#) implies that there is no M_i -augmenting path contained entirely in G_i . Thus, there is no M_i -augmenting path in G_{i+1} at all, because any augmenting path in G_{i+1} that is not contained in G_i must involve the only new vertex of V_1 , namely v_{i+1} . Therefore, by [Theorem 2.2.1](#), M_i is already a maximum matching of G_{i+1} . Since the matching does not change in this case, we have

$$M_{i+1} = M_i,$$

and so M_{i+1} is a maximum matching of G_{i+1} .

In both cases, M_{i+1} is a maximum matching of G_{i+1} . This completes the induction. $\square$

Before each search, we initialize the visited array which takes $O(n)$ time. We call $DfsAugmentingPath$ for each vertex $v \in V_1$ searching for an augmenting path. To find an augmenting path, we will visit each vertex and each edge at most once (similar to the classic DFS), so the total complexity is $O(nm)$ when $m = \Omega(n)$.

Hopcroft-Karp Algorithm Hopcroft and Karp [[HK73](#)] provided a faster algorithm, again based on finding augmenting paths, but in a smarter way. The algorithm runs in phases. In each phase, we find a maximal set of vertex-disjoint shortest M -augmenting paths and take the symmetric difference of the current matching M with the union of these paths. The process stops when no augmenting path can be found.

Our implementation is based on the version of Shimon Even and Alon Itai, who made significant modifications to Dinic's algorithm for the maximum flow problem [[Din70](#), [Din06](#)]. As we will see at the end of this section, maximum flow and maximum bipartite matching are closely connected problems.

The key idea of the algorithm is to efficiently find these paths and alternate their edges. To do that, we construct a new graph called the layered network. We describe this graph with an array called `level`, defined on the vertices of V_1 . Initially, every free vertex of V_1 gets level 1. Then, if a vertex $u \in V_1$ has level i , every vertex of V_1 that can be reached from u by first taking an unmatched edge to a vertex of V_2 and then a matched edge back to V_1 gets level $i + 1$, provided it has not already received a level. The vertices are visited in Breadth-First Search (BFS) order, starting from all free vertices of V_1 . In this way, `level[v]`

represents the minimum alternating distance of $v \in V_1$ from the set of free vertices of V_1 in the current phase. If all edges in the layered network are directed from a source vertex in V_1 to a destination vertex in V_2 , it is clear that the resulting graph is a dag (directed acyclic graph).

Algorithm 2.3 BFS Layered Network Construction

Require: Bipartite graph $G = (V_1 \cup V_2, E)$, arrays $next$, $prev$ represent the current matching

Ensure: Array $level$ for the vertices of V_1 describes the layered network

```

1: function BfsLayeredNetwork(int  $next[]$ , int  $prev[]$ , int  $level[]$ )
2:    $treeDepth \leftarrow 0$ ;
3:   initialize empty queue  $Q$ ;
4:   for all  $u \in V_1$  do
5:     if  $next[u] = \emptyset$  then
6:        $level[u] \leftarrow 1$ ;
7:        $Q.push(u)$ ;
8:     end if
9:   end for
10:  while not  $Q.isEmpty()$  do
11:     $u \leftarrow Q.pop()$ ;
12:    for all  $x \in N(u)$  do
13:      if  $prev[x] = \emptyset$  then
14:         $treeDepth \leftarrow level[u]$ ;
15:        continue;
16:      end if
17:      if  $prev[x] = u$  then
18:        continue;
19:      end if
20:      if  $level[prev[x]] = 0$  then
21:         $level[prev[x]] \leftarrow level[u] + 1$ ;
22:         $Q.push(prev[x])$ ;
23:      end if
24:    end for
25:    if  $treeDepth \neq 0$  then
26:      break;
27:    end if
28:  end while
29:  for all  $u \in V_1$  do
30:    if  $level[u] > treeDepth$  then
31:       $level[u] \leftarrow 0$ ;
32:    end if
33:  end for
34:  return ( $treeDepth \neq 0$ );
35: end function

```

The first time we encounter a free vertex in V_2 , we determine the last useful level in the current phase and we store it in the variable $treeDepth$. From that, we can also determine the length of a shortest augmenting path in the current phase (which is $2 \cdot treeDepth - 1$). We do not need to continue the BFS deeper than that level and the vertices that remain

in the queue belong either to the same level or to the next one. The vertices of the same level may still be used in the searching step to find other shortest augmenting paths, since we have already assigned their correct level. On the other hand, vertices that have already been assigned level $treeDepth + 1$ correspond to longer paths, so we reset their level to 0.

We define an array $next$ for every $v \in V_1$ such that $next[v] = u$ if and only if the edge $\{v, u\}$ belongs to the current matching; otherwise, $next[v] = \emptyset$. Similarly, for every $u \in V_2$, we define $prev[u] = v$ if and only if the edge $\{u, v\}$ belongs to the current matching; otherwise, $prev[u] = \emptyset$. Thus, the arrays $next$ and $prev$ represent the current matching and are updated whenever we find an augmenting path and alternate its edges.

Theorem 2.2.6. *Algorithm 2.3 correctly computes the array level of the layered network of the current matching M . More precisely, if it returns FALSE, then no M -augmenting path exists in G . Otherwise, for every vertex $v \in V_1$, we have $level[v] \neq 0$ if and only if there exists an M -alternating path from a free vertex of V_1 to v . Moreover, if $level[v] \neq 0$, then the length of a shortest such path is $2 \cdot level[v] - 2$.*

Proof. For every free vertex $v \in V_1$, the algorithm sets $level[v] = 1$, and the corresponding alternating path has length 0. Now suppose that a vertex $u \in V_1$ is popped from the queue and that the statement already holds for u . Let $x \in V_2$ be a neighbor of u .

If $prev[x] = \emptyset$, then extending a shortest alternating path to u by the edge $\{u, x\}$ gives an M -augmenting path of length $2 \cdot level[u] - 1$. If $prev[x] = u$, then $\{u, x\}$ is a matched edge and cannot be used to continue an alternating path. Otherwise, if $prev[x] = w \neq u$ and $level[w] = 0$, then by appending the unmatched edge $\{u, x\}$ and the matched edge $\{x, w\}$ to a shortest alternating path ending at u , we obtain an alternating path from a free vertex of V_1 to w of length $(2 \cdot level[u] - 2) + 2 = 2 \cdot (level[u] + 1) - 2$. Hence, the algorithm correctly sets $level[w] = level[u] + 1$. Since vertices are processed in BFS order, this is the minimum possible alternating distance to w .

Therefore, for every vertex $v \in V_1$ with $level[v] \neq 0$, the value $level[v]$ is exactly the level of v in the layered network, and the length of a shortest alternating path from a free vertex of V_1 to v is $2 \cdot level[v] - 2$.

Finally, if the algorithm returns FALSE, then no free vertex of V_2 is reached during the BFS. Therefore, there is no M -augmenting path in G . Indeed, if such a path existed, then the vertex just before its free endpoint on a shortest such path would lie in the layered network, and the free vertex in V_2 would also be reached. $\square$

Corollary 2.2.7. *If Algorithm 2.3 returns TRUE, then the length of a shortest M -augmenting path is $2 \cdot treeDepth - 1$.*

The searching step, Algorithm 2.4, is almost the same as Algorithm 2.1, so we will omit the proof. This time, we move across the layered network based on the $level$ array. We also use an array ptr for all vertices in V_1 . This array, holds for each vertex a counter that indicates the first neighbor that has not been checked yet. Hence, if we return to the same vertex in the same phase, we do not examine again the neighbors that have already returned FALSE. In particular, if $ptr[u]$ reaches the end of the adjacency list of u , then no augmenting path can be found through u in the current phase.

We could of course combine the two *if* statements into one.

Algorithm 2.4 DFS Phase of Hopcroft-Karp

Require: Bipartite graph $G = (V_1 \cup V_2, E)$, vertex $u \in V_1$, arrays $next$, $prev$, $level$, ptr

Ensure: Returns TRUE if a shortest augmenting path is found from u

```
1: function DfsHopcroftKarp(int  $u$ , int  $next[]$ , int  $prev[]$ , int  $level[]$ , int  $ptr[]$ )
2:   for  $ptr[u]$  to  $|N(u)| - 1$  do
3:      $x \leftarrow$  the  $ptr[u]$ -th neighbor of  $u$ ;
4:     if  $prev[x] = \emptyset$  then
5:        $prev[x] \leftarrow u$ ;
6:        $next[u] \leftarrow x$ ;
7:        $ptr[u] \leftarrow |N(u)|$ ;
8:       return TRUE;
9:     end if
10:    if  $level[prev[x]] = level[u] + 1$  and  $DfsHopcroftKarp(prev[x], next, prev, level,$ 
     $ptr)$  then
11:       $prev[x] \leftarrow u$ ;
12:       $next[u] \leftarrow x$ ;
13:       $ptr[u] \leftarrow |N(u)|$ ;
14:      return TRUE;
15:    end if
16:  end for
17:  return FALSE;
18: end function
```

Algorithm 2.5 and lines 9-21 run the phases of the algorithm. In each phase, we call **Algorithm 2.3** (line 9) to construct the layered network, find all augmenting paths of this graph by calling **Algorithm 2.4** for each free vertex of V_1 (lines 13-17), and repeat the whole process. Note that we have to initialize the ptr array to 0 before starting the search, because all vertices will check their first neighbor first. We also have to initialize the $level$ array to zero before building the layered network. The set *matching* contains the edges of the maximum matching.

Algorithm 2.5 Hopcroft–Karp Algorithm

Require: Bipartite graph $G = (V_1 \cup V_2, E)$

Ensure: Array *matching* contains the edges of the maximum matching

```
1: function HopcroftKarp( )
2:   for all  $u \in V_1$  do
3:      $next[u] \leftarrow \emptyset$ ;
4:      $level[u] \leftarrow 0$ ;
5:   end for
6:   for all  $x \in V_2$  do
7:      $prev[x] \leftarrow \emptyset$ ;
8:   end for
9:   while BfsLayeredNetwork(next, prev, level) do
10:    for all  $u \in V_1$  do
11:       $ptr[u] \leftarrow 0$ ;
12:    end for
13:    for all  $u \in V_1$  do
14:      if  $next[u] = \emptyset$  then
15:        DfsHopcroftKarp( $u$ , next, prev, level, ptr);
16:      end if
17:    end for
18:    for all  $u \in V_1$  do
19:       $level[u] \leftarrow 0$ ;
20:    end for
21:  end while
22:  matching  $\leftarrow \emptyset$ ;
23:  for all  $u \in V_1$  do
24:    if  $next[u] \neq \emptyset$  then
25:      matching  $\leftarrow matching \cup \{\{u, next[u]\}\}$ ;
26:    end if
27:  end for
28:  return matching;
29: end function
```

It is evident that constructing the layered network takes no more than $O(n + m)$. Moreover, lines 13-17 take no more than $O(n + m)$ as each edge is examined at most once (with the help of *ptr* array) and as a result when vertex returns FALSE, we are not going to process it again in the current phase.

Lemma 2.2.8. *Each phase, that is calculating the maximal set of vertex-disjoint shortest M -augmenting paths and take the symmetric difference with current matching M takes no more than $O(n + m)$ time.*

We shall show that we need at most $O(\sqrt{n})$ phases, but before that, we have to prove some important lemmas.

Lemma 2.2.9. *Let M and M' be two matchings of a graph G , with $|M'| > |M|$. Then the graph $M \triangle M'$ contains at least $|M'| - |M|$ vertex-disjoint M -augmenting paths.*

Proof. We follow the same logic as in [Theorem 2.2.1](#). We consider the graph $M^* = M \triangle M'$. We can see that the graph contains components, each of which is an alternating path

or an even-length cycle. Cycles have the same number of edges from M and M' , and the same holds for alternating paths of even length. Each component that represents an augmenting path has one more edge from one matching than from the other. In fact, every M -augmenting path has one more edge from M' than M . From $|M'| > |M|$, we can see that we have more M -augmenting paths than M' -augmenting paths, and there must be at least $|M'| - |M|$ such paths. This completes the proof. $\square$

The following is a special case of [Lemma 2.2.9](#).

Lemma 2.2.10. *Given a matching M and a maximum matching M^* , the graph contains $|M^*| - |M|$ vertex-disjoint M -augmenting paths.*

Lemma 2.2.11. *Let $P = \{P_1, P_2, \dots, P_t\}$ be a maximal set of vertex-disjoint shortest M -augmenting paths with length x obtained during a single phase of [Algorithm 2.5](#) and $M' = M \triangle (P_1 \cup P_2 \cup \dots \cup P_t) = M \triangle P_1 \triangle P_2 \triangle \dots \triangle P_t$ with Q be an M' -augmenting path. The set $R = (P_1 \cup P_2 \cup \dots \cup P_t) \triangle Q$ has at least $x(t+1)$ edges.*

Proof. From $M' = M \triangle (P_1 \cup P_2 \cup \dots \cup P_t)$, we have

$$P_1 \cup P_2 \cup \dots \cup P_t = M \triangle M'$$

That is,

$$R = (M \triangle M') \triangle Q = M \triangle (M' \triangle Q)$$

As Q is an M' -augmented path, $M' \triangle Q$ has size of $|M'| + 1 = |M| + t + 1$ (plus $t + 1$ because it will get $t + 1$ more edges from alternating the paths of P and the path Q). By [Lemma 2.2.9](#), there is at least $|M' \triangle Q| - |M| = t + 1$ M -augmenting paths. Because every M -augmenting path has length at least x , it follows that R has at least $x(t+1)$ edges. $\square$

Lemma 2.2.12. *The length of the shortest augmenting path increases in every phase.*

Proof. Let's assume that the current matching is M and denote by $P = \{P_1, P_2, \dots, P_t\}$ the maximal set of vertex-disjoint shortest M -augmenting paths of length x in one phase of [Algorithm 2.5](#). Moreover, suppose that we take $M' = M \triangle (P_1 \cup P_2 \cup \dots \cup P_t)$ (the matching that we get at the end of phase) and let Q be an M' -augmenting path. Obviously, Q has a common vertex v with at least one path from P , otherwise, it would mean that Q is also in M and either $|Q| > x$ (in this case we are done) or it would contradict the maximality of the set. Let $R = (P_1 \cup P_2 \cup \dots \cup P_t) \triangle Q$. From [Lemma 2.2.11](#), R has at least $x(t+1)$ edges. Let $P_i \in P$ such that $v \in P_i$. We observe that v is incident with a matched edge in M' because at the end of the phase we alternate the edges of each path in P . The endpoints of Q do not belong to M' because they are free, so it is guaranteed that v is an internal vertex of Q and therefore it is also incident with a matched edge in M' . Obviously, it's impossible for v to be incident with two different matched edges from M' , so P_i and Q have at least one edge from M' in common. It follows that

$$xt + x \leq |R| \leq |P_1 \cup P_2 \cup \dots \cup P_t \cup Q| \leq xt + |Q| - 1$$

and hence $x + 1 \leq |Q|$. $\square$

Lemma 2.2.13. [Algorithm 2.5](#) performs at most $O(\sqrt{n})$ phases.

Proof. Assume that we have already performed $\sqrt{n}$ phases and the current matching is M . From [Lemma 2.2.10](#), we know that there exist exactly $|M^*| - |M|$ vertex-disjoint M -augmenting paths for a maximum matching M^* . From [Lemma 2.2.12](#) all these augmenting paths will have length at least $\sqrt{n}$, so there cannot be more than $\sqrt{n}$ (we would need more than n vertices) of them, which means that, $|M^*| - |M| \leq \sqrt{n}$. It follows from this that we can't perform more than $\sqrt{n}$ phases from that point. We conclude that the total phases can't be more than $2\sqrt{n} = O(\sqrt{n})$. $\square$

From [Lemma 2.2.8](#) and [Lemma 2.2.13](#) we get the complexity of Hopcroft-Karp algorithm.

Theorem 2.2.14. *Algorithm 2.5 returns a maximum matching in $O((n + m)\sqrt{n})$ time.*

Maximum Bipartite Matching from Max-Flows We can reduce the bipartite maximum matching problem to the maximum flow problem by adding two extra nodes to the initial graph. The first vertex is called the source and will point to all vertices in V_1 with directed edges, and the second vertex is called the sink, with all vertices from V_2 pointing to it. Moreover, all the edges of the initial graph will turn into directed edges, pointing to V_2 from a vertex of V_1 . Assuming capacities of one for each edge (so there exists an integral maximum flow, that is every edge will have flow of 0 or 1), the maximum flow from source to sink is equal to the maximum bipartite matching. Actually, it is easy to see this because all paths that carry flow from source to sink should be edge-disjoint, and each path will have exactly one edge from V_1 to V_2 , so no other path can use this edge again. We can get a maximum flow in the resulting graph from a maximum matching in the initial graph by just taking all the edges of matching and picking the edge from source to the V_1 vertex, and the edge from V_2 to the sink.

Consequently, someone could make the above reduction and use a famous flow algorithm, like Dinic [[Din70](#)] to solve the maximum bipartite problem with $O(n^2m)$. It turns out, that using some kind of the arguments we talked before, that Dinic's algorithm will perform with the same complexity as Hopcroft-Karp algorithm.

Recent Research Maximum flow is one of the most well-known problems in computer science and has been studied extensively over the years. Finding faster algorithms for the maximum flow problem, and especially for the minimum-cost flow problem (to which maximum flow can be reduced), could lead to breakthroughs in many areas. For a long time, algorithms based primarily on combinatorial methods were far from the almost-linear-time bounds achieved by more recent continuous techniques. In 2023, a deterministic $m^{1+o(1)}$ -time algorithm for exact maximum flow and minimum-cost flow was discovered [[BCK⁺23](#)]. This line of work also implies an $m^{1+o(1)}$ -time algorithm for the maximum bipartite matching problem. On the other hand, randomized combinatorial algorithms were later obtained independently for exact maximum flow [[BBST24](#)] and for maximum bipartite matching [[CK24](#)].

2.3 The Stable Marriage Problem

Assume that we are given a set of n men $\{m_1, m_2, \dots, m_n\}$ and n women $\{w_1, w_2, \dots, w_n\}$, where each man has a strict preference ranking over all n women, and each woman also has a strict preference ranking over all n men. We say that a *matching* is a set of unordered pairs consisting of a man and a woman (similarly to the previous section, where we considered the undirected edges of a bipartite graph) and each of them appears at most once. A *marriage* is a perfect matching between men and women, meaning that every man and every woman is matched exactly once. A marriage is *unstable* if there exists a pair $\{m_i, w_j\}$ that does not belong to the matching such that m_i prefers w_j over his actual partner, and w_j prefers m_i over her actual partner. We call such a pair a *blocking pair*. Otherwise, we say that it is *stable*.

The following example shows a stable marriage.

Example 2.3.1. Consider an instance of four men

$$\{m_1, m_2, m_3, m_4\}$$

and four women

$$\{w_1, w_2, w_3, w_4\}.$$

The preference lists of the men are given by

man	1 st	2 nd	3 rd	4 th
m_1	w_1	w_2	w_3	w_4
m_2	w_2	w_1	w_3	w_4
m_3	w_3	w_4	w_1	w_2
m_4	w_4	w_3	w_1	w_2

and the preference lists of the women are

woman	1 st	2 nd	3 rd	4 th
w_1	m_2	m_1	m_3	m_4
w_2	m_1	m_2	m_3	m_4
w_3	m_4	m_3	m_1	m_2
w_4	m_3	m_4	m_1	m_2

Now consider the matching

$$M = \{\{m_1, w_2\}, \{m_2, w_1\}, \{m_3, w_4\}, \{m_4, w_3\}\}.$$

We can see that M is stable. Indeed, each woman is matched to her first choice:

w_1 is matched with m_2 , w_2 is matched with m_1 , w_3 is matched with m_4 , w_4 is matched with m_3 .

Hence, no woman prefers any other man to her assigned partner. Therefore, no blocking pair can exist, since a blocking pair would require both agents to prefer each other over their current partners. Consequently, M is a stable matching. Moreover, this stable matching is not unique, since

$$M' = \{\{m_1, w_1\}, \{m_2, w_2\}, \{m_3, w_3\}, \{m_4, w_4\}\}$$

is also stable.

Example 2.3.2. Consider an instance of four men

$$\{m_1, m_2, m_3, m_4\}$$

and four women

$$\{w_1, w_2, w_3, w_4\}.$$

The preference lists of the men are given by

man	1 st	2 nd	3 rd	4 th
m_1	w_1	w_2	w_3	w_4
m_2	w_2	w_3	w_1	w_4
m_3	w_2	w_1	w_4	w_3
m_4	w_3	w_4	w_1	w_2

and the preference lists of the women are

woman	1 st	2 nd	3 rd	4 th
w_1	m_3	m_1	m_2	m_4
w_2	m_1	m_2	m_3	m_4
w_3	m_2	m_4	m_1	m_3
w_4	m_4	m_3	m_1	m_2

Now consider the matching

$$M = \{\{m_1, w_1\}, \{m_2, w_2\}, \{m_3, w_4\}, \{m_4, w_3\}\}.$$

We claim that M is not stable. Indeed, the pair $\{m_3, w_1\}$ is a blocking pair, since m_3 prefers w_1 to w_4 , while w_1 prefers m_3 to m_1 . Thus, both m_3 and w_1 prefer each other to their assigned partners under M . Hence, M admits a blocking pair and therefore it is not a stable matching.

Gale and Shapley [GS62] provided an algorithm that always outputs a stable marriage. The algorithm is quite simple. In each iteration of the algorithm, we try to match a man who is not matched to any woman by proposing to the woman he currently prefers most, and the woman accepts the best proposal she receives. If a man is matched with a woman and she later receives a better proposal, then she will leave her current partner and accept that proposal. The man will become unmatched again, and we will try to match him again in a later iteration, starting from the next woman in his preference list.

Algorithm 2.6 Gale–Shapley Algorithm

Require: Preference arrays men , $women$ and their size n

Ensure: Array $manPartner$ contains a stable matching

```
1: function StableMarriage(int  $n$ , int  $men[][]$ , int  $women[][]$ )
2:   initialize empty queue  $Q$ ;
3:   for  $i \leftarrow 0$  to  $n - 1$  do
4:      $ptr[i] \leftarrow 0$ ;
5:      $womanPartner[i] \leftarrow \emptyset$ ;
6:      $manPartner[i] \leftarrow \emptyset$ ;
7:      $Q.push(i)$ ;
8:   end for
9:   for  $i \leftarrow 0$  to  $n - 1$  do
10:    for  $j \leftarrow 0$  to  $n - 1$  do
11:       $rank[i][women[i][j]] \leftarrow j$ ;
12:    end for
13:  end for
14:  while not  $Q.isEmpty()$  do
15:     $m \leftarrow Q.pop()$ ;
16:    while  $manPartner[m] = \emptyset$  do
17:       $w \leftarrow men[m][ptr[m]]$ ;
18:       $ptr[m]++$ ;
19:      if  $womanPartner[w] = \emptyset$  then
20:         $womanPartner[w] \leftarrow m$ ;
21:         $manPartner[m] \leftarrow w$ ;
22:      else
23:        if  $rank[w][m] < rank[w][womanPartner[w]]$  then
24:           $manPartner[m] \leftarrow w$ ;
25:           $Q.push(womanPartner[w])$ ;
26:           $manPartner[womanPartner[w]] \leftarrow \emptyset$ ;
27:           $womanPartner[w] \leftarrow m$ ;
28:        end if
29:      end if
30:    end while
31:  end while
32:  return  $manPartner$ ;
33: end function
```

The input of the algorithm is the size n and the preference lists $women$ and men . $women[i]$ is the preference list of woman i and $men[j]$ is the preference list of man j . Arrays $womanPartner$ and $manPartner$ represent the current matching. We will use two extra arrays that will help us see if a proposal can be made and whether it benefits us. Array ptr will store, for a man i , the most highly preferred woman that he has not proposed to yet. With this array, we will be able to know the answer immediately. Array $rank$ will help us determine, for a woman, whether she prefers the current matched man or the proposing one in $O(1)$. Specifically, for a woman i , we store at $rank[i][j]$ the position of the man j in her preference list. This (lines 9-13), requires $O(n^2)$ preprocessing. In lines 14 – 31 we perform the proposals.

See that if a woman receives a proposal, then she will either accept it or stay with her

current matching. This leads to the following lemma.

Lemma 2.3.3. *After a woman receives a match, she never becomes unmatched again.*

Note that it is not necessary to check whether $ptr[m]$ becomes greater than $n - 1$, which would mean that we popped a man who is unmatched, but all the women are already matched.

Lemma 2.3.4. *Algorithm 2.6 always halts and produces a marriage.*

Proof. Assume that a man gets popped in line 15, which means that he is unmatched, but has already proposed to all women. Then every woman has rejected him for some other man and, by Lemma 2.3.3, all women are matched. This is a contradiction, because this would mean that a man appears in more than one match, so necessarily an unmatched woman exists. Consequently, every time we pop a man from the queue, there will always exist a woman who is unmatched. Since each man proposes to each woman at most once, there exist at most n^2 proposals, so the algorithm halts. Finally, when the algorithm halts, no man is unmatched, hence the output is a marriage. $\square$

Now are going to prove the output of the algorithm is stable.

Lemma 2.3.5. *Algorithm 2.6 produces a stable marriage.*

Proof. By Lemma 2.3.4, we know that it produces a marriage. Assume, to the contrary, that the output is not stable, which means that a blocking pair (m_i, w_j) exists. Because (m_i, w_j) does not belong to the matching, two cases are possible.

In the first case, the man m_i proposed to w_j and she rejected him (immediately or accepted him temporarily and later left him for a better proposal). This means that w_j prefers the man from the matching. A contradiction.

In the second case, the man m_i never proposed to w_j , which means that he matched with a woman who is higher on his preference list. Also a contradiction. $\square$

As we perform at most $O(n^2)$ proposals and we can decide whether to accept a proposal or not in $O(1)$ (using $O(n^2)$ preprocessing), the total complexity is $O(n^2)$.

Theorem 2.3.6. *Algorithm 2.6 computes a stable marriage in $O(n^2)$.*

Definition 2.3.7. *Algorithm 2.6 operates as a men-proposing algorithm since a man first proposes to his most preferred woman, leaving the woman to accept the best proposal available to her.*

Theorem 2.3.8. *The men-proposing Algorithm 2.6 is man-optimal, as every man is matched to the best partner he could possibly obtain in any stable marriage.*

Proof. Suppose, for the sake of contradiction, that it is not man-optimal, and that the output of Algorithm 2.6 is a marriage M . This means that there exist some rejections in our algorithm such that the corresponding pairs are matched in another stable marriage M' . From those rejections, fix the first one. That is, a man m_i got rejected by woman w_j because w_j prefers m_z to m_i , and another stable marriage M' exists, where m_i is matched with w_j , i.e., $\{m_i, w_j\} \in M'$, and m_z is matched with w_k , i.e., $\{m_z, w_k\} \in M'$. If m_z prefers w_j to w_k , then $\{m_z, w_j\}$ is a blocking pair in M' , which leads to a contradiction. If m_z prefers w_k to w_j , then it would be impossible for the first rejection to be that of m_i by w_j , because it would mean that w_j is already matched with m_z , implying that m_z was rejected by w_k in some previous iteration. This also leads to a contradiction. $\square$

Although the output of the algorithm is man-optimal, it is the worst matching for women.

Theorem 2.3.9. *The men-proposing Algorithm 2.6 is female-pessimal, meaning every woman is matched with the least preferred valid partner she could have in any stable matching.*

Proof. Similar to the previous proof, assume to the contrary that woman w_j is matched with man m_i in the marriage output M of Algorithm 2.6 and that there exists another stable marriage M' such that w_j is matched with a man m_z whom she prefers less than m_i and m_i is matched with a woman w_k . Because M is man-optimal by Theorem 2.3.8, m_i prefers w_j to w_k . The pair $\{m_i, w_j\}$ is a blocking pair for M' . This is a contradiction, since M' is stable. $\square$

Further Variants of the Model Up to this point, we have focused on a one-to-one matching model, which dictates that every individual is paired with exactly one counterpart. The classical framework, however, can be extended to accommodate more complex scenarios, including many-to-one assignments, incomplete lists, and preferences with ties. Additionally, stability is just one of many criteria used to evaluate the quality of a matching. In a later chapter, we will study some of these extended scenarios.

Chapter 3

Polyhedral Approaches to Matching Problems

References

- [BBST24] Aaron Bernstein, Joakim Blikstad, Thatchaphol Saranurak, and Ta-Wei Tu. Maximum flow by augmenting paths in $n^{2+o(1)}$ time. In *2024 IEEE 65th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 2056–2077, 2024.
- [BCK⁺23] Jan Van Den Brand, Li Chen, Rasmus Kyng, Yang P. Liu, Richard Peng, Maximilian Probst Gutenberg, Sushant Sachdeva, and Aaron Sidford. A deterministic almost-linear time algorithm for minimum-cost flow. In *2023 IEEE 64th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 503–514, 2023.
- [Ber57] Claude Berge. Two theorems in graph theory. *Proceedings of the National Academy of Sciences*, 43(9):842–844, 1957.
- [CK24] Julia Chuzhoy and Sanjeev Khanna. Maximum bipartite matching in $\tilde{O}(n^2)$ time via a combinatorial algorithm. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing*, page 83–94. Association for Computing Machinery, 2024.
- [Din70] Yefim A. Dinitz. Algorithm for solution of a problem of maximum flow in networks with power estimation. *Soviet Mathematics Doklady*, 11:1277–1280, 1970.
- [Din06] Yefim Dinitz. Dinitz’ algorithm: The original version and even’s version. In Oded Goldreich, Arnold L. Rosenberg, and Alan L. Selman, editors, *Theoretical Computer Science: Essays in Memory of Shimon Even*, pages 218–240. Springer, Berlin, Heidelberg, 2006.
- [GS62] D. Gale and L. S. Shapley. College admissions and the stability of marriage. *The American Mathematical Monthly*, 69(1):9–15, 1962.
- [HK73] John E Hopcroft and Richard M Karp. An $n^{5/2}$ algorithm for maximum matchings in bipartite graphs. *SIAM Journal on computing*, 2(4):225–231, 1973.
- [Pet91] Julius Petersen. Die theorie der regulären graphs, 1891.