GrayCo Construction Services, LLC
4007 Broadway Rd., Bartlett TN 38135 | (901) 585-0944
TN License # 85034 | AR License # 0486990627 | MS License # 27769 | TIN # 33-2106808

LEAD ABATEMENT OCCUPANT PROTECTION PLAN

Lead 07 – Required before any lead abatement in a pre-1978 home or child-occupied facility

A written occupant protection plan is required for every abatement project (40 CFR 745.227(e)(5); Arkansas ADH Rules Pertaining to Lead-Based Paint Activities; Tennessee Rule 0400-13-01). It must be unique to this building, prepared by the certified abatement supervisor or project designer before work starts, and describe how occupants – especially children – are kept from lead exposure during the work. Give a copy to the owner, keep one on site, and keep it with the abatement report for at least 3 years.

1. PROJECT

Owner / customer: _____ Job no.: _____

Property address: _____ Year built: _____

Building type: _____ State notice filed (date): _____

Abatement dates: _____ Work hours: _____

Certified supervisor: _____ Certification no. / state: _____

GrayCo firm license no. (AR ADH / TN TDEC): _____ EPA firm cert. no.: _____

2. LEAD HAZARDS TO BE ABATED

Source (inspection / risk assessment report, date, inspector):

_____

_____

Components or areas, with locations:

_____

_____

Abatement method (removal, enclosure, encapsulation, replacement, soil removal or permanent cover):

_____

_____

3. OCCUPANT ACCESS AND RELOCATION

☐ Occupants (list who is in the building – children, staff, residents): _____

☐ Work areas closed to occupants for the whole project – no children, staff or residents enter until clearance passes

☐ Occupants relocated during work: ☐ Not needed – work area isolated ☐ Partial (rooms / area): _____ ☐ Full relocation to: _____

☐ Owner notified of dates, hours, closed areas and entrances to use – date notified: _____

☐ Separate entrance / route for workers so occupants never pass through the work area or waste path

☐ Owner and center director contact for daily coordination: _____

4. CONTAINMENT, SIGNS AND BARRIERS

☐ Interior: 2–3 layers of 6-mil plastic on floors, extending at least 6 ft past the work area; two-layer flap entry at every doorway; all windows and doors closed

☐ HVAC shut off; all return grilles blocked and supply registers covered in the work area

☐ Exterior: 6-mil plastic on the ground extending at least 10 ft (or more) past the work area; windows and doors within 20 ft closed; no work in high wind

☐ Bilingual lead warning signs and caution tape at every entrance to the work area before work starts – left up until clearance passes

☐ Containment never blocks an exit or egress path

☐ Furniture, rugs and contents removed, or wrapped and sealed in plastic

5. WORK PRACTICES AND PROHIBITED METHODS

☐ Prohibited: open-flame burning or torching; machine sanding or grinding without HEPA shroud; abrasive blasting without HEPA vacuum collection; dry scraping (except small areas near electrical outlets); heat guns at 1,100 °F or higher; dry sweeping; shop vacuums

☐ GrayCo standard: no sanding of any kind on lead surfaces; wet methods; battery-powered or GFCI-protected tools; HEPA vacuums only

☐ Workers in coveralls, shoe covers, gloves and N100/P100 respirators; protective clothing removed and hands and face washed before leaving the work area; tack pads at every exit

☐ OSHA 29 CFR 1926.62: exposure assessment and full worker protection until air monitoring shows exposure below the action level

6. DAILY CLEANUP AND WASTE

☐ Work area cleaned at the end of every day – HEPA vacuum, wet wipe, debris bagged; never leave the site with the work area uncleaned

☐ Waste in 6-mil bags, gooseneck-sealed, or in covered containers; stored inside the barrier or a locked container – never left where children can reach it

☐ Waste disposal: TCLP testing if required; hauled to: _____

☐ Waste route from the work area to the truck or container does not cross occupied areas, or is covered with plastic first

7. CLEARANCE BEFORE RE-OCCUPANCY

☐ Visual inspection by the certified supervisor, then clearance sampling by a certified inspector or risk assessor (not GrayCo's crew)

☐ Dust clearance where any interior work was done – results below the state clearance levels before occupants return

☐ Signs, barriers and containment stay up until clearance passes; area reopened only after written clearance

☐ Abatement report (GrayCo form F12) to the owner, with clearance results, waste records and this plan

8. EMERGENCIES AND CHANGES

☐ If a child or occupant enters the work area: stop work, remove them, notify the owner and the supervisor, wash exposed skin and clothing, document it

☐ Any change to areas, dates or methods: update this plan and file a revised state notice before the change

☐ Nearest hospital / emergency contact: _____

SIGNATURES

Prepared by the certified supervisor / project designer:

Name: _____ Certification no.: _____

Signature: _____ Date: _____

Owner / facility acknowledgment – I received this plan and understand the closed areas and dates:

Name / title: _____ Date: _____

Signature: _____ _____

Refused or unavailable to sign

☐ Plan delivered on _____ and owner refused or was unavailable to sign. Delivered by: ☐ hand ☐ email (copy attached) ☐ certified mail (receipt attached)

Keep with the abatement project records for at least 3 years.