


JEV

THE DECISION MODEL

# 12 Jobs for Jev

Twelve practical workflows, with prompts you can hand to your coding agent and adapt to your own data.

01–05 Easy starts

06–08 Intermediate workflows

09–12 Advanced patterns

12 Reusable starter prompts

# Give your agent a decision to build around.

Jev returns a typed choice, score or yes/no decision from the options you define. Your software decides what to do with that result. These prompts are starting points: replace the examples with your categories, files and rules.

**01 · DEFINE**

State the decision and the allowed answers.

→

**02 · SET A FALLBACK**

Choose what happens when confidence is low.

→

**03 · REVIEW**

Test real examples before automating actions.

### USE THE PROMPT AS A BRIEF

Paste it into Claude Code, Codex or your preferred agent. Ask the agent to show its plan, files changed and tests before it runs anything consequential.

### KEEP THE DECISION BOUNDED

Give Jev a fixed set of labels or a defined scale. Keep the action in ordinary code; don't ask the model to invent a free-form response.

### KEEP A HUMAN IN THE LOOP

Choose a confidence threshold and make uncertain or high-impact cases easy to review. These examples are workflow patterns, not production guarantees.

### BRING YOUR OWN DATA

Use a small, permissioned test set first. The prompts contain no sample results or performance claims to imply that a run has already happened.

**Currency in the video:** cost figures are written in dollars for readability (for example, $0.07). Spoken wording remains as filmed.

# 01 Triage customer enquiries

EASY

Route routine messages quickly, but make uncertain cases easy for a person to catch.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Build an automation where every incoming enquiry is sent to Jev to pick one of: billing, bug, question. Return the category and confidence. If confidence is under 60%, route it to a person; otherwise route it automatically.

WHAT TO BRING

A permissioned set of sample enquiries, three labels, and the support inbox or queue you want to route into.

KEEP IT BOUNDED

Start in preview mode. Keep the under-60% path human-reviewed and log the chosen label and confidence.

FIRST TEST · PREVIEW ONLY

Try one clear billing request and one ambiguous message. Confirm the uncertain case stays with a person instead of disappearing into automation.

RESOURCES Jev question primitives · models and pricing

# 02 Screen CVs against must-haves

EASY

Apply a defined checklist consistently, then leave hiring decisions to a person.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Here are the CVs in applications/ and the job description. For each CV, ask Jev yes/no on my must-haves: [years of experience, tools used], then score fit 1–5. Rank the ones that pass, and draft a personalised email or message for the top 5 only.

### WHAT TO BRING

A real job description, a small set of CVs you are authorised to process, and explicit job-related must-haves.

### KEEP IT BOUNDED

Do not use protected characteristics or proxies. Do not auto-reject or contact candidates; require a human review before any hiring action.

**FIRST TEST · PREVIEW ONLY** Use one CV that meets the stated must-haves and one that misses a job-related requirement. Check the evidence, then have a person review both.

**RESOURCES** Use your organisation's hiring policy and privacy guidance before connecting candidate data.

# 03 Categorise rows in Google Sheets

Turn a free-text column into one of the categories you maintain in a Config sheet.

EASY

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Build me a Google Sheets add-on. When I add a column whose heading matches a category set in a Config sheet (e.g. Expense category: groceries, transport, subscriptions, rent, other), call Jev for every row with that row's text and the category set, and write the chosen category into the row.

WHAT TO BRING

A copied test spreadsheet with a Config tab, a text column and a destination column.

KEEP IT BOUNDED

Add a preview or undo path. Never overwrite the source text; report rows that have no confident match.

FIRST TEST · PREVIEW ONLY

Test one obvious category, one borderline row and one blank cell in a copied sheet. Confirm the source text is untouched and uncertain rows are flagged.

RESOURCES Google Apps Script for Sheets · Jev question primitives

# 04 Sort your Downloads folder

EASY

Classify files into a known folder set, then move them only after you approve the plan.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Look at every file in ~/Downloads. Use Jev to pick one folder for each from: Invoices, Receipts, Contracts, Screenshots, Photos, Videos. Move each file into its folder.

WHAT TO BRING

A test copy of the folder and a fixed list of destination folders.

KEEP IT BOUNDED

First produce a dry-run table. Do not delete or overwrite. Ask before moving files outside the test copy.

FIRST TEST · PREVIEW ONLY

Run against three copied files, including two with the same filename. Inspect the dry-run destinations and confirm nothing is overwritten or moved yet.

RESOURCES Your operating system's file permissions and backup/recovery process.

# 05 Tag competitor ads

EASY

Build a structured swipe file from ads you are allowed to review.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

For ads I have manually saved or am authorised to access, ask Jev to choose a hook type, offer and angle from my tag lists. Save the tags and the source URL beside each ad in a database.

WHAT TO BRING

A small set of manually collected ad examples, source URLs and controlled tag lists.

KEEP IT BOUNDED

Do not scrape Meta Ad Library without permission. Keep advertiser attribution and source links with each record.

FIRST TEST · PREVIEW ONLY

Use a handful of ads you collected manually. Check that every tag stays beside its original source link and can be corrected.

RESOURCES Meta Ad Library · check its current access rules before building.

# 06 Search notes and B-roll by meaning

INTERMEDIATE

Match a query to a paragraph or clip description even when its exact words differ.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Build a search tool over my notes and my B-roll library. Split notes into paragraphs; for clips use the description. When I type a query, ask Jev which candidate matches best and open it.

### WHAT TO BRING

A folder of notes, a clip manifest with written descriptions, and a query field.

### KEEP IT BOUNDED

Return a candidate from the supplied list only. Show the source filename and let me choose when the match is uncertain.

**FIRST TEST · PREVIEW ONLY**

Search for a concept that is described in your notes with different words. Check that the result opens the exact paragraph or clip it came from.

**RESOURCES** Jev Choice questions · your own B-roll manifest.

# 07 Filter before the big model

INTERMEDIATE

Use a narrow relevance decision before sending a larger set of material to an agent.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Before Claude reads any new transcript in creator-references-library/, ask Jev yes/no: is this reel on-topic for my channel? Only pass the yeses to Claude.

### WHAT TO BRING

A local reference library, your channel's relevance criteria, and a review folder for uncertain items.

### KEEP IT BOUNDED

Do not send private or unlicensed material to a third party. Save the reason/context needed for a human to audit the decision.

**FIRST TEST · PREVIEW ONLY**

Test one relevant transcript and one clearly unrelated one. Confirm only the relevant item is handed to the larger agent and uncertainty is reviewable.

**RESOURCES** TypeSafe developer docs · your library's access and retention rules.

# 08 Route skills and models

INTERMEDIATE

Choose from the tools already installed instead of asking an agent to inspect a long list every time.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Write a Claude Code hook that runs on every prompt. Send the prompt and my skill names and descriptions to Jev and ask it to pick one skill. Then make a /jev command that asks Jev to choose the model: Haiku for simple jobs, Opus for hard ones.

### WHAT TO BRING

A current allowlist of installed skill names/descriptions and available model aliases.

### KEEP IT BOUNDED

Only accept listed names. Add a safe default when the answer is uncertain, and keep the final choice visible and reversible.

**FIRST TEST · PREVIEW ONLY**

Try a simple task, a complex task and an unfamiliar prompt. Confirm each choice is on the allowlist and the unfamiliar case takes the safe fallback.

**RESOURCES** Jev Choice questions · maintain your skill/model allowlist.

# 09 Build a feed slop filter

ADVANCED

A starter prompt for the bounded yes/no pattern shown by community examples in the video.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Build a browser extension that evaluates each visible post against my written “AI slop” criteria. Ask Jev to choose “slop” or “keep” only. If it chooses “slop” above my confidence threshold, collapse the post; otherwise leave it visible. Include an obvious per-post undo and a global pause switch.

### WHAT TO BRING

Your own definition of “slop”, a local test feed or posts you have permission to use, and a confidence threshold.

### KEEP IT BOUNDED

Keep filtering reversible. Do not hide posts solely because of a person’s identity or viewpoint. Treat community demos as examples, not endorsements.

**FIRST TEST · PREVIEW ONLY**

Use two posts you have permission to test, one matching your written criteria and one that does not. Confirm the filter is reversible and easy to pause.

**RESOURCES** Jev yes/no questions · credit creators when showing their original projects.

# 10 Design a smarter task app

ADVANCED

Suggest a tag and urgency while someone types, using only the tag set they choose.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Build a small to-do app. As the user types a task, send the text and my tag list [Finance, Clients, Content, Admin, Personal] to Jev to pick one tag, and ask Jev yes/no: is this urgent? Update the tag and priority live.

### WHAT TO BRING

A small task app, a fixed tag list and a clear definition of urgent.

### KEEP IT BOUNDED

Show suggestions as editable. Do not let an uncertain urgency score silently change deadlines or send notifications.

**FIRST TEST · PREVIEW ONLY**

Type one task with an obvious tag and urgency, then one ambiguous task. Confirm suggestions remain editable and do not trigger actions by themselves.

**RESOURCES** Jev Choice and yes/no questions.

# 11 Pick B-roll for each line

ADVANCED

Decide whether a line needs coverage, then choose a clip from a described library.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

For each sentence in transcript.md, ask Jev yes/no: does this line need B-roll? If yes, ask Jev to choose the best clip from b-roll-manifest.json by its description. Flag anything under 70%.

### WHAT TO BRING

A transcript, a B-roll manifest with useful descriptions, and a confidence threshold.

### KEEP IT BOUNDED

Never invent a source clip. Flag uncertain matches for a human editor; keep the spoken line visible and correctly timed.

**FIRST TEST · PREVIEW ONLY**

Use one line that clearly needs a visual, one that does not, and one ambiguous line. Confirm the chosen clips exist in the manifest and uncertain matches are flagged.

**RESOURCES** Your own transcript and B-roll manifest. Verify the source and usage rights of every clip.

# 12 Choose an editing effect

ADVANCED

Select a known effect per line, or explicitly choose none.

STARTER PROMPT · ADAPT THE BRACKETED DETAILS

Run npx hyperframes catalog --json to get the effect list. For each sentence in transcript.md, ask Jev to pick one effect from that list (or "none"). Apply the picks and build the HyperFrames composition.

### WHAT TO BRING

The current effect catalog, a transcript aligned to its video and a short list of visual rules for your channel.

### KEEP IT BOUNDED

Validate every selected effect name against the current catalog. Use "none" when it does not help. Review the edit before rendering.

**FIRST TEST · PREVIEW ONLY**

Check one line with a number, one describing a UI and one plain line. Confirm every chosen effect exists in the current catalog and "none" is allowed.

**RESOURCES** Run `npx hyperframes catalog --json` locally · Jev Choice questions.

# Useful starting points.

Official documentation and source pages referenced by this pack. Check each provider's current terms, features and pricing before shipping an integration.

### TYPESAFE DEVELOPER DOCS

Jev concepts, API setup and integration guides.
docs.typesafe.ai

### QUESTIONS / PRIMITIVES

Choice, Score and yes/no question patterns.
docs.typesafe.ai/primitives

### MODELS AND PRICING

Check current model names and rates before estimating a workflow.
docs.typesafe.ai/models

### SYSTEM ONE OVERVIEW

How TypeSafe describes decision models for software.
System One concepts

### GOOGLE APPS SCRIPT · SHEETS

Official guide for building spreadsheet automations.
Google Apps Script guides

### META AD LIBRARY

Use the official library manually or through an approved access path; don't scrape it without permission.
facebook.com/ads/library

### OPENAI DECISIONS API

Official guide for a related typed-decision API.
Decisions guide

### HYPERFRAMES EFFECT CATALOG

Inspect available effects locally before choosing one in a workflow: `npx hyperframes catalog --json`.

**Examples, not endorsements.** The advanced feed and page-building patterns can be prototyped with fictional or permissioned sample content. If you reference a creator's project, credit that creator and use their original post or repository.