



A researcher states a goal; a planning model proposes the project and its agents, and the researcher corrects it. They then run in a sandbox, on data they harvest, take from a robot as it drives, or receive by upload, and train on it round after round unwatched. A loop like that is only as good as what it reports about itself. This sheet is that coordination, and the review that makes it checkable.

Weed Detection



The corpus exists to train the weed detector the laser robot needs. Two agents work it unprompted: one harvests and audits public imagery, the other trains. Over 150,000 labelled images.

Rover



A four-wheel skid-steer narrow enough for a crop row, carrying its own battery and compute. Every drive it opens becomes a governed dataset as it runs: camera, GPS and two inertial units, over one API key.

Laser Weed Control Robot




The end use the collection is for. A YOLO detector localises each weed and two galvanometer lasers aim at it and fire, destroying it in place—no chemical, and nothing touches the crop beside it.

Humanoid and Quadruped



Legs reach ground wheels cannot, and in the field this one crossed it faster than the cart. A wide stance and a level gait hold the camera steady, which is what a collector needs.

Four projects, one platform. Each was opened by the same procedure, and its data is registered the same way whether it was harvested, driven in by a robot, or uploaded.



Agent Workflow Diagram

Figure 1. The harvest-and-train loop, as it runs unattended. A researcher's goal is planned into keyword queries, what they return is audited, what survives is trained on, and the round is scored. The stopping rule is a plateau test today and a reviewer's judgement by design. Review follows every step.

ONE PLATFORM SUPPORTS ANY ROBOT OR DATASET OPEN-WEIGHT MODELS REVIEW IN TIERS WHAT THE AGENTS DECIDED ON THEIR OWN WHAT THE AGENTS DECIDED ON THEIR OWN (CONT.)

- agentAI is one platform for every laboratory robot
- Both the Rover and the laser robot transmit data
- Each drive becomes a dataset at its start
- Every data type and domain forms its own project



The platform is live; the QR code links to it

lab-b660m-c.tailfa6424.ts.net

Sign in with a Google account to open it.




Figure 2. (e) Recall and (f) grounded recall on 149 frozen failures taken from this project's own record, scored by the project's own scorer. Each arrow runs from the model reading the raw files to the same model handed the twelve checks' findings. Grounded counts only the cases where the model also quoted a line that resolves the failure. The dotted arrow carries no head: its two ends were scored on different cases, 57 against 114.

- We froze 149 real failures from our own history and asked open-weight models to find them. Good reviewers cite their evidence; size matters less. Handed the twelve checks' findings, a 27-billion model found 0.149 more, a 14-billion one 0.012.
- Review runs even when nothing looks wrong

What the lab model says stays a draft

On the cluster	the answer is authoritative
plan the next step	qwen3.8 27B
review in depth	glm-4.7-flash
hard one-off reasoning	deepseek-v3 671B
decide what to collect	gemma 4
judge dataset quality	qwen2.5 7B
label assistance	minicpm-v

On the lab box

turn intent into a project	qwen2.5 3B
summarise a dataset	qwen2.5 3B

Figure 3. The eight jobs that need a model, and the model each one was given, read from the router's own table. A filled square marks a job that exercises judgement. The six on the cluster come back authoritative; the two in the lab come back marked a draft.

- Eight jobs need a model. Most run on the cluster; two run in the lab on a 3B model, because a person is waiting. A lab answer is marked so it cannot count as a decision: the rule about where a judgement counts travels with the answer, not with the configuration.
- The model's explanation failed its own test

- The search ran dry after round three

WHAT THE COLLECTION PRODUCED

- 156,521 labelled by machine, 3,208 kept
- Gemma 4 said yes to every box
- One bad box hides from a dataset filter