

TECHNICAL DOCUMENTATION

Orders module

How operators create, fulfil and monitor orders across the web app and the API

Module	orders
Company	Acme Test
Audience	Developers + product (handover)
Generated	2026-09-14
web	a1b2c3d4e5 main
api	0f1e2d3c4b main



Uniunea Europeană



Guvernul României



PNRR

Finanțat de Uniunea Europeană – NextGenerationEU — Project: Acme Orders Platform · Contract: 760123/23.05.2024 · Beneficiary: Acme Test SRL



Contents


1. Summary
2. How it works
3. Architecture
4. User flows
 - 4.1 Create and fulfil an order
5. Data model
6. API surface
7. Configuration
8. Dependencies
9. Security — what to watch for
10. Operations — what to monitor
11. Glossary

1. Summary

The Orders module lets an operator create an order, send it to fulfilment, and follow it to completion. It exists because the previous spreadsheet process had no UI and no history. The mechanism in one sentence: the web app saves an order through the API, the API queues a fulfilment job, a worker charges the payment provider and stores the result, and the web app polls until the job is done.

2. How it works

An order is a row in `orders` . Each fulfilment attempt is a row in `order_jobs` . The API never calls the payment provider in the request path: it only enqueues a BullMQ job so the HTTP response stays fast and retries are handled by the queue, not by the browser.



High-level architecture of the Orders module

Design choice: polling instead of websockets. Jobs take 5 to 40 seconds, and the team already had a polling hook. A websocket channel was judged not worth the operational cost. Source: comment in ``api/src/orders/orders.service.ts:41``.


3. Architecture

Component	Repo	Path	Responsibility
Orders pages	web	src/app/orders/	List, create and inspect orders
useOrders()	web	src/hooks/useOrders.ts	Data fetching and polling
OrdersController	api	src/orders/orders.controller.ts	HTTP surface, validation, auth guard

Component	Repo	Path	Responsibility
OrderFulfilmentProcessor	api	src/orders/order-fulfilment.processor.ts	Executes fulfilment jobs against the payment API

4. User flows

4.1 Create and fulfil an order



Flow 1: create and run an order

1. The operator fills the order form and clicks **Save & send**.
2. The web app validates the form with zod and sends `POST /orders`.
3. `OrdersService.create()` saves the order and enqueues a fulfilment job.
4. `OrderFulfilmentProcessor` calls the payment API and stores the result.
5. `order_jobs.status` becomes `done`.
6. The API returns the order with its latest job.
7. The web app polls `GET /orders/:id` every 3 seconds.
8. The operator sees the status and the output.

Failure path: after three payment API errors the job is marked `failed` and the list shows a retry button.

5. Data model

Entity	Key fields	Relations	Store
Order	id, customerId, total, note, ownerId, createdAt	has many OrderJob ; belongs to User	PostgreSQL orders
OrderJob	id, orderId, status (queued, running, done, failed), output, error, startedAt, finishedAt	belongs to Order	PostgreSQL order_jobs

status moves `queued` → `running` → `done` or `failed` ; a failed job keeps its `error` and can be retried from the list.

6. API surface

Method	Path	Auth	Purpose	Frontend caller
GET	/orders	JWT, role operator	List orders with latest job	useOrders()
POST	/orders	JWT, role operator	Create an order and enqueue a fulfilment job	OrderForm
GET	/orders/:id	JWT, role operator	One order with its latest job (polled)	useOrders()
POST	/orders/:id/retry	JWT, role operator	Retry fulfilment of an existing order	OrderList

7. Configuration

Variable	Repo	Purpose
PAYMENT_API_KEY	api	Credential for the payment provider
REDIS_URL	api	BullMQ connection
NEXT_PUBLIC_API_URL	web	Base URL of the API

8. Dependencies

Package	Used by	Declared	Installed	Latest	Installed age	Status	Advisory
@nestjs/bullmq	2 files	^10.1.0	10.1.1	11.0.2	1.4 y	1 major behind	—
bullmq	2 files	^5.7.0	5.7.8	5.34.0	1.6 y	minor/patch	—

Package	Used by	Declared	Installed	Latest	Installed age	Status	Advisory
stripe	1 file	^14.5.0	14.5.0	15.3.0	1.8 y	1 major behind	—
class-validator	3 files	^0.14.0	0.14.0	0.14.1	2.5 y	minor/patch behind	—
@tanstack/react-query	2 files	^5.28.0	5.28.4	5.62.0	1.5 y	minor/patch behind	—
zod	2 files	^3.22.4	3.22.4	3.24.1	1.9 y	minor/patch behind	—

Watch list:

- stripe 14.x is one major behind. 15.x changed the webhook signing helpers; only `order-fulfilment.processor.ts` calls it, so the upgrade is contained.
- @nestjs/bullmq 10.x pairs with NestJS 10; moving to 11 goes together with the framework upgrade.
- class-validator 0.14.0 is 2.5 years old with no vulnerability reported; the DTOs in `src/orders/dto/` are the only users.

9. Security — what to watch for

- `POST /orders/:id/retry` has the JWT guard but no ownership check: any operator can retry any order (`orders.controller.ts:48`). Add a tenant/owner guard before opening the module to more roles.
- The order note is stored as-is and sent to the payment provider as metadata without length limits (`orders.service.ts:33`). A 200 kB note is accepted; cap it in `CreateOrderDto` .
- The job result is rendered with `dangerouslySetInnerHTML` in `OrderJobResult.tsx:21` ; it contains provider messages, treat them as untrusted and render as plain text or sanitise.
- `PAYMENT_API_KEY` is read once at boot; rotation needs a restart. Logs at `order-fulfilment.processor.ts:58` print the full card metadata at `debug` level — keep `debug` off in production.

10. Operations — what to monitor

Signal	Where	Normal	When it is off
fulfilment queue depth	Redis / Bull board	< 20	Worker down or payment API slow; check worker logs
Failed jobs in fulfilment	Bull board, <code>order_jobs.status = failed</code>	0–2 per day	Inspect <code>order_jobs.error</code> ; retries are exhausted after 3
Payment API latency	<code>order-fulfilment.processor.ts</code> log line <code>run done in Nms</code>	5–40 s	> 60 s means rate limiting; check the 429 counter

Signal	Where	Normal	When it is off
POST /orders 4xx rate	API access log	< 5 %	Validation errors from a new frontend build

11. Glossary

- **Job:** one fulfilment attempt for an order, stored in `order_jobs`.
- **Operator:** a signed-in user with the `operator` role.