Benchmarking Open Instruction-Tuned LLMs for Greek NLP: A Reproducible Multi-Task Evaluation

Anonymous Author(s)

ABSTRACT

We present a reproducible benchmark for evaluating open instruction-tuned large language models on Greek NLP. The benchmark covers grammatical error correction, intent classification, legal document classification, machine translation, named entity recognition, part-of-speech tagging, and summarization. We evaluate five open models under a deterministic capped-test protocol that preserves ordering and exact reproducibility while reducing the runtime burden of very large test sets. Across nine benchmark segments, `gemma2:9b` ranks first overall on normalized quality, while `aya-expanse:8b` is strongest on legal classification and English machine translation, and `llama3.1:8b-instruct` performs best on summarization. The paper is paired with repository-native tables, vector figures, and combined prediction exports so that benchmark execution and manuscript preparation remain tightly coupled.

CCS CONCEPTS

• **Computing methodologies** → **Natural language processing**; *Language resources*; • **Information systems** → Data analytics.

KEYWORDS

Greek NLP, benchmarking, large language models, reproducibility, evaluation

1 INTRODUCTION

Broad evaluation has become central to modern language model research because single-task scores rarely capture deployment-relevant trade-offs in robustness, latency, and transfer [1, 3, 4]. Yet, for Greek NLP, evaluation resources still remain fragmented across task-specific datasets, metrics, and execution pipelines. This makes it difficult to compare open instruction-tuned LLMs under a shared protocol, especially when the goal is not a single downstream task but a broader view across heterogeneous settings.

Instruction tuning has made general-purpose language models more usable across many tasks without task-specific retraining [2, 5]. However, evaluating such models on Greek remains cumbersome in practice. This paper packages our evaluation workflow into a reproducible benchmark suitable for SETN 2026. The benchmark aggregates seven task families into nine reporting segments: grammatical error correction (GEC), intent classification, legal classification, machine translation into three target languages, named entity recognition (NER), part-of-speech (POS) tagging, and summarization. The runner produces per-task summaries, per-instance predictions, combined CSV outputs, HTML visualizations, and publication-facing figures.

Our contribution is practical rather than algorithmic. First, we provide a unified multi-task evaluation setup for Greek NLP with open local models. Second, we adopt a deterministic capped-test protocol that remains reproducible without relying on random sampling. Third, we expose benchmark outputs in a form that flows directly into a conference paper.

2 BENCHMARK SETUP

2.1 Tasks and Models

The benchmark covers seven task families:

- GEC
- intent classification
- legal classification
- machine translation
- NER
- POS tagging
- summarization

We evaluate five open instruction-tuned models served locally through Ollama: `qwen2.5:7b-instruct`, `llama3.1:8b-instruct`, `aya-expanse:8b`, `gemma2:9b`, and `falcon3:7b-instruct`.

2.2 Deterministic Capped-Test Protocol

The full test sets are very uneven in size, with legal classification and machine translation being especially large. To keep evaluation tractable while preserving reproducibility, we use a deterministic capped-test profile that always takes the first instances in dataset order instead of random samples. The resulting capped evaluation contains:

- GEC: 175 examples
- intent classification: 436 examples
- legal classification: 500 examples
- machine translation: 300 English pairs, 4 Persian pairs, and 9 Japanese pairs
- NER: 500 examples
- POS: 456 examples
- summarization: 300 examples

This design keeps the smaller tasks intact while reducing the runtime burden of the largest tasks. It also supports exact reruns because the selected subset is deterministic.

2.3 Metrics

We report task-appropriate primary metrics. For classification-style tasks we use accuracy and macro-F1, with macro-F1 treated as the primary comparison metric. For GEC we report exact match and edit-distance-derived measures against the reference and source text. For machine translation and summarization we currently rely on word error rate (WER) and character error rate (CER), where lower values are better. Latency is reported as average per-instance generation time in seconds.

To compare models across heterogeneous metrics, we additionally compute a direction-aware normalized quality score per benchmark segment. Within each segment, the best model receives the highest normalized value and the worst model the lowest. These

segment-normalized scores are then averaged to obtain an overall ranking.

3 IMPLEMENTATION NOTES

The benchmark pipeline was adjusted in several ways to make end-to-end runs stable and paper-ready. We added combined prediction exports so that the full suite produces unified CSV files across tasks. We also changed legal classification from opaque subject identifiers to coarse-grained human-readable volume labels, which avoids the degenerate all-zero behavior observed with raw numeric class IDs. For POS tagging, we added a fallback parser that tolerates _ head values in CoNLL-U files. At the backend level, we introduced retry and backoff logic around transient Ollama failures. Finally, we generated publication-oriented reports, tables, and vector graphics directly from benchmark outputs.

4 RESULTS

Table 1 summarizes the best model in each benchmark segment. Figure 1 visualizes normalized quality across segments, while Figure 2 shows the trade-off between quality and inference speed.

Three patterns stand out. First, `gemma2:9b` is the strongest overall model in this run. It ranks first on the normalized aggregate and wins four benchmark segments, namely GEC, intent classification, NER, and POS. Second, `aya-expanse:8b` is especially competitive on cross-lingual tasks, winning legal classification and English machine translation, and tying for the best Japanese machine translation WER. Third, `llama3.1:8b-instruct` performs best on summarization, although its advantage comes at a higher latency than the fastest summarization model.

Legal classification remains the most difficult benchmark component. Even after replacing opaque identifiers with coarse-grained volume labels, the best macro-F1 is only 0.011. This suggests that the task is still demanding under zero-shot prompting and may benefit from better label descriptions, exemplars, or task-specific fine-tuning. By contrast, intent classification is comparatively mature in this setup, with `gemma2:9b` reaching 0.737 macro-F1 on 436 capped test examples.

Machine translation is mixed. `aya-expanse:8b` is clearly strongest for English translation, but the Persian and Japanese segments are extremely small in this deterministic capped profile. As a result, conclusions for those two languages should be treated as suggestive rather than definitive.

5 DISCUSSION

The benchmark is useful because it combines multiple Greek NLP settings in a single reproducible workflow, but the current evaluation still has limitations. The capped protocol is intentionally pragmatic rather than exhaustive. It is well suited for iterative comparison and paper-scale reporting, but it is not a substitute for full test-set evaluation when final archival numbers are required. Some metric choices are also provisional. In particular, summarization and machine translation would benefit from stronger semantic metrics and human assessment, while legal classification would benefit from richer label semantics.

Despite these caveats, the benchmark already exposes meaningful structure in model behavior. Some models offer strong general performance across multiple tasks, while others are better understood as specialists for translation or summarization. This kind of cross-task perspective is hard to obtain from isolated task runs and is exactly where a unified benchmark becomes valuable.

6 REPRODUCIBILITY AND ARTIFACT STRUCTURE

The repository includes the benchmark runner, combined CSV outputs, HTML task visualizations, report generation scripts, and publication-ready assets. The capped run used in this draft is stored under the repository's completed-run hierarchy, and the article-facing tables and vector figures are generated into a dedicated `article_assets` subdirectory. This structure allows the manuscript to be regenerated directly from benchmark outputs without manual copy-paste into the paper.

7 CONCLUSION

We presented a reproducible Greek NLP benchmark draft for open instruction-tuned LLMs and used it to compare five models across seven task families and nine benchmark segments. Under a deterministic capped-test protocol, `gemma2:9b` ranks first overall, while `aya-expanse:8b` and `llama3.1:8b-instruct` emerge as strong specialists on legal classification and summarization respectively. The current pipeline is already useful for comparative evaluation, and it also provides a clean path from benchmark execution to publication assets.

A OVERALL RANKING TABLE

The table below reports the overall model ranking induced by the normalized segment scores.

B WINNER MARGINS BY SEGMENT

REFERENCES

[1] Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, Shyamal Buch, Dallas Card, Rodrigo Castellon, Niladri Chatterji, Annie Chen, Kathleen Creel, Jared Davis, Dorottya Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Judy Grossman, Tatsunori B. Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Kyle Hong, Kelvin Hsu, Jing Huang, Thomas Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Fereshte Khani, Omar Khattab, Pang Wei Kohli, Mark Krass, Ranjay Krishna, Rohit Kuditipudi, Ananya Kumar, Jure Leskovec, Isin Levent, Percy Liang, Chaitanya Mandal, Kathryn Ma, Ali Malik, Christopher D. Manning, Suvir Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Deepak Narayanan, Richard Ngo, Julian Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Jeanne Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Rob Reich, Hongyu Ren, Frieda Rong, Yusuf Roohani, Camilo Ruiz, Justin Ryan, Christopher Ré, Dorsa Sadigh, Shiori Sagawa, Omid Salehi, Karan Santhanam, Shreya Sarkar, Eli Schroeder, Yash Sen, Ananya Sharma, Hao Shan, Kyle Shanmugam, Sharon Shen, Avanika Song, Krishna Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Cathy Xiong, Yangsibo Xu, Ziyi Yang, Shun Zhang, Jiajun Zhang, Yufan Zhang, Lucy Zheng, Kaitlyn Zhou, and Percy Liang. 2021. On the Opportunities and Risks of Foundation Models. *arXiv preprint arXiv:2108.07258* (2021).

[2] Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Sharan Narang, Gaurav Mishra, Adams Wei Yu, Vincent Y. Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. 2024. Scaling Instruction-Finetuned Language Models. *Journal of Machine Learning Research* 25, 70 (2024), 1–53.

Table 1: Best-performing model per benchmark segment on the deterministic capped evaluation run (GEC=175, Intent=436, Legal=500, MT(ENG=300, FAS=4, JPN=9), NER=500, POS=456, Summarization=300). Lower WER is better; higher Exact Match and Macro-F1 are better.

Task Segment	Winner	Primary Metric	Value
GEC	Gemma2 9B	Exact Match	0.137
Intent	Gemma2 9B	Macro-F1	0.737
Legal	Aya Expanse 8B	Macro-F1	0.011
MT-ENG	Aya Expanse 8B	WER	55.642
MT-FAS	Qwen2.5 7B Instruct	WER	86.345
MT-JPN	Aya Expanse 8B	WER	100.000
NER	Gemma2 9B	Macro-F1	0.122
POS	Gemma2 9B	Macro-F1	0.486
Summ.	Llama 3.1 8B Instruct	WER	173.585



Figure 1: Normalized quality heatmap across the nine benchmark segments. Scores are normalized within each segment so that higher is always better, even when the underlying metric is lower-is-better such as WER.

Table 2: Overall ranking of the evaluated models across the nine benchmark segments in the deterministic capped benchmark run. Normalized quality is averaged over segment-level, direction-aware scores.

Model	Rank	Avg. Quality	Avg. Latency (s)	Segment Wins
Gemma2 9B	1	80.2	1.43	4
Aya Expanse 8B	2	60.5	1.06	3
Llama 3.1 8B Instruct	3	49.9	1.12	1
Qwen2.5 7B Instruct	4	48.1	1.27	1
Falcon3 7B Instruct	5	44.5	1.21	0

[3] Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sidney Black, Guy Blasi, Anthony Casey, Nate Cheeseman, Juan Ciro, Sasha Crabtree, Nicholas Currier, Xingyu Dang, Clementine Decoopman, Chris Foster, Raphael Gontijo Lopes, Huan He, Kevin Hu, Brandon Knight, Jorge Larios, Logan Li, Xander Lin, Shawn Miller, Niklas Muennighoff, Aryan Naeini, Hyunwoo Nam, Sam Pan, Louis Schmid, Hailey Schoelkopf, Xiang Wang, Albert Webson, Mitchell Wortsman, Yuxi Yao, Stella Biderman, Douwe Kiela, Teven Le Scao, Colin Raffel, Andy Zhou, Dan Hendrycks, et al. 2023. A Framework for Few-Shot Language Model Evaluation. In *Advances in Neural Information Processing Systems Datasets and Benchmarks Track*.

[4] Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, Benjamin Newman, Binhang Yuan, Bonnie Yan, Ce Zhang, M. Cosgrove, Christopher D. Manning, Christopher Ré, and Tatsunori B. Hashimoto. 2023. Holistic Evaluation of Language Models. *Transactions on Machine Learning Research* (2023).

[5] Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. 2022. Finetuned Language Models Are Zero-Shot Learners. *arXiv preprint arXiv:2109.01652* (2022).

Figure 2: Quality-latency trade-off across models and task families. Each point corresponds to one model-task pair after averaging within the task family.



Figure 3: Normalized quality margin between the winning model and the runner-up for each benchmark segment. Large margins indicate clearer task-level separation between the top two models.