

Prediction of cancer mutation states across multiple data modalities reveals the utility and redundancy of gene expression and DNA methylation

This manuscript ([permalink](#)) was automatically generated from [greenelab/mpmp-manuscript@a9fb1d9](#) on June 4, 2021.

Authors

- **Jake Crawford**

 [0000-0001-6207-0782](#) ·  [jjc2718](#) ·  [jjc2718](#)


Genomics and Computational Biology Graduate Group, Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA, USA; Department of Systems Pharmacology and Translational Therapeutics, Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA, USA · Funded by National Institutes of Health's National Cancer Institute (R01 CA237170); National Institutes of Health's National Human Genome Research Institute (R01 HG010067)

- **Brock C. Christensen**

 [0000-0003-3022-426X](#)

Department of Epidemiology, Geisel School of Medicine, Dartmouth College, Lebanon, NH, USA · Funded by Grant XXXXXXXX

- **Maria Chikina**

 [0000-0003-2550-5403](#) ·  [mchikina](#)

Department of Computational and Systems Biology, School of Medicine, University of Pittsburgh, Pittsburgh, PA, USA · Funded by Grant XXXXXXXX

- **Casey S. Greene**

 [0000-0001-8713-9213](#) ·  [cgreene](#) ·  [GreeneScientist](#)

Department of Biochemistry and Molecular Genetics, University of Colorado School of Medicine, Aurora, CO, USA; Center for Health AI, University of Colorado School of Medicine, Aurora, CO, USA · Funded by National Institutes of Health's National Cancer Institute (R01 CA237170); National Institutes of Health's National Human Genome Research Institute (R01 HG010067)

Abstract

Introduction

Although cancer can be initiated and driven by many different genetic alterations, these tend to converge on a limited number of pathways or signaling processes [1]. A comprehensive understanding of how diverse genetic alterations perturb these central pathways is vital to precision medicine and biomarker identification efforts, as driver mutation status alone confers limited prognostic information [2,3]. While many methods exist to distinguish driver mutations from passenger mutations based on genomic sequence characteristics [4,5,6], until recently it has been a challenge to connect driver mutations to downstream changes in gene expression and cellular function within individual tumor samples.

The Cancer Genome Atlas (TCGA) Pan-Cancer Atlas provides uniformly processed, multi-platform -omics measurements across tens of thousands of samples from 33 cancer types [7]. Enabled by this publicly available data, a growing body of work on linking the presence of driving genetic alterations in cancer to downstream gene expression changes has emerged. Recent studies have considered Ras pathway alteration status in colorectal cancer [8], alteration status across many cancer types in Ras genes [9,10], *TP53* [11], and *PIK3CA* [12], and alteration status across cancer types in frequently mutated genes [13]. More broadly, other groups have drawn on similar ideas to distinguish between the functional effects of different alterations in the same driver gene [14], to link alterations with similar gene expression signatures within cancer types [15], and to identify trans-acting expression quantitative trait loci (trans-eQTLs) in germline genetic studies [16].

These studies share a common thread: they each combine genomic (point mutation and copy number variation) data with transcriptomic (RNA sequencing) data within samples to interrogate the functional effects of genetic variation. RNA sequencing is ubiquitous and cheap, and its experimental and computational methods are relatively mature, making it a vital tool for generating insight into cancer pathology [17]. Some driver mutations, however, are known to act indirectly on gene expression through varying mechanisms. For example, oncogenic *IDH1* and *IDH2* mutations in glioma have been shown to interfere with histone demethylation, which results in increased DNA methylation and blocked cell differentiation [18,19]. Other genes implicated in aberrant DNA methylation in cancer include the TET family of genes [20] and *SETD2* [21]. Certain driver mutations, such as those in DNA damage repair genes, may lead to detectable patterns of somatic mutation [22]. Additionally, correlation between gene expression and protein abundance in cancer cell lines is limited, and proteomics data could correspond more directly to certain cancer phenotypes and pathway perturbations [23]. In these contexts and others, integrating different data modalities or combining multiple data modalities could be more effective than relying solely on gene expression as a functional signature.

Here, we seek to compare -omics data types profiled in the TCGA Pan-Cancer Atlas for use as a multivariate functional readout of genetic alterations in cancer. We focus on DNA methylation (27K and 450K probe chips), reverse phase protein array (RPPA), and mutational signatures data [24] as alternative readouts. Prior studies have identified univariate correlations of CpG site methylation [25,26] and correlations of RPPA protein profiles [27] with the presence or absence of certain driver mutations. Other relevant past work includes linking point mutations and copy number variants (CNVs) with changes in methylation and expression at individual genes [28,29] and identifying functional modules that are perturbed by somatic mutations [30,31]. However, no direct comparison has been made between different data types for this application, particularly in the multivariate case where we consider changes to -omics-derived gene signatures rather than individual genes in isolation.

We select a collection of potential cancer drivers with varying functions and roles in cancer development [32]. We use mutation status in these genes as labels to train classifiers, using each of the data types listed as training data, in a pan-cancer setting; we follow similar methods to the elastic net logistic regression approach described in Way et al. 2018 [9] and Way et al. 2020 [13]. We show that there is considerable predictive signal for many genes relative to a random baseline, and that gene expression and DNA methylation generally provide the best predictions of mutation state. Surprisingly, we find that across a variety of target genes, they are approximately equally effective predictors; the target gene, rather than the data type, is the primary determinant of performance. In addition, we observe that combining data types into a single multi-omics model provides little, if any, performance benefit over the most performant model using a single data type. Our results will help to inform the design of future functional genomics studies in cancer, suggesting that for many strong drivers with clear functional signatures, gene expression and DNA methylation measurements provide similar information content.

Methods

Mutation data download and preprocessing

To generate binary mutated/non-mutated gene labels for our machine learning model, we used mutation calls for TCGA samples from MC3 [33] and copy number threshold calls from GISTIC2.0 [34]. MC3 mutation calls were downloaded from the Genome Data Commons (GDC) of the National Cancer Institute, at <https://gdc.cancer.gov/about-data/publications/pancanatlas>. Copy number threshold calls are from an older version of PanCanAtlas, and are available here: https://figshare.com/articles/dataset/TCGA_PanCanAtlas_Copy_Number_Data/6144122. We removed hypermutated samples (defined as five or more standard deviations above the mean non-silent somatic mutation count) from our dataset to reduce the number of false positives (i.e., non-driver mutations). In total, this resulted in 9,074 TCGA samples with mutation and copy number data. Any sample with a non-silent somatic variant in the target gene was included in the positive set. We also included copy number gains in the target gene for oncogenes, and copy number losses in the target gene for tumor suppressor genes, in the positive set; all remaining samples were considered negative for mutation in the target gene.

Omics data download and preprocessing

RNA sequencing, 27K and 450K methylation array, and RPPA datasets for TCGA samples were all downloaded from GDC, at the same link provided above. Mutational signatures information for TCGA samples with whole-exome sequencing data was downloaded from the International Cancer Genome Consortium (ICGC) data portal, at https://dcc.icgc.org/releases/PCAWG/mutational_signatures/Signatures_in_Samples/SP_Signatures_in_Samples. For our experiments, we used only the “single base signature” (SBS) mutational signatures, generated in [24]. We standardized (took z-scores of) each column of RNA sequencing and RPPA data; methylation data and mutational signatures data were left untransformed (beta values and mutation counts respectively), except in multi-omics experiments where all data types were standardized. For the RNA sequencing dataset, we used only the top 8,000 gene features by mean absolute deviation as predictors in our models, except in multi-omics experiments where all 15,639 genes were used.

In order to remove missing values from the methylation datasets, we removed the 10 samples with the most missing values, then performed mean imputation for probes with 1 or 2 values missing. All probes with missing values remaining after sample filtering and imputation were dropped from the analysis. This left us with 20,040 CpG probes in the 27K methylation dataset, and 370,961 CpG probes in the 450K methylation dataset. For experiments where “raw” methylation data was used, we used

the top 100,000 probes in the 450K dataset by mean absolute deviation for computational efficiency, and we used all of the 20,040 probes in the 27K dataset. For experiments where “compressed” methylation data was used, we used principal component analysis (PCA), as implemented in the `scikit-learn` Python library [35], to extract the top 5,000 principal components from the methylation datasets. We initially applied the beta-mixture quantile normalization (BMIQ) method [36] to correct for variability in signal intensity between type I and type II probes, but we observed that this had no effect on our results. We report uncorrected results in the main paper for simplicity.

Comparing data modalities

We made three main comparisons in this study, listed in the results section: one between different sets of genes using only expression data, one comparing expression and DNA methylation data types, and one comparing all data types. This was mainly due to sample size limitations – running a single comparison using all data types would force us to use only samples that are profiled for every data type, which would discard a large number of samples that lack profiling on only one or a few data types. Thus, for each of the three comparisons, we used the intersection of TCGA samples having measurements for all of the datasets being compared in that experiment. This resulted in three distinct sets of samples: 9,074 samples shared between {expression, mutation} data, 7,981 samples shared between {expression, mutation, 27K methylation, 450K methylation}, and 5,226 samples shared between {expression, mutation, 27K methylation, 450K methylation, RPPA, microRNA, mutational signatures}. When we dropped samples between experiments as progressively more data types were added, we observed that the dropped samples had approximately the same cancer type proportions as the dataset as a whole. In other words, samples that were profiled for one data type but not another did not tend to come exclusively from one or a few cancer types. Exceptions included acute myeloid leukemia (LAML) which had no samples profiled in the RPPA data, and ovarian cancer (OV) which had only 8 samples with 450K methylation data. More detailed information on cancer type proportions profiled for each data type is provided in (the supplement).

For each target gene, in order to ensure that the training dataset was reasonably balanced (i.e. that there would be enough mutated samples to train an effective classifier), we included only cancer types with at least 15 mutated samples and at least 5% mutated samples, which we refer to here as “valid” cancer types. After applying these filters, the number of valid cancer types remaining for each gene varied based on the set of samples used: more data types resulted in fewer shared samples, and fewer samples generally meant fewer valid cancer types. In some cases, this resulted in genes with no valid cancer types, which we dropped from the analysis. Out of the 127 genes from the original cancer gene set described in Vogelstein et al. 2013 [32], for the analysis using {expression, mutation} data we retained 85 target genes, for the {expression, mutation, 27k methylation, 450k methylation} analysis we retained 84 genes, and for the analysis using all data types we retained 75 genes.

We additionally explored mutation prediction from gene expression alone using 3 gene sets of equal size: the cancer-related genes from Vogelstein et al. 2013 described above, a set of frequently mutated genes in TCGA, and a set of random genes with mutations profiled by MC3. To match the size of the Vogelstein et al. gene set, we took the 85 most frequently mutated genes in TCGA as quantified by MC3, all of which had at least one valid cancer type. For the random gene set, we first filtered to the set of all genes with 2 or more valid cancer types by the above criteria, then sampled 85 of these genes uniformly at random. Based on the results of the gene expression experiments, we used the Vogelstein et al. gene set for all subsequent experiments comparing -omics data types.

Training classifiers to detect cancer mutations

We trained logistic regression classifiers to predict whether or not a given sample has a mutational event in a given target gene, using data from various -omics datasets as explanatory variables. Our

model is trained on -omics data (X) to predict mutation presence or absence (y) in a target gene. To control for varying mutation burden per sample, and to adjust for potential cancer type-specific expression patterns, we included one-hot encoded cancer type and \log_{10} (sample mutation count) in the model as covariates. Since our -omics datasets tend to have many dimensions and comparatively few samples, we used an elastic net penalty to prevent overfitting [37], in line with the approach used in Way et al. 2018 [9] and Way et al. 2020 [13]. Elastic net logistic regression finds the feature weights $\hat{w} \in \mathbb{R}^p$ solving the following optimization problem:

$$\hat{w} = \operatorname{argmin}_w \ell(X, y; w) + \alpha \lambda \|w\|_1 + \frac{1}{2} \alpha (1 - \lambda) \|w\|_2^2$$

where $i \in \{1, \dots, n\}$ denotes a sample in the dataset, $X_i \in \mathbb{R}^p$ denotes features (omics measurements) from the given sample, $y_i \in \{0, 1\}$ denotes the label (mutation presence/absence) for the given sample, and $\ell(\cdot)$ denotes the negative log-likelihood of the observed data given a particular choice of feature weights, i.e.

$$\ell(X, y; w) = - \sum_{i=1}^n y_i \log \left(\frac{1}{1 + e^{-w^\top X_i}} \right) + (1 - y_i) \log \left(1 - \frac{1}{1 + e^{-w^\top X_i}} \right)$$

This optimization problem leaves two hyperparameters to select: α (controlling the tradeoff between the data log-likelihood and the penalty on large feature weight values), and λ (controlling the tradeoff between the L1 penalty and L2 penalty on the weight values). Although the elastic net optimization problem does not have a closed form solution, the loss function is convex, and iterative optimization algorithms are commonly used for finding reasonable solutions. For fixed values of α and λ , we solved for \hat{w} using stochastic gradient descent, as implemented in `scikit-learn`'s `SGDClassifier` method.

Given weight values \hat{w} , it is straightforward to predict the probability of a positive label (mutation in the target gene) $P(y^* = 1 \mid X^*; \hat{w})$ for a test sample X^* :

$$P(y^* = 1 \mid X^*; \hat{w}) = \frac{1}{1 + e^{-\hat{w}^\top X^*}}$$

and the probability of no mutation in the target gene, $P(y^* = 0 \mid X^*; \hat{w})$, is given by (1 - the above quantity).

For each target gene, we evaluated model performance using 2 replicates of 4-fold cross-validation, where train and test splits were stratified by cancer type and sample type. That is, each training set/test set combination had equal proportions of each cancer type (BRCA, SKCM, COAD, etc) and each sample type (primary tumor, recurrent tumor, etc). To choose the elastic net hyperparameters, we used 3-fold nested cross-validation, with a grid search over the following hyperparameter ranges: $\lambda = [0.0, 0.05, 0.1, 0.3, 0.5, 0.7, 0.9, 1.0]$ and $\alpha = [0.0001, 0.001, 0.01, 0.1, 1, 10]$. Using the grid search results, for each evaluation fold we selected the set of hyperparameters with the optimal area under the precision-recall curve (AUPR), averaged over the three inner folds.

Although we stratified our train and test datasets for cancer type and sample type, we opted not to stratify by label. In other words, we did not ensure that cross-validation splits had proportions of positive (mutated) and negative (non-mutated) samples that were exactly equal to each other; we instead sampled randomly with respect to labels. Label-stratified cross-validation chooses test sets that have exactly the same label balance as the training set, which could select a model that is less robust to shifts in the label proportion than one that is trained and evaluated without controlling label

balance. Particularly for the problem of mutation prediction, the proportion of samples that are mutated in a given cancer type or subtype often varies considerably, which makes robustness across variation in label proportions important.

Evaluating mutation prediction classifiers

To quantify classification performance for a continuous or probabilistic output, such as that provided by logistic regression, the area under the receiver-operator curve (AUROC) [38] and the area under the precision-recall curve (AUPR) [39] metrics are frequently used. These metrics summarize performance across a variety of binary label thresholds, rather than requiring choice of a single threshold to determine positive or negative predictions. In the main text, we report results using AUPR, summarized using average precision. AUPR has been shown to distinguish between models more accurately than AUROC when there are few positively labeled samples [40,41]. As an additional correction for imbalanced labels, in many of the results in the main text we report the difference in AUPR between a classifier fit to true mutation labels, and a classifier fit to data where the mutation labels are randomly shuffled. In cases where mutation labels are highly imbalanced (very few mutated samples and many non-mutated samples), a classifier with shuffled labels may perform well simply by chance, e.g. by predicting the negative/non-mutated class for most samples. To maintain the same label balance for the classifiers with shuffled labels as the classifiers with the true labels, we shuffled labels separately in the train and test sets for each cross-validation split.

Recall that for each target gene and each -omics dataset, we ran 2 replicates of 4-fold cross-validation, for a total of 8 performance results. To make a statistical comparison between two models using these performance distributions, we used paired-sample *t*-tests, where performance measurements derived from the same cross-validation fold are considered paired measurements. We used this approach to compare a model trained on true labels with a model trained on shuffled labels (addressing the question, “for the given gene using the given data type, can we predict mutation status better than random”), and to compare a model trained on data type A with a model trained on data type B (addressing the question, “for the given gene, can we make more effective mutation status predictions using data type A or data type B”). We corrected for multiple tests using a Benjamini-Hochberg false discovery rate correction. For all of our experiments, we set a conservative corrected threshold of $p = 0.001$; we were able to estimate the number of false positives by examining genes with better performance for shuffled mutation labels than true labels. We chose our threshold to ensure that none of these genes were considered significant, since we would never expect permuting labels to improve performance. However, our results were not sensitive to the choice of this threshold.

Multi-omics prediction experiments

To predict mutation presence or absence in cancer genes using multiple data types simultaneously, we concatenated individual datasets into a large feature matrix, then used the same elastic net logistic regression method described previously. For this task, we considered only the gene expression, 27K methylation, and 450K methylation datasets. We used only these data types to limit the number of multi-omics combinations: the expression and methylation datasets resulted in the best overall performance across the single-omics experiments so we limited combinations to those datasets here. For gene expression we used all 15,639 genes available in our RNA sequencing dataset, for the 27K methylation dataset we used all 20,040 CpG probes, and for the 450K methylation dataset we used the top 5,000 principal components.

To construct the multi-omics models, we considered each of the pairwise combinations of the datasets listed above, as well as a combination of all 3 datasets. When combining multiple datasets, we concatenated along the column axis, including covariates for cancer type and sample mutation

burden as before. For all multi-omics experiments, we used only the samples from TCGA with data for all three data types (i.e. the same 7,981 samples used in the single-omics experiments comparing expression and methylation data types). Due to computational demands, we considered only a limited subset of the Vogelstein et al. genes as target genes, including *EGFR*, *IDH1*, *KRAS*, *PIK3CA*, *SETD2*, and *TP53*. We selected these genes because we have previously observed that they have good predictive performance, and they represent a combination of alterations that have strong gene expression signatures (*KRAS*, *EGFR*, *IDH1*, *TP53*) and strong DNA methylation signatures (*IDH1*, *SETD2*, *TP53*).

Data and code availability

All analyses were implemented in the Python programming language and are available in the following GitHub repository: <https://github.com/greenelab/mpmp>, under the open-source BSD 3-clause license. Scripts to download large data files from GDC and other sources are located in the `00_download_data` directory. Scripts to run experiments comparing data modalities used individually are located in the `02_classify_mutations` directory, and scripts to run multi-omics experiments are located in the `05_classify_mutations_multimodal` directory. The Python environment was managed using `conda`, and directions for setting up the environment can be found in the `README.md` file. All analyses were run locally on a CPU.

Results

Using diverse data modalities to predict cancer alterations

We collected five different data modalities from cancer samples in the TCGA Pan-Cancer Atlas, capturing five steps of cellular function that are perturbed by genetic alterations in cancer (Figure 1A). These included gene expression (RNA-seq data), DNA methylation (27K and 450K Illumina BeadChip arrays), protein abundance (RPPA data), microRNA expression data, and patterns of somatic mutation (mutational signatures). To link these diverse data modalities to changes in mutation status, we used elastic net logistic regression to predict the presence or absence of mutations in cancer genes, using these readouts as predictive features (Figure 1B). We evaluated the resulting mutation status classifiers in a pan-cancer setting, preserving the proportions of each of the 33 cancer types in TCGA for 8 train/test splits (4 folds x 2 replicates) in each of 85 cancer genes (Figure 1C).

We sought to compare classifiers against a baseline where mutation labels are permuted (to identify genes whose mutation status correlates strongly with a functional signature in a given data type), and also to compare classifiers trained on true labels across different data types (to identify data types that are more or less predictive of mutations in a given gene). To account for variation between dataset splits in making these comparisons, we treat classification metrics from the 8 train/test splits as performance distributions, which we compare using *t*-tests. We summarize performance across all genes in our cancer gene set using a similar approach to a volcano plot, in which each point is a gene. In our summary plots, the x-axis shows the magnitude of the change in the classification metric between conditions, and the y-axis shows the *p*-value for the associated *t*-test. Figure 1C illustrates this evaluation pipeline.




Figure 1: A. Cancer mutations can perturb cellular function via a variety of cellular processes. Arrows represent major potential paths of information flow from a somatic mutation in DNA to its resulting cell phenotype; circular arrow represents the ability of certain mutations (e.g. in DNA damage repair genes) to alter somatic mutation patterns. Note that this does not reflect all possible relationships between cellular processes: for instance, changes in gene expression can lead to changes in somatic mutation rates. **B.** Predicting presence/absence of somatic alterations in cancer from diverse data modalities. In this study, we use functional readouts from TCGA as predictive features and the presence or absence of mutation in a given gene as labels. This reverses the primary direction of information flow shown in Panel A. **C.** Schematic of evaluation pipeline.

Selection of cancer-related genes improves predictive signal

As a baseline, we evaluated prediction of mutation status from gene expression data across several different gene sets. Past work has evaluated mutation prediction for the top 50 most mutated genes in TCGA [13], and we sought to extend this to a broader list of gene sets. We compared a set of cancer-related genes from Vogelstein et al. 2013 [32] with a set of random genes having equal size, and a set of the most mutated genes in TCGA having equal size. For all gene sets, we used only the set of TCGA samples for which both gene expression and somatic mutation data exists, resulting in a total of 9,074 samples from all 33 cancer types (Figure 2A). This set of samples was further filtered for each target gene to cancer types containing at least 15 mutated samples and at least 5% of samples mutated for that cancer type. We then evaluated the performance for each target gene in each of the three gene sets.

Figure 2B summarizes performance for all genes in each gene set. Genes from the Vogelstein et al. set were more predictable than randomly chosen genes or those selected by total mutation count. Figures 2C, 2D, and 2E show performance for each gene in the random gene set, most mutated gene set, and Vogelstein et al. gene set respectively. In total, for a significance threshold of $\alpha = 0.001$, 47/85 genes (55.3%) in the Vogelstein et al. gene set are significantly predictable from gene expression data, compared to 12/85 genes (14.1%) in the random gene set and 15/85 genes (17.6%) in the most mutated gene set. Additionally, Figure 2D shows that many of the significant genes in the most mutated gene set are clustered close to the significance threshold, while the significant genes in the Vogelstein et al. gene set tend to be further from the threshold in Figure 2E (i.e. higher AUPR

differences and lower p -values). These results suggest that selecting target genes for mutation prediction based on prior knowledge of their involvement in cancer pathways and processes, rather than randomly or based on mutation frequency alone, can improve predictive signal and identify more highly predictable mutations from gene expression data.




Figure 2: **A.** Overlap of TCGA samples between gene expression and MC3 somatic mutation data. **B.** Overall distribution of performance across 3 gene sets. Each data point represents mean cross-validated AUPR difference, compared with a baseline model trained on permuted mutation presence/absence labels, for one gene in the given gene set; notches show bootstrapped 95% confidence intervals. “random” = 85 random genes, “most mutated” = 85 most mutated genes, “Vogelstein et al.” = 85 cancer related genes from Vogelstein et al. 2013 gene set. **C, D, E.** Volcano-like plots showing mutation presence/absence predictive performance for each gene in each of the 3 gene sets. The x-axis shows the difference in mean AUPR compared with a baseline model trained on permuted labels, and the y-axis shows p -values for a paired t -test comparing cross-validated AUPR values within folds.

Comparing gene expression and DNA methylation reveals widespread redundancy

We compared gene expression with DNA methylation as downstream readouts of the effects of cancer alterations. In these analyses, we considered both the 27K probe and 450K probe methylation datasets generated for the TCGA Pan-Cancer Atlas. We performed this comparison using the cancer-related gene set derived from Vogelstein et al. [32]. We used samples that had data for each of the data types being compared, including somatic mutation data to generate mutation labels. This process retained 7,981 samples in the intersection of the expression, 27K methylation, 450K methylation, and mutation datasets, which we used for subsequent analyses. The most frequent missing data types were somatic mutation data (1,114 samples) and 450K methylation data (1,072 samples) (Figure 3A).

For most genes, predictions are better than our baseline model where labels are permuted (most values greater than 0 in the box plots), suggesting that there is considerable predictive signal in both expression and methylation datasets across the Vogelstein et al. gene set (Figure 3B). Performance distributions are similar for expression and methylation, and aggregate performance is also similar for models using both 8,000 raw features (genes or CpG probes for expression and methylation

respectively, selected using mean absolute deviation) or 5,000 principal components. After filtering for genes that exceed the significance threshold, median gene expression with raw gene features is slightly higher than for other data types or for PCA preprocessed features, although confidence intervals overlap with the methylation data types (Figure 3C). Comparing distributions provides weak evidence that gene expression measurements may be a slightly better predictor of mutation status than DNA methylation, but the difference does not appear to be substantial.

Considering each target gene in the Vogelstein gene set individually, we observed that 42/84 genes significantly outperformed the shuffled baseline using gene expression data, as compared to 42/84 genes for 27K methylation and 39/84 genes for 450K methylation (Figure 3D-F). Genes in the top right of Figure 3D-F are well predicted using the relevant data type (high mean difference vs. permuted baseline and low p -value); in most cases these well-predicted genes tended to be similar between data types. For example, *TP53*, *BRAF*, and *PTEN* appear in the top right of all 3 plots, suggesting that mutations in these genes have strong gene expression and DNA methylation signatures, and these signatures tend to be preserved across cancer types.

In addition to comparing mutation classifiers trained on different data types to the permuted baseline, we also compared classifiers trained on true labels directly to each other, using a similar methodology (Figure 3G-H). We observed that 6/100 genes were significantly more predictable from expression data than 27K methylation data, and 2/100 genes were significantly more predictable from expression data than 450K methylation data. In both cases, 0/100 genes were significantly more predictable using the methylation data types. For both comparisons (expression vs. 27K methylation and expression vs. 450K methylation), we observed that the majority of points were clustered around the origin, indicating that the data types appear to confer similar information about mutation status. In other words, for genes near the origin, matching the gene being studied with the “correct” data modality seems to be unimportant: either mutation status has a strong signature which can be extracted from both expression and DNA methylation data roughly equally, or mutation presence/absence does not have a strong effect on either data modality.




Figure 3: **A.** Count of overlapping samples between gene expression, 27K methylation, 450K methylation, and somatic mutation data used from TCGA. Only non-zero overlap counts are shown. **B.** Predictive performance for genes in the Vogelstein et al. gene set, using each of the three data types as predictors. The x-axis shows the number of PCA components used as features, “raw” = no PCA compression. **C.** Predictive performance for genes where at least one of the considered data types predicts mutation labels significantly better than the permuted baseline. **D-F.** Predictive performance for each gene in the Vogelstein et al. gene set, for each data type, compared with a baseline model trained on shuffled labels. **G-H.** Predictive performance for each gene in the Vogelstein et al. gene set, comparing gene expression directly to each methylation dataset (with classifiers trained on true labels).

Focusing on several selected genes of interest, we observed that relative classifier performance varies by gene (Figure 4). Past work has indicated that mutations in *TP53* are highly predictable from gene expression data [11], and we saw that the methylation datasets provided similar predictive performance (Figure 4A). Similarly, for *IDH1* both expression and methylation features result in similar performance, consistent with *IDH1*’s known role in regulating both DNA methylation and gene expression (Figure 4D) [42]. Mutations in *KRAS* and *ERBB2* (*HER2*) were most predictable from gene expression data, and in both cases the methylation datasets significantly outperformed the baseline as well (Figure 4B and 4E). A detectable gene expression signature of *ERBB2* overexpression has been identified in breast cancer [43], and samples with activating *ERBB2* mutations have been shown to share sensitivities to some small-molecule inhibitors across cancer types [44], consistent with the pan-cancer expression signature that we observed here. *NF1* mutations were also most predictable from gene expression data, although the gene expression-based *NF1* mutation classifier did not significantly outperform the baseline with permuted labels at a cutoff of $\alpha = 0.001$ (Figure 4C). *SETD2* is an example of a gene that is more predictable from the methylation datasets than from gene expression, although gene expression with raw gene features significantly outperformed the permuted baseline as well (Figure 4F). *SETD2* is widely mutated across cancer types and affects H3K36 histone methylation most directly, but *SETD2*-mediated changes in H3K36 methylation have been

linked to dysregulation of diverse cellular processes including DNA methylation and RNA splicing [21,45].




Figure 4: Performance across varying PCA dimensions for specific genes of interest. Dotted lines represent results for "raw" features (8,000 gene features for gene expression data and 8,000 CpG probes for both methylation datasets, selected by largest mean absolute deviation). Error bars and shaded regions show bootstrapped 95% confidence intervals. Stars in boxes show statistical testing results compared with the permuted baseline model: each box refers to the model using the number of PCA components it is over (far right box = models with raw features). **: $p < 0.01$, ***: $p < 0.001$, no stars: not statistically significant for a cutoff of $p = 0.05$.

Comparing six different readouts favors expression and DNA methylation

Next, we expanded our comparison to all five functional data modalities (six total readouts, since there are two DNA methylation datasets) available in the TCGA Pan-Cancer Atlas. As with previous experiments, we limited our comparison to the set of samples profiled for each readout, resulting in 5,226 samples with data for all readouts. The data types with the most missing samples were RPPA data (2,215 samples that were missing RPPA data) and 450K methylation (630 samples that were missing 450K methylation data) (Figure 5A). Summarized over all genes in the Vogelstein et al. dataset, we observed that gene expression and both methylation datasets tended to produce similar quality predictions, and these tended to be slightly better than the remaining data types (Figure 5B). For the set of genes having at least one significant predictor (i.e. "well-predicted" genes), median performance using gene expression was slightly higher than for the methylation data types, although this difference was not statistically significant (Figure 5C).

On the individual gene level, mutations in 25/75 genes were significantly predictable from RPPA data relative to the permuted baseline, compared to 24/75 genes from microRNA data and 3/75 genes from mutational signatures data (Figure 5D-F). For the remaining data types on this smaller set of samples, 34/75 genes outperformed the baseline for gene expression data, 32/75 for 27k methylation, and 30/75 for 450k methylation. Compared to the methylation experiments shown in Figure 3, we observed slightly fewer "well-predicted" genes for the expression and methylation datasets here (likely due to the considerably smaller sample size) but relative performance was comparable. Direct comparisons between each added data type and gene expression data showed that RPPA data produces comparable or improved predictions for a small number of genes (Figure 5G), but microRNA and mutational signatures data generally provide similar or worse performance (Figure 5H-I). Performance using RPPA data is notable because of its drastically smaller dimensionality than the other data types (190 proteins, compared to thousands of features for the expression and

in Figure 6), only three of them are well-predicted exclusively by a single data type, meaning that mutations in the other 37 genes can be predicted effectively using at least two different data sources. This supports our observation that choosing the “correct” data modality is often unimportant for driver genes with strong functional signatures. Notable exceptions included *NF1* (only well-predicted using gene expression data), *SETD2* (only well-predicted using the two methylation datasets), and *TSC1* (only well-predicted using gene expression data). Gene expression provided the best performance in 25/39 genes with at least one significant data type (red highlighted boxes in Figure 6), but only 2 of those 25 genes did not have any other significantly predictive data types (*NF1* and *TSC1*); in the other 23 genes one or more non-expression data types also outperformed the permuted baseline.




Figure 6: Heatmap displaying predictive performance for mutations in each of the 75 genes from the Vogelstein et al. gene set, across all 6 TCGA data modalities. Each cell quantifies performance for a target gene, using predictive features derived from a particular data type. Blue highlights indicate that the given data type provides significantly better predictions than the permuted baseline for the given gene; red highlights indicate the same and additionally that the given data type provides the best performance for the given gene, relative to other data types.

Simple multi-omics baseline provides no performance benefit

We also trained “multi-omics” classifiers to predict mutations in six well-studied and widely mutated driver genes across various cancer types: *EGFR*, *IDH1*, *KRAS*, *PIK3CA*, *SETD2*, and *TP53*. Each of these genes is well-predicted from several data types in our earlier experiments (Figure 6), consistent with having strong pan-cancer driver effects. For the multi-omics classifiers, we considered all pairwise combinations of the top three performing individual data types (gene expression, 27K methylation, and 450K methylation), in addition to a model using all three data types. We trained a classifier for multiple data types by concatenating features from the individual data types, then fitting the same elastic net logistic regression model as we used for the single-omics models. Here, we show results using the top 5000 principal components from each data type as predictive features, to ensure that feature count and scale is comparable between data types; results for raw features are shown in (supplement).

For each of the six target genes, we observed comparable performance between the best single-omics classifier (blue boxes in Figure 7A) and the best multi-omics classifier (orange boxes in Figure 7A). Across all classifiers and data types, we found varied patterns based on the target gene. For *IDH1* and *TP53* performance is relatively consistent regardless of data type(s), suggesting that baseline performance is high and there is little room for improvement as data is added (Figure 7C, G). For *EGFR*, *KRAS*, and *PIK3CA*, combining gene expression with methylation data seems to result in similar (although slightly improved) performance to gene expression alone; classifiers trained only on methylation data perform considerably worse (Figure 7B, D, E). The best classifiers for *SETD2* use methylation data alone; results are comparable whether 27K methylation or 27K+450K methylation features are used (Figure 7F). Overall, we saw that combining data types in a relatively simple manner (i.e. by concatenating features from each individual data type) provided little or no improvement in predictive ability over the best individual data type. This supports our earlier observations of the redundancy of gene expression and methylation data as functional readouts, since our multi-omics classifiers are not in general able to extract gains in predictive performance as more data types are added for this set of cancer drivers.




Figure 7: A. Comparing the best-performing model (i.e. highest mean AUPR relative to permuted baseline) trained on a single data type against the best “multi-omics” model for each target gene. None of the differences between single-omics and multi-omics models were statistically significant using paired-sample *t*-tests across cross-validation folds, for a threshold of 0.05. **B-G.** Classifier performance, relative to baseline with permuted labels, for mutation prediction models trained on various combinations of data types. Each panel shows performance for one of the six target genes; box plots show performance distribution over 8 evaluation sets (4 cross-validation folds x 2 replicates).

Acknowledgements

We would like to thank Alexandra Lee, Ben Heil, Milton Pividori, and Natalie Davidson for reviewing the software associated with this work and providing insightful feedback. Figure 1 (the schematic of the background and evaluation pipeline) was created using BioRender.com.

References

1. **Oncogenic Signaling Pathways in The Cancer Genome Atlas**

Francisco Sanchez-Vega, Marco Mina, Joshua Armenia, Walid K. Chatila, Augustin Luna, Konnor C. La, Sofia Dimitriadou, David L. Liu, Havish S. Kantheti, Sadegh Saghafein, ... Armaz Mariamidze
Cell (2018-04) <https://doi.org/gc7r9b>
DOI: [10.1016/j.cell.2018.03.035](https://doi.org/10.1016/j.cell.2018.03.035) · PMID: [29625050](https://pubmed.ncbi.nlm.nih.gov/29625050/) · PMCID: [PMC6070353](https://pubmed.ncbi.nlm.nih.gov/PMC6070353/)

2. **Systematic identification of mutations and copy number alterations associated with cancer patient prognosis**

Joan C Smith, Jason M Sheltzer
eLife (2018-12-11) <https://doi.org/gf4zgg>
DOI: [10.7554/elife.39217](https://doi.org/10.7554/elife.39217) · PMID: [30526857](https://pubmed.ncbi.nlm.nih.gov/30526857/) · PMCID: [PMC6289580](https://pubmed.ncbi.nlm.nih.gov/PMC6289580/)

3. **Challenges in identifying cancer genes by analysis of exome sequencing data**

Matan Hofree, Hannah Carter, Jason F. Kreisberg, Sourav Bandyopadhyay, Paul S. Mischel, Stephen Friend, Trey Ideker
Nature Communications (2016-07-15) <https://doi.org/f8x7t3>
DOI: [10.1038/ncomms12096](https://doi.org/10.1038/ncomms12096) · PMID: [27417679](https://pubmed.ncbi.nlm.nih.gov/27417679/) · PMCID: [PMC4947162](https://pubmed.ncbi.nlm.nih.gov/PMC4947162/)

4. **Evaluating the evaluation of cancer driver genes**

Collin J. Tokheim, Nickolas Papadopoulos, Kenneth W. Kinzler, Bert Vogelstein, Rachel Karchin
Proceedings of the National Academy of Sciences (2016-12-13) <https://doi.org/f9d77w>
DOI: [10.1073/pnas.1616440113](https://doi.org/10.1073/pnas.1616440113) · PMID: [27911828](https://pubmed.ncbi.nlm.nih.gov/27911828/) · PMCID: [PMC5167163](https://pubmed.ncbi.nlm.nih.gov/PMC5167163/)

5. **Detailed modeling of positive selection improves detection of cancer driver genes**

Siming Zhao, Jun Liu, Pranav Nanga, Yuwen Liu, A. Ercument Cicek, Nicholas Knoblauch, Chuan He, Matthew Stephens, Xin He
Nature Communications (2019-07-30) <https://doi.org/gjmhnn>
DOI: [10.1038/s41467-019-11284-9](https://doi.org/10.1038/s41467-019-11284-9) · PMID: [31363082](https://pubmed.ncbi.nlm.nih.gov/31363082/) · PMCID: [PMC6667447](https://pubmed.ncbi.nlm.nih.gov/PMC6667447/)

6. **Review: Precision medicine and driver mutations: Computational methods, functional assays and conformational principles for interpreting cancer drivers**

Ruth Nussinov, Hyunbum Jang, Chung-Jung Tsai, Feixiong Cheng
PLOS Computational Biology (2019-03-28) <https://doi.org/gg8jhm>
DOI: [10.1371/journal.pcbi.1006658](https://doi.org/10.1371/journal.pcbi.1006658) · PMID: [30921324](https://pubmed.ncbi.nlm.nih.gov/30921324/) · PMCID: [PMC6438456](https://pubmed.ncbi.nlm.nih.gov/PMC6438456/)

7. **The Cancer Genome Atlas Pan-Cancer analysis project**

John N Weinstein, Eric A Collisson, Gordon B Mills, Kenna R Mills Shaw, Brad A Ozenberger, Kyle Ellrott, Ilya Shmulevich, Chris Sander, Joshua M Stuart, The Cancer Genome Atlas Research Network
Nature Genetics (2013-09-26) <https://doi.org/f3nt5c>
DOI: [10.1038/ng.2764](https://doi.org/10.1038/ng.2764) · PMID: [24071849](https://pubmed.ncbi.nlm.nih.gov/24071849/) · PMCID: [PMC3919969](https://pubmed.ncbi.nlm.nih.gov/PMC3919969/)

8. **Modeling RAS Phenotype in Colorectal Cancer Uncovers Novel Molecular Traits of RAS Dependency and Improves Prediction of Response to Targeted Agents in Patients**

Justin Guinney, Charles Ferte, Jonathan Dry, Robert McEwen, Gilles Manceau, KJ Kao, Kai-Ming Chang, Claus Bendtsen, Kevin Hudson, Erich Huang, ... Pierre Laurent-Puig
Clinical Cancer Research (2014-01-01) <https://doi.org/f5njhn>
DOI: [10.1158/1078-0432.ccr-13-1943](https://doi.org/10.1158/1078-0432.ccr-13-1943) · PMID: [24170544](https://pubmed.ncbi.nlm.nih.gov/24170544/) · PMCID: [PMC4141655](https://pubmed.ncbi.nlm.nih.gov/PMC4141655/)

9. **Machine Learning Detects Pan-cancer Ras Pathway Activation in The Cancer Genome Atlas**
Gregory P. Way, Francisco Sanchez-Vega, Konnor La, Joshua Armenia, Walid K. Chatila, Augustin Luna, Chris Sander, Andrew D. Cherniack, Marco Mina, Giovanni Ciriello, ... Armaz Mariamidze
Cell Reports (2018-04) <https://doi.org/gfspsb>
DOI: [10.1016/j.celrep.2018.03.046](https://doi.org/10.1016/j.celrep.2018.03.046) · PMID: [29617658](https://pubmed.ncbi.nlm.nih.gov/29617658/) · PMCID: [PMC5918694](https://pubmed.ncbi.nlm.nih.gov/PMC5918694/)
10. **Identification of pan-cancer Ras pathway activation with deep learning**
Xiangtao Li, Shaochuan Li, Yunhe Wang, Shixiong Zhang, Ka-Chun Wong
Briefings in Bioinformatics (2020-10-30) <https://doi.org/gjmd3p>
DOI: [10.1093/bib/bbaa258](https://doi.org/10.1093/bib/bbaa258) · PMID: [33126245](https://pubmed.ncbi.nlm.nih.gov/33126245/)
11. **Genomic and Molecular Landscape of DNA Damage Repair Deficiency across The Cancer Genome Atlas**
Theo A. Knijnenburg, Linghua Wang, Michael T. Zimmermann, Nyasha Chambwe, Galen F. Gao, Andrew D. Cherniack, Huihui Fan, Hui Shen, Gregory P. Way, Casey S. Greene, ... Armaz Mariamidze
Cell Reports (2018-04) <https://doi.org/gfspsc>
DOI: [10.1016/j.celrep.2018.03.076](https://doi.org/10.1016/j.celrep.2018.03.076) · PMID: [29617664](https://pubmed.ncbi.nlm.nih.gov/29617664/) · PMCID: [PMC5961503](https://pubmed.ncbi.nlm.nih.gov/PMC5961503/)
12. **Prediction of PIK3CA mutations from cancer gene expression data**
Jun Kang, Ahwon Lee, Youn Soo Lee
PLOS ONE (2020-11-09) <https://doi.org/gjmd3s>
DOI: [10.1371/journal.pone.0241514](https://doi.org/10.1371/journal.pone.0241514) · PMID: [33166334](https://pubmed.ncbi.nlm.nih.gov/33166334/) · PMCID: [PMC7652327](https://pubmed.ncbi.nlm.nih.gov/PMC7652327/)
13. **Compressing gene expression data using multiple latent space dimensionalities learns complementary biological representations**
Gregory P. Way, Michael Zietz, Vincent Rubinetti, Daniel S. Himmelstein, Casey S. Greene
Genome Biology (2020-05-11) <https://doi.org/gg2mjh>
DOI: [10.1186/s13059-020-02021-3](https://doi.org/10.1186/s13059-020-02021-3) · PMID: [32393369](https://pubmed.ncbi.nlm.nih.gov/32393369/) · PMCID: [PMC7212571](https://pubmed.ncbi.nlm.nih.gov/PMC7212571/)
14. **Systematic interrogation of mutation groupings reveals divergent downstream expression programs within key cancer genes**
Michal R. Grzadkowski, Hannah Manning, Julia Somers, Emek Demir
Cold Spring Harbor Laboratory (2020-06-18) <https://doi.org/gjmd7t>
DOI: [10.1101/2020.06.02.128850](https://doi.org/10.1101/2020.06.02.128850)
15. **Using Transcriptional Signatures to Find Cancer Drivers with LURE**
David Haan, Ruikang Tao, Verena Friedl, Ioannis N Anastopoulos, Christopher K Wong, Alana S Weinstein, Joshua M Stuart
World Scientific Pub Co Pte Lt (2019-12) <https://doi.org/gjmd4t>
DOI: [10.1142/9789811215636_0031](https://doi.org/10.1142/9789811215636_0031)
16. **Reverse regression increases power for detecting trans-eQTLs**
Saikat Banerjee, Franco L. Simonetti, Kira E. Detrois, Anubhav Kaphle, Raktim Mitra, Rahul Nagial, Johannes Söding
Cold Spring Harbor Laboratory (2020-09-02) <https://doi.org/gjmhd8>
DOI: [10.1101/2020.05.07.083386](https://doi.org/10.1101/2020.05.07.083386)
17. **Cancer transcriptome profiling at the juncture of clinical translation**
Marcin Cieřlik, Arul M. Chinnaiyan
Nature Reviews Genetics (2017-12-27) <https://doi.org/gcsmnr>
DOI: [10.1038/nrg.2017.96](https://doi.org/10.1038/nrg.2017.96) · PMID: [29279605](https://pubmed.ncbi.nlm.nih.gov/29279605/)

18. IDH1 and IDH2 Mutations in Gliomas

Hai Yan, D. Williams Parsons, Genglin Jin, Roger McLendon, B. Ahmed Rasheed, Weishi Yuan, Ivan Kos, Ines Batinic-Haberle, Siân Jones, Gregory J. Riggins, ... Darell D. Bigner
New England Journal of Medicine (2009-02-19) <https://doi.org/btz6db>
DOI: [10.1056/nejmoa0808710](https://doi.org/10.1056/nejmoa0808710) · PMID: [19228619](https://pubmed.ncbi.nlm.nih.gov/19228619/) · PMCID: [PMC2820383](https://pubmed.ncbi.nlm.nih.gov/PMC2820383/)

19. IDH mutation impairs histone demethylation and results in a block to cell differentiation

Chao Lu, Patrick S. Ward, Gurpreet S. Kapoor, Dan Rohle, Sevin Turcan, Omar Abdel-Wahab, Christopher R. Edwards, Raya Khanin, Maria E. Figueroa, Ari Melnick, ... Craig B. Thompson
Nature (2012-02-15) <https://doi.org/f4msnt>
DOI: [10.1038/nature10860](https://doi.org/10.1038/nature10860) · PMID: [22343901](https://pubmed.ncbi.nlm.nih.gov/22343901/) · PMCID: [PMC3478770](https://pubmed.ncbi.nlm.nih.gov/PMC3478770/)

20. Connections between TET proteins and aberrant DNA modification in cancer

Yun Huang, Anjana Rao
Trends in Genetics (2014-10) <https://doi.org/f6jm7v>
DOI: [10.1016/j.tig.2014.07.005](https://doi.org/10.1016/j.tig.2014.07.005) · PMID: [25132561](https://pubmed.ncbi.nlm.nih.gov/25132561/) · PMCID: [PMC4337960](https://pubmed.ncbi.nlm.nih.gov/PMC4337960/)

21. SETting the Stage for Cancer Development: SETD2 and the Consequences of Lost Methylation

Catherine C. Fahey, Ian J. Davis
Cold Spring Harbor Perspectives in Medicine (2017-05) <https://doi.org/gjmfvg>
DOI: [10.1101/cshperspect.a026468](https://doi.org/10.1101/cshperspect.a026468) · PMID: [28159833](https://pubmed.ncbi.nlm.nih.gov/28159833/) · PMCID: [PMC5411680](https://pubmed.ncbi.nlm.nih.gov/PMC5411680/)

22. Mechanisms underlying mutational signatures in human cancers

Thomas Hellday, Saeed Eshtad, Serena Nik-Zainal
Nature Reviews Genetics (2014-07-01) <https://doi.org/f25gnp>
DOI: [10.1038/nrg3729](https://doi.org/10.1038/nrg3729) · PMID: [24981601](https://pubmed.ncbi.nlm.nih.gov/24981601/) · PMCID: [PMC6044419](https://pubmed.ncbi.nlm.nih.gov/PMC6044419/)

23. Quantitative Proteomics of the Cancer Cell Line Encyclopedia

David P. Nusinow, John Szpyt, Mahmoud Ghandi, Christopher M. Rose, E. Robert McDonald, Marian Kalocsay, Judit Jané-Valbuena, Ellen Gelfand, Devin K. Schweppe, Mark Jedrychowski, ... Steven P. Gygi
Cell (2020-01) <https://doi.org/ggxbh5>
DOI: [10.1016/j.cell.2019.12.023](https://doi.org/10.1016/j.cell.2019.12.023) · PMID: [31978347](https://pubmed.ncbi.nlm.nih.gov/31978347/) · PMCID: [PMC7339254](https://pubmed.ncbi.nlm.nih.gov/PMC7339254/)

24. The repertoire of mutational signatures in human cancer

Ludmil B. Alexandrov, Jaegil Kim, Nicholas J. Haradhvala, Mi Ni Huang, Alvin Wei Tian Ng, Yang Wu, Arnoud Boot, Kyle R. Covington, Dmitry A. Gordenin, Erik N. Bergstrom, ... PCAWG Consortium
Nature (2020-02-05) <https://doi.org/ggkfnv>
DOI: [10.1038/s41586-020-1943-3](https://doi.org/10.1038/s41586-020-1943-3) · PMID: [32025018](https://pubmed.ncbi.nlm.nih.gov/32025018/) · PMCID: [PMC7054213](https://pubmed.ncbi.nlm.nih.gov/PMC7054213/)

25. Significant associations between driver gene mutations and DNA methylation alterations across many cancer types

Yun-Ching Chen, Valer Gotea, Gennady Margolin, Laura Elnitski
PLOS Computational Biology (2017-11-10) <https://doi.org/gchz8h>
DOI: [10.1371/journal.pcbi.1005840](https://doi.org/10.1371/journal.pcbi.1005840) · PMID: [29125844](https://pubmed.ncbi.nlm.nih.gov/29125844/) · PMCID: [PMC5709060](https://pubmed.ncbi.nlm.nih.gov/PMC5709060/)

26. A pan-cancer analysis of driver gene mutations, DNA methylation and gene expressions reveals that chromatin remodeling is a major mechanism inducing global changes in cancer epigenomes

Ahrim Youn, Kyung In Kim, Raul Rabadan, Benjamin Tycko, Yufeng Shen, Shuang Wang
BMC Medical Genomics (2018-11-06) <https://doi.org/gjmhfb>
DOI: [10.1186/s12920-018-0425-z](https://doi.org/10.1186/s12920-018-0425-z) · PMID: [30400878](https://pubmed.ncbi.nlm.nih.gov/30400878/) · PMCID: [PMC6218985](https://pubmed.ncbi.nlm.nih.gov/PMC6218985/)

27. **Computational analysis reveals histotype-dependent molecular profile and actionable mutation effects across cancers**
Daniel Heim, Grégoire Montavon, Peter Hufnagl, Klaus-Robert Müller, Frederick Klauschen
Genome Medicine (2018-11-15) <https://doi.org/gjmhfc>
DOI: [10.1186/s13073-018-0591-9](https://doi.org/10.1186/s13073-018-0591-9) · PMID: [30442178](https://pubmed.ncbi.nlm.nih.gov/30442178/) · PMCID: [PMC6238410](https://pubmed.ncbi.nlm.nih.gov/PMC6238410/)
28. **CNAmet: an R package for integrating copy number, methylation and expression data**
Riku Louhimo, Sampsa Hautaniemi
Bioinformatics (2011-03-15) <https://doi.org/fbq4p2>
DOI: [10.1093/bioinformatics/btr019](https://doi.org/10.1093/bioinformatics/btr019) · PMID: [21228048](https://pubmed.ncbi.nlm.nih.gov/21228048/)
29. **Impacts of somatic mutations on gene expression: an association perspective**
Peilin Jia, Zhongming Zhao
Briefings in Bioinformatics (2016-04-28) <https://doi.org/gjnd5b>
DOI: [10.1093/bib/bbw037](https://doi.org/10.1093/bib/bbw037) · PMID: [27127206](https://pubmed.ncbi.nlm.nih.gov/27127206/) · PMCID: [PMC5862283](https://pubmed.ncbi.nlm.nih.gov/PMC5862283/)
30. **Inference of patient-specific pathway activities from multi-dimensional cancer genomics data using PARADIGM**
Charles J. Vaske, Stephen C. Benz, J. Zachary Sanborn, Dent Earl, Christopher Szeto, Jingchun Zhu, David Haussler, Joshua M. Stuart
Bioinformatics (2010-06-15) <https://doi.org/bcvgjf>
DOI: [10.1093/bioinformatics/btq182](https://doi.org/10.1093/bioinformatics/btq182) · PMID: [20529912](https://pubmed.ncbi.nlm.nih.gov/20529912/) · PMCID: [PMC2881367](https://pubmed.ncbi.nlm.nih.gov/PMC2881367/)
31. **Systematic analysis of somatic mutations impacting gene expression in 12 tumour types**
Jiarui Ding, Melissa K. McConechy, Hugo M. Horlings, Gavin Ha, Fong Chun Chan, Tyler Funnell, Sarah C. Mullaly, Jüri Reimand, Ali Bashashati, Gary D. Bader, ... Sohrab P. Shah
Nature Communications (2015-10-05) <https://doi.org/f7z86p>
DOI: [10.1038/ncomms9554](https://doi.org/10.1038/ncomms9554) · PMID: [26436532](https://pubmed.ncbi.nlm.nih.gov/26436532/) · PMCID: [PMC4600750](https://pubmed.ncbi.nlm.nih.gov/PMC4600750/)
32. **Cancer Genome Landscapes**
B. Vogelstein, N. Papadopoulos, V. E. Velculescu, S. Zhou, L. A. Diaz, K. W. Kinzler
Science (2013-03-28) <https://doi.org/6rg>
DOI: [10.1126/science.1235122](https://doi.org/10.1126/science.1235122) · PMID: [23539594](https://pubmed.ncbi.nlm.nih.gov/23539594/) · PMCID: [PMC3749880](https://pubmed.ncbi.nlm.nih.gov/PMC3749880/)
33. **Scalable Open Science Approach for Mutation Calling of Tumor Exomes Using Multiple Genomic Pipelines**
Kyle Ellrott, Matthew H. Bailey, Gordon Saksena, Kyle R. Covington, Cyriac Kandoth, Chip Stewart, Julian Hess, Singer Ma, Kami E. Chiotti, Michael McLellan, ... Armaz Mariamidze
Cell Systems (2018-03) <https://doi.org/gf9twn>
DOI: [10.1016/j.cels.2018.03.002](https://doi.org/10.1016/j.cels.2018.03.002) · PMID: [29596782](https://pubmed.ncbi.nlm.nih.gov/29596782/) · PMCID: [PMC6075717](https://pubmed.ncbi.nlm.nih.gov/PMC6075717/)
34. **GISTIC2.0 facilitates sensitive and confident localization of the targets of focal somatic copy-number alteration in human cancers**
Craig H Mermel, Steven E Schumacher, Barbara Hill, Matthew L Meyerson, Rameen Beroukhim, Gad Getz
Genome Biology (2011-04-28) <https://doi.org/dzhjqh>
DOI: [10.1186/gb-2011-12-4-r41](https://doi.org/10.1186/gb-2011-12-4-r41) · PMID: [21527027](https://pubmed.ncbi.nlm.nih.gov/21527027/) · PMCID: [PMC3218867](https://pubmed.ncbi.nlm.nih.gov/PMC3218867/)
35. **Scikit-learn: Machine Learning in Python**
Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, ... Édouard Duchesnay
Journal of Machine Learning Research (2011) <http://jmlr.org/papers/v12/pedregosa11a.html>

36. **A beta-mixture quantile normalization method for correcting probe design bias in Illumina Infinium 450 k DNA methylation data**
Andrew E. Teschendorff, Francesco Marabita, Matthias Lechner, Thomas Bartlett, Jesper Tegner, David Gomez-Cabrero, Stephan Beck
Bioinformatics (2013-01-15) <https://doi.org/f25mvt>
DOI: [10.1093/bioinformatics/bts680](https://doi.org/10.1093/bioinformatics/bts680) · PMID: [23175756](https://pubmed.ncbi.nlm.nih.gov/23175756/) · PMCID: [PMC3546795](https://pubmed.ncbi.nlm.nih.gov/PMC3546795/)
37. **Regularization and variable selection via the elastic net**
Hui Zou, Trevor Hastie
Journal of the Royal Statistical Society: Series B (Statistical Methodology) (2005-04)
<https://doi.org/b8cwww>
DOI: [10.1111/j.1467-9868.2005.00503.x](https://doi.org/10.1111/j.1467-9868.2005.00503.x)
38. **An introduction to ROC analysis**
Tom Fawcett
Pattern Recognition Letters (2006-06) <https://doi.org/bpsghb>
DOI: [10.1016/j.patrec.2005.10.010](https://doi.org/10.1016/j.patrec.2005.10.010)
39. **A critical investigation of recall and precision as measures of retrieval system performance**
Vijay Raghavan, Peter Bollmann, Gwang S. Jung
ACM Transactions on Information Systems (1989-07) <https://doi.org/bg4tps>
DOI: [10.1145/65943.65945](https://doi.org/10.1145/65943.65945)
40. **The Precision-Recall Plot Is More Informative than the ROC Plot When Evaluating Binary Classifiers on Imbalanced Datasets**
Takaya Saito, Marc Rehmsmeier
PLOS ONE (2015-03-04) <https://doi.org/f69237>
DOI: [10.1371/journal.pone.0118432](https://doi.org/10.1371/journal.pone.0118432) · PMID: [25738806](https://pubmed.ncbi.nlm.nih.gov/25738806/) · PMCID: [PMC4349800](https://pubmed.ncbi.nlm.nih.gov/PMC4349800/)
41. **The MCC-F1 curve: a performance evaluation technique for binary classification**
Chang Cao, Davide Chicco, Michael M. Hoffman
arXiv (2020-06-23) <https://arxiv.org/abs/2006.11278>
42. **Integrated genomic characterization of IDH1-mutant glioma malignant progression**
Hanwen Bai, Akdes Serin Harmanci, E Zeynep Erson-Omay, Jie Li, Süleyman Coşkun, Matthias Simon, Boris Krischek, Koray Özdoğan, S Bülent Omay, Eric A Sorensen, ... Murat Günel
Nature Genetics (2015-11-30) <https://doi.org/f895hx>
DOI: [10.1038/ng.3457](https://doi.org/10.1038/ng.3457) · PMID: [26618343](https://pubmed.ncbi.nlm.nih.gov/26618343/) · PMCID: [PMC4829945](https://pubmed.ncbi.nlm.nih.gov/PMC4829945/)
43. **Identification and validation of an ERBB2 gene expression signature in breast cancers**
François Bertucci, Nathalie Borie, Christophe Ginestier, Agnès Groulet, Emmanuelle Charafe-Jauffret, José Adélaïde, Jeannine Geneix, Loïc Bachelart, Pascal Finetti, Alane Koki, ... Daniel Birnbaum
Oncogene (2004-01-26) <https://doi.org/dq9kvk>
DOI: [10.1038/sj.onc.1207361](https://doi.org/10.1038/sj.onc.1207361) · PMID: [14743203](https://pubmed.ncbi.nlm.nih.gov/14743203/)
44. **Pan-Cancer Landscape and Analysis of ERBB2 Mutations Identifies Pozotinib as a Clinically Active Inhibitor and Enhancer of T-DM1 Activity**
Jacquelyne P. Robichaux, Yasir Y. Elamin, R. S. K. Vijayan, Monique B. Nilsson, Lemei Hu, Junqin He, Fahao Zhang, Marlese Pisegna, Alissa Poteete, Huiying Sun, ... John V. Heymach
Cancer Cell (2019-10) <https://doi.org/ggcvt27>
DOI: [10.1016/j.ccell.2019.09.001](https://doi.org/10.1016/j.ccell.2019.09.001) · PMID: [31588020](https://pubmed.ncbi.nlm.nih.gov/31588020/) · PMCID: [PMC6944069](https://pubmed.ncbi.nlm.nih.gov/PMC6944069/)

45. **Shaping the cellular landscape with Set2/SETD2 methylation**

Stephen L. McDaniel, Brian D. Strahl

Cellular and Molecular Life Sciences (2017-04-06) <https://doi.org/gbrd9b>

DOI: [10.1007/s00018-017-2517-x](https://doi.org/10.1007/s00018-017-2517-x) · PMID: [28386724](https://pubmed.ncbi.nlm.nih.gov/28386724/) · PMCID: [PMC5545052](https://pubmed.ncbi.nlm.nih.gov/PMC5545052/)