

Nostrian Conquest

Sysop Manual

A from-scratch Rust recreation inspired by the classic 1990s BBS door game Esterian Conquest.

Version 1.0.0-beta.1 — Beta

Revision date: April 2, 2026



This manual © 2026 Mason A. Green and is licensed under CC BY-NC-SA 4.0.

License text: <https://creativecommons.org/licenses/by-nc-sa/4.0/>

Contents

1. Introduction	2
2. Getting Started: Hosting a Campaign	2
2.1. System Requirements	2
2.2. Building from Source	2
2.3. Current Beta Distribution	2
2.4. Choose Your Deployment	3
2.4.1. Nostr Host	3
2.4.2. Localhost Session	3
2.4.3. BBS Door Host	4
2.5. Game Directory Layout	4
2.6. Initializing a New Game	4
2.7. Recommended Public Host	5
2.8. Hosted Player Identity Management	7
3. Game Directory Structure	7
4. Configuration	7
4.0.1. Hosted / Nostr Host	7
4.0.2. Direct nc-game	8
4.0.3. BBS Door Host	8
4.0.4. BBS config.kdl	8
4.1. Display Defaults	9
5. SSH Access	9
6. Localhost Session Setup	9
7. BBS Door Setup	9
7.1. Flags for Door Mode	10
7.2. Drop File	10
7.3. Modern BBS Hosts	11
8. File-Based Turn Submission	11
9. Turn Processing and Maintenance	12
10. Player Management	13
10.1. Reserving Seats	13
11. Terminology	13
12. CLI Reference	14
12.1. nc-sysop	14
12.2. nc-game and nc-door	15

1. Introduction

Nostrian Conquest is a multi-player strategy game inspired by a DOS-era BBS classic and reimplemented in Rust for modern systems. The Rust-native stack provides the game engine, player client, and admin tooling for modern hosts.

This manual is for the **sysop** — the person responsible for hosting a game instance. It covers:

- choosing the right deployment path
- creating and maintaining a DB-only game
- running the recommended Nostr host
- running a local or direct SSH game
- putting `nc-door` on a BBS
- managing players and yearly maintenance

For player-facing rules and gameplay, see the **Player Manual**.

This manual is the authoritative sysop manual for the Rust edition of Nostrian Conquest. The preserved original `.DOC` set in `original/v1.5/` remains historical reference material and an ambiguity fallback for classic operator intent, not a higher-authority replacement for the current Rust manuals.

2. Getting Started: Hosting a Campaign

2.1. System Requirements

- Linux, macOS, or Windows
- Rust toolchain (stable) for normal self-host and VPS deployment
- For the recommended public-hosted flow: an SSH-accessible host plus a Nostr relay reachable by players
- A terminal emulator for localhost or direct SSH play
- A BBS server with socket support only if you specifically want legacy door deployment

2.2. Building from Source

From the repository root:

```
cargo build --release -p nc-sysop -p nc-game -p nc-connect
```

The release binaries will be in `target/release/`.

2.3. Current Beta Distribution

During the current beta, public GitHub Releases include Windows x64, Linux x64, and macOS Apple Silicon `nc-connect` player archives. Public releases also include Windows x64 and Linux x64 `nc-sysop` BBS/sysop packages.

Keep the binary roles straight.

`nc-connect` is the packaged player client for the recommended Nostr path. `nc-game` is the direct localhost and SSH/VPS session client. `nc-door` is the BBS door entrypoint on Windows and Linux. `nc-sysop` is the administrator's tool for creation, settings, maintenance, and hosted operations.

For the Rust edition:

1. VPS sysops should build from tagged source with Cargo and use `scripts/install_vps.sh`.
2. Hosted players can use the public GitHub Releases `nc-connect` archives with the player manual on Windows, Linux, or macOS.
3. BBS sysops can use the public `nc-sysop` package on Linux x64 or Windows x64, or build from tagged source with Cargo.
4. Localhost sysops build from tagged source with Cargo and run `nc-game` directly.

The public Nostrian packages do not bundle preserved Esterian Conquest executables, manuals, or DOS helper assets.

2.4. Choose Your Deployment

NC has three practical ways to run the Rust game.

2.4.1. Nostr Host

Use this when a sysop wants the normal public multiplayer path. Players use `nc-connect`. The host runs `nc-sysop nostr serve`, and the live game runs inside `nc-game` over SSH.

1. Build the binaries.
2. Create a game directory with `nc-sysop new-game`.
3. Register the game with the host and start `nc-sysop nostr serve`.
4. Run `nc-sysop maint` when the year should advance.

The standard VPS layout is:

```
/usr/local/bin/nc-game  
/usr/local/bin/nc-sysop  
/usr/local/bin/nc-gate-keys  
/etc/nc-gate/config.kdl  
/etc/nc-gate/identity.kdl  
/var/lib/nc-gate/keys/  
/srv/nc/games/<slug>/ncgame.db
```

This path can live on a Linux VPS or any other SSH-reachable Linux host. The full hosted setup is covered below under **Recommended Public Host**.

2.4.2. Localhost Session

Use this when a sysop wants direct same-machine play for himself, hotseat testing, or a small trusted session.

1. Build the binaries from source.
2. Create a game directory with `nc-sysop new-game`.
3. Run `nc-game` directly.
4. Run `nc-sysop maint` when the year should advance.

The simplest localhost setup is:

```
nc-sysop new-game /home/sysop/nc-games/friday-night --name "Friday Night NC" --players 4  
nc-game --dir /home/sysop/nc-games/friday-night --player 1
```

2.4.3. BBS Door Host

Use this when the sysop wants nc-door as a door under Mystic, ENiGMA½, or a similar BBS.

1. Create the game directory.
2. Write a minimal per-game config.kdl with players and any fixed-seat reservations.
3. Initialize it with `nc-sysop new-game --bbs`.
4. Launch nc-door with a BBS dropfile.
5. Keep maintenance outside the door. Run `nc-sysop maint` from the host or the BBS event runner.

For BBS hosting, use the public nc-sysop package or build from source. Localhost play remains a source-build path. VPS/Nostr hosting remains a tagged-source Cargo workflow.

For the exact launcher setups, see:

- docs/sysop/bbs/mystic-bbs-setup.md
- docs/sysop/bbs/enigma-bbs-setup.md
- docs/sysop/bbs/synchronet-bbs-setup.md
- docs/sysop/bbs/wwiv-bbs-setup.md

2.5. Game Directory Layout

Hosted/Nostr campaigns are DB-only:

```
/path/to/mygame/  
ncgame.db
```

BBS door campaigns keep a minimal live config file beside the runtime DB:

```
/path/to/mygame/  
config.kdl  
ncgame.db
```

All tools take `--dir /path/to/mygame` to locate the game.

2.6. Initializing a New Game

Create a new game with `nc-sysop new-game`:

```
sudo -u ncgame nc-sysop new-game /srv/nc/games/friday-night --name "Friday Night NC" --  
players 4
```

This creates one runtime file: `ncgame.db`.

For BBS door campaigns, write `config.kdl` first and then initialize with:

```
nc-sysop new-game --bbs /path/to/mygame
```

IMPORTANT: On a VPS host installed with `scripts/install_vps.sh`, create hosted games as the `ncgame` service user. If you create `/srv/nc/games/<slug>` as root, the `nc-nostr.service` daemon may fail to write session leases and hosted joins can time out.

The supported public creation flags are:

- **--name:** String. Optional game title stored in `ncgame.db`. If omitted, `nc-sysop` derives a title from the directory slug.
- **--players:** Integer. Number of empires. Supported range: 1-25. Default: 4.
- **--seed:** Integer. Optional campaign RNG seed. It controls map layout, starting positions, and all random events. If omitted, the engine picks a random seed and saves it to `ncgame.db`. The seed cannot be changed after creation.
- **--bbs:** Flag. Initialize a BBS campaign from an existing per-game `config.kdl`. In this mode, `--name` and `--players` are not accepted on the command line. Use `--seed` only if you intentionally want a reproducible map for that one campaign.

NOTE: Use a different seed for every game. Reusing the same seed produces the same map, starting positions, and event sequence every time. For BBS campaigns, keep that override on the `new-game --bbs --seed ...` command line instead of storing it in `config.kdl`.

The target directory basename becomes the stable game slug. It must use only lowercase ASCII letters, digits, and dashes. The slug is distinct from the human-readable `game_name`, and both are distinct from the per-seat invite codes used by `nc-connect`.

2.7. Recommended Public Host

For new public campaigns, the recommended deployment path is `nc-sysop nostr` plus `nc-connect`. In that model, the `sysop` runs the normal Rust engine on a host, publishes the Nostr-facing daemon, and players join from their own machines with invite codes. The daemon handles identity and seat routing; the live game still runs inside `nc-game` over SSH. This keeps the original asynchronous NC rhythm without requiring per-player Unix account management or BBS door middleware.

If you are recruiting players for a live public game, point them first to nostrian-conquest.com. That landing page can carry the current public contact points and community links before you issue seat-specific invites. At the moment, it should direct them to the Discord channel at discord.gg/FMr8sfBa.

A minimal hosted setup looks like:

```
sudo -u ncgame nc-sysop new-game /srv/nc/games/friday-night --name "Friday Night NC" --
players 4
sudo nc-sysop host games add --config /etc/nc-gate/config.kdl --dir /srv/nc/games/
friday-night
sudo systemctl restart nc-nostr.service
nc-sysop nostr init
nc-sysop nostr serve
```

The values handed to players come from `/etc/nc-gate/config.kdl`:

- `relay` is the Nostr relay URL
- `ssh-host` and `ssh-port` are published in relay discovery during the first session handshake

For a self-hosted relay, that relay URL must already work from outside the box. If `nostr-rs-relay` is listening only on loopback, also run the public HTTPS reverse proxy for the relay hostname before expecting hosted joins to work.

After the daemon is running, view the hosted seat state and get the ready-to-distribute invite commands:

```
nc-sysop nostr seats --dir /path/to/mygame
```

The output lists every seat. Pending seats show the canonical join line:

```
Seat 1 [pending]
      amber-river@relay.example.com
```

```
Seat 2 [claimed]
      npub1...
```

Send each player the raw invite code. The player:

1. Runs `nc-connect`.
2. Presses `N`.
3. Pastes the invite code and presses Enter.

That is the full player-side flow. The invite carries the seat token and relay host, and `nc-connect` discovers the rest from the relay. No extra flags are normally required.

On first join, `nc-connect` creates or unlocks the player's encrypted identity and opens the SSH-backed `nc-game` session. The hosted seat is not claimed until the player actually saves the in-game empire name. If the player disconnects before that save, the invite is still pending and can be used again. After a completed first join, `nc-connect` caches the game locally, downloads the static starmap bundle, and returning players reconnect without re-entering any flags.

One hosted identity can claim only one seat in a given game. If the same keychain identity tries to redeem a second invite for that game, the daemon now rejects it and expects the player to reconnect with the already-claimed seat.

If an invite code is lost or compromised, reissue it:

```
nc-sysop nostr reissue --dir /path/to/mygame --player 2
```

This generates a fresh code for that seat, clears the old claim, and lets the player join again with the new code. On a normal host with the daemon config and identity present, `nc-sysop` now also republishes that game's public 30500 metadata immediately so the relay sees the new invite hash without waiting for a daemon restart.

If a player reports that a pending invite cannot be found on the relay, check and repair the published hosted metadata directly:

```
nc-sysop nostr verify --dir /path/to/mygame
nc-sysop nostr publish --dir /path/to/mygame
```


2.8. Hosted Player Identity Management

Hosted seats are bound to the first player identity that completes the in-game join and saves the empire name. In practice this means the seat is tied to one `npub` until the `sysop` changes it. Returning players should reconnect with the same local NC keychain identity they used when they finished that first join.

Players should not expect to paste the same invite into a brand-new keychain and take over an already-claimed seat. `nc-gate` treats that as a different player identity and rejects the join.

Players also should not expect one keychain identity to hold two seats in the same hosted game. Seat 1 and seat 2 in one campaign must be claimed by different identities, even if the same human is testing both paths.

If a player loses or forgets the original local identity, the supported recovery path is:

1. Reissue that seat with `nc-sysop nostr reissue`.
2. Send the player the new invite.
3. Have the player redeem it from the new keychain identity.

Reissuing is the deliberate “move this seat to a new identity” action. It clears the old `npub` binding and rotates the invite code at the same time.

Hosted seat claims are stored in `ncgame.db`. That SQLite state is the authority for invite codes, claim status, and bound player `npubs`. Hosted claim state no longer lives in a per-game roster file.

NOTE: `/etc/nc-gate/config.kdl` is host-owned. Game-registry edits such as `host games add` and `host games remove` should be run as root. Restart `nc-nostr.service` after changing the game list so the daemon reloads the config.

3. Game Directory Structure

ncgame.db The SQLite runtime database. All game state lives here. Hosted seat claims live here too. Do not edit it by hand.

config.kdl Present only for BBS door campaigns. It holds `players` and optional `seat reservations`. Hosted/Nostr campaigns do not use it.

4. Configuration

Keep these three paths separate:

4.0.1. Hosted / Nostr Host

- Live state: `/etc/nc-gate/config.kdl` plus per-game `ncgame.db`
- Runtime path: `nc-gate` launches hosted `nc-game` sessions
- Operator rule: use `nc-sysop settings set` on the game directory; `maint-all` scheduling applies here

4.0.2. Direct nc-game

- Live state: per-game `ncgame.db`
- Runtime path: `nc-game --dir ... --player ...` on localhost or over SSH
- Operator rule: this uses the same non-BBS settings surface as hosted games, but there is no gate, no relay, and no normal `maint-all` use

4.0.3. BBS Door Host

- Live state: per-game `config.kdl` plus `ncgame.db`
- Runtime path: `nc-door` with a dropfile; ENiGMA¹/₂ also passes `--socket-port` and native Windows Synchronet passes `--socket-descriptor`
- Operator rule: BBS `config.kdl` supports only players and reservations; settings `set` does not apply
- Common hosts: Mystic, ENiGMA¹/₂, and native Windows Synchronet

Use `nc-sysop settings ...` to inspect any non-BBS campaign:

```
nc-sysop settings show --dir /srv/nc/games/friday-night
nc-sysop settings set --dir /srv/nc/games/friday-night --game-name "Friday Night NC"
nc-sysop settings reserve --dir /srv/nc/games/friday-night --player 1 --alias SYSOP
```

For the full non-BBS settings reference, including the raw `settings show` shape and the advanced carried-forward state fields, see `docs/sysop/rust/campaign-settings.md`.

4.0.4. BBS config.kdl

BBS campaigns use a minimal live per-game `config.kdl` instead of the non-BBS settings surface:

```
players 4
reservations {
    seat player=1 alias="SYSOP"
    seat player=2 alias="NightShade"
}
```

Supported BBS fields are only:

- `players`
- `reservations`

`nc-sysop settings show --dir /path/to/mygame` reports BBS campaigns in a different shape:

```
mode=bbs
players=4
reservation seat=1 alias=SYSOP
reservation seat=2 alias=NightShade
```

Do not put `game_name`, `theme`, `snoop`, `session`, `inactivity`, or `maintenance` in the BBS file. Do not put `seed` there either. It is a one-shot new-game command line override, not live BBS config.

For BBS campaigns, `nc-sysop settings reserve` and `settings unreserve` edit this file for you. `settings set` is a non-BBS command surface.

4.1. Display Defaults

The default display look is controlled by `default_theme_key`. That key names a compiled-in color set. It is not a file path.

Players may still choose a local color theme inside `nc-game`. That choice is stored in `ncgame.db` as a player preference.

In BBS door mode, `nc-door` does not use `default_theme_key` at runtime. Door sessions always force the bundled `mag16` palette so ANSI16 terminals and BBS clients get a predictable color-safe baseline.

5. SSH Access

The recommended hosted path above already uses SSH under the hood: players enter through `nc-connect`, and the daemon opens a PTY running `nc-game`. You can also run `nc-game` over SSH directly when you want a private shared-host setup, manual debugging, or a simple trusted deployment without the Nostr invite flow.

`nc-game` runs cleanly over SSH. No special flags are required for modern terminal sessions.

Color mode is auto-detected from the environment:

- `COLORTERM=truecolor` → 24-bit RGB
- `TERM` containing `256color` → 256-color
- Otherwise → 16-color ANSI fallback

Force a specific mode with `--color-mode` if your SSH setup does not propagate `COLORTERM` reliably:

```
nc-game --dir /path/to/mygame --player 1 --color-mode 256
```

UTF-8 encoding (the default) is correct for SSH sessions on modern terminals. Use `--encoding cp437` only if you are proxying through a BBS or a CP437 terminal emulator over SSH.

6. Localhost Session Setup

Localhost play remains a fully supported secondary mode for solo campaigns, hotseat sessions, and sysop testing. Run `nc-game` directly in your terminal:

```
nc-game --dir /path/to/mygame --player 1
```

Color mode and encoding default to `auto / utf8`, which is correct for modern terminal emulators. The client detects `COLORTERM` and `TERM` automatically.

7. BBS Door Setup

`nc-door` is the standard BBS entrypoint on Windows and Linux. Use it when the host is a BBS. Keep `nc-game` for direct localhost and SSH/VPS sessions. In door mode, `nc-door` uses CP437 and 16-color ANSI for classic terminal clients.

7.1. Flags for Door Mode

```
nc-door --dir /path/to/mygame --dropfile /path/to/D00R32.SYS --encoding cp437 --color-mode ansi16
```

--encoding cp437 switches box-drawing characters and other extended characters to the CP437 code page, which is required for correct rendering in classic ANSI-aware BBS terminals (SyncTERM, NetRunner, etc.).

When --encoding cp437 is active, --color-mode defaults to ansi16 automatically. Override only if you know your BBS clients support a richer color depth.

Door sessions also force the bundled mag16 theme regardless of the campaign's normal default_theme_key. The in-game **A>nsi color ON/OFF** command toggles between that ANSI16 palette and a greyscale monochrome projection.

7.2. Drop File

nc-door can read a BBS drop file directly with --dropfile <path>:

```
nc-door --dir /path/to/mygame --dropfile /path/to/D00R32.SYS
```

Supported drop file formats (auto-detected by filename, case-insensitive):

- D00R32.SYS — modern standard (Enigma, Mystic, Talisman, etc.)
- D00R.SYS — legacy, widest BBS software support
- CHAIN.TXT — WWIV format

The drop file supplies the player alias and session time limit. Explicit CLI flags always override drop file values. When --dropfile is given and --encoding is not, encoding defaults to cp437 automatically.

--timeout <minutes> sets a session time limit independently of a drop file.

Reserve seats in the BBS campaign's config.kdl when you want the caller alias to determine the empire automatically. You can either edit the file directly or use:

```
nc-sysop settings reserve --dir /path/to/mygame --player 1 --alias SYSOP
nc-sysop settings reserve --dir /path/to/mygame --player 2 --alias NightShade
```

With that in place, a reserved caller can launch with --dropfile alone. If the caller alias is not reserved, nc-door still uses the same dropfile-only door flow:

- if the alias already matches a stored joined player handle, that caller resumes the matching empire automatically
- if the alias does not match an existing joined empire, the caller lands on the BBS first-time menu and can claim the lowest-numbered open unreserved empire only when the join is actually confirmed
- if the game is full, the caller still reaches the BBS first-time menu, but is refused with the normal no-open-empires notice

NOTE: The original DOS ECGAME.EXE v1.5 expects a strict 32-line WWIV-style CHAIN.TXT drop file. Enigma BBS-generated D00R.SYS / D0RINFO files will crash ECGAME.EXE. See the

legacy DOS compatibility section in `docs/sysop/bbs/enigma-bbs-setup.md` if you need to host the original binary.

7.3. Modern BBS Hosts

The native Rust `nc-door` binary is now verified on Mystic, ENiGMA¹/₂, and Synchronet. The shared core launch shape is simple: pass `--dir` and a dropfile, keep `--encoding cp437`, and use ANSI16 color for classic terminal clients. The helper wrapper at `tools/bbs/run_nc_rust.sh` remains useful only for source-tree testing and is not the normal packaged door path.

Mystic uses the direct dropfile path:

```
nc-door --dir /path/to/mygame --dropfile /path/to/D00R32.SYS
```

ENiGMA¹/₂ uses the same dropfile plus its temporary localhost socket server:

```
nc-door --dir /path/to/mygame --dropfile /path/to/D00R32.SYS --socket-port {srvPort}
```

Native Windows Synchronet also passes the inherited socket descriptor:

```
nc-door --dir /path/to/mygame --dropfile %f --socket-descriptor %H
```

WWIV is documented separately as an experimental Windows host path:

```
nc-door --dir /path/to/mygame --dropfile /path/to/CHAIN.TXT
```

For the exact launcher setups, see `docs/sysop/bbs/mystic-bbs-setup.md`, `docs/sysop/bbs/enigma-bbs-setup.md`, `docs/sysop/bbs/synchronet-bbs-setup.md`, and `docs/sysop/bbs/wwiv-bbs-setup.md`.

8. File-Based Turn Submission

For localhost, shared-host, or custom-client workflows, players can submit orders by writing a KDL turn file and passing it to `nc-game submit-turn`. Use `--check` to validate without writing, then run without it to apply:

```
nc-game submit-turn --check --dir /path/to/mygame --player 1 --file /path/to/player1-turn.kdl
```

```
nc-game submit-turn --dir /path/to/mygame --player 1 --file /path/to/player1-turn.kdl
```

The `--player` value must match the `turn player=...` header in the file. If any order in the file is invalid, the entire submission is rejected and nothing is written. This is a direct apply command, not a queue or upload inbox.

A minimal turn file:

```
turn player=1 year=3000
tax rate=37
```

A fuller example:

```
turn player=1 year=3000

tax rate=37
```

```
planet record=16 {
    build points=4 kind="scout"
}

fleet record=1 {
    order speed=3 kind="scout_system" x=16 y=13
}

message to=2 subject="Border" body="Watching the north lane."
```

For the full node reference and schema, see `docs/sysop/rust/turn-kdl.md`.

9. Turn Processing and Maintenance

Run yearly maintenance with:

```
nc-sysop maint /path/to/mygame [turns]
nc-sysop maint-all [--config /etc/nc-gate/config.kdl]
```

`nc-sysop maint` advances the campaign in `ncgame.db` immediately. It does not change the schedule fields. NC does not schedule maintenance by itself. For one direct localhost game, one manual SSH/VPS game, or one BBS game, invoke `nc-sysop maint` from your own scheduler or event tooling:

- a systemd timer
- cron
- a BBS event runner
- or manual sysop operation

For multi-game hosted/Nostr operation, prefer a single global timer that runs `nc-sysop maint-all`. It reads the configured game directories from the gate config, advances only games whose schedule is enabled and already due, and skips games with live session leases so a player is never interrupted by maintenance. After a scheduled run, it writes the next due time back into `ncgame.db`.

To put one hosted game on a real schedule, turn scheduling on and set the first due time yourself:

```
nc-sysop settings set --dir /srv/nc/games/friday-night --maintenance-enabled on --
maintenance-interval-minutes 10080 --maintenance-next-due 1775347200
```

That example enables weekly scheduling. 10080 is seven days in minutes. 1775347200 is just a sample Unix timestamp. Replace it with the first due time you actually want.

Treat these schedule fields as hosted `maint-all` metadata. They do not create their own timer. They are not BBS `config.kdl` fields. If you run a direct localhost or manual SSH game, you can ignore them and schedule `maint` `/path/to/mygame` yourself.

10. Player Management

Non-BBS campaigns keep player reservations and the carried-forward inactivity-related state in `ncgame.db`. BBS door campaigns do not use a separate inactivity block in `config.kdl`; caller idle handling belongs to the BBS software.

10.1. Reserving Seats

To reserve empire slots for specific BBS users, edit the per-game BBS `config.kdl` or use:

```
nc-sysop settings reserve --dir /path/to/mygame --player 1 --alias SYSOP
nc-sysop settings reserve --dir /path/to/mygame --player 2 --alias NightShade
```

Each `seat` entry binds one 1-based empire slot to one caller alias. Alias matching is ASCII case-insensitive, so `NightShade`, `nightshade`, and `NIGHTSHADE` are treated as the same reservation.

With reservations in place, launch `nc-door` with `--dropfile` and let the caller alias choose the empire automatically:

```
nc-door --dir /path/to/mygame --dropfile /path/to/D00R32.SYS
```

Important rules:

- if the caller alias is reserved, `--dropfile` alone is enough
- if the caller alias is not reserved and already matches a stored joined player handle, that caller resumes the matching empire automatically
- if the caller alias is not reserved and does not match an existing joined player handle, the caller starts on the BBS first-time menu
- if a reservation conflicts with an already-stored different player handle, `nc-door` will stop with a clear error so the sysop can reconcile the reservation and the runtime state
- if no open unreserved empires remain, J from the BBS first-time menu is refused and the caller stays on that menu

Reserving a seat does not by itself join or pre-name the empire. It only routes the caller to the intended slot. The usual first-time join flow still claims an empire only on successful join confirmation, and that first successful join records the caller alias into the player record for later dropfile logins.

For localhost and direct console play, use `nc-game` and follow the localhost setup section earlier in this manual instead of the BBS dropfile path.

11. Terminology

game directory The directory containing `ncgame.db` for one running game. Passed to all tools with `--dir`.

nc-sysop The public Rust command-line sysop tool for campaign creation maintenance, and Nostr hosting.

nc-connect The beta-quality player-side connection client for the recommended hosted flow. It manages the player's Nostr identity, joins games by invite code, downloads the static starmap bundle on first join, and opens the SSH-backed `nc-game` session.

nc-game The Rust TUI player client for direct localhost and SSH/VPS sessions.

nc-door The Rust BBS door entrypoint. It runs the same game flow as `nc-game`, but it is the staged binary for Windows and Linux BBS hosts.

ncgame.db The SQLite database that is the runtime source of truth for the Rust engine.

non-BBS campaign settings The sysop-managed runtime policy rows stored in `ncgame.db` for hosted/Nostr and direct `nc-game` campaigns. They control game name, the default compiled-in color set, hosted maintenance metadata, optional alias reservations, and a small set of carried-forward classic setup fields.

config.kdl Present only for BBS door campaigns. It holds `players` and optional seat reservations.

12. CLI Reference

12.1. nc-sysop

`nc-sysop <subcommand> [options]`

- **new-game:** Create a new campaign directory. Hosted/Nostr campaigns use `--name`, `--players`, and `--seed`. BBS campaigns use `new-game --bbs` with a minimal per-game `config.kdl`.
- **settings show|set|reserve|unreserve:** Inspect or edit non-BBS runtime policy in `ncgame.db`, or edit BBS seat reservations in per-game `config.kdl`.
- **host games list|add|remove:** Inspect or edit the global game registry in `/etc/nc-gate/config.kdl`.
- **host status:** Summarize the configured host, served game directories, claim counts, busy state, and maintenance-due state.
- **nostr init:** Initialize the Nostr-hosting identity and config for the recommended public multiplayer path.
- **nostr serve:** Run the Nostr-facing daemon that authenticates players and launches `nc-game` sessions.
- **nostr seats:** List the hosted seat state stored in `ncgame.db` for one game directory.
- **nostr reissue:** Generate a fresh invite code for one hosted seat, clear its old player binding, and republish that game's public 30500 metadata when possible.
- **nostr claim:** Manually bind one hosted seat to a specific `npub` and republish that game's public 30500 metadata when possible.
- **nostr publish:** Republish one game's public 30500 metadata to the configured relay immediately.
- **nostr verify:** Compare one game's local hosted-seat state against the latest published 30500 on the configured relay.
- **maint:** Run one or more maintenance turns against `ncgame.db`.
- **maint-all:** Sweep every game registered in the gate config, skip games that are not due or that currently have active sessions, and advance only games whose schedule is enabled.

12.2. nc-game and nc-door

```
nc-game --dir <game_dir> [--player <1-based index>] [options]
nc-door --dir <game_dir> --dropfile <path> [options]
nc-game submit-turn [--check] --dir <game_dir> --player <record> --file <turn.kdl>
```

Use `nc-game` for direct localhost and SSH/VPS sessions. Use `nc-door` for BBS door launches. The interactive flags below apply to both binaries unless a host setup guide says otherwise.

Interactive client flags:

- **--dir <path>**: Game directory containing `ncgame.db`. Required.
- **--player <N>**: 1-based empire index for direct localhost or SSH play. Normal BBS dropfile launches can omit it.
- **--encoding <utf8|cp437>**: Output encoding. Default: `utf8`. Use `cp437` for BBS or door mode.
- **--color-mode <ansi16|256|truecolor|auto>**: Color depth. Default: `auto` from the environment. CP437 mode defaults to `ansi16`.
- **--dropfile <path>**: Parse a BBS drop file (`D00R32.SYS`, `D00R.SYS`, or `CHAIN.TXT`). It supplies the alias and timeout, defaults encoding to `cp437`, and resolves the player seat through BBS `config.kdl` reservations or stored joined-player aliases.
- **--socket-port <value>**: Connect back to a localhost door socket. Mainly for ENiGMA½ `abracadabra` in socket mode.
- **--socket-descriptor <value>**: Native Windows door socket handle. Mainly for Synchronet-style socket door launches.
- **--session-token <hex>**: Hosted-session lease token injected by `nc-gate` during Nostr or SSH login. Normal local and BBS launches do not pass this flag.
- **--timeout <minutes>**: Session time limit in minutes. It overrides any drop file value.
- **--export-root <path>**: Optional map or export staging root for local or BBS file handoff workflows.
- **--queue-dir <path>**: Override turn queue directory. Default: `<game_dir>/queue`.

submit-turn flags:

- **--check**: Validate the KDL file without mutating the campaign.
- **--dir <path>**: Game directory containing `ncgame.db`. Required.
- **--player <N>**: 1-based empire index. Required, and it must match the KDL header.
- **--file <path>**: Turn submission KDL file to validate or apply. Required.

NOTE: `nc-game submit-turn` is all-or-nothing. If any command in the file is invalid, the entire submission is rejected and nothing is written to `ncgame.db`.