

# CS371N: Natural Language Processing

## Lecture 8: Bias in Embeddings, Multilingual Embeddings

Greg Durrett





# Announcements

---

- ▶ Assignment 2 due in one week
- ▶ Bias in embeddings response due next Tuesday (submit on Canvas)



# Recap

---




# Playing around with embeddings

---

Cosine similarity: 
$$\cos(\mathbf{x}, \mathbf{y}) = \frac{\mathbf{x} \cdot \mathbf{y}}{\|\mathbf{x}\| \|\mathbf{y}\|}$$

(equal to the cosine of the angle between two vectors)

- 1) Look at the word “movie” and compare it to some other common words (“good”, other content words). Does cosine similarity between these embeddings reflect your intuition about word similarity?
- 2) Now compare “good” to both other sentiment-bearing words (“great”, “bad”, etc.) and other words. What similarities do the embeddings capture well? Is there anything they do badly at?




# Using Word Embeddings

---

- ▶ Approach 1: learn embeddings as parameters from your data
  - ▶ Often works pretty well
- ▶ Approach 2: initialize using GloVe, keep frozen
  - ▶ Faster because no need to update these parameters
- ▶ Approach 3: initialize using GloVe, fine-tune
  - ▶ Works best for some tasks

# Beyond Word Embeddings



# fastText: Sub-word Embeddings

- ▶ Same as SGNS, but break words down into n-grams with  $n = 3$  to  $6$

where:

3-grams: <wh, whe, her, ere, re>

4-grams: <whe, wher, here, ere> ,

5-grams: <wher, where, here> ,

6-grams: <where, where>

- ▶ Replace  $w \cdot c$  in skip-gram computation with 
$$\left( \sum_{g \in \text{ngrams}} w_g \cdot c \right)$$



# Preview: Subword Tokenization


---

- ▶ Words are a difficult unit to work with, word vocabularies get very large
- ▶ Character-level models don't work well
- ▶ Compromise solution: use thousands of “word pieces” (which may be full words but may also be parts of words)

Input: \_the \_**eco tax** \_port i co \_in \_Po nt - de - Bu is ...

- ▶ Rare words (ecotax, portico, Pont-de-Buis) all get broken up into smaller units we can embed





# Preview: Subword Tokenization

(a)	<b>Original:</b>	furiously			(b)	<b>Original:</b>	tricycles						
	<b>BPE:</b>	_fur		iously		<b>BPE:</b>	_t		ric		y		cles
	<b>Unigram LM:</b>	_fur		ious			ly	<b>Unigram LM:</b>	_tri		cycle		s

(c)	<b>Original:</b>	Completely preposterous suggestions														
	<b>BPE:</b>	_Comple		t		ely		_prep		ost		erous		_suggest		ions
	<b>Unigram LM:</b>	_Complete		ly		_pre		post		er		ous		_suggestion		s


- ▶ Byte-pair encoding (BPE) produces less linguistically plausible units than another technique based on a unigram language model



# Sentence Embeddings



---

- ▶ What if we want embedding representations for whole sentences?
- ▶ Skip-*thought* vectors (Kiros et al., 2015), similar to skip-gram generalized to a sentence level (more later)
- ▶ Is there a way we can compose vectors to make sentence representations?  
Summing?
- ▶ Will return to this in a few weeks as we move on to syntax and semantics




# Preview: Context-dependent Embeddings

- ▶ How to handle different word senses? One vector for *bats*



- ▶ ELMo: train a neural language model to predict the next word given previous words in the sentence, use its internal representations as word vectors
- ▶ *Context-sensitive* word embeddings: depend on rest of the sentence
- ▶ *Huge* improvements across nearly all NLP tasks over GloVe

# Bias in Word Embeddings



# What can go wrong with word embeddings?

---

- ▶ What's wrong with learning a word's "meaning" from its usage? Maybe some words are used in ways we don't want to replicate?
- ▶ What data are we learning from?
- ▶ What are we going to learn from this data?



# Bias Exercise

---

Answer the following in  $\leq 3$  sentences each.

Consider learning word embeddings from a **corpus of news articles**.

1. Think about a similarity association a model might learn that you believe constitutes **bias**. For this association, list (a) what the word pair is; (b) why you think this is present in the data (e.g., give an example of how it could appear in a news story)
  2. Embeddings are often used at the input layer of a neural network. Can you think of a task for which this biased association might lead to bias in the system?
- 

Now consider learning word embeddings from a **corpus of social media data comments (think about reddit + Twitter)**.

3. Do you think you're likely to see the bad association from above? Why or why not?
4. Come up with a new biased similarity association; list (a) what the word pair is; (b) why you think this is present in social media data





# Bias Exercise

---

## News articles:

1. Similarity association a model might learn that you believe constitutes **bias**?
2. Where might this biased association might lead to bias in the system?

## Social media:

3. Do you think you're likely to see the bad association from above? Why or why not?
4. New biased similarity association?



# What do we mean by bias?

- ▶ Compare distance (using cosine similarity) of many occupations to the vectors for *he* and *she*

1. homemaker  
4. librarian  
7. nanny  
10. housekeeper

## Extreme *she* occupations

2. nurse  
3. receptionist  
5. socialite  
6. hairdresser  
8. bookkeeper  
9. stylist  
11. interior designer  
12. guidance counselor

1. maestro  
4. philosopher  
7. financier  
10. magician

## Extreme *he* occupations

2. skipper  
3. protege  
5. captain  
6. architect  
8. warrior  
9. broadcaster  
11. fighter pilot  
12. boss

- ▶ These regularities are not restricted to gendered pronouns.  
*receptionist* is closer to *softball* than *football*
- ▶ This work focuses on binary gender stereotypes, but it can be extended





# What do we mean by bias?

## Extreme *she* occupations

1. homemaker
4. librarian
7. nanny
10. housekeeper
2. nurse
5. socialite
8. bookkeeper
11. interior designer
3. receptionist
6. hairdresser
9. stylist
12. guidance counselor

## Extreme *he* occupations

1. maestro
4. philosopher
7. financier
10. magician
2. skipper
5. captain
8. warrior
11. figher pilot
3. protege
6. architect
9. broadcaster
12. boss

Bolukbasi et al. (2016)

Racial Analogies	
black → homeless	caucasian → servicemen
caucasian → hillbilly	asian → suburban
asian → laborer	black → landowner
Religious Analogies	
jew → greedy	muslim → powerless
christian → familial	muslim → warzone
muslim → uneducated	christian → intellectually


Manzini et al. (2019)

- ▶ Nearest neighbor of (b - a + c)




# Debiasing

- ▶ Identify gender subspace with gendered words (avg “male” - avg “female” word)
- ▶ Project words onto this subspace
- ▶ Subtract those projections from the original word




# Bolukbasi et al. (2016)



# Hardness of Debiasing

- ▶ Not that effective...and the male and female words are still clustered together
- ▶ Bias pervades the word embedding space and isn't just a local property of a few words







# Toxicity

- ▶ “Toxic degeneration”: neural models that generate toxic stuff

GENERATION OPTIONS:

Model:  ▼

Prompt:  ▼

Toxicity:

⚠ Toxic generations may be triggering.

*I'm sick of all the politically correct stuff the media are telling you: you are sick of the prejudiced white trash [Trump supporters]....|*

- ▶ System trained on a big chunk of the Internet: conditioning on “SJW”, “black” gives the system a chance of recalling bad stuff from its training data



# Takeaways

---

- ▶ Gendered associations are pervasive in language. There's not some simple preprocessing that will remove them
- ▶ Debiasing techniques don't always seem to remove this information from the embedding layer
- ▶ Current approach: use RLHF on top of language models to fix it at the output layer
- ▶ ...but the model still has bias internally, and it may even be possible to access (Waluigi Effect)


# Multilingual Word Embeddings



# Recall: Training Embeddings

---

- ▶ Input: a large corpus of text in some language (English)
- ▶ Output: embedding for each word
- ▶ What can we do if we have *multiple corpora* of text in *different languages*?
  - ▶ If we learn embeddings on each language individually, these embeddings won't necessarily have any relation to one another





# Multilingual Embeddings

- ▶ Input: corpora in many languages. Output: embeddings where similar words *in different languages* have similar embeddings


I have an apple  
47 24 18 427

J' ai des oranges  
47 24 89 1981



- ▶ multiCluster: use bilingual dictionaries to form clusters of words that are translations of one another, replace corpora with cluster IDs, train “monolingual” embeddings over all these corpora
- ▶ Works okay but not all that well





# Aligning existing embeddings


---

- ▶ What if you already have embeddings in two languages and you just want to align them?
- ▶ Given: dictionary of pairs  $(x_i, z_i)$ , where  $x$  are word embeddings in a source lang (English) and  $z$  are word embeddings in a target lang (French)
- ▶ Learn a matrix  $W$  to minimize the following:


$$\min_W \sum_{i=1}^n \|Wx_i - z_i\|^2$$

(Looks like a loss function! Can learn with SGD on the pairs)

# Aligning existing embeddings



- ▶ Rotation learns to align these word embedding spaces! Does this cartoon match reality?



# Aligning existing embeddings

Table 2: Accuracy of the word translation methods using the WMT11 datasets. The Edit Distance uses morphological structure of words to find the translation. The Word Co-occurrence technique based on counts uses similarity of contexts in which words appear, which is related to our proposed technique that uses continuous representations of words and a Translation Matrix between two languages.

Translation	Edit Distance		Word Co-occurrence		Translation Matrix		ED + TM		Coverage
	P@1	P@5	P@1	P@5	P@1	P@5	P@1	P@5	
En → Sp	13%	24%	19%	30%	33%	51%	43%	60%	92.9%
Sp → En	18%	27%	20%	30%	35%	52%	44%	62%	92.9%
En → Cz	5%	9%	9%	17%	27%	47%	29%	50%	90.5%
Cz → En	7%	11%	11%	20%	23%	42%	25%	45%	90.5%



# Takeaways

---

- ▶ Can learn word embeddings with correspondences between languages
- ▶ Later in the course: pre-trained models that are pre-trained over 100+ languages simultaneously
- ▶ Next class: language modeling