
Consuming Senders from Coroutine-Native Code

Document Number: D4055R0
Date: 2026-03-13
Audience: LEWG
Reply-to: Vinnie Falco vinnie.falco@gmail.com
Steve Gerbino steve@gerbino.co

Table of Contents

Abstract

Revision History

R0: March 2026 (post-Croydon mailing)

1. Disclosure

2. The Bridge

3. Demonstration

4. What the Bridge Does

5. What the Bridge Does Not Require

6. The Narrowest Abstraction

7. Acknowledgments

References

Appendix A. Bridge Implementation

Abstract

An `IoAwaitable` bridge ([P4003R0](#)^[3]) consumes `std::execution` senders with inline operation state, correct stop token propagation, and automatic executor dispatch-back. The bridge is one class template. The complete implementation is in Appendix A.

This paper is one of a suite of five that examines the relationship between compound I/O results and the sender three-channel model. The companion papers are [D4050R0](#)^[13], “On Task Type Diversity”; [D4053R0](#)^[2], “Sender I/O: A Constructed Comparison”; [D4054R0](#)^[11], “Two Error Models”; and [D4056R0](#)^[12], “Producing Senders from Coroutine-Native Code.”

Revision History

R0: March 2026 (post-Croydon mailing)

- Initial version.
-

1. Disclosure

The authors developed [Capy](#)^[4] and [Corosio](#)^[6] and believe coroutine-native I/O is the correct foundation for networking in C++. The bridge depends on [Capy](#)^[4] (coroutine primitives, no sockets, no platform I/O) and [beman::execution](#)^[5]. The authors provide information, ask nothing, and serve at the pleasure of the chair.

2. The Bridge

```
copy::task<int> compute(auto sched)
{
    int result = co_await copy::await_sender(
        ex::schedule(sched)
        | ex::then([] {
            std::cout
                << " sender running on thread "
                << std::this_thread::get_id()
                << "\n";
            return 42 * 42;
        }));

    std::cout
        << " coroutine resumed on thread "
        << std::this_thread::get_id() << "\n";

    co_return result;
}
```

`await_sender` returns a `sender_awaitable` satisfying `IoAwaitable` (P4003R0^[3]). Any coroutine type that propagates `io_env` through `await_suspend(h, io_env const*)` can use it. Complete implementation in Appendix A.

3. Demonstration

```
main thread: 32208
  sender running on thread 9560
  coroutine resumed on thread 34356
result: 1764
```

The sender ran on the `run_loop` thread. The coroutine resumed on the Copy thread pool. Zero bytes allocated beyond the coroutine frame.

4. What the Bridge Does

The bridge consumes any `std::execution` sender. Operation state stored inline. `set_value`, `set_error`, `set_stopped` handled. Any pipeline - `when_all`, `then`, `let_value`, `on` - works.

The bridge inspects error completion signatures at compile time. If the sender advertises

`set_error(std::error_code)`, `await_resume` returns `io_result<T>`:

```
auto [ec, val] = co_await await_sender(sndr);
```

No exceptions for `error_code`. Otherwise `await_resume` returns `T` directly; genuine exceptions are rethrown. Static dispatch.

This is the consuming side of the abstraction floor (D4056R0^[12] Section 4):

Region	What the code sees
Above the floor	<code>error_code</code> alone - composition works
Below the floor	<code>(error_code, size_t)</code> - both values intact

When the sender completes, the bridge posts the resumption back to the coroutine's originating executor. The coroutine resumes in the correct context regardless of where the sender executed.

Does not use `execution::task`.

5. What the Bridge Does Not Require

Property	<code>execution::task</code>	Bridge
Routine I/O errors become exceptions	Yes	No
Type erasure on connect	Yes	No
AS-EXCEPT-PTR for <code>error_code</code>	Yes	No
Zero allocations beyond coroutine frame	No	Yes

`std::execution::task` is not necessary to consume senders.

6. The Narrowest Abstraction

The bridge depends on `Capy`^[4] and `std::execution`. No platform I/O dependency. The coroutine type does not change when the bridge is added.

7. Acknowledgments

The authors thank Dietmar Kühl for `beman::execution`^[5] and for the channel-routing enumeration in `P2762R2`^[7], Michał Dominiak, Eric Niebler, and Lewis Baker for `std::execution`, Chris Kohlhoff for identifying the partial-success problem in `P2430R0`^[8], Kirk Shoop for the completion-token heuristic analysis in `P2471R1`^[9], Fabio Fracassi for `P3570R2`^[10], Ville Voutilainen and Jens Maurer for reflector discussion on dispatch patterns, Herb Sutter for identifying the need for tutorials and documentation, Mark Hoemmen for insights on `std::linalg` and the layered abstraction model, and Peter Dimov for the refined channel mapping.

References

1. `P2300R10` - “std::execution” (Michał Dominiak et al., 2024). <https://wg21.link/p2300r10>
2. `D4053R0` - “Sender I/O: A Constructed Comparison” (Vinnie Falco, Steve Gerbino, 2026). <https://wg21.link/d4053r0>
3. `P4003R0` - “Coroutines for I/O” (Vinnie Falco, Steve Gerbino, Mungo Gill, 2026). <https://wg21.link/p4003r0>
4. `cppalliance/capy` - Coroutine primitives library. <https://github.com/cppalliance/capy>
5. `bemanproject/execution` - Community implementation of `std::execution`. <https://github.com/bemanproject/execution>
6. `cppalliance/corosio` - Coroutine-native networking library. <https://github.com/cppalliance/corosio>
7. `P2762R2` - “Sender/Receiver Interface For Networking” (Dietmar Kühl, 2023). <https://wg21.link/p2762r2>
8. `P2430R0` - “Partial success scenarios with P2300” (Chris Kohlhoff, 2021). <https://wg21.link/p2430r0>
9. `P2471R1` - “NetTS, ASIO and Sender Library Design Comparison” (Kirk Shoop, 2021). <https://wg21.link/p2471r1>

10. **P3570R2** - "Optional variants in sender/receiver" (Fabio Fracassi, 2025). <https://wg21.link/p3570r2>
 11. **D4054R0** - "Two Error Models" (Vinnie Falco, 2026). <https://wg21.link/d4054r0>
 12. **D4056R0** - "Producing Senders from Coroutine-Native Code" (Vinnie Falco, Steve Gerbino, 2026).
<https://wg21.link/d4056r0>
 13. **D4050R0** - "On Task Type Diversity" (Vinnie Falco, 2026). <https://wg21.link/d4050r0>
-

Appendix A. Bridge Implementation

```
#include <boost/capy/error.hpp>
#include <boost/capy/ex/io_env.hpp>
#include <boost/capy/io_result.hpp>

#include <beman/execution/execution.hpp>

#include <coroutine>
#include <exception>
#include <new>
#include <stop_token>
#include <system_error>
#include <tuple>
#include <type_traits>
#include <utility>
#include <variant>

namespace boost::capy {

namespace detail {

struct stopped_t {};

struct operation_cancelled {};

struct bridge_env
{
    std::stop_token st_;

    auto query(
        beman::execution::get_stop_token_t const&)
        const noexcept
    {
        return st_;
    }
};

template<class Sender>
using sender_single_value_t =
    beman::execution::value_types_of_t<
        Sender,
        bridge_env,
        std::tuple,
        std::type_identity_t>;
```

```

template<class Sender>
struct has_error_code_completion
{
    template<class... Es>
    struct checker
    {
        static constexpr bool value =
            (std::is_same_v<
                Es, std::error_code> || ...);
    };

    static constexpr bool value =
        beman::execution::error_types_of_t<
            Sender,
            bridge_env,
            checker>::value;
};

template<class Sender>
constexpr bool has_error_code_v =
    has_error_code_completion<Sender>::value;

// Variant when sender can complete with
// set_error(error_code): separate slot for
// error_code so it is not wrapped in
// exception_ptr.
template<class ValueTuple>
using ec_result_variant = std::variant<
    std::monostate,
    ValueTuple,
    std::error_code,
    std::exception_ptr,
    stopped_t>;

// Variant when sender does not complete with
// set_error(error_code).
template<class ValueTuple>
using no_ec_result_variant = std::variant<
    std::monostate,
    ValueTuple,
    std::exception_ptr,
    stopped_t>;

template<class ValueTuple, bool HasEc>
using result_variant = std::conditional_t<
    HasEc,

```



```

    ec_result_variant<ValueTuple>,
    no_ec_result_variant<ValueTuple>>;

template<class ValueTuple, bool HasEc>
struct bridge_receiver
{
    using receiver_concept =
        beman::execution::receiver_t;

    result_variant<ValueTuple, HasEc>* result_;
    std::coroutine_handle<> cont_;
    io_env const* env_;

    auto get_env() const noexcept -> bridge_env
    {
        return {env_>stop_token};
    }

    template<class... Args>
    void set_value(Args&&... args) && noexcept
    {
        result_>template emplace<1>(
            std::forward<Args>(args)...);
        env_>executor.post(cont_);
    }

    template<class E>
    void set_error(E&& e) && noexcept
    {
        if constexpr (
            HasEc &&
            std::is_same_v<
                std::decay_t<E>,
                std::error_code>)
            result_>template emplace<2>(
                std::forward<E>(e));
        else if constexpr (
            std::is_same_v<
                std::decay_t<E>,
                std::exception_ptr>)
        {
            constexpr auto idx = HasEc ? 3 : 2;
            result_>template emplace<idx>(
                std::forward<E>(e));
        }
        else
        {

```

```

        constexpr auto idx = HasEc ? 3 : 2;
        result_>template emplace<idx>(
            std::make_exception_ptr(
                std::forward<E>(e)));
    }
    env_>executor.post(cont_);
}

void set_stopped() && noexcept
{
    constexpr auto idx = HasEc ? 4 : 3;
    result_>template emplace<idx>(
        stopped_t{});
    env_>executor.post(cont_);
}
};

} // namespace detail

template<class Sender>
struct sender_awaitable
{
    static constexpr bool has_ec =
        detail::has_error_code_v<Sender>;

    using value_tuple =
        detail::sender_single_value_t<Sender>;
    using variant_type =
        detail::result_variant<
            value_tuple, has_ec>;
    using receiver_type =
        detail::bridge_receiver<
            value_tuple, has_ec>;
    using op_state_type = decltype(
        beman::execution::connect(
            std::declval<Sender>(),
            std::declval<receiver_type>()));

    Sender sndr_;
    variant_type result_{};

    alignas(op_state_type)
    unsigned char op_buf_[sizeof(op_state_type)];
    bool op_constructed_ = false;

    explicit sender_awaitable(Sender sndr)
        : sndr_(std::move(sndr))

```

```

{
}

sender_awaitable(sender_awaitable&& o)
    noexcept(
        std::is_nothrow_move_constructible_v<
            Sender>)
    : sndr_(std::move(o.sndr_))
{
}

sender_awaitable(
    sender_awaitable const&) = delete;
sender_awaitable& operator=(
    sender_awaitable const&) = delete;
sender_awaitable& operator=(
    sender_awaitable&&) = delete;

~sender_awaitable()
{
    if(op_constructed_)
        std::launder(
            reinterpret_cast<op_state_type*>(
                op_buf_))->~op_state_type();
}

bool await_ready() const noexcept
{
    return false;
}

std::coroutine_handle<>
await_suspend(
    std::coroutine_handle<> h,
    io_env const* env)
{
    ::new(op_buf_) op_state_type(
        beman::execution::connect(
            std::move(sndr_),
            receiver_type{
                &result_, h, env}));
    op_constructed_ = true;
    beman::execution::start(
        *std::launder(
            reinterpret_cast<
                op_state_type*>(
                    op_buf_)));
}

```

```

        return std::noop_coroutine();
    }

    auto await_resume()
    {
        if constexpr (has_ec)
            return await_resume_ec();
        else
            return await_resume_no_ec();
    }

private:
    // Sender can complete with
    // set_error(error_code). Return io_result
    // so the error code is a value, not an
    // exception.
    auto await_resume_ec()
    {
        // exception_ptr at index 3
        if(result_.index() == 3)
            std::rethrow_exception(
                std::get<3>(result_));

        if constexpr (
            std::tuple_size_v<
                value_tuple> == 0)
        {
            // stopped at index 4
            if(result_.index() == 4)
                return io_result<>{
                    make_error_code(
                        error::canceled)};

            if(result_.index() == 2)
                return io_result<>{
                    std::get<2>(result_)};

            return io_result<>{};
        }
        else if constexpr (
            std::tuple_size_v<
                value_tuple> == 1)
        {
            using T = std::tuple_element_t<
                0, value_tuple>;
            if(result_.index() == 4)
                return io_result<T>{
                    make_error_code(
                        error::canceled)};
        }
    }

```

```

        if(result_.index() == 2)
            return io_result<T>{
                std::get<2>(result_)};
        return io_result<T>{
            {},
            std::get<0>(
                std::get<1>(
                    std::move(result_)))});
    }
    else
    {
        if(result_.index() == 4)
            return io_result<value_tuple>{
                make_error_code(
                    error::canceled)};
        if(result_.index() == 2)
            return io_result<value_tuple>{
                std::get<2>(result_)};
        return io_result<value_tuple>{
            {},
            std::get<1>(
                std::move(result_))});
    }
}

// Sender does not complete with
// set_error(error_code). Return the value
// directly; rethrow exceptions.
auto await_resume_no_ec()
{
    // exception_ptr at index 2
    if(result_.index() == 2)
        std::rethrow_exception(
            std::get<2>(result_));
    // stopped at index 3
    if(result_.index() == 3)
        throw detail::operation_cancelled{};

    if constexpr (
        std::tuple_size_v<
            value_tuple> == 0)
        return;
    else if constexpr (
        std::tuple_size_v<
            value_tuple> == 1)
        return std::get<0>(
            std::get<1>(

```

```

        std::move(result_));
    else
        return std::get<1>(
            std::move(result_));
    }
};

template<class Sender>
auto await_sender(Sender&& sndr)
{
    return sender_awaitable<
        std::decay_t<Sender>>(
            std::forward<Sender>(sndr));
}

} // namespace boost::copy

```