

|                                                     |
|-----------------------------------------------------|
| Шунки цепи<br>сигнализации                          |
| Вызов                                               |
| Неисправность<br>терминала +<br>неисправность защит |
| Срабатывание защит                                  |

The diagram illustrates four different SFP port configurations (A1, A2, A3, A4) for a 100BASE-FX network. Each configuration is represented by a table with three columns: SFP port, SFP module, and TX/RX pairs.

**A1**

|          |                          |           |
|----------|--------------------------|-----------|
| SFP port | SFP Модуль<br>100BASE-FX | M10.X1:TX |
|          |                          | M10.X1:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X2:TX |
|          |                          | M10.X2:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X3:TX |
|          |                          | M10.X3:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X4:TX |
|          |                          | M10.X4:RX |

**A2**

|          |                          |           |
|----------|--------------------------|-----------|
| SFP port | SFP Модуль<br>100BASE-FX | M10.X1:TX |
|          |                          | M10.X1:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X2:TX |
|          |                          | M10.X2:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X3:TX |
|          |                          | M10.X3:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X4:TX |
|          |                          | M10.X4:RX |

**A3**

|          |                          |           |
|----------|--------------------------|-----------|
| SFP port | SFP Модуль<br>100BASE-FX | M10.X1:TX |
|          |                          | M10.X1:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X2:TX |
|          |                          | M10.X2:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X3:TX |
|          |                          | M10.X3:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X4:TX |
|          |                          | M10.X4:RX |

**A4**

|          |                          |           |
|----------|--------------------------|-----------|
| SFP port | SFP Модуль<br>100BASE-FX | M10.X1:TX |
|          |                          | M10.X1:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X2:TX |
|          |                          | M10.X2:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X3:TX |
|          |                          | M10.X3:RX |
| SFP port | SFP Модуль<br>100BASE-FX | M10.X4:TX |
|          |                          | M10.X4:RX |

The diagram illustrates three identical experimental setups, labeled A1, A2, and A3, arranged vertically. Each setup consists of a source (A1, A2, A3) and a detector (A1.1, A2.1, A3.1) connected by a fiber optic cable (WE5, WE6, WE7) and a lens system. The source and detector are connected via a fiber optic cable (WE5, WE6, WE7) and a lens system. The source and detector are connected via a fiber optic cable (WE5, WE6, WE7) and a lens system.

The diagram shows a 220V AC power supply (220 B) connected to two parallel branches. Each branch contains a switch (SQ1, SQ3) and a load (EL1, EL2). The switches are controlled by two different signals (X:173, X:174 and X:175, X:176). The loads are represented by a circle with a cross inside, and the switches are represented by a circle with a diagonal line through it.

Power supply: 220 B

Branch 1 (Top):

- Input: X:173, X:174
- Switch: SQ1 (11, 21)
- Load: EL1 (1, 2)

Branch 2 (Bottom):

- Input: X:175, X:176
- Switch: SQ3 (11, 21)
- Load: EL2 (1, 2)