

# Data Science Companion

Greg Simon, [gregorygsimon@gmail.com](mailto:gregorygsimon@gmail.com)

October 3, 2020

## Abstract

A reference for basic data science tools and vocabulary, explaining essential terms and concepts, examining core ideas in major areas, and putting methods in historical context.

## Contents

<b>1</b>	<b>Natural Language Processing</b>	<b>2</b>
<b>2</b>	<b>Deep Learning</b>	<b>2</b>
<b>3</b>	<b>Time series &amp; Forecasting</b>	<b>2</b>
3.1	ARIMA . . . . .	2
3.2	In R . . . . .	2
3.3	In Python . . . . .	2
3.4	References . . . . .	2

# 1 Natural Language Processing

## 2 Deep Learning

## 3 Time series & Forecasting

### 3.1 ARIMA

An  $\text{ARIMA}(p, d, q)$  is an *autoregressive integrated moving-average* with  $p$  autoregressive terms (AR),  $d$  differencings, and  $q$  moving average (MA) terms.

$$\phi(B)(1 - B)^d Y_t = c + \theta(B)\epsilon_t$$

where

- $B$  is the back-shift/lag operator  $BY_t = Y_{t-1}$ .
- $\phi(B) = (1 - \phi_1 B - \dots - \phi_p B^p)$  is the autoregressive  $\text{AR}(p)$  component
- $c$  is a constant
- $\theta(B) = 1 + \theta_1 B + \dots + \theta_q B^q$  is the moving average of the errors  $\text{MA}(q)$  component.
- $\epsilon_t$  is the error of the  $\text{AR}(p)$  model at time  $t$
- The  $(1 - B)^d$  term induces  $d$  differencing

### 3.2 In R

`auto.arima` utilizes AIC and MLE to decide on best ARIMA parameters

### 3.3 In Python

### 3.4 References

<https://otexts.com/fpp2/non-seasonal-arima.html>