SUTD404: Denoising Language Models for Room Address Lookup

G. Lim, E. Ang, M. Shaswat, M. Ramaswamy

April 2026

1 Introduction

Singapore University of Technology and Design (SUTD) has over 200 rooms split across 5 buildings. Rooms are often communicated by name (e.g. "Think Tank 1"), and each room is assigned an address of the form

`x.y-z`

where `x` is a building number, `y` is a floor number, and `z` is a room number. Room address lookup—mapping rooms to their addresses—can be a hassle for staff, students, and visitors alike. However, resources for this task remain limited. Physical resources like campus signs exist, but often require one to expend energy and time walking around. Over the years, digital resources like the SUTD Assistive Maps (SAM) Telegram bot (Telegram, n.d.) have been developed. However, they often fail on noisy input (e.g. strings with typos), which can be especially common for visitors unfamiliar with the rooms and people with less experience typing in English.

To address this gap, we introduce SUTD404, a digital resource for room address lookup. Visit **github.com/gregorylimeurhen/sutd404** for our code repository, and **sutd404.vercel.app** for our web application.

2 Methodology

Let V be a vocabulary, and $R \subseteq V^*$ be a room set, and $\prec$ be a total order on R, and $L \in \mathbb{N}_{\geq 1}$ be a result count, and $\prec_L$ be a total order on $R^L_{\prec}$, and $A \subseteq V^*$ be an address set, and $B \subseteq V$ be a boundary set, and $C \in \mathbb{N}$ be a corruption count, and $\alpha \in \mathbb{R}_{[0,1]}$ be a transposition rate, and $\beta \in \mathbb{R}_{[0,1]}$ be a substitution rate, and $\boldsymbol{\pi} = (\pi_{\text{train}}, \pi_{\text{val}}, \pi_{\text{test}}) \in \Delta^2_C$ be a training-validation-testing split, and $I : V \rightharpoonup \mathbb{Z}^2$ be a keyboard-position map.

Definition 1 (Keyboard)**.**

$$K = \begin{bmatrix} \texttt{`} & \texttt{1} & \texttt{2} & \texttt{3} & \texttt{4} & \texttt{5} & \texttt{6} & \texttt{7} & \texttt{8} & \texttt{9} & \texttt{0} & \texttt{-} & \texttt{=} \\ \texttt{q} & \texttt{w} & \texttt{e} & \texttt{r} & \texttt{t} & \texttt{y} & \texttt{u} & \texttt{i} & \texttt{o} & \texttt{p} & \texttt{[} & \texttt{]} & \texttt{\backslash} \\ & \texttt{a} & \texttt{s} & \texttt{d} & \texttt{f} & \texttt{g} & \texttt{h} & \texttt{j} & \texttt{k} & \texttt{l} & \texttt{;} & \texttt{'} & \\ & \texttt{z} & \texttt{x} & \texttt{c} & \texttt{v} & \texttt{b} & \texttt{n} & \texttt{m} & \texttt{,} & \texttt{.} & \texttt{/} & & \\ & & & & & \texttt{␣} & \texttt{␣} & \texttt{␣} & \texttt{␣} & \texttt{␣} & & & \end{bmatrix}$$

Our keyboard uses the 60% ANSI QWERTY en-US keyboard layout without backspace, tab, caps lock, enter, shift, ctrl, alt, and system keys (Wikipedia contributors, 2026). All keys have equal spacing between them.



Figure 1: Official SUTD contact pages.

We obtained R by politely scraping official SUTD contact pages. The facility search function was queried by enumerating buildings and floors.

Algorithm 1 CORRUPT($\boldsymbol{x}$)

Require: $\boldsymbol{x} \in V^*$

$(T_L, T_M, T_R) \leftarrow (V^*B \cup \{()\}, (V \setminus B)^+, BV^* \cup \{()\})$

$T \leftarrow \{\boldsymbol{uwbvz} \mid \boldsymbol{u} \in T_L,\ \boldsymbol{v}, \boldsymbol{w} \in T_M,\ \boldsymbol{z} \in T_R,\ b \in B,\ \boldsymbol{x} = \boldsymbol{uvbwz}\} \setminus \{\boldsymbol{x}\}$

if $T \neq \varnothing$ **then** $\boldsymbol{x} \sim \alpha\,\mathcal{U}(T) + (1-\alpha)\,\delta(\boldsymbol{x})$

for $i \in [1..|\boldsymbol{x}|]$ **do**

  $S \leftarrow \{k \in K \setminus \{x_i\} \mid I(k) - I(x_i) \in [-1..1] \times [-2..2]\}$

  if $S \neq \varnothing$ **then** $x_i \sim \beta\,\mathcal{U}(S) + (1-\beta)\,\delta(x_i)$

return $\boldsymbol{x}$

Algorithm 2 SPLIT()

$(D_{\text{train}}, D_{\text{val}}, D_{\text{test}}) \leftarrow (\varnothing, \varnothing, \varnothing)$

for $r \in R$ **do**

  $P \leftarrow \varnothing$

  while $|P| < C$ **do**

    $r' \sim$ CORRUPT(r)

    if $r' \neq r$ **then** $P \leftarrow P \cup \{(r', r)\}$

  $P_{\text{train}} \sim \mathcal{U}(\{Q \subseteq P \mid |Q| = \pi_{\text{train}} C\})$

  $P_{\text{val}} \sim \mathcal{U}(\{Q \subseteq P \setminus P_{\text{train}} \mid |Q| = \pi_{\text{val}} C\})$

  $P_{\text{test}} \leftarrow P \setminus (P_{\text{train}} \cup P_{\text{val}})$

  $(D_{\text{train}}, D_{\text{val}}, D_{\text{test}}) \leftarrow (D_{\text{train}} \cup P_{\text{train}}, D_{\text{val}} \cup P_{\text{val}}, D_{\text{test}} \cup P_{\text{test}})$

return $(D_{\text{train}}, D_{\text{val}}, D_{\text{test}})$

We generated corrupted strings and split corrupted-uncorrupted room pairs into training, validation, and testing sets. Our corruption algorithm corrupts strings by transposing spans and substituting characters. First, the algorithm samples whether to transpose spans by uniformly sampling from the space of span transpositions. Then, for each character in the string, the algorithm samples whether to substitute the character by uniformly sampling from the space of character substitutions. This space contains nearby characters collected by sliding a window of height 3 and width 5 centred at each position in K. Finally, the algorithm returns the string. The split is stratified by room to make the training, validation, and test sets comparable across rooms. We set $C = 50$, and $\alpha = 0.5$, and $\beta = 0.05$, and $\boldsymbol{\pi} = (0.8, 0.1, 0.1)$ to generate plausible-looking typos in a tractable way.

We set $L = 26$ because, grouping rooms by shared prefix up to terminal numbers, the largest group (the group of Think Tank rooms) contains 26 rooms, so showing 26 results could allow a user to find their room by prefix without using terminal numbers for disambiguation.

Definition 2 (Denoiser)**.** Let $f : V^* \times R \to \mathbb{R}$ be a scorer.

$$\mathscr{D}_f : V^* \to R$$
$$\mathscr{D}_f(x) = \min_{\prec} \arg\max_{r \in R} f(x, r)$$

Our denoiser is a Nanochat-parameterised, character-level transformer of depth 2 with decoding constrained to the trie induced by R (Karpathy, 2025). We use character-level tokenisation as typos are often character-level, and room names are often short enough for individual characters to be meaningful lexical units for our task. We use trie-constrained decoding to efficiently avoid room hallucination. Our denoiser is trained using a standard cross-entropy loss and AdamW optimiser. A more complete list of hyperparameters can be found in our code repository.

For training and testing, we snapshot essential data and code files for each run into a portably compressed (e.g. ZIP) file for auditability. On each epoch, we maintain the latest weights (i.e. the weights for that epoch) and best weights (i.e. the weights for the epoch with lowest validation loss) to ensure resumability for robustness to hardware instability. We use early stopping to avoid spending compute after validation loss plateaus. We log training losses, validation losses, and gradient norms to monitor fitting progress and stability. We also log model answers and scores for convenient analysis. Our model was trained on 1 T4 GPU hour.

Definition 3 (Lookup)**.**

$$\mathscr{L} : R \to A$$

Our lookup is a standard room-address table.

Algorithm 3 $\textsc{Infer}(f, x)$

Require: $f : V^* \times R \to \mathbb{R}$, $x \in V^*$
  if $x \notin R$ **then** $x \leftarrow \mathscr{D}_f(x)$
  $x \leftarrow \mathscr{L}(x)$
  return x

Our inference algorithm receives a scorer and string as input. Firstly, the algorithm denoises the string to a room using the scorer if the string is not a room. Then, the algorithm looks up the address of the room. Finally, the algorithm returns the address.

3 Experimentation

We conducted experiments for empirical validation of our denoiser and system. Accuracy was measured as the percentage of test inputs for which the final predicted address equalled the gold address. Top-L accuracy was measured as the percentage of test inputs for which the gold address appeared among the final L predicted addresses. (Mean) latency was measured in milliseconds using the mean time taken to get an output from giving an input. For fairness and reproducibility, we use a fixed seed and hardware.

Denoiser	**Accuracy**	**Latency**
LCP	29.2	**0.1**
DL	71.9	16.7
SJ	89.3	20.8
Ours	**97.3**	8.2

Table 1: Denoiser evaluation results summary.

We evaluated our denoiser against substring Jaccard similarity (SJ), negative Damerau–Levenshtein distance (DL), and longest common prefix length (LCP) denoisers, measuring the accuracy and mean latency of each denoiser on the test set. Our denoiser outperformed the LCP, DL, and SJ denoisers by non-negligible margins, suggesting greater noise robustness.

Algorithm 4 $\textsc{Predict}(x)$

Require: $x \in V^*$
  $x \leftarrow \textsc{Strip}(x)$
  $x \leftarrow \textsc{Depunctuate}(x)$
  $x \leftarrow \textsc{Lowercase}(x)$
  $x \leftarrow \textsc{AlphanumericSplit}(x)$
  $x \leftarrow \textsc{Alias}(x)$
  if $x \in R$ **then return** $((x, \mathscr{L}(x)))$
  $\boldsymbol{f} \leftarrow (\mathrm{LCP}, \mathrm{SJ}, \mathrm{DL}, \textsc{Ours})$
  for $r \in R$ **do**
    for $f \in \boldsymbol{f}$ **do**
      $p(r, f) \leftarrow |\{r' \in R \mid f(x, r') > f(x, r)\}| + 1$
  for $r \in R$ **do**
    $s(r) \leftarrow \sum_{i=1}^{|\boldsymbol{f}|} (1/|R|^{i-1})(|R| - p(r, f_i))$
  $\boldsymbol{o} \leftarrow \min_{\prec_L} \arg\max_{\boldsymbol{r} \in R^L_{\prec}} \sum_{i=1}^{L} s(r_i)$
  return $((o, \mathscr{L}(o)) \mid o \in \boldsymbol{o})$

We implemented and deployed our system as a web application. Our prediction algorithm receives a string as input. Firstly, the algorithm normalises the

string by stripping whitespace, removing punctuation, lowercasing, separating letters from numbers, and replacing words with their aliases, to make the string more closely match training strings. Then, the algorithm computes top-ranked rooms using a Borda-style ranking. We prioritise scorers by assumed error frequency, placing prefix-sensitive signals first for more common errors and using the trained denoiser for rarer errors. Finally, the algorithm looks up the address of each room, returning top-ranked room-address pairs.



Figure 2: Web application.

To further improve the user experience, we also implemented the following features to make our web application more efficient and responsive.

- **Prefix caching.** We KV-cache previously computed prefix states and only process newly appended characters.
- **Incremental prediction.** We predict during typing rather than waiting for final submission.
- **Debounced querying.** We introduce a short debounce to avoid redundant intermediate inference on rapid keystrokes.
- **Bounded result caching.** We memoise recent solved queries while capping cache growth to prevent performance degradation over time.
- **Redundant-query suppression.** We skip empty, already displayed, and exact-match queries when full recomputation is unnecessary.

Off-the-shelf model	Accuracy	Latency
`sentence-transformers/all-MiniLM-L6-v2`	15.1	**465.8**
`sentence-transformers/all-mpnet-base-v2`	37.0	567.3
`BAAI/bge-large-en-v1.5`	**62.5**	1719.4
`TinyLlama/TinyLlama-1.1B-Chat-v1.0`	23.8	**639.8**
`meta-llama/Llama-3.2-3B-Instruct`	47.7	1901.2
`Qwen/Qwen2.5-7B-Instruct`	**70.6**	3009.8

Table 2: Off-the-shelf model evaluation results summary.

As a "sanity check", we evaluated off-the-shelf embedding and language models, measuring the accuracy and mean latency of each off-the-shelf model on the test set. The language models were queried with the lookup in context, and embedding models used top-L retrieval on the lookup. We concluded that for our task, their accuracies were too low, and their mean latencies were too high.



Figure 3: SAM.

We also evaluated our system against SAM, measuring the accuracy of each system on the test set.

System	Top-L Accuracy
SAM	40.0
Ours	**100.0**

Table 3: System evaluation results summary.

Input	design bdhavioural laboratory 1
Gold	behavioural design laboratory 1
Prediction	–
Input	capstone rolm 8
Gold	capstone room 8
Prediction	capstone room 8, capstone room 7, capstone room 6, capstone room 5
Input	lecturr 5 theatre
Gold	lecture theatre 5
Prediction	lecture theatre 5, lecture theatre 4, lecture theatre 2, lecture theatre 3
Input	com;ositemdesign laboratory
Gold	composite design laboratory
Prediction	–
Input	thinl tank 23
Gold	think tank 23
Prediction	think tank 15, think tank 24, a c toh think tank 25, think tank 22
Input	temasekvlaboratories and itrust labiratkry 6
Gold	temasek laboratories and itrust laboratory 6
Prediction	temasek laboratories and itrust laboratory 6
Input	think 2mtank
Gold	think tank 2
Prediction	think tank 2, think tank 14
Input	section compos7te
Gold	composite section
Prediction	cohort classroom 7
Input	hokkien lecture coundayioh theatre 4
Gold	hokkien foundation lecture theatre 4
Prediction	hokkien foundation lecture theatre 4, lecture theatre 2, lecture theatre 3, lecture theatre 1
Input	cohference capsrone ro9m 2
Gold	capstone conference room 2
Prediction	capstone room 9

Table 4: SAM evaluation results.

Our results suggest that SAM can be effective on mildly corrupted inputs with strong lexical overlap—occasionally recovering the exact target—but degrades markedly as noise becomes more severe. We conclude that SAM can be robust to limited orthographic variation, but can also fail to generalise beyond surface-form similarity. Our system convincingly outperformed SAM, achieving complete recovery.

4 Conclusion

We introduced SUTD404, a digital resource for room address lookup, to address the limitations of existing systems. Overall, we believe the experimental results demonstrate the strong promise of SUTD404 and provide practical foundations for building more reliable campus assistance systems.

5 Appendix

Notation 1. Let $n \in \mathbb{N}_{\geq 1}$.

$$R^n_{\prec} = \{\boldsymbol{r} \in R^n \mid r_1 \prec \cdots \prec r_n\}$$

Notation 2. Let $c \in \mathbb{N}$.

$$\Delta^2_c = \left\{ \boldsymbol{p} \in \mathbb{R}^3_{[0,1]} \;\middle|\; \sum_{i=1}^{3} p_i = 1,\, c\boldsymbol{p} \in \mathbb{N}^3 \right\}$$

References

Andrej Karpathy. nanochat: The best chatgpt that $100 can buy. `https://github.com/karpathy/nanochat`, 2025.

Telegram. Telegram: Launch @sutdmapbot, n.d. URL `https://t.me/SUTDMapBot`.

Wikipedia contributors. Qwerty. `https://en.wikipedia.org/wiki/QWERTY`, 2026.