A Gentle Primer on Neurosymbolic AI

Building a Chess Tutor

Gregor Heinrich

October 2026 · v01

Purpose and audience

This primer explains how a language model works, where it fails in a systematic way, and how a symbolic system beside it turns those failures into something reliable. It does that with one application, Kibitz, a chess tutor in which Stockfish calculates and Claude explains. Chess is the example because its truth is exact: a move is legal or it is not, and a position is better or worse by a number the engine can compute. That makes the model's flaws visible in a way a business process rarely does, but the insights from chess transfer easily to other common systems: databases, deterministic business logic, and automation systems with clear execution behavior.

It is intended for readers who are interested in the fascinating mechanism of Large Language Models (LLMs) but do not necessarily have a background in machine learning, or in chess beyond the basics, such as "the bishop attacks the knight that defends the pawn" (anyone who wants more can open the app and play as hard as they like).

The three parts follow that order. Part 1 shows how the capabilities of a language model, up to reasoning over a complex context, come from one algorithm, the transformer, without mathematics. Part 2 shows the model's limitations on the chessboard, and then not only retrieval and action but how to compensate for the flaws of a pure language model by making it the human front end to a specialized symbolic system: the engine holds the truth, the model handles the conversation, and a checker between them verifies what the model says. Part 3 is about running such a system responsibly: injected instructions, personal data, regulation, cost, failures, evidence, and the path from a demo to a product. The chess engine is a placeholder throughout; a table at the end maps the parts onto a scheduler, a rules engine or a billing system.

The engine lines and the coach's answers quoted here come from the Kibitz flipbook of Morphy's Opera Game. The app reruns the engine, so numbers differ slightly between runs.

Introduction: the flaw and the fix

Ask a language model to play chess and it will do something strange. For a dozen moves it plays well, often very well, because it has read millions of games and the openings are familiar text. Then it moves a bishop through a pawn, castles with a rook that has already moved, or captures a piece that is not there. Ask it why, and it gives a reason that sounds right. Ask a reasoning model, one that thinks for a minute before answering, and it fails later and less often, but it still fails. Thinking longer produces more text about the same uncertain picture of the board.

That is not a chess problem. It is the clearest demonstration of what a language model is: a system that continues text with the most plausible next piece of text. In chess, plausible and correct come apart on a board everyone can see. In an operations assistant, a customer-service bot or a code generator they come apart just as often, but the board is hidden.

The fix is not a bigger model. It is to put something beside the model that knows: a chess engine that holds the exact board, generates only legal moves, and evaluates positions by searching millions of them. The model talks; the engine knows. Kibitz is built on that split, and its flipbook, a walkthrough of Paul Morphy's

Opera Game from 1858, shows what each side adds. The engine's part is exact and silent: scores, best moves, a graph of the game. The model's part is language: what the plan is, why the sacrifice works, what to practice next. And everything the model says about a concrete move is checked against the engine before the player sees it.

The flaws and their fixes line up as pairs, and Figure 1 shows them side by side. Part 1 explains the model and ends each step with the flaw that step causes. Part 2 walks through the app and opens each step with the flaw it compensates.




Figure 1. Flaw to fix. Each systematic flaw of the model on the left, and the part of the application that compensates it on the right.

The game that runs through the primer is short. Morphy, playing White against two noblemen who consulted on their moves, won in seventeen moves at the Paris opera:

1. e4 e5 2. Nf3 d6 3. d4 Bg4 4. dxe5 Bxf3 5. Qxf3 dxe5 6. Bc4 Nf6 7. Qb3 Qe7 8. Nc3 c6 9. Bg5 b5 10. Nxb5 cxb5 11. Bxb5+ Nbd7 12. O-O-O Rd8 13. Rxd7 Rxd7 14. Rd1 Qe6 15. Bxd7+ Nxd7 16. Qb8+ Nxb8 17. Rd8# 1-0

Every turning point in it is an opening lesson: develop your pieces, do not open lines while your king is in the center, watch the pinned piece. Part 1 uses its third move; Part 2 picks the game up after the ninth.

Part 1: Context and generation

Step 1: Tokenization

A language model never sees letters, squares or pieces. It sees tokens: short chunks of text from a fixed vocabulary of fifty to two hundred thousand entries, learned by counting which character sequences occur together most often in a large corpus. Common words are one token; rare words and codes are several. The sentence "The bishop pins the knight to the queen." becomes nine tokens, one per word and one for the period, and the model's view of it is close to a person's.

Chess notation is rarer text, and the cut gets worse. The move list of the Opera Game, 1. e4 e5 2. Nf3 d6 3. d4, becomes something like "1", ".", " e", "4", " e", "5", " 2", ".", " N", "f", "3", " d", "6", " 3", ".", " d", "4". The square e4 is two tokens, and Nf3 is three. A position written as a FEN string, the engine's standard notation, is cut into chunks that run across squares and ranks. The model's view of a game starts with a

bad cut: it has no square as a unit and no piece as a unit. It has to learn, from text alone, that ” e” followed by “4” names a place on an eight-by-eight board. Figure 2 shows the three cuts; the exact pieces depend on the vocabulary, and the figure follows the one of GPT-2, which many open models inherit.




Figure 2. Tokenization. A sentence is one token per word; the move list and a FEN string are cut into fragments that run across squares and ranks.

Flaw: for the model there is no square and no piece, only text fragments, and everything it knows about the board is reconstructed from them. The engine represents the board as sixty-four squares with a piece or nothing on each, and a move as a change of two of them.

Step 2: Embedding

Each token is turned into a point in a space with thousands of dimensions; GPT-3 uses 12,288. The position of the point is learned so that tokens used in similar ways end up close together. Start with ordinary words. “king” and “queen” lie close to each other, and so do “man” and “woman”, and the step from “man” to “king” is nearly the same as the step from “woman” to “queen”, so that king − man + woman lands near queen. Nothing in the space is labeled. It is pure geometry, and the geometry is what the rest of the model works with.

The point for a token is the same wherever the token appears. That is a problem, because the meaning is not. “bank” in “the river bank” and “bank” in “the bank approved the loan” start from the same point, somewhere between the two senses. Step 3 shows how the model moves the point to where the context says it belongs.

Chess notation is the same picture with rarer words. Nf3 sits near Nc3, “knight” and “develop”; Bg4 near “pin” and Bg5. And d4 as the first move of a game and d4 after 1. e4 e5 2. Nf3 d6, where it challenges the pawn on e5 in a known opening, the Philidor Defense, start from the same point, just as the two banks do. Figure 3 shows both, the words on the left and the moves on the right.




Figure 3. Embedding. Left: ordinary words, with the parallel from man to king and woman to queen, and the word bank between its two senses. Right: chess tokens grouped by use, and the point for d4 moved by its context (Step 3). Two of 12,288 dimensions, illustrative.

Flaw: similarity is not equality. Two positions that differ by one pawn can be a win and a loss, and two FEN strings that differ by one character are, to the geometry, almost the same point. Any system that looks up positions by the similarity of their text will mix them up. Part 2 uses exact keys instead.

Step 3: Transformer

Working principle. The transformer is the algorithm that turns a sequence of embedded tokens into a prediction of the next one. It is a stack of identical layers, 96 in GPT-3, and each layer does two things to every token. Attention gathers context between tokens: each token looks back at the tokens before it and pulls in what is relevant. The MLP, a small feed-forward network, refines the features of each token on its own: it combines what the token now holds into new features. Both add their result to the token's point in the embedding space, so the point moves a little in each layer. After 96 layers the point for the last token has moved to where the next token should be, and the model reads off the nearest tokens as probabilities. Figure 4 shows the whole path for the running example.

The example is the third move of the Opera Game. The input is 1. e4 e5 2. Nf3 d6 3. d4, and the model predicts Black's reply. The prediction is Bg4 with high probability, exd4 next, then Nd7 and Nf6.




Figure 4. The transformer for 1. e4 e5 2. Nf3 d6 3. d4. Top: input, 96 layers, output. Middle: attention with three heads, and the MLP. Bottom: the embedding shift of d4, and the unembedding.

Attention: context from other tokens. In each layer several attention heads work in parallel, and each head looks for a different kind of relation. Three matter in the example. One relates the moves of the same side and kind: e4 and d4, the two center pawns, so the model sees a pawn center forming. One relates the sequence as a whole: e4 e5 Nf3 d6 d4 is a pattern it has seen thousands of times, the Philidor Defense, and the pattern predicts what usually follows. One relates attacker and target: d4 attacks e5, and the knight on f3 can be pinned to the queen on d1 by a bishop on g4. Each head gives every earlier token a weight, and the weights of one token add up to one. Figure 5 shows the weights as a grid, one row per token, with the row for d4 highlighted.




Figure 5. Attention pattern. One row per token, the d4 row highlighted with its weights; the cells above the diagonal are masked. Illustrative weights.

Two properties of the grid matter later. A token only looks back, never ahead, so the upper half of the grid is empty. And the grid grows with the square of the number of tokens: ten tokens give a hundred cells, a thousand tokens a million. That is why context has a price, which Step 4 takes up.

MLP: new features from the combination. After attention, each token holds a mix of what it gathered. The MLP turns the mix into features: the e5 pawn is attacked; the knight on f3 can be pinned; this is a famous game. It does this with thousands of small detectors, each sensitive to one combination of inputs, and the combinations are nonlinear, so a feature can depend on several things being true at once. Nobody writes the detectors; they emerge in training. Across the 96 layers the features become more abstract, from which piece, through which pattern, to what usually happens next.

Embedding shift across 96 layers. The point for d4 starts where every d4 starts, at “a pawn move”. Each layer pushes it, and the pushes add up: toward “center pawn”, then toward “Philidor”, then toward “challenge to e5 with the bishop pin available”. Figure 6 shows the path. The meaning of the token is not stored anywhere; it is the position the point reaches after the context has acted on it. The same token in a different game ends up somewhere else.

Figure 6. Embedding shift. The point for d4 moves with each attention push (a) and each MLP push (m); after 96 layers it has turned toward its meaning in this game.

Unembedding: from meaning to the next token. At the end the model compares the final point with the

embedding of every token in the vocabulary and turns the distances into probabilities. For the example: Bg4 48 %, exd4 25 %, Nd7 10 %, Nf6 7 %, and a thin remainder spread over everything else, including moves that are not legal in this position. The numbers are illustrative. The answer is a distribution, and the model, or the application around it, picks from it.

Flaw: the output is a probability over plausible moves, and the most plausible move here is the famous inaccuracy. Bg4 is what Black played in the Opera Game, so it appears in the text many times, and it looks natural. The engine prefers exd4: Bg4 gives up the bishop for the knight and brings White's queen into play for free. Nothing in the 96 layers checks legality or quality. A small probability sits on impossible moves, and a model that picks from the distribution thousands of times will pick one of them eventually.

Step 4: Context

Everything the model works with sits in its context window: the text it is given before it answers. In chess that is the move list, plus whatever the application adds. The window has a limit, from a few thousand tokens in early models to hundreds of thousands now, and the cost of attention grows with its square, so long contexts are slow and expensive.

The model has no board. What it has is the move list, and from the move list it builds something like a board inside its layers. Research on models trained on chess games has found exactly that: a readable, approximate representation of which piece stands on which square, built from the moves alone (Karvonen 2024). It is approximate in two ways. It drifts: after thirty or forty moves the internal board and the real board no longer agree, and the model plays a move that was legal three moves ago. And it dilutes: as the context grows, each token's attention spreads over more tokens, and the detail of the opening has faded by the time the endgame comes.

A reasoning model, one that writes out its thinking before answering, does better, because it can list the pieces and check its own moves in text. But the text it reasons over is the same reconstruction, so the errors come later and less often, not never. More thinking adds text, not a board. Figure 7 shows the window: what is in it, what has fallen out of it, and what the model never had.




Figure 7. The context window. What is in the window, the board the model never had, and the drift between its internal board and the real one.

Flaw: drift and dilution in long games, and the illegal move at move thirty. The engine has an exact board at every move, and it takes the position, not the history, as its input. That is the hand-off to Part 2.

Part 2: The model as a front end to a symbolic system

Part 1 ended with a model that writes fluent, plausible text about a board it cannot see. Part 2 shows how an application compensates for that, step by step, and the result is a different kind of product: the language model is the human front end, the part that reads the question, explains and teaches, while a

specialized symbolic system, the chess engine, holds the truth. Retrieval and tool use are the techniques, but the point is the division of labor and the checks between the two sides.

The steps follow the Kibitz flipbook, eleven pages captured from the running app as it walks through the Opera Game. Each step opens with the flaw it compensates and closes with what the engine, the index or the checker now guarantees that the model alone could not. Figure 8 draws the loop that all six steps share: the engine produces facts, the model turns them into words, the checker verifies the words, and the player decides.




Figure 8. The loop. The engine produces facts, the help setting decides how many of them the model sees, the checker verifies the answer, the player decides.

Step 5: Facts first, the engine answers and the model explains

Flaw compensated: confident wrong judgments, and reasons made up to fit them.

The flipbook starts with the position after 9. Bg5. White has developed four pieces and is ready to castle queenside; Black's king is still on e8. Stockfish, at depth 14, puts White ahead by about two and a half pawns (+2.67). The player asks the coach: what is the main plan for the side to move here, and why?

Before the model sees the question, the app collects the facts. In the code this is one function, contextFor(), and it assembles: the player's level and the game so far; the position as a FEN string and as a board diagram; Stockfish's top lines in move notation, with their scores; the motifs in the best move (a pin, a fork, a loose piece); the last move's rating and the engine's alternative; the themes of the position; board facts such as loose pieces and king shelter; and the references retrieval found (Step 7). Then come the standing rules for the coach: take every move and line from the engine's lines or the game, at most six plies deep; explain ideas, not variations; describe evaluations in words; recommend only the references provided; stay short.

Only then does the question go in. The answer in the flipbook is a plan, not a number. Black's main plan is to survive the opening: develop the queenside, then trade queens or castle before White's lead in development turns into an attack. Why Black is in trouble: White's queen on b3 and bishop on c4 both aim at f7, and the queen also hits b7; Black's queen on e7 guards both b7 and f7 and sits behind the knight on f6 that the bishop on g5 pins, one piece doing three jobs. The engine's plan: 9… Na6 develops with tempo, and after 10. Bxa6 bxa6 11. O-O Black offers a queen trade with 11… Qb4. Figure 9 shows the page.




Figure 9. Flipbook page 2. The coach's answer to "What is the main plan for the side to move here, and why?": backed moves highlighted, and the count under the answer. Source: Kibitz flipbook.

Two design points. The judgment is the engine's and the words are the model's: the evaluation, the best line and the motifs arrive as facts, and the model is told to explain them, not to assess the position itself. And the facts are pushed into the prompt rather than pulled by the model. Pushing is simpler, deterministic and testable; the same position with the same settings produces the same context, which is why the app can cache coach comments by position, move, aspect, engine view, level and model. Pulling, where the model decides what to ask the engine through tool calls, is planned for questions whose facts cannot be known in advance (Step 10).

What the engine guarantees here: the score, the best move and the line are correct for the search depth. What the model adds: the plan in words a club player can use. What neither guarantees yet: that every move the model wrote is one of the engine's. That is the next step.

Step 6: The checker, every move the model names is verified

Flaw compensated: illegal moves and invented lines.

The model's answer is text, and text can name any move. So the app treats the answer as untrusted and checks it before it is shown. A function, checkAnswer(), finds every move-like token in the answer and sorts it: in Stockfish's lines for this position or the one before; one of the game's moves; legal but not in any

line; invalid; or a bare square. Moves joined by move numbers must form a contiguous run of an engine line or of the game, so a sequence of individually legal moves that the engine does not have is caught too. Claims like “the bishop on b5” are checked against the board. Legality comes from chess.js, the rules library that also drives the board.

The player sees the result. Moves the engine backs are highlighted, legal moves it does not list are grayed, and wrong moves are struck through. Every answer ends with a count. For the plan above: 11 moves backed by Stockfish or the game, 1 legal but not in its lines, none wrong.

The third page of the flipbook shows why this matters, and it shows the model doing something the engine cannot. The player asks the coach to leave Stockfish’s first choice aside and suggest an idea of its own, one a club player would understand, and then to say honestly how it compares with the engine’s lines. The coach proposes 9… h6: it asks the bishop on g5 a question, because the pin on the f6 knight is what keeps Black’s queen stuck on e7. It marks the move as unchecked, not in the engine’s lines. It argues for it, and finds the catch itself: on f6 the queen would no longer guard b7, so Qb3 could take that pawn; Black’s queen is guarding b7, f7 and the pinned knight at once, and almost any freeing move drops one of those jobs. Then it compares: the engine’s own pawn try, 9… h5, already scores worse for Black than 9… Na6, so h6 can be expected to be no better. One move in that answer is struck through: Qxf6, the recapture after a hypothetical Bxf6. The checker verifies moves in the position on the board and the one before it; a move two hypothetical moves deep cannot be verified, so it is marked wrong rather than trusted. The count reads: 9 backed, 4 legal but not in its lines, 1 wrong. Figure 10 shows the page with the strike-through.




Figure 10. Flipbook page 3. The coach's own idea, 9… h6, marked as unchecked; Qxf6 struck through by the checker; the note under the answer counts 9 backed, 4 unlisted, 1 wrong. Source: Kibitz flipbook.

This is the central mechanism of the primer. Generation stays free: the model may have ideas, and its idea here is a good teaching idea, since the catch it finds is the real lesson of the position. Verification is symbolic and sits after generation, outside the model. The engine keeps the model honest, and the player can see where it was wrong.

What the checker guarantees: no illegal move reaches the player unmarked, and no line is presented as the engine's unless it is. What it does not guarantee: that the prose around the moves is right. That is why the facts come first (Step 5) and the references are limited (Step 7).

Step 7: Retrieval by theme and by position

Flaw compensated: invented facts, such as games that never happened and books that do not exist; outdated knowledge; and mixed-up positions.

A model answers from what it absorbed in training. Ask it for a book on the Philidor and it will name one, and the name may be real, half real or invented. Retrieval replaces recall: the application looks things up and hands the model the results, with the rule to recommend only from those. Kibitz has three kinds of retrieval, and the contrast between them is the lesson.

By theme. A catalog of books holds metadata and theme tags, not the book text: *Fundamental Chess Openings* for opening plans, *Logical Chess: Move by Move* for development and king safety, *How to Reassess Your Chess* for imbalances. The catalog and the player's own references are ranked by overlap with the position's themes and by closeness to the player's level, and the top hits go into the context with the matching chapter where it is known. This is retrieval-augmented generation in its usual form, and for text it works: a theme is a word, and words can be matched or embedded.

By exact position. Chess positions have a structure that text embeddings would blur, so Kibitz uses keys from chess itself. The exact position is the EPD, a FEN without the move counters, so that transpositions, the same position reached by different move orders, match. Every game in the player's library is indexed by EPD, and the current position is looked up there; the matches, with the notes made in those games, go into the context as "seen before". The engine's evaluations are stored by EPD too, shared by the board, the review and the coach. A second key is the pawn structure, so that a game with the same structure is found even when the pieces stand elsewhere. A third is the set of theme tags the detectors produce: isolated queen pawn, Carlsbad structure, opposite castling, passed pawn, bishop pair. Planned are fuzzier keys, material and piece-placement signatures and a distance between pawn structures, and text embeddings for annotations, combined with the structural keys in one ranking.

By graph. Positions are nodes, moves are edges, and transpositions join branches. Walking from the current position to the known continuations, with counts and results, is what an opening explorer does. A reader who knows Graph RAG, which extracts an entity graph from text with a model and summarizes its communities, may ask about scale. The answer is that the position graph is never built. Each position is a key, the engine generates the neighbors on demand, and a walk is one lookup per ply; Lichess's opening explorer serves trillions of positions this way from a key-value store, with the database well below three times the size of the compressed games. The cost grows with the branching factor times the depth, so a walk stops after a few plies or below a count. Graph RAG over text is the expensive case, because the graph has to be extracted first: Microsoft puts the indexing cost of vector retrieval at a thousandth of its full GraphRAG, and its later LazyGraphRAG defers the graph work to query time for that reason.

The rule to take away: when a structure exists, use the structure. Vector similarity is for text without one, and a FEN string is not such text. Figure 13, in Step 10, shows the Reading tab with the references found for the position.

What retrieval guarantees: every book, chapter and earlier game the coach names exists and was found for this position. What it does not guarantee: that the coach's sentence about the book is the book's. It is the model's summary of a catalog entry.

Step 8: Review, the symbolic side on its own

Flaw compensated: not repeatable. Ask a model the same question twice and the answers differ; ask it to rate a game and the rating drifts with the wording.

The Review tab is the deterministic system working alone. It runs Stockfish over every position of the game, scores each move by how much it changed the evaluation, and classifies it: book, best, good, inaccuracy, mistake, blunder. From the drops it computes an accuracy for each side, 94 for Morphy and 83 for the allies. It draws the evaluation over the game as a graph and lists the turning points: 3… Bg4 (+0.4 to +1.1), 6… Nf6 (+1.3 to +2.5), 9… b5 (+2.7 to +4.2) and 10… cxb5 (+4.2 to +6.6). No language model is involved. Figure 11 shows the tab.

Game Coach Review Library Reading

Paul Morphy – Duke Karl / Count Isouard

Re-run review

White · Paul Morphy
94 accuracy

Black · Duke Karl / Count Isouard
83 accuracy

	White	Black
?? Blunders	0	0
? Mistakes	0	0
?! Inaccuracies	0	4
· Good	3	4
· Best	11	6
· Book	3	2



TURNING POINTS

?! 3... Bg4 · an inaccuracy
+0.4 → +1.1 · best was exd4 — Show Explain

?! 6... Nf6 · an inaccuracy
+1.3 → +2.5 · best was Qd7 — Show Explain

?! 9... b5 · an inaccuracy
+2.7 → +4.2 · best was Na6 — Show Explain

?! 10... cxb5 · an inaccuracy
+4.2 → +6.6 · best was Qb4+ — Show Explain

COACH SUMMARY — Write summary

The coach can turn these numbers into a short write-up: how the opening went, what decided the game, and what to practise.

Figure 11. Flipbook page 6. The Review tab: accuracy 94 and 83, the move classification, the evaluation graph and the four turning points. No language model is involved. Source: Kibitz flipbook.

Everything here is exact and repeatable. Run it again and the same moves are flagged with the same numbers, give or take the engine's search noise, which the app reports. It is also silent. The review says that 9… b5 lost one and a half pawns of evaluation and that Na6 was better. It does not say why, and it does not see that the four inaccuracies have something in common. That is the limit of the symbolic side: it can find the truth and cannot teach it.

What the engine guarantees: which moves were mistakes and how large, independent of who asks. What it cannot do: explain.

Step 9: The model reads the graph

Flaw compensated: the engine's silence, and the model's habit of inventing reasons when it is asked to explain a number.

The player asks the coach to read the evaluation graph: where did the game turn, and what did Black's mistakes have in common? The coach gets the review as facts, the turning points with their evaluations, the better moves and the motifs, and answers with a story. The graph is a steady slide, not a single collapse. White made no errors. Black lost ground through four inaccuracies: trading the bishop for the knight brought White's queen into play for free; 6… Nf6 allowed 7. Qb3, which attacks f7 and b7 at once; 9… b5 was a pawn move instead of developing, and it loosened the diagonal to e8; 10… cxb5 grabbed the knight and opened lines to the king. The common thread: each move gave White time or opened lines while Black's king stayed in the center and the queenside pieces stayed home. Black never castled. Figure 12 shows the page.



Figure 12. Flipbook page 7. The coach reads the evaluation graph: four inaccuracies and the common thread. Source: Kibitz flipbook.

That common thread is the model's own finding. The engine scored the moves one at a time; the pattern across them is something the engine does not look for and the model sees at once, because patterns in text are what it is made of. This is the division of labor at its best: the numbers are exact, and the lesson is drawn from them rather than from the model's memory of similar games.

Each turning point has an Explain button. The coach is given the position before the move, the move played, the engine's better move with its line, and the motifs that refute the mistake, and it explains only from those. For 9… b5: the pawn drove the bishop away but created a target, and White simply took it; after 10. Nxb5, recapturing opens the diagonal to the king on e8; the deeper flaw is a pawn move while behind in development; better was 9… Na6, which develops a piece and eyes c5 and b4. The lesson in one line: when your king is uncastled, develop first and avoid opening lines. The summary of the whole game follows the same recipe at larger scale and names 44 moves, none wrong.

What the pairing guarantees: every move in the explanation is the engine's or the game's, and every number is the review's. What the model adds: the reason, the pattern, and the lesson.

Step 10: Agents, the study plan and the sparring partner

Flaw compensated: giving the game away, and acting without bounds.

An agent is a model that takes several steps toward a goal, uses tools along the way, and decides at each step what to do next. Kibitz has two small agents and one planned.

The study plan. Asked what to study, the coach works from the review's themes, the references retrieval found for them, and the player's level, and writes a plan: three themes from the game, each with what happened, what to do in one's own games, and what to read. For the Opera Game: development and open lines, pins and loose pieces, and the opening concessions in the Philidor. Each step of the plan is grounded in a step before it, so the plan is checked at every link. Figure 13 shows it beside the references.



Game
Coach
Review
Library
Reading
Reading for this position
Open on Lichess ↗
C41 Philidor Defense
Opening play
Fundamental Chess Openings
Paul van der Sterren · 2009
A one-volume survey of every major opening that explains the ideas and typical plans behind each line instead of listing raw theory.
Start with the chapter on this opening family.
1.e4 e5 open games
Opening play
Mastering the Chess Openings (4 vols)
John Watson · 2006
Explains why openings are played the way they are, with the strategic themes that carry into the middlegame. Volume 4 covers the English and Réti.
1.e4 e5 open games
Opening play
Logical Chess: Move by Move
Irving Chernev · 1957
Explains every single move of 33 master games, a gentle introduction to principled play.
Opening play
EEN BEFORE IN YOUR LIBRARY
SAME POSITION
Open
The Opera Game · Paul Morphy – Duke Karl / Count Isouard, after 9... b5
Ask the coach for a study plan
Three themes stand out here: development and open lines, the pin and loose pieces that make 10. Nxb5 work, and Black's early opening concessions.
Development lead and opening lines
White has every minor piece active, while Black's queenside is still at home and the king is in the centre.
Morphy's sacrifice 10. Nxb5 cxb5 11. Bxb5+ Nbd7 12. O-O-O opens files straight at the king.
In your games, find moments where you were ahead in development. Did you open the position, or let your opponent catch up?
Read: *Logical Chess: Move by Move* (Chernev). Its move-by-move commentary keeps returning to development and open lines.
Pins and loose pieces
Bg5 pins the f6-knight to the queen on e7, and the bishop on c4 eyes f7.
Before 9... b5, Stockfish already rated White as better (+2.7). After it, White is clearly winning (+4.24).
In your games, list every pinned or undefended piece before you move. Check whether a sacrifice could exploit them.
Read: *Logical Chess* again, for how the tactics grow out of good piece placement.
Opening concessions in the Philidor
3... Bg4 and 4... Bxf3 gave up the bishop pair for nothing, and 6... Nf6 allowed Qb3.
Stockfish preferred 3... exd4 or 6... Qd7.
In your games, flag early piece trades that only helped your opponent develop.
Read: *Fundamental Chess Openings* (van der Sterren), the chapter on this opening family.
▸ Add your own book, course or notes

Figure 13. Flipbook page 10. The Reading tab: references found for the position, the same position seen before in the library, and the study plan. Source: Kibitz flipbook.

The sparring partner. The player starts a game from the position after 9… b5, plays 10. Nxb5 as Morphy did, and Stockfish replies. The coach comments after each move: what the last move did, what comes next, what to keep in mind. The loop has a human in it, and the human decides every move. What the coach may know is set by the player: with help Full, the coach sees Stockfish's lines; with help Flag mistakes, it learns only how the player's own move rated and cannot give the game away; with help Off, it sees no engine data at all. This is enforced where the context is built, not by asking the model to keep a secret. A model told to keep a secret keeps it most of the time; a model that was never given the secret keeps it always. Figure 14 shows the game with help Full.



Figure 14. Flipbook page 11. Playing 10. Nxb5 against Stockfish from the position after 9… b5, with the coach's comment and the engine's view. Source: Kibitz flipbook.

The coach as an agent (planned). The next step is to let the model ask the symbolic side questions instead of receiving a fixed context: analyze a position, try a move, list the threats, compare two moves, find a mate; find the motifs over a line; load a game. With those tools the coach can answer "why did I lose this game?" or "find where I went wrong in my last three losses" by loading the games, running the engine on the critical moments, looking up the patterns and the literature, and explaining what it found. The bounds are decided before the first line of code: a cap on tool calls and engine time per answer; tools are read-only by default; every line the model quotes must come from a tool result; nothing leaves the current game without the player's confirmation; and every claim stays traceable to the tool result that backs it, which the chat can show as evidence.

Those bounds are the general lesson of Part 2. None of the six steps asked for a stronger model. The reliability comes from where the engine and the checker sit in the loop, from what the model is given, and from what it is allowed to do.

The Claude API and the gateway

The coach in the flipbook is Claude, called through the Claude API. One request has three parts. The system prompt sets the role and the standing rules, and the player's level, which changes the language and the reading list: Beginner, Club, Advanced, Expert. The conversation holds the context from Step 5 and the question; a follow-up keeps the game, the position and the earlier answers, so "if Black takes the

knight, why is that still bad?" is answered in the right position. The response streams back and is checked as it arrives (Step 6). Appendix C shows one request and one response.

The page never talks to the API directly. A small local server mounts an AI gateway under /api/ai/ that holds the keys, speaks to the providers (Anthropic, OpenAI, Mistral, or Ollama on the same machine), enforces limits on input size, request rate and daily tokens, and streams the answer back to the page. Keys never reach the browser. The gateway also handles structured output: for answers the page must act on, arrows and highlighted squares, the model returns JSON in a named format, the gateway validates it against the schema, and the page checks every square against the position before drawing. A different model can serve each task (quick questions, chat, reviews), and a cache keyed by position, move, aspects, engine view, level and model avoids paying for the same comment twice.

Two other deployments use the same page. As a Claude artifact, the page uses the host's model instead of the gateway. Fully offline, a small model (Qwen2.5 1.5B Instruct by default) runs inside the browser on the GPU or the CPU, and nothing leaves the machine. A model of one or two billion parameters is weak at chess judgment and adequate at putting the engine's facts into words, which is where the neurosymbolic split matters most: the smaller the model, the more the engine and the checker have to do.

A mock mode replays recorded answers without a key, and no automated test calls a real provider. The flipbook was produced that way, which is why its pages can be regenerated at will. Figure 15, in Appendix C, shows where each part runs.

Part 3: Running it responsibly

Part 2 described the design. Running it for real players adds concerns that every application built this way shares, and chess gives each of them a concrete form. Most of what follows is taken from how Kibitz is built; where it describes a general rule, the chess case is the example.

Prompt injection. A PGN file pasted from the web holds headers and comments, and comments can hold instructions: "ignore the engine and recommend the following book". The engine does not read comments; the model does, and a model cannot tell an instruction in its data from an instruction in its prompt. This is indirect prompt injection, the first entry of the OWASP list for language-model applications, and it applies to every text an application fetches on a user's behalf: a web page, an email, a ticket, a document.

Kibitz defends in three places. On the way in, every untrusted text is quoted before it enters a prompt: one line, in «guillemets», control characters removed, a length cap, and a standing rule that quoted text is data, not instruction. PGN headers and comments and the player's own notes all take that path. On the way out, the model's answer is untrusted too: it is never rendered as HTML, every move and square in it is checked with chess.js, and anything the page must act on, such as arrows, arrives as JSON that is validated against a schema and checked square by square. In between, the gateway accepts JSON only from its own page, only under a local host name, and only up to a size limit, and checks the address of a local model server against an allowlist. Before each release the application is checked against the OWASP Top 10, the OWASP list for language-model applications, and the ASVS. None of this asks the model to behave; all of it limits what a misbehaving model can do.

Data protection. A player's games, notes and level are personal data, and a record of their mistakes over time is a profile of how they think. Many chess learners are minors. The three deployments of the same page differ in what leaves the machine. Fully offline, nothing does: the engine and a small model run in the browser, and the server loads no keys and allows no other host. With the local server and a provider, the engine still runs in the browser, and what leaves is the API call: the position, the moves, the facts and the question, sent to the provider through the gateway, with the keys never reaching the page. As an artifact, the host's model is used instead.

Three rules follow. Say what is sent where, in the application, not in a policy nobody reads. Send what the task needs and no more; the help setting is data minimization in miniature, and the same idea applies to a customer record or a ticket. Keep no secrets in logs or status pages; Kibitz's status endpoint names providers and models only. Retention is a design decision too: the player's library is theirs, the cache of coach comments is keyed by position rather than by person, and a product for minors should keep less

than it could.

Regulation. The EU AI Act follows a risk-based approach. A chess tutor falls outside the high-risk categories, whose obligations the Digital Omnibus on AI, Regulation (EU) 2026/1744, moved to December 2, 2027. The line is worth knowing, though: Annex III lists systems used to evaluate learning outcomes in education and vocational training, so a tutor that grades students in a school program would have to check where it stands, while a hobby coach does not. Transparency duties apply to the coach as they do to any chatbot: a person talking to it must be told that it is an AI system, which has been required since August 2, 2026. The obligations for general-purpose models fall on the model's provider, not on the application that calls it, but the application inherits the provider's terms on what may be sent and stored. An application for minors should take the Act's attention to vulnerable groups seriously even where no specific obligation applies.

Cost and latency. The two sides of the system are priced differently. The engine runs in the browser and costs nothing per call; the model is metered by the token and answers in seconds. That asymmetry decides where work goes: everything that can be computed goes to the symbolic side, and the model is called for words. Kibitz adds four controls. A model per task, so that quick questions, chat and reviews can use different models. A daily token budget and a per-minute rate limit in the gateway. A cache of coach comments keyed by position, move, aspects, engine view, level and model, so the same comment is never paid for twice. And a setting that sends only the quick requests, chips and automatic comments, to the in-browser model and everything else to a provider.

When parts fail. The coach is optional. Without any language model, play, analysis, flags, review, library and reading suggestions all still work, because the symbolic side stands alone. That is a design principle, not an accident: the product must be complete without the model, and the model is an addition that can be switched off. Smaller failures are handled the same way. Every asynchronous step, engine, coach or review, checks that the game is still the one it started for before showing anything, so a stale answer is dropped rather than shown. The engine falls back from the multithreaded build to a single thread where the page is not cross-origin isolated. The in-browser model loads only when the player asks, after a memory check, and unloads after ten idle minutes. For a process engine the rule reads: the system of record must work when the assistant is down.

Evidence and audit. Trust in the coach is visible, not assumed. Every move it names is highlighted, grayed or struck through, every answer ends with a count of backed and wrong claims, and a claim the player doubts can be checked against the board with one hover. The planned agent keeps the same discipline at larger scale: every claim traceable to the tool result that backs it, which the chat can show as evidence. For any application built this way, the audit record is not the model's answer alone but the facts that were handed to the model, the answer, and the checker's verdicts, kept together. That is what makes an answer reviewable after the fact, and it is the reason facts first (Step 5) matters beyond quality.

From demo to production. The symbolic side makes the system testable in a way a model alone is not. Unit tests cover the motifs, the classification, the tutor logic and the answer check. Contract tests replay recorded provider responses through the real client libraries, so the gateway is tested without a key. A browser test drives the built page through whole games, the engine fallbacks and the coach, with a regression test for every fixed bug. No automated test calls a real provider; live tests run only behind an explicit flag. A planned evaluation set scores the coach's answers on reference positions per provider, with engine checks and a model as judge, which is how a provider or a prompt change gets compared before it ships.

Two numbers tell whether the design works: the rate of wrong moves in the coach's answers, which the checker counts on every page of the flipbook, and the rate of flagged claims the player sees. Both can be measured with and without the engine in the loop, and the difference is the argument of this primer in two figures. The same two numbers, with their own definitions of "wrong", are the acceptance test for any model placed in front of a database, a rules engine or an automation system.

Transfer: the engine as a placeholder

The chess engine stands for any deterministic process engine. The pattern of Part 2 is the same whether the engine plays chess, schedules jobs, prices an order or checks a contract against a rulebook: the engine holds the state and the truth, the model handles language and explanation, and a checker between them verifies what the model says against the engine before anyone acts on it.

In the chess tutor	In any process engine
Stockfish	The scheduler, rules engine, billing system or simulator that holds the truth
The position (FEN)	The system state, handed to the model in full rather than as a history
Legal moves (chess.js)	Permitted operations; schema and policy validation
Evaluation and main line	A forecast, a policy score, an SLA check
Facts first (contextFor)	The grounded context: state, the engine's results, the relevant rules, the retrieved documents
The checker on named moves	Every action, identifier or reference the model names is validated against the system before it is shown
Turning points in the review	Incidents and variances in a post-mortem
Opening book and library	Runbooks, manuals, past tickets, indexed by exact keys where they exist
Help setting: Off, Flag mistakes, Full	What the model is allowed to see: need-to-know, data minimization
Playing a position yourself	A sandbox or simulation before anything is executed
The player decides the move	Owner approval before an action; the model recommends
Quoted PGN comments	Every external text quoted as data before it enters a prompt

Appendix A: The transformer in more depth

This appendix complements Steps 2 and 3. It stays with the geometric picture and names the research behind each claim. Full references are in Appendix B.

A.1 Meaning as direction

The idea that meaning is geometry is older than language models. Bengio et al. (2003) trained the first neural language model with learned word vectors. Mikolov et al. (2013a) showed with word2vec that such vectors capture similarity at scale, and Mikolov et al. (2013b) found the regularities behind king − man + woman ≈ queen.

For language models, the working assumption is that a concept corresponds to a direction in the vector space. Park et al. (2023) formalize this as the linear representation hypothesis. A model can hold far more concepts than it has dimensions, because it packs them into directions that are almost at right angles to each other, an effect called superposition (Elhage et al., 2022). Templeton et al. (2024) extracted millions of such directions from a production model. Real features therefore exist, but the detectors in Step 3 ("the e5 pawn is attacked") were invented for the example.

The input embedding has one vector per token. Inside the transformer, the same token ends up in very different places depending on its context, and more so in the upper layers (Ethayarajh, 2019). These contextual embeddings are the two meanings of d4 in Step 2, measured in practice. For chess in particular,

Karvonen (2024) trained a GPT on move lists alone and found, with linear probes, that the running vectors hold a readable representation of the board and of the players' skill. That is the approximate board of Step 4.

A.2 One running vector per token

Each position owns one vector that runs through the whole network, often called the residual stream (Elhage et al., 2021). Every attention block and every MLP reads this vector, computes an update and adds it. The pushes of Step 3 are literal vector additions. After a few layers the vector at d4 describes more than the token d4; it holds information copied in from the earlier moves, and that is what makes it useful for predicting the next one.

The sizes quoted here are those of GPT-3 with 175 billion parameters: 96 layers, 96 heads per layer, vectors of 12,288 values, each head in a smaller space of 128 values, and 49,152 detectors in each MLP (Brown et al., 2020).

Position. Attention by itself is blind to order, so position has to be added. GPT-3 learns one position vector per slot and adds it to the token's embedding. Many newer models rotate the query and key vectors by an angle that depends on the position, rotary position embedding (Su et al., 2021); relative position becomes an angle between vectors.

Normalization. Before each of the two adjustments the vector is rescaled to a standard size (Ba et al., 2016), placed in front of attention and in front of the MLP, which makes deep stacks easier to train (Xiong et al., 2020). Geometrically, the vector each block reads lies on a sphere of fixed radius, so its direction matters and its length does not (Molina, 2023).

A.3 Attention: moving information between tokens

Each head derives three things from every vector (Vaswani et al., 2017). The query says what the current token is looking for; the key says what a source token has to offer; the value is what gets copied if the two match. How well a query matches a key is measured by how closely the two vectors point in the same direction, the same geometry as similarity in Step 2. The scores over all allowed positions are turned into weights that sum to one, and the output of the head is the weighted mix of the values. The pushes of all 96 heads are added to the running vector; adding them one by one gives the same result, which is why Figure 6 can draw an attention push as the sum of its head contributions.

A token can draw only on itself and on earlier positions, which is what lets the model generate text from left to right and what leaves the upper half of Figure 5 empty. GPT-3 alternates layers that allow all earlier positions with layers that allow only a local band of recent ones (Brown et al., 2020, following Child et al., 2019).

Research on trained heads shows a mixed picture. In BERT and in translation models, studies found heads that track syntax, heads that attend to the previous token, and many heads that can be removed with little loss (Clark et al., 2019; Voita et al., 2019). In GPT-style models, pairs of heads form induction heads: they find an earlier occurrence of the current pattern and copy what followed it, a mechanism behind learning from examples in the prompt (Olsson et al., 2022), and the natural reading of the "opening pattern" head in Step 3. The three heads there are in this spirit, but invented.

A.4 The MLP: refining meaning within a token

The MLP sees one vector at a time. It expands the vector to 49,152 values, applies the GeLU nonlinearity (Hendrycks and Gimpel, 2016) and projects the result back; the outcome is added to the running vector. Geva et al. (2021) read this as a key-value memory: each detector watches for one direction, its key, and responds when the running vector points that way; each has a direction it writes, its value; the update is the sum of the values of the detectors that fired. In words: if the point lies in this region, push it that way. Detectors in lower layers respond to shallow patterns, such as particular tokens, and detectors in upper layers to more semantic ones.

The nonlinearity is essential. Without it, the two steps of the MLP would collapse into one linear map that treats every ingredient separately. The gate lets the MLP respond to a combination, such as pawn attacked and knight pinnable and famous game, while staying quiet for each part alone. Decoded into vocabulary terms, the value directions often promote recognizable concepts (Geva et al., 2022), and factual associations can be located in the MLPs of middle layers and edited there (Meng et al., 2022). Much of what a model knows about chess openings by name lives in these detectors.

A.5 Across the layers

Because both adjustments are additions, the final vector is the input embedding plus the sum of all updates, the precise meaning of "the embedding plus 192 pushes" in Step 3. Different depths do different work: in BERT, Tenney et al. (2019) found word-level and syntactic information resolved early and semantic roles late. In GPT models the intermediate vector can be decoded directly into vocabulary terms, and the guesses for the next token get steadily better with depth, the logit lens (nostalgebraist, 2020). Applied to the running example, the lens would show Bg4 overtaking exd4 somewhere in the upper layers, where "famous game" outweighs "best move".

A.6 Limits of interpreting the weights

The heads and detectors in Step 3 have tidy jobs because they were invented. In a trained model such roles have to be recovered from billions of numbers, and three obstacles stand in the way. Neurons are shared: a single neuron often responds to several unrelated concepts (Elhage et al., 2022), so the meaningful unit is a direction spread across many neurons. Attention weights are weak explanations: they show where a head looks, and Jain and Wallace (2019) found that they often disagree with other measures of which inputs mattered, a result Wiegreffe and Pinter (2019) qualify. Behavior is spread across components: a capability is usually a circuit of several heads and MLPs in different layers (Olah et al., 2020).

Progress is visible; specific circuits have been reverse-engineered and dictionary-learning methods extract interpretable directions at scale (Templeton et al., 2024). Still, a model's reasoning cannot yet be audited by inspecting its weights. Trust therefore has to come from the evidence and the verification around the model, which is the design of Part 2.

A.7 From the final vector to the next token

The final vector of the last position is compared with a vector for every entry of the vocabulary, and the comparison scores are turned into probabilities: unembedding. GPT-style models usually reuse the embedding table for this comparison (Press and Wolf, 2017; Radford et al., 2019), so the map of Step 2 is used twice. The model then draws one token. A setting called temperature scales the scores before the draw: close to zero the most likely token always wins, which makes the output nearly repeatable; at one the model samples from the distribution it learned. Related settings, top-k and top-p, cut off the unlikely tail (Holtzman et al., 2019). Temperature is one source of the variation from run to run that Step 8 contrasts with the engine; it also means that the illegal moves in the tail of the distribution are drawn eventually.

A.8 The research behind the other steps

Step 1: most tokenizers build on byte-pair encoding, which splits rare strings into frequent pieces (Sennrich et al., 2016). Step 4: models use the start and end of a long context more reliably than the middle (Liu et al., 2023). Step 7: Lewis et al. (2020) introduced retrieval-augmented generation; dense retrieval goes back to Karpukhin et al. (2020); Edge et al. (2024) describe Graph RAG. Step 10: Schick et al. (2023) showed that a model can learn when and how to call tools, and the loop of reasoning and acting follows ReAct (Yao et al., 2023).

A.9 Hallucination in more depth

The term covers several kinds of error, from contradicting the source to inventing facts; Ji et al. (2023) survey the variants and the remedies. Kalai and Vempala (2024) prove that a well-calibrated model has to hallucinate on facts that are rare in its training data, and Kalai et al. (2025) add the incentive: most benchmarks grade answers right or wrong, so a guess scores better than "I don't know". Anthropic (2025) found that declining to answer is the model's default behavior and that recognition of a known entity suppresses it; familiarity and knowledge are different directions, and the first can be present without the second, which is the Opera Game's Bg4 in one sentence. Kadavath et al. (2022) found that large models are mostly well calibrated when asked whether their own answer is correct. Farquhar et al. (2024) detect confabulation from outside by sampling several answers and measuring how much their meanings scatter, semantic entropy. Zhang et al. (2025) show that dominant knowledge can obscure less prominent knowledge, and Lin et al. (2022) that models repeat common misconceptions. Li et al. (2024) measured instruction drift within eight rounds of conversation, which argues for short, focused exchanges, and Chen et al. (2023) found that the same commercial model changes behavior between versions, which argues for re-testing after an update.

For the chess tutor the practical summary is Part 2: give the model the facts, limit what it may cite, and check what it says.

Appendix B: Glossary and literature

B.1 Glossary

Term	Meaning in this primer
Token	A chunk of text from the model's vocabulary; the unit the model reads and writes
Embedding	The point in a high-dimensional space that stands for a token; nearby points have similar use
Attention	The step in which a token gathers information from earlier tokens, weighted by relevance
MLP	The step in which a token's features are combined into new features, one token at a time
Context window	Everything the model is given before it answers; the whole of what it can see
Unembedding	Turning the final point into probabilities over the vocabulary
Temperature	The setting that controls how much the draw from those probabilities varies
FEN	A one-line text notation for a chess position, including side to move and castling rights
EPD	A FEN without the move counters, used as the key for a position so that transpositions match
SAN	Standard algebraic notation for a move, such as Nf3 or Bxb5+
PGN	The text format for a whole game: headers, moves, comments
UCI	The text protocol between a user interface and a chess engine
NNUE	The small neural network inside Stockfish that evaluates positions at the leaves of its search

Term	Meaning in this primer
Motif	A tactical pattern detected on the board: pin, fork, discovered attack, back rank
Retrieval	Looking material up and handing it to the model, instead of relying on what the model remembers
Facts first	Building the model's context from the engine's results before the question is asked
Checker	The function that verifies every move the model names against the board and the engine's lines
Help setting	Off, Flag mistakes or Full: how much engine data the coach may see during a game
Agent	A model that takes several steps toward a goal, using tools, and decides each step itself
Prompt injection	Instructions hidden in data the model reads, such as comments in a PGN file

B.2 Literature

Grouped by theme and ordered by year. The application itself is documented in its repository (Kibitz: README.md, ARCH.md, the flipbook).

Chess, engines and language models

- Karvonen, A. (2024). Emergent World Models and Latent Variable Estimation in Chess-Playing Language Models. COLM.
- Stockfish developers. Stockfish, an open-source chess engine. stockfishchess.org.
- Lichess. lila-openingexplorer, the opening explorer for lichess.org. github.com/lichess-org/lila-openingexplorer.
- chess.js. A JavaScript chess library for move generation, validation and PGN. github.com/jhlywa/chess.js.

Word vectors and the geometry of meaning

- Bengio, Y., Ducharme, R., Vincent, P., Jauvin, C. (2003). A Neural Probabilistic Language Model. Journal of Machine Learning Research 3.
- Mikolov, T., Chen, K., Corrado, G., Dean, J. (2013a). Efficient Estimation of Word Representations in Vector Space. ICLR Workshop.
- Mikolov, T., Yih, W., Zweig, G. (2013b). Linguistic Regularities in Continuous Space Word Representations. NAACL-HLT.
- Ethayarajh, K. (2019). How Contextual are Contextualized Word Representations? EMNLP.
- Elhage, N. et al. (2022). Toy Models of Superposition. Transformer Circuits Thread.
- Park, K., Choe, Y. J., Veitch, V. (2023). The Linear Representation Hypothesis and the Geometry of Large Language Models. ICML 2024.
- Templeton, A. et al. (2024). Scaling Monosemanticity: Extracting Interpretable Features from Claude 3 Sonnet. Transformer Circuits Thread.

Tokenization, transformer and GPT

- Sennrich, R., Haddow, B., Birch, A. (2016). Neural Machine Translation of Rare Words with Subword Units. ACL.
- Hendrycks, D., Gimpel, K. (2016). Gaussian Error Linear Units (GELUs). arXiv.
- Vaswani, A. et al. (2017). Attention Is All You Need. NeurIPS.
- Press, O., Wolf, L. (2017). Using the Output Embedding to Improve Language Models. EACL.
- Radford, A. et al. (2019). Language Models are Unsupervised Multitask Learners. OpenAI.
- Child, R., Gray, S., Radford, A., Sutskever, I. (2019). Generating Long Sequences with Sparse Transformers. arXiv.

- Brown, T. B. et al. (2020). Language Models are Few-Shot Learners. NeurIPS.
- Ba, J. L., Kiros, J. R., Hinton, G. E. (2016). Layer Normalization. arXiv.
- Holtzman, A. et al. (2019). The Curious Case of Neural Text Degeneration. ICLR 2020.
- Xiong, R. et al. (2020). On Layer Normalization in the Transformer Architecture. ICML.
- Su, J. et al. (2021). RoFormer: Enhanced Transformer with Rotary Position Embedding. arXiv.
- Molina, R. (2023). Traveling Words: A Geometric Interpretation of Transformers. arXiv.

Learned functions of heads and MLPs, and their interpretation

- Clark, K., Khandelwal, U., Levy, O., Manning, C. D. (2019). What Does BERT Look At? BlackboxNLP at ACL.
- Voita, E. et al. (2019). Analyzing Multi-Head Self-Attention: Specialized Heads Do the Heavy Lifting, the Rest Can Be Pruned. ACL.
- Tenney, I., Das, D., Pavlick, E. (2019). BERT Rediscovers the Classical NLP Pipeline. ACL.
- Jain, S., Wallace, B. C. (2019). Attention is not Explanation. NAACL-HLT.
- Wiegreffe, S., Pinter, Y. (2019). Attention is not not Explanation. EMNLP.
- nostalgebraist (2020). interpreting GPT: the logit lens. LessWrong.
- Olah, C. et al. (2020). Zoom In: An Introduction to Circuits. Distill.
- Geva, M., Schuster, R., Berant, J., Levy, O. (2021). Transformer Feed-Forward Layers Are Key-Value Memories. EMNLP.
- Elhage, N. et al. (2021). A Mathematical Framework for Transformer Circuits. Transformer Circuits Thread.
- Geva, M. et al. (2022). Transformer Feed-Forward Layers Build Predictions by Promoting Concepts in the Vocabulary Space. EMNLP.
- Meng, K., Bau, D., Andonian, A., Belinkov, Y. (2022). Locating and Editing Factual Associations in GPT. NeurIPS.
- Olsson, C. et al. (2022). In-context Learning and Induction Heads. Transformer Circuits Thread.

Hallucination and drift

- Kadavath, S. et al. (2022). Language Models (Mostly) Know What They Know. arXiv.
- Lin, S., Hilton, J., Evans, O. (2022). TruthfulQA: Measuring How Models Mimic Human Falsehoods. ACL.
- Chen, L., Zaharia, M., Zou, J. (2023). How Is ChatGPT's Behavior Changing over Time? arXiv.
- Ji, Z. et al. (2023). Survey of Hallucination in Natural Language Generation. ACM Computing Surveys.
- Kalai, A. T., Vempala, S. S. (2024). Calibrated Language Models Must Hallucinate. STOC.
- Li, K. et al. (2024). Measuring and Controlling Instruction (In)Stability in Language Model Dialogs. COLM.
- Farquhar, S., Kossen, J., Kuhn, L., Gal, Y. (2024). Detecting hallucinations in large language models using semantic entropy. Nature 630.
- Zhang, Y. et al. (2025). The Law of Knowledge Overshadowing. Findings of ACL.
- Kalai, A. T., Nachum, O., Vempala, S. S., Zhang, E. (2025). Why Language Models Hallucinate. arXiv.
- Anthropic (2025). Tracing the thoughts of a large language model.

Context, retrieval, tools, agents and security

- Lewis, P. et al. (2020). Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. NeurIPS.
- Karpukhin, V. et al. (2020). Dense Passage Retrieval for Open-Domain Question Answering. EMNLP.
- Liu, N. F. et al. (2023). Lost in the Middle: How Language Models Use Long Contexts. TACL.
- Schick, T. et al. (2023). Toolformer: Language Models Can Teach Themselves to Use Tools. NeurIPS.
- Yao, S. et al. (2023). ReAct: Synergizing Reasoning and Acting in Language Models. ICLR.
- Greshake, K. et al. (2023). Not what you've signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. arXiv.

- Edge, D. et al. (2024). From Local to Global: A Graph RAG Approach to Query-Focused Summarization. arXiv.
- Microsoft Research (2024). LazyGraphRAG: Setting a new standard for quality and cost. Blog.
- OWASP (2025). OWASP Top 10 for LLM Applications 2025. OWASP GenAI Security Project.
- Sanderson, G. (2024). Visualizing transformers and attention. Talk at TNG Big Tech Day; the visual approach to attention that Figure 5 follows.

Appendix C: The symbolic engine and its interface

This appendix follows the application's architecture notes (ARCH.md) and shows the pieces that Part 2 refers to. Where the primer reconstructs a text the app builds at run time, it says so.

C.1 The shared representation

The model and the engine share three text formats, and they are the contract between the two sides. A position is a FEN string. After 9. Bg5 in the Opera Game:

```
rn2kb1r/pp2qppp/2p2n2/4p1B1/2B1P3/1QN5/PPP2PPP/R3K2R b KQkq - 1 9
```

The eight groups before the first space are the ranks from Black's side down, letters for pieces (upper case White) and digits for empty squares; then the side to move, the castling rights, the en passant square, the half-move clock and the move number. The EPD is the same string without the last two numbers, and it is the key under which the app stores evaluations and indexes the player's games, so that a position reached by a different move order is found. A move is written in standard algebraic notation (Bg5, Nxb5, Bxb5+, O-O-O, Rd8#), and a game is a PGN file: headers in brackets, the moves, comments in braces. The model reads and writes these strings as text; the engine and chess.js parse them exactly, which is what makes the checker possible.

C.2 The engine in the browser

Stockfish runs inside the page as WebAssembly, in Web Workers so that the interface stays responsive; the flipbook shows Stockfish 19 Lite with four threads, and the analysis depth is 14 by default. When the page is cross-origin isolated, the multithreaded build is used. One worker analyzes, another plays the opponent's moves. The exchange with the engine is UCI, a line-based text protocol. Abbreviated, for the position above:

```
> position fen rn2kb1r/pp2qppp/2p2n2/4p1B1/2B1P3/1QN5/PPP2PPP/R3K2R b KQkq - 1 9
> go depth 14
< info depth 14 multipv 1 score cp 267 pv b8a6 c4a6 b7a6 e1g1 e7b4 ...
< info depth 14 multipv 2 score cp 298 pv h7h5 ...
< bestmove b8a6
```

The score is in hundredths of a pawn from the side to move's point of view, and the pv is the principal variation, the line the engine expects. The app converts the moves to SAN, stores the result by EPD from White's point of view, and shares it between the board, the review and the coach.

C.3 Legality and parsing

chess.js holds the board, generates the legal moves, validates every move before it is played, and parses the moves the model names in its answers. Everything that enters the page from outside is checked with it: imported PGN files, model output, library text. In the position above there are 27 legal moves for Black; h6 and Na6 are among them, and Qxf6 is not, which is why the checker struck it through on the third flipbook page.

C.4 The facts-first context

The context the app builds for a question is assembled by one function, contextFor(). The following is a reconstruction of its content for the plan question of Step 5, abbreviated; the real text is longer and its wording is the app's.

```
Level: club player. Game: Philidor Defense, after 9. Bg5, Black to move.
Moves so far: 1. e4 e5 2. Nf3 d6 3. d4 Bg4 4. dxe5 Bxf3 5. Qxf3 dxe5
  6. Bc4 Nf6 7. Qb3 Qe7 8. Nc3 c6 9. Bg5
Position (FEN): rn2kb1r/pp2qppp/2p2n2/4p1B1/2B1P3/1QN5/PPP2PPP/R3K2R b KQkq - 1 9
[board diagram]
Stockfish, depth 14, from White's view:
  1. 9... Na6 10. Bxa6 bxa6 11. O-O Qb4 ...      +2.67
  2. 9... h5 ...                                  +2.98
  3. 9... a6 10. a4 a5 11. O-O-O Na6 ...          +2.67
Motifs in the best move: develops with tempo; offers a queen trade.
Themes: development lead (White), uncastled king (Black), pin on f6.
Board facts: Black's queen guards b7 and f7; the f6 knight is pinned
  to the queen; White's queen and bishop both aim at f7.
References: Fundamental Chess Openings (van der Sterren), Philidor chapter.
Rules: take every move and line from the lines above or the game, at most
  six plies; explain ideas, not variations; describe evaluations in words;
  recommend only the references given; stay short.
Question: What is the main plan for the side to move here, and why?
```

Three things about this text. The evaluations and lines are the engine's, and the model is not asked to produce any. The references are the retrieval's, and the model may recommend no others. And the PGN headers and comments, had there been any, would have entered as quoted data, one line each in guillemets.

The response is the one on the second flipbook page, and the checker's note under it reads: 11 moves backed by Stockfish or the game, 1 legal but not in its lines, none wrong.

C.5 The checker

checkAnswer() sorts every move-like token in an answer into one of five bins: in Stockfish's lines for the position or the one before; one of the game's moves; legal but unchecked; invalid; a bare square. Moves joined by move numbers must form a contiguous run of an engine line or of the game. Claims about the board ("the bishop on b5") are checked against the position. The page renders the answer as text with a minimal markdown subset built from DOM nodes, never as HTML, and marks the moves: backed moves highlighted and clickable, so that hovering one draws it on the board; legal but unchecked moves grayed; invalid moves struck through; and a note with the counts. A stale answer, one that arrives after the game or the position changed, is dropped before it is shown.

C.6 The Claude API call

The coach is called through the gateway, which holds the key and talks to the Claude API. The shape of a request, abbreviated:

```
system:   You are a chess coach for a club player. <standing rules>
messages: user: <the context of C.4, then the question>
          assistant: <earlier answer, on a follow-up>
          user: <follow-up question>
model:    claude-opus-5-5     (quick questions, chat, reviews)
stream:   true
```

The gateway streams the answer back as newline-delimited JSON, the page checks the moves as the text arrives, and the finished answer is cached under a key made of position, move, aspects, engine view,

level and model. For answers the page must act on, arrows and highlighted squares, the request asks for a named JSON format; the gateway asks the provider for native JSON-schema output first, falls back to parsing JSON out of text, validates the result against the schema in both cases, and the page checks every square against the position before drawing. The same page can run against the host model as a Claude artifact, or fully offline with a small model inside the browser; the coach code does not know where the model runs, because the two clients expose the same call. Figure 15 shows where each part runs.




Figure 15. Where things run. The browser page with the board, Stockfish, the symbolic knowledge, the checker and the optional in-browser model; the local server with the gateway and the keys; the providers. After ARCH.md.

C.7 Stockfish specifics

- Search. Alpha-beta search with depth as the budget; MultiPV returns several candidate lines, which is how the coach can compare the engine's own alternatives (Na6 against h5 in Step 6); the principal variation is the evidence the model explains from.
- Evaluation. Since 2020 the evaluation at the leaves of the search is a small neural network, NNUE, trained on positions scored by deeper searches. The search is symbolic, the evaluation is learned, and the neural part is caged inside a deterministic search. The symbolic engine is itself a hybrid; it is the closing image of this primer.
- Strength and style. The app's strength slider (1488 in the flipbook, a solid club player) maps to the engine's UCI_LimitStrength and UCI_Elo options. The styles Solid, Balanced, Active, Aggressive and Reckless pick among the engine's top moves by a rule, so style is a selection on top of the engine, not a different engine.
- Review metrics. A move's loss is the drop in evaluation it caused from the mover's point of view; thresholds turn losses into inaccuracy, mistake and blunder, and an accuracy per side is computed from the losses over the game. The numbers depend on depth, which is why the app reports that runs differ.
- Tablebases. For positions with few pieces, Syzygy tablebases give the exact result and the distance to it, a lookup rather than a search, the purest form of symbolic knowledge in chess.
- Deployment. The WebAssembly build inside the browser for a local engine, as here; the native binary on a server where more depth is needed. The in-browser model and the engine compete for CPU cores, so the analyst runs with fewer threads while the model generates.
- Contrast. Leela Chess Zero combines a large neural network with Monte Carlo tree search, the other way to pair the two. Both engines are far stronger than any language model at chess, and neither can explain a move to a club player. That gap is the model's job, and the reason the tutor needs both.