

trieFinder

Gabriel Renaud

Max Planck Institute for Evolutionary Anthropology

`gabriel.reno [at sign] gmail.com`

August 23, 2012

Contents

1	Description	2
1.1	Requirements	2
1.2	Procedure	3
2	Installation	3
2.1	Building the binaries	3
2.2	Setting up the databases	3
3	Running the software	4
4	Output description	5

1 Description

trieFinder in summary:

Feature	Description
Input data	MPSS sequence tags (with a common prefix)
Use	align the input, annotate the results and parse them automatically
Language	C++ core functions and Perl wrapper scripts
Input format for sequence tags	fastq
Input format for databases	fasta
Output format	custom tab delimited (see section 4)

trieFinder is a software for the automatic alignment of tags stemming from Massively Parallel Signature Sequencing (MPSS) to preannotated databases of putative sequence tags from both the genome and transcriptome (Refseq and Unigene). Thus, the laborious process of aligning the tags and parsing the results to create a final summary for each tag is obviated. The core elements of trieFinder are written in C++ with high order scripts in Perl. Although the software was originally written to deal with Zebrafish data, it can be easily accomodated for other species.

Our approach relies on prefix trees built on the database which has the advantage of assuring correct results even if the sequence is shorter than the one stored in the database. Therefore, the user does not have to rebuild the database for each iteration.

1.1 Requirements

trieFinder needs:

- Perl installed
- a C++ compiler
- The genome and transcriptome (see section 2.2)
- Adequate disk space to store the resulting indices
- Sufficient RAM to store the indices into memory (10-20G should suffice)

1.2 Procedure

trieFinder will:

- Build a database of the putative sequence tags within 1 mismatch of a common prefix (representing the restriction enzyme recognition sequence) for the RefSeq, Unigene and Genomic database
- Combine the putative tags into a single database of all putative sequence tags
- Searches the input tags against the single database and produces a final tab delimited file detailing the matches for each sequence tag

To avoid running into the upper limit of the RAM, we divide the last two steps into chunks which are automatically combined later on.

2 Installation

2.1 Building the binaries

Make sure the main script and worker scripts are executable:

```
chmod u+x mainScript.pl
chmod u+x src/mergeAnnotation.pl
chmod u+x src/readFiles.pl
```

Build the C++ binaries:

```
cd src/
make
```

if the following files are present, the build was succesful:

```
src/allTag
src/trieTag
```

2.2 Setting up the databases

Download the databases:

- Download the RefSeq for Zebrafish, for example we used

```
ftp://ftp.ncbi.nih.gov/refseq/D_rerio/mRNA_Prot/zebrafish.rna.fna.gz
```

- Download the Unigene for Zebrafish, for example we used

```
ftp://ftp.ncbi.nih.gov/repository/UniGene/Danio_rerio/Dr.seq.all.gz
```

- Download the Genome for Zebrafish, for example we used

```
ftp://ftp.ncbi.nih.gov/genomes/D_rerio/
```

- Concatenate all the genomic sequences for the Zebrafish chromosomes (genomic database) into a single file, this can be done using the unix “cat” command :

```
cat [list of all chromosomes] > whole_genome.fa
```

- Unzip any database file you have downloaded as the program requires raw fasta for the database files.

3 Running the software

To run the software type:

```
./mainScript.pl
```

This will give you a list of options. The first time the software is executed, it needs to be the formatted databases for the search. On subsequent searches, if the same directory where the database files are stored are specified, it will merely use the existing files. Be sure to delete these files if the database you have build is older than 1 year and download the databases from scratch. If you only wish to build the databases, use the “-d” option.

The output will be created by adding the “.out” extention to the input fastq file containing the tags. If you do not have write permissions in the directory where the input file is store, you can merely create a symbolic link.

Here is an example of use:

```
./mainScript.pl -r GATC -o /home/user/project/zebrafish/db/
-s /mnt/db/zebrafish.rna.fna -u /mnt/db/Dr.seq.all
-g /mnt/db/whole_genome.fa -i /home/user/project/zebrafish/tags.fa
```

This will build the database for the Sau3A1 restriction enzyme (recognition sequence = GATC), will create and store the database files in :

```
/home/user/project/zebrafish/db/
```

Using the following raw fasta files for RefSeq, Unigene and the full zebrafish genome respectively:

```

/mnt/db/zebrafish.rna.fna
/mnt/db/Dr.seq.all
/mnt/db/whole_genome.fa

```

and will read the following fastq file as input:

```
/home/user/project/zebrafish/tags.fa
```

The output will be produced as :

```
/home/user/project/zebrafish/tags.fa.out
```

4 Output description

The output is a tab delimited file where the following columns contain:

Column #	Content
1	Original id of the input sequence
2	Original sequence for this id
3	Perfect matches to the refseq database ¹
4	Number of initial perfect matches to the refseq database
5	Degenerate ² matches to the refseq database ¹
6	Number of initial degenerate matches to the refseq database
7	Perfect matches to the unigene database ¹
8	Number of initial perfect matches to the unigene database
9	Degenerate ² matches to the unigene database ¹
10	Number of initial degenerate matches to the unigene database
11	Perfect matches to the genome ¹
12	Number of initial perfect matches to the genome
13	Degenerate ² matches to the genome ¹
14	Number of initial degenerate matches to the genome

¹ : By default, the program will only report at most 10 matches. The number of original matches will be report in round brackets in the next column.

² : Degenerate means matches with greater or equal than 1 mismatches.