EXERCISE 2

① COUT() FUNCTION

```
SELECT COUNT(*) AS TOTAL-EMPLOYEES
FROM EMPLOYEES
```

TOTAL EMPLOYEES
10

2 SUM() FUNCTIONS

```
SELECT SUM(Salary) AS TOTAL-IT-SALARY
WHERE department = 'IT'
```

TOTAL IT Salary
220.000

3. AVG() FUNCTION

```
SELECT AVG(SALARY) AS Average-SALARY
FROM employees
WHERE department = 'HR'
```

AVERAGE SALARY
50000

4 MIN() and MAX() FUNCTIONS

```
SELECT
        MAX(SALARY) AS HIGHEST_SALARY
        MIN(SALARY) AS LOWEST_SALARY
FROM: EMPLOYEES
```

HIGHEST SALARY	LOWEST_SALARY
62000	48000

5. GROUP BY STATEMENT

```
SELECT department, SUM(salary) AS TOTAL_SALARY
FROM EMPLOYEES
GROUP BY department
```

department	TOTAL_SALARY
IT	223000
HR	99000
FINANCE	119000
MARKETING	105000

6. GROUP BY and COUNT()

```
SELECT CITY, COUNT(*) AS TOTAL_Emplo
FROM EMPLOJEES
GROUP BY CITY
```

CITY	TOTAL EMPLOJEES
NEW JORK	2
CHICAGO	3
LOS ANGELES	2
SAN FRANCISCO	2
HOUSTON	1

7 GROUP BY AND ORDER BY.

```
SELECT department,
       AVG(SALARY) AS Average_Salary
FROM EMPLOJEES
GROUP BY department
ORDER BY Average_SALARY DESC;
```

Department	AVERAGE SALARY
HR	48000
MARKETING	52000
FINANCE	59000
I T	62000

8. HAVING CLAUSE

```
SELECT Department, SUM(SALARY) AS TOTAL_SALARY
FROM EMPLOYEES
GROUP BY department
HAVING SUM(SALARY) > 100.000;
```

Department	TOTALSALARY
IT	223000
FINANCE	119000
Marketing	108000

9. Combining GROUP BY, HAVING and ORDER BY

```
SELECT CITY, COUNT(*) AS Employees_COUNT
FROM EMPLOYEES
GROUP BY CITY
HAVING COUNT(*) > 1
ORDER BY EMPLOYEES_COUNT DESC;
```

CITY	EMPLOYEES_COUNT
NEW YORK	2
CHICAGO	3
LOS ANGELES	2
SAN FRANCISCO	2

10. Combining Aggregate Functions

```
SELECT
  COUNT(*) AS TOTAL_EMPLOJEES
  AVG(SALARY) AS AVERAGA_SALARY
  MAX(SALARY) AS highest_SALARY
  MIN(SALARY) AS Lowest_SALARY
FROM : EMPLOJEES.
```