

INTRODUCTION TO LOGISTIC REGRESSION

Adam Jones, PhD

Data Scientist @ Critical Juncture

INTRODUCTION TO LOGISTIC REGRESSION

LEARNING OBJECTIVES

- Build a logistic regression classification model using the statsmodels library
- Describe a sigmoid function, and odds, as well as how they relate to logistic regression
- Evaluate a model using metrics such as classification accuracy/error, confusion matrices, ROC curves/AUC, and loss functions

COURSE

PRE-WORK

PRE-WORK REVIEW

- Implement a linear model with sklearn
 - `LinearRegression()`
- Understand what a coefficient is
- Recall metrics such as accuracy and misclassification
- Recall the differences between L1 and L2 regularization

OPENING

INTRODUCTION TO LOGISTIC REGRESSION

INTRODUCTION TO LOGISTIC REGRESSION



EXERCISE

ANSWER THE FOLLOWING QUESTIONS

Read through the following questions and brainstorm answers for each:

1. What are the main differences between linear and KNN models? What is different about how they approach solving the problem?
 - a. For example, what is *interpretable* about OLS compared to what's *interpretable* in KNN?
2. What would be the advantage of using a linear model like OLS to solve a classification problem, compared to KNN?
 - a. What are some challenges for using OLS to solve a classification problem (say, if the values were either 1 or 0)?

DELIVERABLE

Answers to the above questions

INTRODUCTION



LOGISTIC REGRESSION

LOGISTIC REGRESSION

- Logistic regression is a *linear* approach to solving a *classification* problem
- That is, we can use a linear model, similar to Linear regression, in order to solve if an item *belongs* or *does not belong* to a class label

CHALLENGE! LINEAR REGRESSION RESULTS FOR CLASSIFICATION

- Regression predictions can have a value range from $-\infty$ to ∞
- Classification is used when predicted values (i.e. class labels) are not greater than or less than each other



CHALLENGE! LINEAR REGRESSION RESULTS FOR CLASSIFICATION

- But, since most classification problems are binary (0 or 1) and 1 is greater than 0, does it make sense to apply the concept of regression to solve classification?
- How might we contain those bounds?
- Let's review some approaches to make classification with regression feasible

FIX 1: PROBABILITY

- One approach is predicting the probability that an observation belongs to a certain class
- We could assume the *prior probability* (the ***bias***) of a class is the class distribution

FIX 1: PROBABILITY

- For example, suppose we know that roughly 700 of 2200 people from the Titanic survived
 - Without knowing anything about the passengers or crew, the probability of survival would be ~ 0.32 (32%)
- However, we still need a way to use a linear function to either increase or decrease the probability of an observation given the data about it

ACTIVITY: KNOWLEDGE CHECK



EXERCISE

ANSWER THE FOLLOWING QUESTIONS

1. Recall the ordinary least squares formula
2. The prior probability is most similar to which value in the ordinary least squares formula?

DELIVERABLE

Answers to the above questions

FIX 2: LINK FUNCTIONS AND THE SIGMOID FUNCTION

- Another advantage of OLS is that it allows for *generalized* models using a *link function*
- Link functions allows us to build a relationship between a linear function and the mean of a distribution
- We can now form a specific relationship between our linear predictors and the response variable

ACTIVITY: KNOWLEDGE CHECK

ANSWER THE FOLLOWING QUESTIONS



EXERCISE

1. What was the distribution most aligned with OLS/Linear Regression?

DELIVERABLE


Answers to the above questions

FIX 2: LINK FUNCTIONS AND THE SIGMOID FUNCTION

- For classification, we need a distribution associated with categories: given all events, what is the probability of a given event?
- The link function that best allows for this is the *logit* function, which is the inverse of the *sigmoid* function

FIX 2: LINK FUNCTIONS AND THE SIGMOID FUNCTION


- A *sigmoid function* is a function that visually looks like an “S”



- Mathematically, it is defined as $f(x) = \frac{1}{1 + e^{-x}}$

FIX 2: LINK FUNCTIONS AND THE SIGMOID FUNCTION

- Recall that e is the *inverse* of the natural log
- As x increases, the results is closer to 1
- As x decreases, the result is closer to 0
- When $x = 0$, the result is 0.5



FIX 2: LINK FUNCTIONS AND THE SIGMOID FUNCTION

- Since x decides how much to increase or decrease the value away from 0.5,
 - x can be interpreted as something like a coefficient

DEMO

PLOTTING A SIGMOID FUNCTION

PLOTTING A SIGMOID FUNCTION


- Use the sigmoid function definition with values of x between -6 and 6 to plot it on a graph
- Do this by hand or write Python code to evaluate it
 - e.g. `1 / (1 + numpy.exp(-logit))`
- Recall that $e = 2.71$
- Do we get the “S” shape we expect?

INTRODUCTION

LOGISTIC REGRESSION

FIX 3: ODDS AND LOG-ODDS

- The logit function allows for values between $-\infty$ and ∞ , but provides us probabilities between 0 and 1



ACTIVITY: KNOWLEDGE CHECK



EXERCISE

ANSWER THE FOLLOWING QUESTIONS

1. Why is it important to take values between $-\infty$ and ∞ , but provide probabilities between 0 and 1?
2. What does this remind us of?

DELIVERABLE

Answers to the above questions

FIX 3: ODDS AND LOG-ODDS


Logistic regression from scratch - example

```
# First grab prediction from scikit learn model (for later)
prediction = lm.predict_proba(X.iloc[[0]])[0][1]

# Now look at coefficients and single sample
a = X.iloc[[0]]
b = lm.coef_
print(b)
print(a.as_matrix())


# Calculate linear prediction
scratch_pred = lm.intercept_ + np.sum(a.as_matrix()*b)
print(scratch_pred)
# Convert to probability
prob = sigmoid_func(scratch_pred)
print(prob)
print(prediction)

[[ 0.73323585  0.03063781 -0.55742461 -0.82369768]]
[[0 0 1 0]]
[-1.17467325]
[0.23601131]
0.23601131219840463
```




FIX 3: ODDS AND LOG-ODDS

```
[[ 0.73323585  0.03063781 -0.55742461 -0.82369768]]  
[[0 0 0 1]]  
[-1.44094631]  
[0.19139885]  
0.19139884909295155
```




FIX 3: ODDS AND LOG-ODDS

```
[[ 0.73323585  0.03063781 -0.55742461 -0.82369768]]  
[[1 0 0 0]]  
[0.11598722]  
[0.52896434]  
0.528964340721897
```




FIX 3: ODDS AND LOG-ODDS

- The *logit* function is the inverse of the *sigmoid* function
- This will act as our *link* function for logistic regression
- The value within the natural log, $p / (1-p)$ represents the *odds*
 - Taking the natural log of odds generates *log odds*
 - For example: `np.log(odds)`



FIX 3: ODDS AND LOG-ODDS

- ▶ With these coefficients, we get our overall probability: the logistic regression draws a linear *decision line* which divides the classes



GUIDED PRACTICE

WAGER THOSE ODDS!

ACTIVITY: WAGER THOSE ODDS!



EXERCISE

DIRECTIONS (15 minutes)

1. Given the odds below for some football games, use the *logit* function and the *sigmoid* function to solve for the *probability* that the “better” team would win.
 - a. Stanford : Iowa, 5:1
 - b. Alabama : Michigan State, 20:1
 - c. Clemson : Oklahoma, 1.1:1
 - d. Houston : Florida State, 1.8:1
 - e. Ohio State : Notre Dame, 1.6:1

DELIVERABLE

The desired probabilities

ACTIVITY: WAGER THOSE ODDS!



EXERCISE

STARTER CODE

```
def logit_func(odds):  
    # uses a float (odds) and returns back the log odds (logit)  
    return None
```

```
def sigmoid_func(logit):  
    # uses a float (logit) and returns back the probability  
    return None
```

DELIVERABLE

The desired probabilities

INDEPENDENT PRACTICE

LOGISTIC REGRESSION IMPLEMENTATION

ACTIVITY: LOGISTIC REGRESSION IMPLEMENTATION



EXERCISE

DIRECTIONS (15 minutes)

Use the data `collegeadmissions.csv` and the `LogisticRegression` estimator in `sklearn` to predict the target variable `admit`

1. What is the bias, or prior probability, of the dataset?
2. Build a simple model with one feature and explore the `coef_` value
3. Build a more complicated model using multiple features
 - a. Interpreting the odds, which features have the most impact on admission rate?
 - b. Which features have the least?
4. What is the accuracy of your model?

DELIVERABLE

Answers to the above questions

INTRODUCTION

ADVANCED CLASSIFICATION METRICS

ADVANCED CLASSIFICATION METRICS

- Accuracy is only one of several metrics used when solving a classification problem
- $\text{Accuracy} = \frac{\text{total predicted correct}}{\text{total observations in dataset}}$
- Accuracy alone doesn't always give us a full picture
- If we know a model is 75% accurate, it doesn't provide *any* insight into why the 25% was wrong

ADVANCED CLASSIFICATION METRICS

- Was it wrong across all labels?
- Did it just guess one class label for all predictions?
- It's important to look at other metrics to fully understand the problem

ADVANCED CLASSIFICATION METRICS

- ▶ We can split up the accuracy of each label by using the *true positive rate* and the *false positive rate*
- ▶ For each label, we can put it into the category of a true positive, false positive, true negative, or false negative

		<u>True class</u>	
		p	n
<u>Hypothesized class</u>	Y	True Positives	False Positives
	N	False Negatives	True Negatives
Column totals:		P	N

ADVANCED CLASSIFICATION METRICS

- ▶ True Positive Rate (TPR) asks, “Out of all of the target class labels, how many were accurately predicted to belong to that class?”
- ▶ For example, given a medical exam that tests for cancer, how often does it correctly identify patients with cancer?

		<u>True class</u>	
		p	n
<u>Hypothesized class</u>	Y	True Positives	False Positives
	N	False Negatives	True Negatives
Column totals:		P	N

tp rate = $\frac{TP}{P}$

ADVANCED CLASSIFICATION METRICS

- False Positive Rate (FPR) asks, “Out of all items not belonging to a class label, how many were predicted as belonging to that target class label?”
- For example, given a medical exam that tests for cancer, how often does it trigger a “false alarm” by incorrectly saying a patient has cancer?

		<u>True class</u>	
		p	n
<u>Hypothesized class</u>	Y	True Positives	False Positives
	N	False Negatives	True Negatives
Column totals:		P	N

fp rate = $\frac{FP}{N}$

ADVANCED CLASSIFICATION METRICS

- These can also be inverted
- How often does a test *correctly* identify patients without cancer?

		<u>True class</u>			
		p	n		
<u>Hypothesized class</u>	Y	True Positives	False Positives		
	N	False Negatives	True Negatives	$\frac{TN}{TN+FN}$	
Column totals:		P	N		

ADVANCED CLASSIFICATION METRICS

- How often does a test *incorrectly* identify patient as cancer-free?

		<u>True class</u>	
		p	n
<u>Hypothesized class</u>	Y	True Positives	False Positives
	N	False Negatives	True Negatives
Column totals:		P	N

$\frac{FN}{TN+FN}$

ADVANCED CLASSIFICATION METRICS

- The true positive and false positive rates gives us a much clearer pictures of where predictions begin to fall apart
- This allows us to adjust our models accordingly

ADVANCED CLASSIFICATION METRICS

- A good classifier would have a true positive rate approaching 1 and a false positive rate approaching 0
- In our smoking problem, this model would accurately predict *all* of the smokers as smokers and not accidentally predict any of the nonsmokers as smokers

ADVANCED CLASSIFICATION METRICS

- We can vary the classification threshold for our model to get different predictions. But how do we know if a model is better overall than other model?
- We can compare the FPR and TPR of the models, but it can often be difficult to optimize two numbers at once
- Logically, we like a single number for optimization
- Can you think of any ways to combine our two metrics?


ADVANCED CLASSIFICATION METRICS

- This is where the Receiver Operating Characteristic (ROC) curve comes in handy
- The curve is created by plotting the true positive rate against the false positive rate at various model **threshold*** settings
- Area Under the Curve (AUC) summarizes the impact of TPR and FPR in one single value

* Some cut-off used in classification


ADVANCED CLASSIFICATION METRICS

- There can be a variety of points on an ROC curve




ADVANCED CLASSIFICATION METRICS

- We can begin by plotting an individual TPR/FPR pair for one threshold




ADVANCED CLASSIFICATION METRICS

- We can continue adding pairs for different thresholds




ADVANCED CLASSIFICATION METRICS

- We can continue adding pairs for different thresholds




ADVANCED CLASSIFICATION METRICS

- Finally, we create a full curve that is described by TPR and FPR




ADVANCED CLASSIFICATION METRICS

- ▶ With this curve, we can find the Area Under the Curve (AUC)



ADVANCED CLASSIFICATION METRICS

- This [interactive visualization](#) can help practice visualizing ROC curves



ADVANCED CLASSIFICATION METRICS

- If we have a TPR of 1 (all positives are marked positive) and FPR of 0 (all negatives are not marked positive), we'd have an AUC of 1
 - This means everything was accurately predicted
- If we have a TPR of 0 (all positives are not marked positive) and an FPR of 1 (all negatives are marked positive), we'd have an AUC of 0
 - This means nothing was predicted accurately
- An AUC of 0.5 would suggest randomness (somewhat) and is an excellent benchmark to use for comparing predictions (i.e. is my AUC above 0.5?)

ADVANCED CLASSIFICATION METRICS

- There are several other common metrics that are similar to TPR and FPR

		<u>True class</u>			
		p	n		
<u>Hypothesized class</u>	Y	True Positives	False Positives	$\text{fp rate} = \frac{FP}{N}$	$\text{tp rate} = \frac{TP}{P}$
	N	False Negatives	True Negatives	$\text{precision} = \frac{TP}{TP+FP}$	$\text{recall} = \frac{TP}{P}$
Column totals:		P	N	$\text{accuracy} = \frac{TP+TN}{P+N}$	
				$\text{F-measure} = \frac{2}{1/\text{precision}+1/\text{recall}}$	

- Sklearn has all of the metrics located on [one convenient page](#)

GUIDED PRACTICE

**WHICH METRIC
SHOULD I USE?**

ACTIVITY: WHICH METRIC SHOULD I USE?

DIRECTIONS (15 minutes)

While AUC seems like a “golden standard”, there will be instances where error in positive or negative matches will be more important

For each of the following examples:

1. Write a confusion matrix: true positive, false positive, true negative, false negative
 - Then decide what each square represents for that specific example
2. Define the *benefit* of a true positive and true negative
3. Define the *cost* of a false positive and false negative
4. Determine at what point does the cost of a failure outweigh the benefit of a success?
This would help you decide how to optimize TPR, FPR, and AUC

Examples:

1. A test is developed for determining if a patient has cancer or not
2. A newspaper company is targeting a marketing campaign for "at risk" users that may stop paying for the product soon
3. You build a spam classifier for your email system

DELIVERABLE

Answers for each example



EXERCISE

INDEPENDENT PRACTICE

EVALUATING LOGISTIC REGRESSION WITH ALTERNATIVE METRICS

ACTIVITY: EVALUATING LOGISTIC REGRESSION

DIRECTIONS (35 minutes)

[Kaggle's common online exercise](#) is exploring survival data from the Titanic



EXERCISE

1. Spend a few minutes determining which data would be most important to use in the prediction problem
 - You may need to create new features based on the data available
 - Consider using a feature selection aide in sklearn
 - For a worst case scenario, identify one or two strong features that would be useful to include in this model

DELIVERABLE

Answers to the above question and a Logistic model on the Titanic data

ACTIVITY: EVALUATING LOGISTIC REGRESSION



EXERCISE

DIRECTIONS (35 minutes)

2. Spend 1-2 minutes considering which *metric* makes the most sense to optimize. Accuracy? FPR or TPR? AUC? Given the business problem of understanding survival rate aboard the Titanic, why should you use this metric?
3. Build a tuned Logistic model
 - Be prepared to explain your design (including regularization), metric, and feature set in predicting survival using any tools necessary (such as a fit chart)
 - Use the starter code to get you going

DELIVERABLE

Answers to the above question and a Logistic model on the Titanic data

CONCLUSION

TOPIC REVIEW

REVIEW QUESTIONS

- What's the link function used in logistic regression?
- What kind of machine learning problems does logistic regression address?
- What do the *coefficients* in a logistic regression represent?
 - How does the interpretation differ from ordinary least squares?
 - How is it similar?

REVIEW QUESTIONS

- How does True Positive Rate and False Positive Rate help explain accuracy?
- What would an AUC of 0.5 represent for a model? What about an AUC of 0.9?
- Why might one classification metric be more important to tune than another?
 - Give an example of a business problem or project where this would be the case

COURSE

BEFORE NEXT CLASS

BEFORE NEXT CLASS

DUE DATE

- Unit Project 3 due: ***This Thurs*** (4/19)

LESSON

Q & A

LESSON

EXIT TICKET

DON'T FORGET TO FILL OUT YOUR EXIT TICKET