| | Pro | otocol: STN POST OP 8PARF | RENT 9 | | |
|---------|---------------------------|---------------------------|-------------------------|---------------|---------|
| | PATIENT POSITION | | IMAGING PARAMETERS | | |
| | Patient Entry | Head First | Gradient Mode | WHOLE | |
| | Patient Position | Supine | Imaging Mode | 2D | |
| | Coil Configuration | HEAD | Pulse Sequence | Gradient Echo | |
| | Plane | SAGITTAL | Imaging Options | None | |
| | Series Description | SAG LOC | Acceleration Factor | 1.00 | |
| | SCAN TIMING | | SCAN RANGE | | |
| | Flip Angle | 20 | FOV | 30.0 | |
| | TE | 20.0 | Slice Thickness | 5.0 | |
| | Number of Echoes | 1 | Slice Spacing | 1.0 | |
| | TR | 250.0 | | | |
| | Receiver Bandwidth | 19.23 | | | |
| | IMAGE ENHANCE | | ACQ TIMING | | |
| | Filter Choice | None | Freq | 256 | |
| | | | Phase | 128 | |
| | | | Freq DIR | S/I | |
| | | | NEX | 1.00 | |
| () | | | Phase FOV | 1.00 | () |
| 2 | | | Auto Shim | Auto | SAG LOC |
| SAG LOC | | | Phase Correction | No | AG |
| S | GATING/TRIGGER | | FMRI | | S |
| | Auto Trigger Type | Off | PSD Trigger | Internal | |
| | | | Slice Order | Interleaved | |
| | | | View Order | Bottom/Up | |
| | | | # of Repetitions REST | 0 | |
| | | | # of Repetitions ACTIVE | 0 | |
| | MULTI-PHASE | | SAT | | |
| | # of Acquisition | 0 | Tag Type | None | |
| | Seperate Series | 0 | | | |
| | Mask Phase | 0 | | | |
| | Mask Pause | 0 | | | |
| | ASSET | | TRICKS | | |
| | Slice Acceleration Factor | 1.00 | Pause On/Off | On | |
| | Phase Acceleration Factor | 1.00 | Auto Subtract | 0 | |
| | | | Auto SCIC | Off | |
| | CONTRAST | | MULTI-STATION | | |
| | Contrast Yes/No | No | Number of Stations | 0 | |
| | | | Station Number | 0 | |

| | | rotocol: STN POST OP 8PAR | ILLINI 5 | | |
|-----------|-----------------------------------|---------------------------|----------------------|-----------|-----------|
| | PATIENT POSITION | | IMAGING PARAMETERS | | |
| | Patient Entry | Head First | Gradient Mode | WHOLE | |
| | Patient Position | Supine | Imaging Mode | 2D | |
| | Coil Configuration | HEAD | Pulse Sequence | Spin Echo | ł |
| | Plane | AXIAL | Imaging Options | EPI, DIFF | |
| | Series Description | DIFFUSION | PSD Name | epi2 | |
| | SCAN TIMING | | SCAN RANGE | | |
| | TE | Minimum | FOV | 24.0 | |
| | TR | 10000.0 | Slice Thickness | 5.0 | |
| | Number of Shots | 1 | Slice Spacing | 0.0 | |
| | IMAGE ENHANCE | E ENHANCE ACQ TIMING | | | |
| | Filter Choice | None | Freq | 128 | |
| | | | Phase | 192 | |
| | | | Freq DIR | R/L | |
| | | | NEX | 1.00 | |
| | | | Phase FOV | 1.00 | |
| Z | | | Auto Shim | Auto | Z |
| SIC | | | Phase Correction | Yes | DIFFUSION |
| DIFFUSION | GATING/TRIGGER | | USER CVS | | LE |
| □ | Auto Trigger Type | Off | User CV0 | 1.00 | ቯ |
| | MULTI-PHASE | | SAT | | |
| | Seperate Series | 0 | Tag Type | None | |
| | Mask Phase | 0 | | | |
| | Mask Pause | 0 | | | |
| | DIFFUSION | | TRICKS | | |
| | B Value | 1000 | Pause On/Off | On | |
| | Optimized TE | Yes | Auto Subtract | 0 | |
| | Diffusion Directions | All | Auto SCIC | Off | |
| | Number of Diffusion Directions | 6 | | | |
| | Number of T2 Images | 1 | | | |
| | Dual Spin Echo | Off | | | |
| | Recon All Images | On | | | |
| | CONTRAST | | MULTI-STATION | | |
| | Contrast Yes/No | No | Number of Stations | 0 | |
| | | | Station Number | 0 | |

| | 11 | otocol: STN POST OP 8PAR | ILINI 9 | | |
|-------|-------------------------|--------------------------|---------------------------|----------------------|------------|
| | PATIENT POSITION | | IMAGING PARAMETERS | | |
| | Patient Entry | Head First | Gradient Mode | WHOLE | |
| | Patient Position | Supine | Imaging Mode | 3D | |
| | Coil Configuration | HEAD | Pulse Sequence | SPGR | |
| | Plane | AXIAL | Imaging Options | EDR, Fast, IrP, ZIP2 | |
| | Series Description | AX 3D SPGR | Acceleration Factor | 1.00 | |
| | SCAN TIMING | | SCAN RANGE | | |
| | Flip Angle | 15 | FOV | 30.0 | |
| | TE | Min Full | Slice Thickness | 2.0 | |
| | ті | 500 | Location per Slab | 128 | |
| | Receiver Bandwidth | 19.23 | Overlap Locations | 0 | |
| | IMAGE ENHANCE | | ACQ TIMING | | |
| | Filter Choice | None | Freq | 256 | |
| | | | Phase | 256 | |
| | | | Freq DIR | A/P | |
| | | | NEX | 1.00 | |
| - 4 | | | Phase FOV | 1.00 | - 4 |
| SPGR | | | Auto Shim | Auto | GR |
| SF | | | Phase Correction | No | AX 3D SPGR |
| AX 3D | GATING/TRIGGER | | USER CVS | | X 3 |
| A | Auto Trigger Type | Off | User CV23 | 100.00 | A |
| | FMRI | | MULTI-PHASE | | |
| | PSD Trigger | Internal | # of Acquisition | 0 | |
| | Slice Order | Interleaved | Seperate Series | 0 | |
| | View Order | Bottom/Up | Mask Phase | 0 | |
| | # of Repetitions REST | 0 | Mask Pause | 0 | |
| | # of Repetitions ACTIVE | 0 | | | |
| | SAT | | ASSET | | |
| | Tag Type | None | Slice Acceleration Factor | 1.00 | |
| | | | Phase Acceleration Factor | 1.00 | |
| | TRICKS | | CONTRAST | | |
| | Pause On/Off | On | Contrast Yes/No | No | |
| | Auto Subtract | 0 | | | |
| | Auto SCIC | Off | | | |
| | MULTI-STATION | | | | |
| | Number of Stations | 0 | | | |
| | Station Number | 0 | | | |

| PATIENT POSITION Patient Entry Head First Gradient Mode ZOOM Patient Position Supine Imaging Mode 2D Coil Configuration HEAD Pulse Sequence Gradient Echo Plane AXIAL Imaging Options FC Series Description AX MPGR Acceleration Factor SCAN TIMING Flip Angle 20 FOV 22.0 | |
|--|---------|
| Patient Position Supine Imaging Mode 2D Coil Configuration HEAD Pulse Sequence Gradient Echo Plane AXIAL Imaging Options FC Series Description AX MPGR Acceleration Factor 1.00 SCAN TIMING SCAN RANGE | |
| Coil Configuration HEAD Pulse Sequence Gradient Echo Plane AXIAL Imaging Options FC Series Description AX MPGR Acceleration Factor 1.00 SCAN TIMING SCAN RANGE | |
| Plane AXIAL Imaging Options FC Series Description AX MPGR Acceleration Factor 1.00 SCAN TIMING SCAN RANGE | |
| Series Description AX MPGR Acceleration Factor 1.00 SCAN TIMING SCAN RANGE | |
| SCAN TIMING SCAN RANGE | ۱ |
| | ı |
| Flin Angle 20 FOV 22.0 | |
| The Angle | |
| TE 20.0 Slice Thickness 5.0 | |
| Number of Echoes 1 Slice Spacing 1.0 | |
| TR 600.0 | |
| Receiver Bandwidth 20.83 | |
| IMAGE ENHANCE ACQ TIMING | |
| Filter Choice None Freq 256 | |
| Phase 192 | |
| Freq DIR A/P | |
| NEX 2.00 | |
| Phase FOV 0.75 | ~ |
| Auto Shim Auto | PGF |
| Auto Shim Auto Phase Correction No | AX MPGR |
| GATING/TRIGGER FMRI | 3 |
| Auto Trigger Type Off PSD Trigger Internal | |
| Slice Order Interleaved | |
| View Order Bottom/Up | |
| # of Repetitions REST 0 | |
| # of Repetitions ACTIVE 0 | |
| MULTI-PHASE SAT | |
| # of Acquisition 0 Tag Type None | |
| Seperate Series 0 | |
| Mask Phase 0 | |
| Mask Pause 0 | |
| ASSET | |
| Slice Acceleration Factor 1.00 Pause On/Off On | |
| Phase Acceleration Factor 1.00 Auto Subtract 0 | |
| Auto SCIC Off | |
| CONTRAST MULTI-STATION | |
| Contrast Yes/No No Number of Stations 0 | |
| Station Number 0 | |

| | ГІ | otocol: STN POST OP 8PAR | KEINI 9 | | |
|--------------|-------------------------|--------------------------|---------------------------|----------------------|----------------------|
| | PATIENT POSITION | | IMAGING PARAMETERS | | |
| | Patient Entry | Head First | Gradient Mode | WHOLE | |
| | Patient Position | Supine | Imaging Mode | 3D | |
| | Coil Configuration | HEAD | Pulse Sequence | SPGR | |
| | Plane | AXIAL | Imaging Options | EDR, Fast, IrP, ZIP2 | |
| | Series Description | OPTION AX 3D STEALTH | Acceleration Factor | 1.00 | |
| | SCAN TIMING | | SCAN RANGE | | |
| | Flip Angle | 15 | FOV | 30.0 | |
| | TE | Min Full | Slice Thickness | 2.0 | |
| | TI | 500 | Location per Slab | 90 | |
| | Receiver Bandwidth | 16.67 | Overlap Locations | 0 | |
| | IMAGE ENHANCE | | ACQ TIMING | | |
| | Filter Choice | None | Freq | 256 | |
| | | | Phase | 256 | |
| | | | Freq DIR | A/P | |
| | | | NEX | 1.00 | |
| 픋 | | | # of Acq. Before Pause | 0 | 王 |
| STEALTH | | | Phase FOV | 1.00 | ΞAΓ |
| ST | | | Auto Shim | Auto | ST |
| 3D | | | Phase Correction | No | 3D |
| OPTION AX 3D | GATING/TRIGGER | | USER CVS | | Ι¥ |
| ō | Auto Trigger Type | Off | User CV23 | 100.00 | ō |
| OPT | FMRI | | MULTI-PHASE | | OPTION AX 3D STEALTH |
| | PSD Trigger | Internal | # of Acquisition | 0 | |
| | Slice Order | Interleaved | Seperate Series | 0 | |
| | View Order | Bottom/Up | Mask Phase | 0 | |
| | # of Repetitions REST | 0 | Mask Pause | 0 | |
| | # of Repetitions ACTIVE | 0 | | | |
| | SAT | | ASSET | | |
| | Tag Type | None | Slice Acceleration Factor | 1.00 | |
| | | | Phase Acceleration Factor | 1.00 | |
| | TRICKS | | CONTRAST | | |
| | Pause On/Off | On | Contrast Yes/No | No | |
| | Auto Subtract | 0 | | | |
| | Auto SCIC | Off | | | |
| | MULTI-STATION | | | | |
| | Number of Stations | 0 | | | |
| | Station Number | 0 | | | |