Puppet Puppet Agent Timer Module

RHEL 8 / 9 / 10 - custom OpenVox/Puppet module documentation

Purpose: Install and enable a business-hours-aware systemd timer for Puppet agent runs.

Module layout

```
custom/
  manifests/puppet_timer.pp
  functions/source_candidates.pp
  files/puppet_timer/ces-puppet-agent-run.service
  files/puppet_timer/ces-puppet-agent-run.timer
```

Configuration

```
include custom::puppet_timer
```

Behavior and safety: Puppet manages the service and timer units through the standard source-candidate order. Unit changes trigger systemctl daemon-reload and refresh the enabled timer.

Supported platform: Red Hat Enterprise Linux 8, 9, and 10. Generated from the repository sources; rerun **tools/generate_custom_module_docs.ps1** after code changes.

Puppet Agent Timer

custom/manifests/puppet_timer.pp

```
# @summary
#   Runs Puppet on a business-hours-aware systemd timer.
class custom::puppet_timer {
  if $facts['os']['family'] != 'RedHat' {
    fail('custom::puppet_timer supports only Red Hat family operating systems')
  }

  case $facts['os']['release']['major'] {
    '8', '9', '10': { }
    default: {
      fail('custom::puppet_timer supports RHEL major versions 8, 9, and 10 only')
    }
  }

  file { 'custom systemd unit directory':
    ensure => directory,
    path   => '/etc/systemd/system',
    owner  => 'root',
    group  => 'root',
    mode   => '0755',
  }

  file { 'custom Puppet agent service unit':
    ensure       => file,
    path         => '/etc/systemd/system/ces-puppet-agent-run.service',
    owner        => 'root',
    group        => 'root',
    mode         => '0644',
    source       => custom::source_candidates('puppet:///modules/custom/puppet_timer/ces-puppet-agent-run.service'),
    sourceselect => 'first',
    require      => File['custom systemd unit directory'],
    notify       => Exec['reload custom systemd units'],
  }

  file { 'custom Puppet agent timer unit':
    ensure       => file,
    path         => '/etc/systemd/system/ces-puppet-agent-run.timer',
    owner        => 'root',
    group        => 'root',
    mode         => '0644',
    source       => custom::source_candidates('puppet:///modules/custom/puppet_timer/ces-puppet-agent-run.timer'),
    sourceselect => 'first',
    require      => File['custom systemd unit directory'],
    notify       => Exec['reload custom systemd units'],
  }

  exec { 'reload custom systemd units':
    command     => '/usr/bin/systemctl daemon-reload',
    refreshonly => true,
    notify      => Service['ces-puppet-agent-run.timer'],
  }

  service { 'ces-puppet-agent-run.timer':
    ensure  => running,
    enable  => true,
    require => Exec['reload custom systemd units'],
  }
}
```

```
# @summary
#   Returns ordered source candidates for a custom module file.
#
# @param default_source
#   Default puppet:/// source URI. Site-specific files use suffixes beside it.
function custom::source_candidates(String[1] $default_source) >> Array[String] {
  $hostname = $facts['networking']['hostname']
  $network = $trusted['extensions']['pp_network']
  $project = $trusted['extensions']['pp_project']
  $role = $trusted['extensions']['pp_role']

  $hostname_sources = $hostname ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${hostname}"],
  }
  $network_sources = $network ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${network}"],
  }
  $project_sources = $project ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${project}"],
  }
  $role_sources = $role ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${role}"],
  }

  $hostname_sources +
    $network_sources +
    $project_sources +
    $role_sources +
    [$default_source]
}
```

Puppet Agent Timer

custom/files/puppet_timer/ces-puppet-agent-run.service

```
# Managed by CES Puppet.
# Manual changes will be replaced.
[Unit]
Description=Run the Puppet agent
Documentation=man:puppet-agent(8)

[Service]
Type=oneshot
ExecStart=/opt/puppetlabs/bin/puppet agent -t
```

Puppet Agent Timer

custom/files/puppet_timer/ces-puppet-agent-run.timer

```
# Managed by CES Puppet.
# Manual changes will be replaced.
[Unit]
Description=Run the Puppet agent on the CES schedule

[Timer]
# Monday-Friday: every 10 minutes from 06:00 through 15:00.
OnCalendar=Mon..Fri *-*-* 06..14:00,10,20,30,40,50
OnCalendar=Mon..Fri *-*-* 15:00
# Monday-Friday: every 30 minutes from 15:01 through 20:31.
OnCalendar=Mon..Fri *-*-* 15..20:01,31
# Monday-Friday: every two hours from 21:01 through 05:59.
OnCalendar=Mon..Fri *-*-* 21,23:01
OnCalendar=Mon..Fri *-*-* 01,03,05:01
# Saturday-Sunday: every two hours.
OnCalendar=Sat,Sun *-*-* 01,03,05,07,09,11,13,15,17,19,21,23:01
AccuracySec=1s
Persistent=true
Unit=ces-puppet-agent-run.service

[Install]
WantedBy=timers.target
```