Puppet Dconf Support Module

RHEL 8 / 9 / 10 - custom OpenVox/Puppet module documentation

Purpose: Provide the shared dconf directories and refresh command used by graphical custom classes.

Module layout

```
custom/
  manifests/dconf.pp
```

Configuration

```
# Normally contained automatically by branding or
classification_banner.
contain custom::dconf
```

Behavior and safety: The support class creates the GDM and local databases and their lock directories. Its refresh-only exec runs dconf update after subscribing resources notify it.

Supported platform: Red Hat Enterprise Linux 8, 9, and 10. Generated from the repository sources; rerun **tools/generate_custom_module_docs.ps1** after code changes.

Dconf Support

custom/manifests/dconf.pp

```
# @summary
#   Creates the shared dconf directories and refresh command used by this module.
class custom::dconf {
  file { 'custom dconf directory':
    ensure => directory,
    path   => '/etc/dconf',
  }

  file { 'custom dconf database directory':
    ensure => directory,
    path   => '/etc/dconf/db',
  }

  file { 'custom gdm dconf directory':
    ensure => directory,
    path   => '/etc/dconf/db/gdm.d',
  }

  file { 'custom gdm dconf locks directory':
    ensure => directory,
    path   => '/etc/dconf/db/gdm.d/locks',
  }

  file { 'custom local dconf directory':
    ensure => directory,
    path   => '/etc/dconf/db/local.d',
  }

  file { 'custom local dconf locks directory':
    ensure => directory,
    path   => '/etc/dconf/db/local.d/locks',
  }

  exec { 'update custom dconf databases':
    command     => '/usr/bin/dconf update',
    refreshonly => true,
    require     => [
      File['custom gdm dconf directory'],
      File['custom gdm dconf locks directory'],
      File['custom local dconf directory'],
      File['custom local dconf locks directory'],
    ],
  }
}
```