Puppet Log Rotation Module

RHEL 8 / 9 / 10 - custom OpenVox/Puppet module documentation

Purpose: Manage the main logrotate configuration and the rsyslog rotation policy.

Module layout

```
custom/
  manifests/logrotate.pp
  functions/source_candidates.pp
  files/etc/logrotate.conf
  files/etc/logrotate.d/rsyslog
```

Configuration

```
include custom::logrotate
```

Behavior and safety: Both files use the standard custom source-candidate order, allowing hostname, network, project, and role variants while retaining common defaults.

Supported platform: Red Hat Enterprise Linux 8, 9, and 10. Generated from the repository sources; rerun **tools/generate_custom_module_docs.ps1** after code changes.

Log Rotation

custom/manifests/logrotate.pp

```
# @summary
#   Manages the main logrotate configuration and the rsyslog rotation policy.
class custom::logrotate {
  if $facts['os']['family'] != 'RedHat' {
    fail('custom::logrotate supports only Red Hat family operating systems')
  }

  case $facts['os']['release']['major'] {
    '8', '9', '10': { }
    default: {
      fail('custom::logrotate supports RHEL major versions 8, 9, and 10 only')
    }
  }

  file { 'custom logrotate configuration directory':
    ensure => directory,
    path   => '/etc/logrotate.d',
    owner  => 'root',
    group  => 'root',
    mode   => '0755',
  }

  file { 'custom /etc/logrotate.conf':
    ensure       => file,
    path         => '/etc/logrotate.conf',
    owner        => 'root',
    group        => 'root',
    mode         => '0644',
    source       => custom::source_candidates('puppet:///modules/custom/etc/logrotate.conf'),
    sourceselect => 'first',
  }

  file { 'custom /etc/logrotate.d/rsyslog':
    ensure       => file,
    path         => '/etc/logrotate.d/rsyslog',
    owner        => 'root',
    group        => 'root',
    mode         => '0644',
    source       => custom::source_candidates('puppet:///modules/custom/etc/logrotate.d/rsyslog'),
    sourceselect => 'first',
    require      => File['custom logrotate configuration directory'],
  }
}
```

```
# @summary
#   Returns ordered source candidates for a custom module file.
#
# @param default_source
#   Default puppet:/// source URI. Site-specific files use suffixes beside it.
function custom::source_candidates(String[1] $default_source) >> Array[String] {
  $hostname = $facts['networking']['hostname']
  $network = $trusted['extensions']['pp_network']
  $project = $trusted['extensions']['pp_project']
  $role = $trusted['extensions']['pp_role']

  $hostname_sources = $hostname ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${hostname}"],
  }
  $network_sources = $network ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${network}"],
  }
  $project_sources = $project ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${project}"],
  }
  $role_sources = $role ? {
    undef   => [],
    ''      => [],
    default => ["${default_source}.${role}"],
  }

  $hostname_sources +
    $network_sources +
    $project_sources +
    $role_sources +
    [$default_source]
}
```

Log Rotation

custom/files/etc/logrotate.conf

```
# Managed by CES Puppet.
# Manual changes will be replaced.

monthly
rotate 4
create
compress
dateext
include /etc/logrotate.d
```

Log Rotation

custom/files/etc/logrotate.d/rsyslog

```
# Managed by CES Puppet.
# Manual changes will be replaced.

/var/log/cron
/var/log/maillog
/var/log/messages
/var/log/secure
/var/log/spooler
/var/log/sudo.log
{
    missingok
    sharedscripts
    postrotate
        /usr/bin/systemctl -s HUP kill rsyslog.service >/dev/null 2>&1 || true
    endscript
}
```