Puppet RPM Installation Module

RHEL 8 / 9 / 10 - custom OpenVox/Puppet module documentation

Purpose: Install and remove package names supplied through Hiera.

Module layout

```
custom/
  manifests/rpm_install.pp
  data/common.yaml
```

Configuration

```
include custom::rpm_install

custom::rpm_install::rpms:
  - package-one
custom::rpm_install::xrpms:
  - unwanted-package
```

Behavior and safety: The rpms and xrpms arrays use unique Hiera merges. Puppet rejects any package present in both lists, installs requested packages, and removes explicitly unwanted packages.

Supported platform: Red Hat Enterprise Linux 8, 9, and 10. Generated from the repository sources; rerun **tools/generate_custom_module_docs.ps1** after code changes.

RPM Installation

custom/manifests/rpm_install.pp

```
# @summary
#   Installs RPM packages supplied through Hiera.
#
# @param rpms
#   Package names to install. Hiera merges this array uniquely across all
#   hierarchy levels.
# @param xrpms
#   Package names to remove. Hiera merges this array uniquely across all
#   hierarchy levels.
class custom::rpm_install (
  Array[String[1]] $rpms = [],
  Array[String[1]] $xrpms = [],
) {
  if $facts['os']['family'] != 'RedHat' {
    fail('custom::rpm_install supports only Red Hat family operating systems')
  }

  $conflicting_rpms = $rpms.filter |String[1] $rpm| {
    $rpm in $xrpms
  }
  if $conflicting_rpms != [] {
    fail("custom::rpm_install cannot install and remove the same packages: ${conflicting_rpms.join(', ')}")
  }

  $rpms.each |String[1] $rpm| {
    package { $rpm:
      ensure => installed,
    }
  }

  $xrpms.each |String[1] $rpm| {
    package { $rpm:
      ensure => absent,
    }
  }
}
```

```
---
lookup_options:
  custom::rpm_install::rpms:
    merge:
      strategy: unique
  custom::rpm_install::xrpms:
    merge:
      strategy: unique

custom::rpm_install::rpms: []
custom::rpm_install::xrpms: []
```