


Variant calling




Chris Miller

Some slides adapted from Dave Larson, Aaron Quinlan, Sam Peters, and Alex Paul

Small Variant Calling




Our data



Mapping


Genome Reference Sequence




- Single-end reads can be longer, less unique depending on sequence context
- Paired-end reads can span repetitive regions, provide additional information
- Mapping has gotten quite fast, <24 hours for 120 Gbp of sequence
- Split-read alignments are the norm (BWA mem)




Duplication



Duplication




Duplication




Overlapping reads



Overlapping reads



Overlapping reads



Overlapping reads



Every aspect of this process is fraught with error

- Base calling is not perfect: *0.5% error on average*
- Mapping is not perfect: *the reads are short*
- The reference sequence is not perfect

We have a little help

- Some uncertainty is encapsulated in quality scores
 - the rate at which the data is expected to be wrong
- Each base call (ACTGN) comes with a quality
 - Phred-scaled ($-10 * \log_{10}$ of quality)
 - A base call with quality of 20 is wrong 1 out of every 100 times.
- Read mapping has quality too
 - These are also Phred-scaled

Phred quality score calculation

$$Q = -10 \cdot \log_{10}(P_{\text{err}})$$

Error probability (P_{err})	$\log_{10}(P_{\text{err}})$	Phred quality score
1	0	0
0.1	-1	10
0.01	-2	20
0.001	-3	30
0.0001	-4	40

Goals of a Variant Caller


- Sensitive detect mutations
- Precisely detect mutations
 - Confounded by the error we just talked about
 - FDR must be very low as we're looking across a very large space!

Goals of a Variant Caller


- Sensitive detect mutations
- Precisely detect mutations
 - Confounded by the error we just talked about
 - FDR must be very low as we're looking across a very large space!
 - **An FDR of 0.001 = 3.2 million false positives!**

Homozygous for the "C" allele

Improper
(too far/too
close) pairs




Sequencing errors fall out as noise (most of the time)




It is not always so easy

Random versus systematic error



Pileups of many differences from paralogy



RESEARCH ARTICLE | OPEN ACCESS

FLAGS, frequently mutated genes in public exomes

Casper Shyr, Maja Tarallo-Graovac, Michael Gottlieb, Jessica JY Lee, Clara van Karnebeek and Wyeth W Wasserman

BMC Medical Genomics 2014 7:64 | DOI: 10.1186/s12920-014-0064-y | © Shyr et al.; licensee BioMed Central Ltd. 2014

Received: 16 June 2014 | Accepted: 24 October 2014 | Published: 3 December 2014

Open Peer Review reports




Calling INDELs is *much* harder than SNPs




Begin Exercise

Germline SNV and Indel Calling

Call Genotypes Using GATK HaplotypeCaller




Call Genotypes Using GATK HaplotypeCaller




Indel "realignment"



Call Genotypes Using GATK HaplotypeCaller




Main steps for Germline Single-Sample Data




Other Germline Variant callers

- Freebayes: lighter weight, faster
- DeepVariant: Neural-network based caller from Google ML




DeepVariant




<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6450397/>

<https://www.nature.com/articles/nbt.4235>




DeepVariant




<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6450397/>

<https://www.nature.com/articles/nbt.4235>




DeepVariant




<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6450397/>

<https://www.nature.com/articles/nbt.4235>




DeepVariant



<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6450397/>

<https://www.nature.com/articles/nbt.4235>



DeepVariant

Here are 3 examples that we would consider canonical easy-to-classify loci, and that DeepVariant calls confidently and correctly:



The variant above is a "2", which means both chromosomes match the variant allele, so this locus represents a homozygous alternate locus.



DeepVariant correctly classifies the variant above as a "1", which means that one of the two alleles matches the variant allele, i.e. it is heterozygous.

