





Cold  
Spring  
Harbor  
Laboratory

# RNA-Seq Module 3

## Abundance Estimation and Differential Expression

Felicia Gomez, Charlz Jerold, Obi Griffith, Malachi Griffith,  
My Hoang, Mariam Khanfar, Chris Miller, Kartik Singhal, Jennie Yao  
Advanced Sequencing Technologies & Bioinformatics Analysis November 10-21, 2025



 Washington University in St. Louis  
SCHOOL OF MEDICINE

# Alternatives to FPKM

- Raw read counts for differential expression analysis
  - Assign reads/fragments to defined genes/transcripts, get “raw counts”
    - Transcript structures could still be defined by something like Stringtie

- HTSeq (htseq-count)





- <https://htseq.readthedocs.io/>

```
htseq-count --mode intersection-strict --stranded no --minqual 1 --type exon --idattr transcript_id  
accepted_hits.sam chr22.gff > transcript_read_counts_table.tsv
```

- Caveats of ‘transcript’ analysis by htseq-count:

- Designed for genes - ambiguous reads from overlapping transcripts may not be handled!
  - <http://seqanswers.com/forums/showthread.php?t=18068>

# HTSeq-count basically counts reads supporting a feature (exon, gene) by assessing overlapping coordinates

	union	intersection_strict	intersection_nonempty
	gene_A	gene_A	gene_A
	gene_A	no_feature	gene_A
	gene_A	no_feature	gene_A
	gene_A	gene_A	gene_A
	gene_A	gene_A	gene_A
	ambiguous	gene_A	gene_A
	ambiguous	ambiguous	ambiguous

Note, if gene\_A and gene\_B on opposite strands, sequence data is stranded, and correct HTSeq parameter set then this read may not be ambiguous

Whether a read is counted depends on the nature of overlap and “mode” selected

We are on a Coffee Break & Networking  
Session