

AI as a Research Assistant

Presented By

Obi Griffith

Date


May 16-21, 2026

What is Artificial Intelligence?

- Artificial Intelligence (AI) is the theory and development of computer systems able to perform tasks that normally require human intelligence, such as visual perception, speech recognition, decision-making, and other complex tasks

Examples of advanced AI appearing throughout society

- Manufacturing robots
- Automated financial investing
- Social media monitoring
- Conversational bots
 - ChatGPT, Claude, Gemini, etc.
- Smart assistants
- Agentic coding




Many others...

Applications in biomedical field far too many to list

- Medical image analysis
 - MRI segmentation
 - Histopathological cancer classification
 - Mammographic lesion detection
- Protein structure prediction
- Genome analysis
 - Gene expression inference
 - Enhancer prediction
 - Variant pathogenicity prediction
- Text mining
- Physician note taking

AI has gone through several eras



What is Generative AI?

Generative AI refers to models that create new content (text, images, code, audio, video) rather than only classifying or predicting from existing data, typically built on large neural networks trained on massive unlabeled datasets and controllable through natural language.

- Shifts from "predict" to "produce"
- One foundation model replaces many task-specific ones.
- Self-supervised training on internet-scale unlabeled data
- Emergent capabilities appear at scale

slido

Share your experiences with generative AI

Join at
slido.com
#4153 195



Survey Q1 - In the past 12 months how often have you used AI tools?

- Every day, all day
- A few times a day
- A few times a week
- Rarely
- Never

Survey Q2 – What AI technologies/apps/approaches have you tried?

- Name three AI tools, services, or techniques you have found useful recently.

Survey Q3 – What have you used AI for?

- Personal uses (trip planning, taxes, writing birthday cards, etc., etc.)
- Scientific writing (grants, papers, progress reports, etc.)
- Coding (scripts, pipelines, data visualization)
- Office productivity (responding to emails, scheduling, organizing files, etc.)
- Original research (developing experiments, hypothesis, literature review, etc.)

Survey Q4 – How should researchers approach the use of AI??

- AI should be embraced as rapidly as possible, it's our only hope of overcoming the bottlenecks of basic and translational research.
- AI should be adopted cautiously, only to enhance human experts, and only while following strict guidelines for use.
- AI should not be used for research, the dangers outweigh the benefits
- The cat is out of the bag. We have no choice but to accept that all knowledge will be influenced by AI going forward, whether we like it or not.

Survey Q5 - Where are you on the abundance → apocalypse spectrum?

- I will be interacting with an AI agent that is smarter than me, transforming the way I work.
- AI will continue to improve modestly and will have a substantial impact on my work.
- AI will remain little more than a glorified “next word predictor”, the hype will subside, and all our problems will remain.
- Despite its valuable use cases, disruptions related to AI will lead to major problems.
- AI will lead to the total collapse of civilization as we know it.

Survey Q6 - Share an interesting use case, thought, question, or concern you have relating to AI

- Anything you want to add that we haven't covered so far?

How can you use AI as a research assistant?


Some successes and failures from recent experiences

Task: We have developed a machine learning classifier in R that accurately predicts which neoantigens will be prioritized by our immunotherapy tumor board (ITB) but now we want to incorporate into our python package pVACtools



Jennie Yao


Success! R and Python versions have equivalent performance



R model performance:

- 88.89% sensitivity
- 86.84% specificity
- 0.936 AUC

actual_values	rfd_s_pred	
	Reject	Accept
Reject	198	30
Accept	9	72



Python model test set performance:

- 90.12% sensitivity
- 85.52% specificity
- 0.932 AUC

Python Test set Confusion Matrix

This confusion matrix for the Python model shows the following counts: 195 true rejections, 30 false rejections, 8 false acceptances, and 73 true acceptances. The axes are labeled 'Actual Values' and 'Predicted Labels'.

Actual Values	Predicted Labels	
	Predicted Reject	Predicted Accept
Actual Reject	195	30
Actual Accept	8	73

Task: We need a catchy acronym for a new single cell DLBCL classification system

Create an acronym for a DLBCL Classification System

We have developed a classification system for Diffuse large B cell lymphoma (DLBCL) based on single cell gene expression patterns of the lymphoma microenvironment (LME). We define three DLBCL classifications or LME archetypes: (1) fibroblast/macrophage (FMAC), that were characterized by high frequencies of macrophage subsets and fibroblast subsets including cancer associated fibroblasts, (2) T-effector/exhausted (TEX), characterized by high frequencies of effector and exhausted CD8 T-cells and and (3) lymph-node (LN), characterized by lymph-node structural cell types, antigen presenting cells, and naïve and memory T-cells. These archetypes are important for understanding DLBCL biology and for selection of patients most likely to benefit from cellular therapy (e.g., CAR T cell therapy). Can you provide options for a catchy name to describe this classification system?

Success! Create an acronym for a DLBCL Classification System

Updated saved memory

Here are some catchy name options for your DLBCL classification system:

1. **LymphoMap** (Lymphoma Microenvironment Archetype Profiling)
2. **DLBCL-MicroNet** (Diffuse Large B-cell Lymphoma Microenvironment Network)
3. **ArchetypeLymph** (Lymphoma Archetype Classifier)
4. **LymphoSignature** (Lymphoma Microenvironment Signature Classification)
5. **MicroClass-DLBCL** (Microenvironmental Classification System for DLBCL)
6. **DLBCL-Scape** (DLBCL Single-cell Archetype Explorer)
7. **CAR-T Map** (Classification of Lymphoma Archetypes for Response to Therapy)
8. **MicroDLBCL** (Microenvironment-Based DLBCL Archotyping)
9. **LME-Trio** (Lymphoma Microenvironment Triad Classification)
10. **DLBCL-TAP** (Tumor Archetype Profiling for DLBCL)

Xubin Li*, Kartik Singhal*, Qing Deng*
et al. Large B cell lymphoma
microenvironment archetype profiles
(LymphoMAPs). *Cancer Cell*. 2025.
43(7):1347-1364

Task: I need to figure out how to load a defined list of barcodes in Loupe

Learn how to use a piece of bioinformatics software

can you import a defined list of cell barcodes to visualize in the loupe browser?

Thought for 2m 32s >

Yes. Loupe Browser lets you bring in an external list of barcodes and display those cells just like any other cluster. The most reliable workflow is to load the list as a new **"Category"** (i.e., a set of clusters):

Step	What to do
1. Prepare a CSV	Make a text file with Unix line endings. Header must start with "Barcode". Give each barcode a label in a second column if you want multiple clusters. <pre>csv
Barcode,MySubset
AAACCTGGTGCAACGA-1,MySubset
AAAGATGTCTCGGACG-1,MySubset
_
</pre>
2. Import in Loupe	Open the <code>.cloupe</code> file → Categories panel (right-hand side) → three-dot menu → Import Categories. Point to the CSV. A new category appears; cells in your list are grouped under the label(s) you supplied. 10x Genomics 10X Genomics
3. Visualize & analyse	Select the new category in the drop-down to colour the UMAP/t-SNE, run differential expression, save selections, etc. You can export the barcodes again at any time with Export from the same menu. 10X Genomics

Success! After clarification the bot tells me where to find the (hidden option)

I'm looking at Loupe Browser version 8.1.2 and can't find the Categories Panel

Thought for 1m 47s >

Since v7 (and therefore 8.1.x) Loupe's UI was reorganized: the old **Categories** panel is now folded into the **Clusters mode** on the left-hand *Mode Selector* strip.

How to get it back

1. Reveal the Mode Selector

- If you see only the scatterplot, click the small $\cdot/\llcorner$ arrow at the extreme left to expand the side bar.

10x Genomics

2. Switch to Clusters mode

- Click the icon that looks like a set of coloured squares (hover tooltip: "Clusters").
- A list of cluster *groups* appears (Graph-Based, K-means, any custom groups, etc.). This list functionally replaces the old Categories panel.

10x Genomics

3. Import your barcode list as a new group

- Scroll to the bottom of the Clusters list.
- Click  (**upload**) just to the right of + **Create a new group**.
- Choose your two-column CSV (header row required, first column = barcodes, second column = group label). After import the new group shows up alongside the others and you can colour, split-view, or run differential expression exactly as before.

10x Genomics

Task: A colleague has proposed a collaboration using whole-exome-sequencing to investigate the mutational landscape of multiglandular parathyroid disease (MGD)

What is already known about the mutational landscape of this disease?

Google NotebookLM allows queries of source material, and auto-generates audio overview (“podcast”), Study Guide, FAQ and more...

The screenshot displays the Google NotebookLM interface. The top bar shows the document title "Genomic Insights into Atypical Parathyroid Tumors" and options for "Share", "Settings", and a user profile. The interface is divided into three main panels:

- Sources:** A list of uploaded documents and links, including "1-s2.0-S0039606014005510-main...", "1-s2.0-S2451965024000085-main...", "72_5357.pdf", "All notes 5/2/2025", "International Journal of Genomics - ...", "Whole-exome sequencing of atypic...", "dgae441.pdf", "dgae506.pdf", "erc-ERC-18-0304.pdf", "fendo-12-631680.pdf", and "fendo-14-1180211.pdf".
- Chat:** The main content area showing the document title "Genomic Insights into Atypical Parathyroid Tumors" and a summary of the text: "These texts collectively examine the molecular characteristics of parathyroid tumors, including adenomas, atypical adenomas, and carcinomas. They explore genetic alterations, such as mutations (somatic and germline) and copy number variations, in genes like MEN1, CDCT3, and those in the PI3K/AKT/mTOR and Wnt signaling pathways. The sources employ genomic sequencing techniques like whole-exome and next-generation sequencing to identify these changes and link them to the clinical and pathological features of the tumors, aiming to improve diagnosis, prognosis, and treatment strategies for parathyroid disease. Some studies specifically focus on the distinct genetic landscapes of different parathyroid tumor types and investigate potential biomarkers like WT1." Below the text are buttons for "Save to note", "Add note", "Audio Overview", and "Mind Map".
- Studio:** A panel on the right showing the "Audio Overview" section with a play button and a progress bar. Below it are buttons for "Study guide", "Briefing doc", "FAQ", and "Timeline". The "Notes" section lists generated content: "Genetic Alterations in Parathyroid Tumors Detailed Briefing Document: Genetic Alterations in Parathyroid Tumors Date: Ma...", "Parathyroid Tumor Genetics: Syndromes... Click to open the Mind Map", "Parathyroid Tumor Genetics Research... Here is a detailed timeline and cast of characters based on the provided sources...", and "Genetics of Parathyroid Tumors: MEN1... Briefing Document: Genetic Alterations of..."

Success! Summarizes the exome sequencing studies performed to date

A summary of the WES studies identified in the sources is provided in the table below:

Study (First Author, Year)	Number of Samples with WES	Sample/Disease Types Studied with WES	Matched Normal/Blood Used?	Key Comparison/Focus
Romero Arenas et al. (2014) 4	14	4 MEN1 HPT (Parathyroid Tissue), 10 Sporadic HPT (Parathyroid Tissue)	Yes (Blood) 14	MEN1 vs. Sporadic HPT mutation patterns 4
Cromer et al. (2012) 1	8	8 Sporadic Parathyroid Adenomas (Tumor)	Yes (Matched constitutional DNA) 15 ...	Identify somatic mutations in sporadic adenomas (Discovery cohort for 185 validation samples studied with other methods) 1 ...
Newey et al. (2012) 2	16	16 Sporadic Parathyroid Adenomas (Tumor)	Yes (Leukocyte DNA) 16	Identify genetic abnormalities in sporadic adenomas (Discovery set for 24 validation samples studied with other methods) 2

Other questions:

- Define the key genetic drivers of parathyroid tumors
- Summarize what is known about the genetics of multiglandular parathyroid disease (MGD)

Success! Summarizes what is known about the genetics of multiglandular parathyroid disease (MGD) and identifies gaps

In summary, sequencing and molecular studies have illuminated the genetic basis of hereditary MGD (primarily MEN1, driven by MEN1 biallelic inactivation and other genes like TP53 and GCM2), and have begun to identify distinct candidate drivers in THPT hyperplasia (PRKDC, TBX20, NOX3, and specific CNVs, notably without MEN1 or CCND1 mutations). However, the specific somatic molecular drivers and genetic landscape of sporadic MGD, particularly sporadic hyperplasia, are less comprehensively defined in the provided sources, which highlight its likely genetic heterogeneity and the limited studies comparing it directly to sporadic single-gland adenomas

The shared interaction using this notebook really helped guide the new collaboration

More successes from Obi's AI history

- Get randomforest internal OOB performance from python scikit-learn
- Write short, informative figure title for caption text
- grep for one string OR another string
- Create grant figures, reports with Claude Project + Claude Code
- Write a letter of support for a scientific proposal
- Configure Apache2 for HTTPS
- Explain cytogenetic nomenclature (e.g., ISCN) to specify a reciprocal translocation?

Task: I need to manipulate a sequence file
(e.g.,. Setting up input for primer design)


Simple sequence manipulation

Give me this sequence with a newline after every 100 characters

```
AGCACAGTTATTCTGTCATTGGCATTAAATTCTAGTAGGGTCTGTTTCCT
TAGCTATAGCTAGTGTCTTTTTGGGAAATAATGCCAAAACAGTTGATG
TTTCGTCAGCATCATACACTTGTTCATCATCAGATTTTCATCAGCAAT
GATGTTCAACTTATTAATGAATTGCTCTACTTCTTTGTGATCAGCAGAT
GCTTTATCATCAGAAATCTTTAAAAATTAATGTCATGCATTTTCTTAA
ATTTCTGCATCTACCCTCTTGAATTTTCACAGTTCACCTTTAGTTTTAG
TTCATTGTGGTAGATCTTTGTTTCATTATCAGCTTATTAAGTGGCATAT
GTTCACTGCAACACTGATGAATCTACTACTTCAATACATGATTAAGATC
TTCCTTTTTAGTTTTATTAAGTTTTTAAAAAAGGTTTTTCATTAACCTC
TGTTCACTACTTTCCAAATAGAACATCAATAGTCTATCCTTTTTTTTTCT
CCAGGTTATATATGGTGGTCATTCCAACACTATACTCTTCTGTAAGATG
TTTCACACTTACACCACTGTCCACTTAGTCTAACACTTTGACTTTCTGT
GCTATAGATAAACATAAATGCTTTAACTTTTCCTTATTTCTGTTACCCA
CAGGGGTATCCATAGATTTTCTTGATTTTTCAACAATAACTTTATACC
ACAGAGCAGAGAATAAGCAAAAGCACCCAGTGAATAATGCACATAGG
TCTTGTTTCCATGCAGGGCATCATGGAACTGGCTCTTGGCATGTCA
AACCACACACTTGCCATTTTATTACTTGTTGTGGGTGTGCATGAGTA
```

Here's your sequence with a newline after every 100 characters:

```
css Copy Edit
AGCACAGTTATTCTGTCATTGGCATTAAATTCTAGTAGGGTCTGTTTCCTAGCTATAGCTAGTGTCTTTTTGGGAAATAA
TGCCAAAACAGTTGATGTTTCGTCAGCATCATACACTTGTTCATCATCAGATTTTCATCAGCAATGATGTTCAACTTAT
TAATGAATTGCTCTACTTCTTTGTGATCAGCAGATGCTTTATCATCAGAAATCTTTAAAAATTAATGTCATGCATTTTC
TTAAATTTCTGCATCTACCCTCTTGAATTTTCACAGTTCACCTTTAGTTTTAGTTTCATTGTTGGTAGATCTTTGTTTCATT
ATCAGCTTATTAAGTGGCATGTTCACTGCAACACTGATGAATCTACTACTTCAATACATGATTAAGATCTTCTTTTC
AGTTTTATTAAGTTTTTAAAAAAGGTTTTTCATTAACCTCTGTTCACTTTTCAAAATAGAACATCAATAGTCTATCCT
TTTTTTCTCCAGGTATATATGGTGGTCATTCCAACACTATACTCTTCTGTAAGATGTTTCACACTTACACCACTGTCC
ACTTAGTCTAACACTTTGACTTTCTGTCTATAGATAAACATAAATGCTTTAACTTTTCTTATTTCTGTTACCCACAGG
GGTATCCATAGATTTTCTGATATTTTCAACAATAACTTTATACCACAGCAGAGAATAAGCAAAAGCACCCAGTGAAT
AATGCACATAGGTCCTGTTTCCATGCAGGGCATCATGGAACTGGCTCTTGGCATGTCAAAACCACACACTTGCCATTT
ATTACTTGTGTGGGTGTGCATGAGTAGGGGAATCTTGGCATGTTTAAAAAGATACATCAGCTAAAGGGAATTTGG
AGGTCTCTTTTTTTCTTTGCGAAGCTAAATAACTGTAATGTGCATATGCATTTGGATGGTGATTTGTCTTTGTCA
TATGAGGTCAAGTGTGGAATTTTCTACTTGTGGTGTCTGTTGACACTCAGAAAGTTTCAGATTTTGGAGCCTTTTAG
```



Malachi Griffith

Something a little more complicated...

Give me the reverse complement of this sequence maintaining the "[]":

Give me the reverse complement of this sequence maintaining the "[]":

```
GGGATATTTGGGGCTCATGGTCATTGTCA[]TTGACACTCAGAAAGTTT
CAGATTTTGGAGCCTTTTAGATCGTGATTTT
TCAAATTAGTGATGCTCAACCTGTACTTTTTCAGCACAATTTAATGACTA
TCAATATCAAAGCCTGAATTTGTAAACCATT
TAGCTATACTTTCTTCCACTCAATCCACAGGAGAATCAAGAGCATAGC
CCTAGTGCTCATAGATTTTCTTTAAGTAAAGA
AAAGCAATGAGGGTAAATCAGGATCCTTGAGTTGATGGAATGTAGCTT
TCTCCCCTGGAATCCTATCATCCATACAAAAG
ATCTTTGTGTACTTTCCCAATTATGGAACCTTAAAGAATAAACTATCATAT
AGAATATGTGATTTGATGGAACATAAAAAG
CTTGTTTACCCTCAGACATCTCCTTCAATTACATACTCCTTGATGATA
TTACTATTAGAATTTGTCCTATGAGGTAATG
CAGTACAGCTCCCCTAAGAATCCTATTAATAATTTAAATATATTACCTGA
TG TAGTAGTTTCTTGGCTGCTATGGTAAAT
TACCAAAAATATGATGGCTTCAAACCTGCACACATTTATTCTCTTACATT
CTGGAGGTCAGAAATCTGAAATCAGTTTCAC
TTGGTCAAAAATCAAGGTGTTGGCATTGTCATGCTCCTTTTCAAGTGGCT
GTAGAGGACGATCTCCTTCCCTTGACCTTTCCAG
CATCTAGAGCTGTATTGCTTGATTTCTTGGCCCATGGCCCCTGCTTC
AATTTTAAAGCCACCTGTGTACCATCTTGCT
```

ChatGPT explains it's plan and gives a sensible looking result

To reverse complement the sequence while preserving the `[]` markers, we'll follow this approach:

Step-by-step plan:

1. Concatenate the sequence into one string, removing newlines.
2. Identify the position of the `[]` (i.e., where it splits the sequence).
3. Remove the `[]` and get the reverse complement of the full sequence.
4. Reinsert the `[]` at the correct mirrored position.

Step 1-2: Get position of `[]`

Original sequence before `[]` :

```
nginx
```

[Copy](#)[Edit](#)

```
GGGATATTTGGGGCTCATGGTCATTGTCA
```

That's 28 bases before `[]` .

ChatGPT explains it's plan and gives a sensible looking result

Step 3: Reverse complement the full sequence (without `[]`)

I'll reverse complement the full sequence, then determine where to place the `[]`.

Total sequence length (excluding `[]`) is 935 bases

Position of `[]` from start = 28

So, in the reverse complement, the `[]` goes after $935 - 28 = 907$ bases.

ChatGPT highlights the brackets in their new position, remembers we like 100 bases per line, and even asks if we'd like it in FASTA format!

✓ Final Result (with newline every 100 bases):

CSS

Copy

Edit

```
ATTAATCCTAAAAAATCACTGTTCTGAGATGTGGTAGGCTGAATAATGGTCCCCAAGATAACCAAGTACTTATCCTT
GGGAAATTTGTAACTTATATAGCAAAATGGACTTGCAGATGTAATTAATGGGAAGATTATCCTAAATTATGTAGATG
GGCCCTAAATGAAATCCAAATTGGGATGTAGAGAGAGATTTGATGCAGAAGAAGGCAATGTGACCACTGAAGCAAGATG
GTACACAGGTGGCTTTAAATTTGAAGCAGGGGCCATGGGCCAAGAAATACAACAAGCAATACAGCTCTAGATGCTGAAAA
GGTCAAGGAAGGAGATCGTCCTCTACAGCCACTGAAAGGAGCATGACAATGCCAACACCTTGATTTTGACCAAGTGAAAC
TGATTTTCAGATTTCTGACCTCCAGAATGTAAGAGAATAAATGTGTGCAGTTTGAAGCCATCATATTTTTGGTAATTTAC
CATAGCAGCCAAGGAACTACTACATCAGGTAATATATTAATTTTAATAGGATCTTAGGGGAGCTGACTGCATTACC
TCATAGGACAAATCTAATAGTAATATCATACAAGGAGTATGTAATTGAAGGAGATGTCTGAGGGTAAACAAGCTTTTTT
ATGTTCCATCAAATCACATATTCTATATGATAGTTTATTCTTTAAGTTCCATAATTGGGAAAGTACACAAAGATCTTTGT
ATGGATGATAGGATTCAGGGGAAGAAAGTACATTCATCAACTCAAGGATCCTATTTACCTCATTGCTTTTCTTTACT
TAAAGAAAATCTATGAGCACTAGGGCTATGCTCTTGATTCTCCTGTGGATTGAGTGGAAGAAAGTATAGCTAAATGGTTT
ACAAATTCAGGCTTTGATATTGATAGTCATTAATTTGTGCTAAAAAGTACAGGTGAGCATCACTAATTTGAAAATACAC
GATCTAAAAGGCTCCAAATCTGAACTTTCTGAGTGTCAA[]TGACAATGACCATGAGCCCCAAATATCCC
```


Let me know if you'd like it saved in a file or converted to FASTA format!

Failure! There's just one problem ...

As final QC check, let's just make sure our sequence still matches the original

Query	241	AGCAATGAGGGTAAATCAGGATCCTTGAGTTGATGGAATGTAGCTTTCTTCCCTGGAAT	300
Sbjct	791	AGCAATGAGGGTAAAT-AGGATCCTTGAGTTGATGGAATGTAGCTTTCTTCCCTGGAAT	733
Query	301	CCTATCATCCATACAAAGATCTTTGTGACTTTCCCAATTATGGAACCTAAAGAATAAAC	360
Sbjct	732	CCTATCATCCATACAAAGATCTTTGTGACTTTCCCAATTATGGAACCTAAAGAATAAAC	673
Query	361	TATCATATAGAATATGTGATTGTGGAACATAAAAA-GCTTGTTTACCCTCAGACATCT	419
Sbjct	672	TATCATATAGAATATGTGATTGTGGAACATAAAAAAGCTTGTTTACCCTCAGACATCT	613
Query	420	CCTTCAATTACATACTCCTTGATGATATTACTATTAGAATTTGCTATGAGGTAATGC	479
Sbjct	612	CCTTCAATTACATACTCCTTGATGATATTACTATTAGAATTTGCTATGAGGTAATGC	553
Query	480	AGTACAGCTCCCCAAGAATCCTATTAATAATTTAAATATATTACCTGATGTAGTAGTTTC	539
Sbjct	552	AGTACAGCTCCCCAAGAATCCTATTAATAATTTAA-TATATTACCTGATGTAGTAGTTTC	494
Query	540	CTTGGCTGCTATGGTAAATTACCAAAAA-TATGATGGCTTCAAACGCACACATTATTTC	598
Sbjct	493	CTTGGCTGCTATGGTAAATTACCAAAAAATATGATGGCTTCAAACGCACACATTATTTC	434
Query	599	TCTTACATTCTGGAGGTCAGAAATCTGAAATCAGTTTCACTTGGTCAAAATCAAGGTGTT	658
Sbjct	433	TCTTACATTCTGGAGGTCAGAAATCTGAAATCAGTTTCACTTGGTCAAAATCAAGGTGTT	374

CCAG 718
CCAG 314
TTAA 775
T-AA 255
CTCT 835
CTCT 195



Lesson: Check the bot's work, very
carefully

Lesson: Sometimes maybe AI isn't the
right/best tool...

Task: I want to understand how the `--soft_filter` options works for the Ensembl `filter_vep` tool

How does this software parameter work?

In the ensembl filter_vep tool, what will happen if the --soft_filter option is used. What will the FILTER column look like in the VCF output file



In the Ensembl filter_vep tool, the --soft_filter option changes how variants that **do not pass your filter criteria** are marked in the output VCF.

Behavior of --soft_filter:

- If --soft_filter is NOT used:
 - Variants that **fail your filter expression** are **excluded** from the output file entirely.
- If --soft_filter is used:
 - All variants are retained in the output, but those that **fail your filter** are **soft-filtered** by modifying the FILTER column.
 - The FILTER column in the VCF for these variants will be set to the **filter expression name** or a custom name provided using --filter_name .



Malachi Griffith

Where is "--filter_name" documented?



You're right to ask — the `--filter_name` option is **not** currently documented in the official Ensembl `filter_vep` documentation (as of the most recent VEP versions). However, it's a **real and supported** option in the `filter_vep` script.

Evidence of `--filter_name`:

1. **Source code:** If you look at the Perl source for `filter_vep` (shipped with the Ensembl VEP distribution), the `--filter_name` option is defined and used to set the label applied in the `FILTER` column when `--soft_filter` is used.

2. **Usage in practice:**

You can test it yourself with:

```
bash
filter_vep --input_file input.vcf --filter "Consequence is missense_variant" --soft_f
```

Copy

Edit

This will tag non-matching variants with `FILTER = missense_filter`.

3. **Hidden/Undocumented option:**

Some VEP scripts have options that are used internally or expected to be known by more advanced users or discovered via command-line help (`--help`) rather than fully documented on the Ensembl site.



Failure!


When I ask about this made up option `--filter_name` it doubles down and provides “evidence”.

All three of these points of evidence are demonstrably false


Lesson: Sometimes AI is just telling you
what you want to hear

Task: I want to create a figure to explain difference between peptide-processing, MHC binding, presentation and immunogenicity


“Create an image the delicious depicts the difference between peptide MHC binding, processing, presentation and immunogenicity”



Malachi Griffith




“Create an image that depicts the difference between peptide mhc binding, processing, presentation and immunogenicity”



“Okay that's nice but
tone down the
deliciousness”

Peptide MHC Binding, Processing, Preinsertion



Peptide MHC Binding, Processing, Presentation

Immunogenicity

“Get rid of the burger aspect”


KEY:

Presentation



Lesson: Current AI “remembers” past things you’ve said, in unexpected ways, and doesn’t always understand

Task: I need to find an opening for yet another meeting



Use Claude to create a personal assistant agent (n8n on gcp)

The image displays a screenshot of the n8n workflow editor interface, showing a workflow for a personal assistant agent. The workflow is titled "Scheduling Agent — Workflow A" and is published. The interface includes a sidebar with navigation options (Overview, Personal), a top bar with the n8n logo and search, and a main editor area with tabs for Editor, Executions, and Evaluations. The workflow diagram shows a sequence of steps: Program Trigger, IF - Auth Correct?, Parse Request (AI), Extract JSON, IF - All Info Present?, a parallel block with five branches (Read Personal Calendar, Read Lab Calendar, Read Travel Calendar, Read ClinGen Calendar, and Read Personal Calendar), Tag Personal, Tag Lab, Tag Travel, Tag ClinGen, Merge Calendars, Slim Calendar Data, Find Available Slots (AI), Extract Slots JSON, and Send Proposed Slots. A red "Execute workflow" button is at the bottom.

On the left, a chat interface shows a conversation with the "Griffith Assistant bot". The user sends a message: "I need to find openings May 6, 7, 8, 12, 14 and 15 9am-12pm or 1-3pm for an Informatics Meeting with Jenny (j.mckenzie@wustl.edu)". The bot responds with a list of available times for a 60 min meeting.

On the right, another chat interface shows the same conversation, but the bot's response is truncated, showing only the first part of the list of available times.

At the bottom left, the CRI Cancer Research Institute logo is visible.

Failure! It constantly makes mistakes, creating conflicts, ignoring my rules, etc

The image displays a screenshot of the n8n workflow editor and a chat interface. The top part shows the n8n workflow editor with a workflow titled "Scheduling Agent — Workflow A". The workflow starts with a "Program Trigger" node, followed by an "IF - Auth Correct?" node. If correct, it proceeds to a "Parse Request" node, then an "Extract JSON" node, and finally an "IF - All Info Present?" node. If all info is present, the workflow branches into five parallel paths, each reading a different calendar (Personal, Lab, Travel, ClinGen, and another Personal) and tagging it. These paths then merge into a "Merge Calendars" node, followed by "Slim Calendar Data", "Find Available Slots", "Extract Slots JSON", and "Send Proposed Slots". If the "IF - All Info Present?" node fails, it leads to an "Ask for Missing Info" node. The bottom part shows a chat interface with a user asking for meeting openings and the Griffith Assistant bot providing a response.

Workflow Editor:

- Workflow: Scheduling Agent — Workflow A
- Nodes: Program Trigger, IF - Auth Correct?, Parse Request, Extract JSON, IF - All Info Present?, Read Personal Calendar, Tag Personal, Read Lab Calendar, Tag Lab, Read Travel Calendar, Tag Travel, Read ClinGen Calendar, Tag ClinGen, Merge Calendars, Slim Calendar Data, Find Available Slots, Extract Slots JSON, Send Proposed Slots, Ask for Missing Info.
- Buttons: Editor, Executions, Evaluations, Execute workflow

Chat Interface:

User: I need to find openings May 6, 7, 8, 12, 14 and 15 9am-12pm or 1-3pm for an Informatics Meeting with Jenny (j.mckenzie@wustl.edu)


Griffith Assistant bot:

Here are available times for a 60 min meeting with Jenny to Informatics Meeting:

1. Wed May 6, 9:30-10:30am CT
2. Thu May 7, 9:00-10:00am CT
3. Thu May 14, 9:30-10:30am CT

Reply with the numbers of the options to offer Jenny (e.g. '1 and 3'), or say 'none' to find different times.

Lesson ... you can't lick a badger twice!



◆ AI Overview

The idiom "you can't lick a badger twice" means you can't trick or deceive someone a second time after they've been tricked once. It's a warning that if someone has already been deceived, they are unlikely to fall for the same trick again.

Here's a more detailed

Take home message

Some CEO (or department chair) maybe looks at this and says “I can fire half my staff and get the same amount of work done”

... maybe a few staff can be saved mundane, unsatisfying work...

But, they should be saying “if we train our staff to use these tools effectively our whole productivity will be like 10x and we will rocket past the competition”

Questions?

Where to learn more

[AI for Decision Makers](#)



Leaders

This set of four mini courses helps leaders make strategic decisions, drive innovation, enhance efficiency, and foster a culture that embraces the transformative power of these technologies.

- AI
- AI Tasks
- Avoiding Harm
- Policy
- Regulations
- Using AI



What is the best chatbot for me
Publication



Everyday AI Cheatsheet



AI Success Stories Video



AI Cautionary Tales Video

[AI for Efficient Programming](#)



Software
Developers



Researchers

This course on AI for software development explores the use of AI large language models (ChatGPT, Bard, etc) and their potential benefits and challenges. Hands-on activities show the ways in which AI can speed up software development tasks and free up time for more creative and strategic work, maximizing benefits/efficiency while limiting harm.

- AI Uses
- Annotate Code
- Artificial Intelligence
- Chatbot
- Ethics
- Learn AI
- LLM
- Refactor Code
- Software Learning
- Understand Code
- Write Code



Everyday AI Cheatsheet




AI Success Stories Video




AI Cautionary Tales Video

Convert an existing R ML model into Python equivalent



Jennie Yao

Google NotebookLM allows AI queries of select sources



Agentic Coding Environments (Warp, Claude Code) moves development from typing code to coding by prompt



FeaturesResourcesPricingCareersEnterprise

Contact salesDownload for Mac

The Agentic Development Environment

Warp is the fastest way to build with multiple AI agents—from writing code to shipping it. The best overall coding and terminal agent.

Download for Mac

```
$ brew install --cask warp
```



Create a docker environment for hands-on bioinformatics workshop

- We host a 3 - 5 day workshop on RNAseq/scRNAseq analysis
- AWS AMI allows students to work through exercises in a consistent/robust environment
 - Requires AWS account (\$\$\$) and prevents self-organized learning and later review/practice
- A docker image with all dependencies would make more broadly accessible year round
 - Dozens of tools, linux dependencies, web server, etc



AWS Setup

[« Integrated Assignment Answers](#)

[Course](#)

[GCP Setup »](#)

Amazon AWS/AMI setup for use in workshop


This tutorial explains how Amazon cloud instances were configured for the course. This exercise is not to be completed by the students but is provided as a reference for future course developers that wish to conduct their hands on exercises on Amazon AWS.

Create AWS account

A helpful tutorial can be found [here](#)

Create a docker environment for hands-on bioinformatics workshop

- Point warp to an existing github repo and (very prelim) attempt at a dockerfile
- Explain that build time and image size should be optimized
- Warp starts building!
 - Review each change carefully
 - Make corrections advice as needed
 - Remind to commit changes along the way
 - Ask for versioning
 - ...



Create a docker environment for hands-on bioinformatics workshop

rnabio.org / docker / course / dockerfile_approach /

...

obigriffith update version examples in readme ✓

fcb3c33 · 2 weeks ago History

Name	Last commit message	Last commit date
..		
CHANGELOG.md	Update CHANGELOG and VERSION	2 weeks ago
Dockerfile	Add ggridges R package and enable man pages for educational use	2 weeks ago
README.md	update version examples in readme	2 weeks ago
VERSION	Update CHANGELOG and VERSION	2 weeks ago
build.sh	Add comprehensive versioning system for Docker image	3 weeks ago
release.sh	Update release script with better GitHub release template for monorepo	3 weeks ago
version.sh	improve release instructions	2 weeks ago

README.md

≡

RNA-seq Bioinformatics Toolkit

This Docker image contains a comprehensive set of bioinformatics tools for RNA-seq analysis, based on the requirements described in the AWS Setup guide from rnabio.org. Currently tools are limited to those needed for bulk RNAseq parts of the course.