

Cox Research & Technology, Inc.  
P.O. Box 77808, Baton Rouge, LA 70879

Model: CP-2365  
Max Full Load Amps: 8.4 Per Pump  
Volts: 120/240  
Phase/Hz: 3/60  
Largest Motor HP: 2HP

See drawing # CP-2365 for wiring schematic

Field wiring to be copper conductors with  
75° insulation rating

Torque terminal strip screws to 9 Nm

THIS AREA IS FOR  
INTRINSICALLY SAFE  
CIRCUITRY ONLY.  
INSTALL IN ACCORDANCE  
WITH ARTICLE 504 OF  
THE NATIONAL ELECTRICAL  
CODE.

DANGER  
"HIGH VOLTAGE"  
SERVICE BY QUALIFIED  
PERSONNEL ONLY

ARC FLASH HAZARD  
APPROPRIATE PPE REQUIRED

WARNING: TO PREVENT  
IGNITION OF FLAMMABLE OR  
COMBUSTIBLE ATMOSPHERES  
DISCONNECT POWER BEFORE  
SERVICING

THIS PANEL PROVIDES  
INTRINSICALLY SAFE CIRCUIT  
EXTENSIONS FOR USE IN  
CLASS 1 & 2, GROUPS C,D,E,F & G  
HAZARDOUS LOCATIONS WHEN  
CONNECTED PER INSTALLATION  
SEE DWG. \_\_\_\_\_

INTRINSICALLY SAFE WIRING ONLY  
NEMA 4X RATED FITTINGS ONLY