



\* DIVERSIFIED ALTERNATOR

PANEL IS DESIGNED TO RUN AERATORS WITH A MINIMUM OF 15 MINUTES OF OFF TIME BETWEEN ALTERNATION. PINS PUSHED IN ON CLOCK INDICATE RUN TIME. PINS PUSHED OUT INDICATE OFF TIME. EACH PIN IS EQUAL TO 15 MINUTES.

IF NO OFF TIME IS REQUIRED BETWEEN ALTERNATION, REMOVE JUMPER FROM TERMINALS ⑤ AND ⑥. PLACE JUMPER ACROSS TERMINALS ⑦ AND ⑧. NOW AERATORS WILL RUN CONTINUOUSLY. SET 1 PIN OUT AT THE TIME YOU WISH THE AERATORS TO ALTERNATE. ALL REMAINING PINS SHOULD BE PUSHED IN.

\* REMOVE JUMPERS AND INSTALL LOCKOUT DEVICES IF REQUIRED

	Drawing Title							
	CONTROL DIAGRAM							
DATE 03/1004	REFERENCE DRAWING		NO.		REVISION-LOCATION		ECN	DATE
	S/N	Sales Engineer C.C.	Application Engineer R.C.		DRAWN BY C. RACHAL		APPROVED BY	DATE
	Project Title		<hr/> <hr/> <b>COX</b> <hr/> <hr/> Research and Technology, Inc. <hr/> <hr/>		P.O. Box 77808 Baton Rouge, LA 70809		PURCHASE ORDER NUMBER	
	DUPLEX BLOWER CONTROL PANEL				DRAWING NUMBER CP-1770		SHEET NUMBER 2	