

# Convolutional neural networks for classification of transmission electron microscopy imagery

Sergii Gryshkevych

Uppsala University

December 14, 2016

# Introduction

## Introduction

# Performance measures

## The Accuracy Paradox

Models with a given accuracy may have greater predictive power than models with higher accuracy.

## Confusion matrix

	Predicted True	Predicted False
Actual True	True Positive	False Negative
Actual False	False Positive	True Negative

# Performance measures

## True positive rate (TPR)

AKA sensitivity or recall:  $TPR = \frac{TP}{TP+FN}$

# Performance measures

## True positive rate (TPR)

AKA sensitivity or recall:  $TPR = \frac{TP}{TP+FN}$

## True negative rate (TNR)

AKA specificity:  $TNR = \frac{TN}{TN+FP}$

# Performance measures

## True positive rate (TPR)

AKA sensitivity or recall:  $TPR = \frac{TP}{TP+FN}$

## True negative rate (TNR)

AKA specificity:  $TNR = \frac{TN}{TN+FP}$

## Positive predicted value (PPV)

AKA precision:  $PPV = \frac{TP}{TP+FP}$

# Performance measures

## True positive rate (TPR)

AKA sensitivity or recall:  $TPR = \frac{TP}{TP+FN}$

## True negative rate (TNR)

AKA specificity:  $TNR = \frac{TN}{TN+FP}$

## Positive predicted value (PPV)

AKA precision:  $PPV = \frac{TP}{TP+FP}$

## Negative predicted value (NPV)

$NPV = \frac{TN}{TN+FN}$

# Performance measures

## True positive rate (TPR)

AKA sensitivity or recall:  $TPR = \frac{TP}{TP+FN}$

## True negative rate (TNR)

AKA specificity:  $TNR = \frac{TN}{TN+FP}$

## Positive predicted value (PPV)

AKA precision:  $PPV = \frac{TP}{TP+FP}$

## Negative predicted value (NPV)

$NPV = \frac{TN}{TN+FN}$

## $F_1$ score

It is a harmonic mean of TPR and TNR



# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation

# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$

# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$
- Vertical shift in the range  $[-10, 10]$  percent of total height

# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$
- Vertical shift in the range  $[-10, 10]$  percent of total height
- Horizontal shift in the range  $[-10, 10]$  percent of total width

# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$
- Vertical shift in the range  $[-10, 10]$  percent of total height
- Horizontal shift in the range  $[-10, 10]$  percent of total width
- Zoom in the range  $[0.8, 1.0]$  which means zoom by a maximum 20%


# Data augmentation techniques

- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$
- Vertical shift in the range  $[-10, 10]$  percent of total height
- Horizontal shift in the range  $[-10, 10]$  percent of total width
- Zoom in the range  $[0.8, 1.0]$  which means zoom by a maximum 20%
- Horizontal flip

# Data augmentation techniques



- Rotation in the range  $[-180, 180]$  degrees with spline interpolation
- Shear transformation in the range  $[0, 0.2]$
- Vertical shift in the range  $[-10, 10]$  percent of total height
- Horizontal shift in the range  $[-10, 10]$  percent of total width
- Zoom in the range  $[0.8, 1.0]$  which means zoom by a maximum 20%
- Horizontal flip
- Vertical flip

# Data augmentation example







# Effect of the data augmentation




# Network architectures



# Popularity of deep learning software as of October 2016



# CNN vs SVM: Lamellarity



# CNN vs SVM: Encapsulation

