

Project Configuration Report

spi_pwm_cli

Target Device:

Target Part: EFR32MG26B420F3200IM68

Boards:

- Wireless Pro Kit Mainboard (BRD4002A Rev A07)
- EFR32xG26 Wireless 2.4GHz 20 dBm QFN68 Radio Board (BRD4121A Rev A05)

Target SDK

Simplicity SDK Suite v2026.6.1: Bluetooth 11.1.1, Bluetooth Mesh SDK 11.0.1, Connect SDK 4.3.1.0, EmberZNet 9.1.1.0, Multiprotocol 1.1.1.0, OpenThread 3.1.1.0 (GitHub-fb274efe6), Peripheral Examples Simplicity SDK\2.1.1, RAIL SDK 3.1.1.0, Sidewalk 2.9.1, Silicon Labs AI/ML SDK 3.0.1, Silicon Labs Matter 2.9.1-1.6, Wi-Fi SDK 4.1.1-rc.2, Z-Wave SDK 8.1.1.0
SDK Version: 2026.6.1

Project Generators

- VS Code (GCC)

Installed Software Components:

- Platform

- Board

- Mainboard

- BRD4002A**

- Configurable: false

- Radio Board

- BRD4121A**

- Configurable: false

- Device

- EFR32MG26

- EFR32MG26B420F3200IM68**

- Sources: system_efr32mg26.c, startup_efr32mg26.c

- Configurable: true

- Configs: device.yaml

- Driver

- LED

- Simple LED**

- Configurable: true

- Configs: sl_simple_led_led0_config.h

- PWM

- PWM**

- Configurable: true

- Configs: sl_pwm_init_pwm1_config.h

- SPI

- SPIDRV USART**

- Configurable: true

- Configs: sl_spidrv_usart_exp_config.h

- Services

- **Clock Manager**

- Clock Manager**

- Sources: sl_clock_manager_init.c

- Configurable: true

- Configs: sl_clock_manager_oscillator_config.h, sl_clock_manager_ext_flash_config.h, sl_clock_manager_tree_config.h

- **Command Line Interface**

- CLI Instance(s)**

- Configurable: true

- Configs: sl_cli_config_cli1.h

- **Device Initialization**

- Automatic Device Initialization**

- Configurable: false

- **IO Stream**

- IO Stream: Recommended Stream**

- Configurable: false

- IO Stream: Retarget STDIO**

- Sources: sl_iostream_retargt_stdio.c

- Configurable: false

- IO Stream: STDLIB Configuration**

- Sources: sl_iostream_stdlib_config.c

- Configurable: false

- **System Setup**

- System Setup (sl_main)**

- Configurable: true

- Configs: sl_main_start_task_config.h

- Timers

Sleep Timer

Sources: sl_sleeptimer.c

Configurable: true

Configs: sl_sleeptimer_config.h

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
CMU	Clock Manager	
EUSART0	IO Stream: EUSART (vcom)	
EUSART1	IO Stream: EUSART (vcom)	
EUSART2	IO Stream: EUSART (vcom)	
EUSART3	IO Stream: EUSART (vcom)	
GPIO	SWO Debug	
I2C0		
I2C1		
I2C2		
I2C3		
IADC0		
KEYSCAN		
LCD		
LETIMER0		
LFXO		
MODEM		
PCNT0		
PRS Channel ASYNCH0		
PRS Channel ASYNCH1		
PRS Channel ASYNCH10		
PRS Channel ASYNCH11		
PRS Channel ASYNCH12		
PRS Channel ASYNCH13		
PRS Channel ASYNCH14		
PRS Channel ASYNCH15		
PRS Channel ASYNCH2		
PRS Channel ASYNCH3		
PRS Channel ASYNCH4		
PRS Channel ASYNCH5		
PRS Channel ASYNCH6		
PRS Channel ASYNCH7		
PRS Channel ASYNCH8		
PRS Channel ASYNCH9		
PRS Channel SYNCH0		

PRS Channel SYNCH1		
PRS Channel SYNCH2		
PRS Channel SYNCH3		
PTI		
TIMER0	PWM (pwm1)	
TIMER1	PWM (pwm1)	
TIMER2	PWM (pwm1)	
TIMER3	PWM (pwm1)	
TIMER4	PWM (pwm1)	
TIMER5	PWM (pwm1)	Mot_PWM
TIMER6	PWM (pwm1)	
TIMER7	PWM (pwm1)	
TIMER8	PWM (pwm1)	
TIMER9	PWM (pwm1)	
USART0	SPIDRV USART (exp)	
USART1	SPIDRV USART (exp)	
USART2	SPIDRV USART (exp)	
VDAC0		
VDAC1		