

## 3.2 The garden in the margin

Everything in the left margin of this page is drawn while the page is being laid out, by a few thousand lines of Rust compiled to WebAssembly and run by Typst as a plugin. There are no image files, no imported paths and no external programs; every petal is a parametric curve evaluated for this page and written straight into it as PDF path operators. This section records how it is done, so that the margin documents itself.

**Definition 3.1.** A *primitive* is a closed outline $\gamma : [0,1] \to \mathbb{R}^2$ authored by hand together with a small set of free parameters $(p_1, \dots, p_k)$ and a recipe for painting it. An *instance* of the primitive samples the parameters from fixed intervals and paints $\gamma$ in a local frame chosen by the caller. The composition on this page is *authored*; only the parameters are *sampled*. This is what "procedural" means here: no flower is grown from a grammar, but no two petals share a shape.

**Construction 3.2** (Palette)**.** There is one document color, `ink`, and from it a ramp $t \mapsto \mathrm{tone}(t)$ from the darkest navy at $t = 0$ to a pale mist at $t = 1$. The ramp is interpolated in OKLCH between six stops whose lightness runs from 0.25 to 0.92 and whose chroma peaks at 0.175 for the cobalt at $t = 0.38$; the hue is that of `ink`, drifting 6° toward violet in the darks and 8° toward cyan in the lights, as ultramarine does when it is thinned with water, and the chroma scales with that of `ink`. Mixing the document color with white, as `ink.lighten(78%)` would, desaturates toward gray instead; the perceptual ramp keeps the light end blue. A second color, `accent`, is a copper used only for hairlines. A third, `blossom`, is optional: the flower primitives then take their washes from a ramp of its hue, and only their darkest touches ($t < 0.16$: stamens, eyes, outlines) from the ink. The style `"sumi-e"` sets a warm black ink and vermilion for blossom and accent: red flowers on black branches.

**Construction 3.3** (Petal)**.** A petal of length 1 pointing along $+y$ has a spine $x = bv^2$, $y = v$ ($b$ bends the tip) and the obovate half-width

$$w(v) = \begin{cases} W\left(0.16 + 0.84 \sin^{1.3} \frac{\pi v}{1.24}\right), & v < 0.62, \\ W\sqrt{1 - q^2}, \quad q = \frac{v - 0.62}{0.38}, & v \geq 0.62, \end{cases} \qquad W \in [0.40, 0.48],$$

a narrow claw, widest at 0.62, with an elliptical cap. The margin is moved along the normal by $0.03 v n(6v)$, where $n$ is a three-octave gradient noise seeded per petal, so it wavers more toward the tip; four petals in ten also get a shallow notch. The outline is sampled once and used twice: as a clipping path, and as the stroke that gives the rim. Inside the clip the petal is painted like a watercolor, in the order a painter would: a flat wash at $\mathrm{tone}(t_0)$, $t_0 \in [0.30, 0.46]$; eight stacked white blobs at the base, each at 10% opacity, for the pale heart; fifteen irregular blotches multiplied over the wash, most darker, some lighter, and a dozen dark specks for the granulation; five to eight darker brush strokes running out from the base; the outline stroked $1.6\ell$ bp wide for a petal $\ell$ cm long and multiplied, of which only the inner half shows, for the pigment that pools at the edge of a wash; nine to thirteen white streaks lifted out in a fan from the base; and a few fine dark veins. There is no outline in the usual sense.



**Construction 3.4** (Tapered strokes)**.** Every streak, vein and rib is a filled shape rather than a stroke, so that it tapers. For a cubic Bézier with control points $P_0, \dots, P_3$ and widths $w_0$, $w_1$ at its ends, push each $P_i$ along its normal by $\pm\frac{1}{2}w(i/3)$, with the normals at $P_1$ and $P_2$ taken from the chords $P_2 - P_0$ and $P_3 - P_1$. The two offset curves joined at the ends are a tapered stroke in two Bézier segments, five times smaller in the file than a sampled ribbon and indistinguishable from one for a gentle curve.

**Construction 3.5** (Flowers)**.** A *flower* is five petals at 72° intervals with ±6° of jitter and lengths in $[0.9, 1.06]$, then a heart of ten white rays, a white disc, fourteen stamens and a copper eye. A quarter of the flowers are painted a shade deeper. A *lily* is six pointed petals, $w(v) = 2W \sin^{0.85}(\pi v^{0.8})(1 - 0.3v)$, arranged in a star and then squashed vertically by a factor in $[0.45, 0.62]$: the star is seen at a tilt, so the petals that point away are short, and since they are drawn first and darker they read as the back of the flower. A *blossom* is the same idea at a few millimeters, and a *floret*, the smallest, is five petals filled as one shape around a dark eye; below 0.7 mm in radius it is a ten-pointed star. Buds, bellflowers and sepals are blades on the same spine.

**Construction 3.6** (Leaves)**.** A leaf of length 1 has the envelope $e(v) = 2.3Wv^{0.55}(1 - v)^{0.95}$. An entire leaf is that envelope with fine teeth. A lobed leaf, like acanthus, is a narrow body of half-width $(1 - 0.75d)e(v)$, where $d$ is the depth of the cut, together with three to five pointed lobes on each side; each lobe is itself a blade that leaves the midrib at 38°–58° toward the tip and reaches the envelope. Body and lobes are filled as one shape, under the nonzero rule, so there is no seam. One half of the leaf is multiplied darker, as if it were folded along its rib; then come the blotches, the pooled edge, and a white midrib with a white vein along every lobe.

**Construction 3.7** (Sprays)**.** A *cyme*, the inflorescence of the forget-me-not, is a stem whose heading turns by $\pm\tau(s/L)^{2.3}$ at arc length $s$, with $\tau \in [170°, 270°]$: straight at first, it curls like a scorpion's tail at the end. Eleven to seventeen florets crowd along it, shrinking into buds toward the curl, and a second, shorter curl forks off it three times in five. A *sprig* is a stem that forks two or three ways four times, each fork 0.58 to 0.74 the length of its parent, with florets and buds at the tips. An *umbel* fans nine to thirteen rays over 110°, each ending in a small umbel of starry florets.

### 3.2.1 Composition

The garden is a plant, not an arrangement. It grows from one root in the bottom-left corner of the page, where the base of the stems curls into a scroll. Three stems run up the column through hand-picked control points, interpolated by Catmull–Rom splines and jittered by a millimeter or so on each page: the tallest ends in the large flower at the top, one in a lily, one in a flower half-way up. A fourth stem leaves the root along the bottom of the page, carrying small leaves that thin out toward its end, and runs out into a copper hairline; it is the footer.



The header is a printer's ivy leaf in copper whose stem becomes the head rule.

Leaves hang at chosen fractions of the stems' length, alternately left and right. Every other motif sits at a chosen point and is joined to a chosen stem by a *branch*: a cubic Bézier that leaves the stem along the stem's own direction turned 28° to 48° toward the target, and arrives along the motif's axis. Because a branch starts tangent to its parent and ends tangent to its flower, every flower can be traced back to the root, and that, more than any detail of the painting, is what makes the margin look grown. Behind everything are one or two *ghosts*: flowers painted with every tone lifted toward the paper, $t \mapsto t + 0.62(1 - t)$, and without their fine detail, which give the column depth.

**Remark 3.8** (Procedural is not random)**.** The generator is seeded from the page number before the garden is drawn. Page $n$ therefore receives the same garden on every compilation, and a different one from page $n + 1$. The variation the reader notices between pages is real; the reproducibility is what makes the document stable enough to typeset.

**Proposition 3.9.** *Let $P$ be the number of primitive instances on a page and $S$ the mean number of path points per instance. The cost of a page is $\Theta(PS)$ floating-point operations in the plugin and $\Theta(PS)$ bytes of output, and Typst does no arithmetic at all; in practice a page takes about a second, for $P \approx 400$ and $S \approx 100$.*

*Proof sketch.* Every coordinate is computed once in the plugin, transformed to the page, and printed with one decimal of a PDF point into the content stream of a one-page PDF, which Typst embeds behind the page as it is. The same curves can be handed to Typst as SVG, but it then re-encodes every number with eight or nine digits and gives every multiplied blotch a transparency group of its own, and the file grows sixfold. The size of the output is the real constraint: about three megabytes of path operators per page, which compress to under one. □

**Exercise 3.10.** The composition above is authored. Replace it by a growth process in the spirit of Wong, Zongker and Salesin (*Computer-generated floral ornament*, SIGGRAPH 1998): starting from the stems, repeatedly find the largest free disc in the margin that is within reach of a stem, choose a primitive that fits it, and grow a branch to it, until no disc larger than a threshold remains. The ornament then adapts to any text block, and a page whose text ends early grows a garden into the space below it.

### 3.2.2 Building and sharing

The package is `florilegium.typ` with a WebAssembly plugin beside it, built from a Rust crate of six modules: `ink.rs` (geometry, color and PDF output), `flora.rs` (the primitives), `authored.rs` and `grow.rs` (the two compositions), `initial.rs` (the decorated initials) and `lib.rs` (the plugin's functions). It began as a port of the Lua code of an earlier LaTeX version, line for line and draw for draw: for the same seed and the same page, the two wrote the same content stream, byte for byte. It needs Typst 0.14 or later, which embeds PDF pages, and one

compilation, at about a second per page. To share it, the three routes that work are, in increasing order of effort: upload the package's files to a project on typst.app and share the link; put it in a Git repository with a continuous integration job that compiles the PDFs on every push; or publish it as a package, so that any document can import the garden and choose its own seed, margin and hue.

**Remark 3.11.** Two mistakes in the port cost time and are worth recording. An interval with no end is not the same as one that ends at infinity: the last frame of the growth animation is drawn at $t = \infty$, where every event's progress is infinite too, and $\infty < \infty$ is false, so the last frame came out empty until the test asked whether the interval had an end instead of comparing with it. And Typst lays a document out more than once when it asks where things are, and in the first pass nothing has a position yet: a background that calls the plugin there grows every garden twice, once for a page without marks and again for the real one. A sentinel at the end of the document, which only the second pass can find, halves the time.