3-TERMINALS 1A POSITIVE VOLTAGE REGULATOR



■ DESCRIPTION

The UTC **78DXXA** family is monolithic fixed voltage regulator integrated circuit. They are suitable for applications that required supply current up to 1 A.

■ FEATURES

* Peak output current up to 1A.
* Fixed output voltage of 5V, 6V, 7V, 8V, 9V, 10V, 12V, 15V and 18V available.
* Thermal overload shutdown protection.
* Short circuit current limiting.
* Output transistor SOA protection.

■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
78DXXAL-AA3-R	78DXXAG-AA3-R	SOT-223	I	G	O	Tape Reel
78DXXAL-TM3-T	78DXXAG-TM3-T	TO-251	I	G	O	Tube
78DXXAL-TN3-R	78DXXAG-TN3-R	TO-252	I	G	O	Tape Reel
78DXXAL-TN3-T	78DXXAG-TN3-T	TO-252	I	G	O	Tube
78DXXAL-TNA-R	78DXXAG-TNA-R	TO-252-3	I	G	O	Tape Reel
78DXXAL-TNA-T	78DXXAG-TNA-T	TO-252-3	I	G	O	Tube

Note: Pin Code: I: Input G: GND O: Output

78DXXAL-AA3-R
(1)Packing Type
(2)Package Type
(3)Lead Free
(4)Output Voltage Code

(1) R: Tape Reel, T: Tube
(2) AA3: SOT-223, TM3: TO-251, TN3: TO-252, TNA: TO-252-3
(3) L: Lead Free, G: Halogen Free
(4) XX: refer to Marking Information

■ MARKING INFORMATION

PACKAGE	VOLTAGE CODE	MARKING
SOT-223	05: 5V 06: 6V 08: 8V 09: 9V 10: 10V 12: 12V 15: 15V 18: 18V	
TO-251 TO-252 TO-252-3		

■ BLOCK DIAGRAM



■ APPLICATION CIRCUIT



Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

■ ABSOLUTE MAXIMUM RATINGS (T_A = 25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Input Voltage		V_{IN}	35	V
Output Current		I_{OUT}	1	A
Power Dissipation (T_C=25°C)	SOT-223	P_D	8.3	W
	TO-251/TO-252 TO-252-3		10	
Junction Temperature		T_J	+150	°C
Operating Temperature		T_{OPR}	-40 ~ +85	°C
Storage Temperature		T_{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are stress ratings only and functional device operation is not implied. The device could be damaged beyond Absolute maximum ratings.
2. The maximum steady state usable output current are dependent on input voltage, heat sinking, lead length of the package and copper pattern of PCB. The data are showed as electrical characteristics table represents pulse test conditions with junction temperatures specified at the initiation of test.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-223	θ_{JA}	150	°C/W
	TO-251/TO-252 TO-252-3		112	
Junction to Case	SOT-223	θ_{JC}	15	°C/W
	TO-251/TO-252 TO-252-3		12.5	

■ ELECTRICAL CHARACTERISTICS

(T_J=25°C, C_I =0.33uF, C_O=0.1uF, $P_D \leq$15W, unless otherwise specified)

For 78D05A (V_{IN} =10V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	4.80	5.0	5.20	V
		V_{IN} =7.5~20V, I_{OUT} =5mA~1.0A	4.75		5.25	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			50	mV
		I_{OUT} =0.25A~0.75A			25	mV
Line Regulation	ΔV_{OUT}	V_{IN} =7~25V			50	mV
		V_{IN} =7.5~20V, I_{OUT} =1.0A			50	mV
Quiescent Current	I_Q	$I_{OUT} \leq$1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =7.5~20V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		40		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-0.6		mV/°C
Ripple Rejection	RR	V_{IN} =8~18V,f=120Hz	62	80		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS(Cont.)

For 78D06A (V_{IN} =11V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	5.76	6.0	6.24	V
		V_{IN} =8.5~21V, I_{OUT} =5mA~1.0A	5.7		6.3	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			60	mV
		I_{OUT} =0.25A~0.75A			30	mV
Line Regulation	ΔV_{OUT}	V_{IN} =8~25V			60	mV
		V_{IN} =8.5~21V, I_{OUT} =1.0A			60	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =8.5~21V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		45		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-0.7		mV/°C
Ripple Rejection	RR	V_{IN} =9~19V,f=120Hz	59	75		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

For 78D07A (V_{IN} =13V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	6.72	7.0	7.28	V
		V_{IN} =9.5~22V, I_{OUT} =5mA~1.0A	6.65		7.35	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			70	mV
		I_{OUT} =0.25A~0.75A			35	mV
Line Regulation	ΔV_{OUT}	V_{IN} =9~25V			70	mV
		V_{IN} =9.5~22V, I_{OUT} =1.0A			70	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =9.5~22V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		50		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-0.8		mV/°C
Ripple Rejection	RR	V_{IN} =10~20V,f=120Hz	59	75		dB
Peak Output Current	I_{PEAK}			1.7		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

For 78D08A (V_{IN} =14V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	7.68	8.0	8.32	V
		V_{IN} =10.5~23V, I_{OUT} =5mA~1.0A	7.6		8.4	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			80	mV
		I_{OUT} =0.25A~0.75A			40	mV
Line Regulation	ΔV_{OUT}	V_{IN} =10.5~25V			80	mV
		V_{IN} =10.5~23V, I_{OUT} =1.0A			80	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =10.5~23V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		58		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-0.9		mV/°C
Ripple Rejection	RR	V_{IN} =11.5~21.5V,f=120Hz	56	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS(Cont.)

For 78D09A (V_{IN} =15V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	8.64	9.0	9.36	V
		V_{IN} =11.5~24V, I_{OUT} =5mA~1.0A	8.55		9.45	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			90	mV
		I_{OUT} =0.25A~0.75A			45	mV
Line Regulation	ΔV_{OUT}	V_{IN} =11.5~25V			90	mV
		V_{IN} =11.5~24V, I_{OUT} =1.0A			90	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =11.5~24V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		58		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-1.1		mV/°C
Ripple Rejection	RR	V_{IN} =12.5~22.5V,f=120Hz	56	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

For 78D10A (V_{IN} =16V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	9.60	10.0	10.40	V
		V_{IN} =12.5~25V, I_{OUT} =5mA~1.0A	9.5		10.5	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			100	mV
		I_{OUT} =0.25A~0.75A			50	mV
Line Regulation	ΔV_{OUT}	V_{IN} =13~25V			100	mV
		V_{IN} =13~25V, I_{OUT} =1.0A			100	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =12.6V~25V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		58		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-1.1		mV/°C
Ripple Rejection	RR	V_{IN} =13~23V,f=120Hz	56	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

For 78D12A (V_{IN} =19V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	11.52	12.0	12.48	V
		V_{IN} =14.5~27V, I_{OUT} =5mA~1.0A	11.4		12.6	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			120	mV
		I_{OUT} =0.25A~0.75A			60	mV
Line Regulation	ΔV_{OUT}	V_{IN} =14.5~30V			120	mV
		V_{IN} =14.6~27V, I_{OUT} =1.0A			120	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =14.5~30V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		75		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-1.5		mV/°C
Ripple Rejection	RR	V_{IN} =15~25V,f=120Hz	55	72		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

■ ELECTRICAL CHARACTERISTICS(Cont.)

For 78D15A (V_{IN} =23V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT} =5mA~1.0A	14.40	15.0	15.6	V
		V_{IN} =17.5~30V, I_{OUT} =5mA~1.0A	14.25		15.75	V
Load Regulation	ΔV_{OUT}	I_{OUT} =5mA~1.0A			150	mV
		I_{OUT} =0.25A~0.75A			75	mV
Line Regulation	ΔV_{OUT}	V_{IN} =18.5~30V			150	mV
		V_{IN} =17.7~30V, I_{OUT} =1.0A			150	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =17.5~30V			1.0	mA
		I_{OUT} =5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		90		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-1.8		mV/°C
Ripple Rejection	RR	V_{IN} =18.5~28.5V,f=120Hz	54	70		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

For 78D18A (V_{IN} =27V, I_{OUT} =0.5A)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Output Voltage	V_{OUT}	I_{OUT}=5mA~1.0A	17.28	18.0	18.72	V
		V_{IN} =21~33V, I_{OUT}=5mA~1.0A	17.1		18.9	V
Load Regulation	ΔV_{OUT}	I_{OUT}=5mA~1.0A			180	mV
		I_{OUT}=0.25A~0.75A			90	mV
Line Regulation	ΔV_{OUT}	V_{IN} =21~33V			180	mV
		V_{IN} =21~33V, I_{OUT} =1.0A			180	mV
Quiescent Current	I_Q	I_{OUT}≤1.0A			8.0	mA
Quiescent Current Change	ΔI_Q	V_{IN} =21.5~33V			1.0	mA
		I_{OUT}=5mA~1.0A			0.5	mA
Output Noise Voltage	eN	10Hz≤f≤100kHz		110		μV
Temperature coefficient of V_{OUT}	$\Delta V_{OUT}/\Delta T$	I_{OUT} =5mA		-2.2		mV/°C
Ripple Rejection	RR	V_{IN} =22~32V,f=120Hz	53	69		dB
Peak Output Current	I_{PEAK}			1.8		A
Short-Circuit Current	I_{SC}	V_{IN} =35V		250		mA
Dropout Voltage	V_D			2.0		V

■ TYPICAL CHARACTERISTICS

Output Voltage vs. Input Voltage



Circuit Operating Current vs. Input Voltage



Bias Current vs. Junction Temperature



Output Voltage vs. Junction Temperature



Dropout Voltage vs. Junction Temperature



Short Current vs. Input Voltage



■ TYPICAL CHARACTERISTICS(Cont.)