

CS2303_HW04

For this assignment, 2 programs were created.

1. sorttest – This program takes in numbers from the command line, puts them into an array, sorts them, and prints out time taken to sort.
2. sorttest2 – This program does much of the same as sorttest except it uses randomly generated values and lets user select sorting function.

Compilation

To compile the program, open the directory into any unix environment and enter make to compile all the source files.

```
$ cd <path to directory>/cs2303_hw04
~/<path to directory>/cs2303_hw04$ make
```

Note: To compile individual testers enter `make sorttest` or `make sorttest2`.

To get doxygen output, configure the target folder in the makefile and enter `make docs`.

```
$ make docs
```

To remove object files and executables, run this command:

```
$ make clean
```

sorttest usage

```
$ ./sorttest num1 num2 nums3
```

Parameter	Type	Description
num1	int	Required. Valid integer to be put in array.
num2, num3, ...	int	Optional. Valid integer to also put in array

sorttest2 usage

```
$ ./sorttest2 array_size sort_type
```

Parameter	Type	Description
array_size	int	Required. Size of random array.
sort_type	string	Required. Type of sorting arrays. Either <code>sort_descending</code> or <code>alt_sort_descending</code> .
sort_type options		Description
<code>sort_descending</code>		Regular bubble sort using array with indexes.
<code>alt_sort_descending</code>		Optimized bubble sort using pointer access.

tests

```
$ ./sorttest 0 1 2 3
Unsorted array:
0
1
2
3
Sorted array (descending order):
3
2
1
0
Timestamp before sorting: Seconds 1675917181, Microseconds:515155
Timestamp after sorting: Seconds 1675917181, Microseconds:515155
Time spent sorting: Seconds 0, Microseconds:0
```

Test #1a: Random Range [0,10]

```
$ ./sorttest2 5000 sort_descending
(list of numbers) ...
Timestamp before sorting: Seconds 1675916377, Microseconds:866438
Timestamp after sorting: Seconds 1675916377, Microseconds:918095
Time spent sorting: Seconds 0, Microseconds:51657
```

Test #1b: Random Range [0,10]

```
$ ./sorttest2 5000 alt_sort_descending
(list of numbers) ...
Timestamp before sorting: Seconds 1675916533, Microseconds:404869
Timestamp after sorting: Seconds 1675916533, Microseconds:404922
Time spent sorting: Seconds 0, Microseconds:53
```

Running test one shows that alt_sort is 974 times faster than running the regular bubble sort.

Test #2a: Random Range [0,100]

```
$ ./sorttest2 10000 sort_descending
(list of numbers) ...
Timestamp before sorting: Seconds 1675916906, Microseconds:382870
Timestamp after sorting: Seconds 1675916906, Microseconds:544238
Time spent sorting: Seconds 0, Microseconds:161368
```

Test #2b: Random Range [0,100]

```
$ ./sorttest2 10000 alt_sort_descending
(list of numbers) ...
Timestamp before sorting: Seconds 1675916972, Microseconds:242782
Timestamp after sorting: Seconds 1675916972, Microseconds:242860
Time spent sorting: Seconds 0, Microseconds:78
```

Running this test again with a different max and more numbers shows that optimized sort is 2068 times faster.

Test #3: Invalid sort_type

```
$ ./sorttest2 10 new_sort
"new_sort" is not a valid sort type!
Only "sort_descending" and "alt_sort_descending" are allowed.
```