

Issue I: Type Theory

Максим Сохацький¹

¹ Національний технічний університет України
Київський політехнічний інститут імені Ігоря Сікорського
8 травня 2019

Анотація

Martin-Löf Type Theory (MLTT), introduced by Per Martin-Löf in 1972 as MLTT-72, is a cornerstone of constructive mathematics, providing a foundation for formalizing mathematical proofs and programming languages. Its 1975 variant, MLTT-75, incorporates dependent types (Π , Σ) and identity types, with the J eliminator as a key construct for reasoning about equality. Historically, internalizing MLTT in a type checker while constructively proving the J eliminator has been challenging due to limitations in pure functional systems. This article presents a canonical formalization of MLTT-75 without disjoint union types and natural numbers \mathbb{N} , denoted as MLTT-73 and its complete internalization in **Per**, a minimal dependent type theory language equipped with cubical type primitives. Using presented type theory, we constructively prove all MLTT-73 inference rules, including the J eliminator, and demonstrate suitability as a robust type checker. We also provide logical, categorical, and homotopical interpretations of MLTT to contextualize its significance. This work advances the mechanization of constructive mathematics and offers a blueprint for future type-theoretic explorations.

Keywords: Martin-Löf Type Theory, Cubical Type Theory.

Зміст

1	Interpretations	3
1.1	Logical Interpretation	4
1.2	Categorical Interpretation	5
1.3	Homotopical Interpretation	5
1.4	Set-theoretical Interpretation	5
2	Dependent Type Theory	6
2.1	Dependent Product (Π)	6
2.2	Dependent Sum (Σ)	10
2.3	Path Space (Ξ)	12
2.4	MLTT-73	17

Introduction to MLTT-73

For decades, type theorists have sought to fully internalize Martin-Löf Type Theory (MLTT) within a type checker, a task akin to building a self-verifying blueprint for mathematics. Introduced by Per Martin-Löf in 1972 [2] and refined in 1975 [3], MLTT-75 is a foundational system that combines dependent types (Π for universal quantification, Σ for existential quantification) with identity types, enabling rigorous reasoning about equality. Central to MLTT-75 is the J eliminator, a rule that governs how identity proofs are used, but its constructive derivation has long eluded pure functional type checkers due to the complexity of equality types.

The MLTT-75 without Disjoint Union Types (+) and Natural Numbers (\mathbb{N}) we will denote MLTT-73. This article addresses this challenge by presenting a canonical formalization of MLTT-73 and its complete internalization in **Per**, a novel type theory language designed for constructive proofs. Leveraging cubical type theory [16], **Per** incorporates Path types and universe polymorphism to faithfully embed MLTT-73 rules, achieving a constructive proof of the J eliminator. This internalization serves as an ultimate test of a type checker’s robustness, verifying its ability to fuse introduction and elimination rules through beta and eta equalities.

To make MLTT accessible, we provide intuitive interpretations of its types: logical (as quantifiers), categorical (as functors), and homotopical (as spaces). These perspectives highlight MLTT’s role as a bridge between mathematics and computation. Our work builds on Martin-Löf’s vision of constructive mathematics, offering a minimal yet powerful framework for mechanized reasoning. We aim to inspire researchers and practitioners to explore type theory’s potential in formalizing mathematics and designing reliable software.

Syntax of Per

The BNF notation of type checker language used in code samples consists of: i) telescopes (contexts or sigma chains) and definitions; ii) pure dependent type theory syntax; iii) inductive data definitions (sum chains) and split eliminator; iv) cubical face system; v) module system. It is slightly based on cubicaltt.

```

F = module I where L
L =  $\emptyset$  | import I | def I T : O := O
T =  $\emptyset$  | ( I : O ) T
O = I | ( O ) | U | O  $\rightarrow$  O | O O
    |  $\Pi$  ( I : O ) , O |  $\lambda$  ( I : O ) , O
    |  $\Xi$  O O O O O |  $\langle$  O  $\rangle$  O | O @ O | transp O O
    | 0 | 1 |  $\neg$ O | O  $\wedge$  O | O  $\vee$  O |  $\square$ 
    |  $\Sigma$  ( I : O ) , O | O .1 | O .2 | O , O

```

Here = (definition), \emptyset (empty set), |, are parts of BNF language and \langle , \rangle , (,), :=, \vee , \wedge , \neg , \rightarrow , 0, 1, @, \square , **module**, **import**, **where**, **transp**, **.1**, **.2**, and , are terminals of type checker language.

1 Interpretations

Type-theoretical Interpretation

Martin-Löf Type Theory (MLTT), introduced by Per Martin-Löf in 1972 [2] and refined in 1975 [3], is a foundational system for constructive mathematics, blending logical rigor with computational expressiveness. Its 1975 variant, MLTT-75, centers on dependent types (Π , Σ) and identity types (Id), which underpin its ability to formalize mathematical reasoning and type checking. This section explores four interpretations of MLTT-75: logical, categorical, homotopical, and set-theoretical; — to illuminate its versatility and contextualize its internalization in the **Per** language. These perspectives reveal MLTT-75 as a unifying framework bridging logic, category theory, homotopy theory, and set theory, with each interpretation highlighting distinct aspects of its types and rules.

In MLTT, types are defined by five classes of rules: (1) *formation*, specifying the type’s signature; (2) *introduction*, defining constructors for its elements; (3) *elimination*, providing a dependent induction principle; (4) *computation* (beta-equality), governing reduction; and (5) *uniqueness* (eta-equality), ensuring canonical forms, though the latter is absent for identity types in homotopical settings.

For MLTT-73, we focus on Π (dependent function types), Σ (dependent pair types), and Id (identity types), with the latter replaced by Path types in cubical type theory to enable constructive proofs, such as the J eliminator, in **Per**. The identity type, introduced in MLTT-75 [3], is particularly significant, enabling reasoning about equality constructively. Unlike MLTT-72, which included only Π and Σ types, MLTT-75’s Id types originally enforced uniqueness of identity proofs (UIP) via an eta-rule.

However, modern homotopical interpretations, pioneered by Hofmann and Streicher [6], refute UIP, adopting Path types that model equality as paths in a space, aligning with cubical type theory’s constructive framework. This shift is crucial for **Per**, as Path types facilitate the internalization of MLTT-75’s rules.

Type checkers operate within contexts, binding variables to indexed universes, built-in types, or user-defined types via de Bruijn indices or names. These contexts enable queries about type derivability and code extraction, forming the core of **Per**’s type checker. By encoding MLTT-75’s syntax and rules, **Per** supports multiple interpretations, each offering unique insights into its structure and applications.

Type Theory	Logic	Category Theory	Homotopy Theory
A type	class	object	space
isProp A	proposition	(-1)-truncated object	space
a:A program	proof	generalized element	point
$B(x)$	predicate	indexed object	fibration
$b(x) : B(x)$	conditional proof	indexed elements	section
0	\perp false	initial object	empty space
1	\top true	terminal object	singleton
2	boolean	subobject classifier	\mathbb{S}^0
$A + B$	$A \vee B$ disjunction	coproduct	coproduct space
$A \times B$	$A \wedge B$ conjunction	product	product space
$A \rightarrow B$	$A \Rightarrow B$	internal hom	function space
$\sum x : A, B(x)$	$\exists_{x:A} B(x)$	dependent sum	total space
$\prod x : A, B(x)$	$\forall_{x:A} B(x)$	dependent product	space of sections
Path _A	equivalence $=_A$	path space object	path space A^I
quotient	equivalence class	quotient	quotient
W-type	induction	colimit	complex
type of types	universe	object classifier	universe
quantum circuit	proof net	string diagram	

1.1 Logical Interpretation

The logical interpretation casts MLTT-75 as a system for intuitionistic higher-order logic, where types correspond to propositions and terms to proofs, embodying the Curry-Howard correspondence. In this view, a type A represents a proposition, and a term $a : A$ is a proof of A . The Π -type, $\prod_{x:A} B(x)$, encodes universal quantification ($\forall x : A, B(x)$), while the Σ -type, $\sum_{x:A} B(x)$, represents existential quantification ($\exists x : A, B(x)$). The identity type, $\text{Id}_A(a, b)$, captures propositional equality ($a =_A b$), with the J eliminator providing a constructive means to reason about equalities.

Each type's five rules (formation, introduction, elimination, computation, and uniqueness, except for Id in cubical settings) mirror the structure of logical inference rules. For instance, the introduction rule for Π constructs a lambda term (proof of a universal statement), while its elimination rule applies the term to an argument (using the universal statement).

MLTT-75 is not standalone framework for constructive mathematics but rather the extended foundational core on top of MLTT-72. Adding **0** (Empty), **1** (Unit), **2** (Bool) types allows resulting type system to internalize intuitionistic propositional logic (IPL), via Gödel's double-negation translation, classical logic can be encoded within IPL [12]. In **Per**, this logical framework underpins the type checker's ability to verify MLTT-75's rules, ensuring constructive consistency.

1.2 Categorical Interpretation

The categorical interpretation models MLTT-75 within category theory, where types are objects, terms are morphisms, and type constructions are functors. This perspective, formalized by Cartmell and Seely [15], views MLTT-75 with **0**, **1**, **2** types as a locally cartesian closed category (LCCC). Here, Π -types correspond to dependent products (right adjoints to base change functors), and Σ -types to dependent sums (left adjoints). The identity type, Id_A , is modeled as a path space object, reflecting equality as a morphism.

For example, given a morphism $f : A \rightarrow B$ in a category, the Π_f functor maps a dependent type over B to one over A , generalizing function spaces, while Σ_f constructs the total space of a fibration. In **Per**, this interpretation informs the type checker’s handling of dependent types, with cubical primitives enabling precise categorical semantics for Path types. Topos-theoretical models, such as presheaves, further enrich this interpretation by treating fibrations as functors, aligning with MLTT-75’s expressive power [10].

1.3 Homotopical Interpretation

The homotopical interpretation, a breakthrough in modern type theory, views MLTT-75’s types as spaces and terms as points, with identity types as paths. Introduced by Hofmann and Streicher’s groupoid model [6], this perspective refutes the uniqueness of identity proofs (UIP) in classical MLTT-75, replacing Id with Path types that model equality as continuous paths in a space. In cubical type theory, Path types are functions from an interval $[0, 1]$ to a type, enabling constructive proofs of MLTT-75’s rules, including the J eliminator, in **Per**.

Here, Π -types represent spaces of sections, Σ -types denote total spaces of fibrations, and Path types form path spaces (A^I). This interpretation connects MLTT-75 to homotopy theory, where types are ∞ -groupoids, and fibrations (dependent types) are studied geometrically. For instance, a Π -type can be seen as a trivial fiber bundle, with its introduction rule constructing a section [1]. In **Per**, cubical primitives like connections and compositions support this interpretation, making MLTT-75’s internalization homotopically robust.

1.4 Set-theoretical Interpretation

The set-theoretical interpretation models MLTT-75’s types as sets and terms as elements, aligning with classical first-order logic. In this view, a type A is a set, and a term $a : A$ is an element. The Π -type represents a set of functions, Σ -type a disjoint union of sets, and $\text{Id}_A(a, b)$ an equality relation. However, this interpretation is limited, as it cannot capture higher equalities (e.g., paths between paths) or inductive types directly, due to its 0-truncated nature [1].

2 Dependent Type Theory

2.1 Dependent Product (Π)

Π is a dependent product type, the generalization of functions. As a function it can serve the wide range of mathematical constructions as its domain and codomain, which are in general: objects, types, or spaces; and could have as its instance: sets, functions, polynomial functors, infinitesimals, ∞ -groupoids, topological ∞ -groupoid, CW-complexes, categories, languages, etc.

At this light there could be many interpretation of Π types from different areas of mathematics. We give here three: i) logical interpretation of Π as \forall quantifier from higher order logic that forms a ground of type theory; ii) geometric interpretation of Π as fiber bundle; iii) categorical interpretation of functions as functors.

Type-theoretical interpretation

As a logical system dependent type theory could correspond to higher order logic. However here only type-theoretical model is given completely.

Definition 1 (Π -Formation). Π -types represents the way we create the spaces of dependent functions $f : \Pi(x : A), B(x)$ with domain in A and codomain in type family $B : A \rightarrow U$ over A .

$$\Pi(A, B) : U =_{def} \prod_{A:U} \prod_{B:A \rightarrow U} \prod_{x:A} B(x).$$

```
def Pi (A : U) (B : A → U) : U := Π (x : A), B x
```

Definition 2 (Π -Introduction). Lambda constructor defines a new lambda function in the space of dependent functions. It is called lambda abstraction and displayed as $\lambda x.b(x)$ or $x \mapsto b(x)$.

$$\lambda(x : A), b(x) : \Pi(A, B) =_{def}$$

$$\prod_{A:U} \prod_{B:A \rightarrow U} \prod_{b:\Pi(A,B)} \lambda x, b_x.$$

```
def lambda (A: U) (B: A → U) (b: Π A B) : Π A B := λ (x : A), b x
def lam (A B: U) (f: A → B) : A → B := λ (x : A), f x
```

When codomain is not dependent on valude from domain the function $f : A \rightarrow B$ is studied in System F_ω , dependent case in studied in System P_ω or Calculus of Construction (CoC).

Definition 3 (Π -Induction Principle). States that if predicate holds for lambda function then there is a function from function space to the space of predicate.

def Π -ind (A : U) (B : A \rightarrow U) (C : Π A B \rightarrow U) (g : Π (x : Π A B), C x)
 : Π (p : Π A B), C p := λ (p : Π A B), g p

Definition 4 (Π -Elimination). Application reduces the term by using recursive substitution.

$$f\ a : B(a) =_{def} \prod_{A:U} \prod_{B:A \rightarrow U} \prod_{a:A} \prod_{f:\prod_{x:A} B(x)} f(a).$$

def apply (A: U) (B: A \rightarrow U) (f: Π A B) (a: A) : B a := f a
 def app (A B: U) (f: A \rightarrow B) (x: A) : B := f x

Theorem 1 (Π -Composition). Composition is using application of appropriate singnatures.

$$f(a) =_{B(a)} (\lambda(x : A) \rightarrow f(a))(a).$$

def \circ^\top (α β γ : U) : U
 := ($\beta \rightarrow \gamma$) \rightarrow ($\alpha \rightarrow \beta$) \rightarrow ($\alpha \rightarrow \gamma$)

def \circ (α β γ : U) : \circ^\top α β γ
 := λ (g : $\beta \rightarrow \gamma$) (f : $\alpha \rightarrow \beta$) (x : α), g (f x)

Theorem 2 (Π -Computation). β -rule shows that composition $\text{lam} \circ \text{app}$ could be fused.

$$f(a) =_{B(a)} (\lambda(x : A) \rightarrow f(a))(a).$$

def Π - β (A : U) (B : A \rightarrow U) (a : A) (f : Π A B)
 : Path (B a) (apply A B (lambda A B f) a) (f a)
 := idp (B a) (f a)

Theorem 3. (Π -Uniqueness). η -rule shows that composition $\text{app} \circ \text{lam}$ could be fused.

$$f =_{(x:A) \rightarrow B(a)} (\lambda(y : A) \rightarrow f(y)).$$

def Π - η (A : U) (B : A \rightarrow U) (a : A) (f : Π A B)
 : Path (Π A B) f (λ (x : A), f x)
 := idp (Π A B) f

Categorical interpretation

The adjoints Π and Σ is not the only adjoints could be presented in type system. Axiomatic cohesions could contain a set of adjoint pairs as a core type checker operations.

Definition 5 (Dependent Product). The dependent product along morphism $g : B \rightarrow A$ in category C is the right adjoint $\Pi_g : C_{/B} \rightarrow C_{/A}$ of the base change functor.

Definition 6 (Space of Sections). Let \mathbf{H} be a $(\infty, 1)$ -topos, and let $E \rightarrow B : \mathbf{H}/_B$ a bundle in \mathbf{H} , object in the slice topos. Then the space of sections $\Gamma_\Sigma(E)$ of this bundle is the Dependent Product:

$$\Gamma_\Sigma(E) = \Pi_\Sigma(E) \in \mathbf{H}.$$

Theorem 4 (Homotopy Equivalence). If fiber space is set for all base, and there are two functions $f, g : (x : A) \rightarrow B(x)$ and two homotopies between them, then these homotopies are equal.

```
def setPi (A: U) (B: A → U)
  (h: Π (x: A), isSet (B x)) (f g: Pi A B)
  (p q: Path (Pi A B) f g)
  : Path (Path (Pi A B) f g) p q
```

Theorem 5 (Contractability). If domain and codomain is contractible then the space of sections is contractible.

```
def piIsContr (A: U) (B: A → U) (u: isContr A)
  (q: Π (x: A), isContr (B x))
  : isContr (Pi A B)
```

Definition 7 (Section). A section of morphism $f : A \rightarrow B$ in some category is the morphism $g : B \rightarrow A$ such that $f \circ g : B \xrightarrow{g} A \xrightarrow{f} B$ equals the identity morphism on B .

Homotopical interpretation

Geometrically, Π type is a space of sections, while the dependent codomain is a space of fibrations. Lambda functions are sections or points in these spaces, while the function result is a fibration. Π type also represents the cartesian family of sets, generalizing the cartesian product of sets.

Definition 8. (Fiber). The fiber of the map $p : E \rightarrow B$ in a point $y : B$ is all points $x : E$ such that $p(x) = y$.

Definition 9. (Fiber Bundle). The fiber bundle $F \rightarrow E \xrightarrow{p} B$ on a total space E with fiber layer F and base B is a structure (F, E, p, B) where $p : E \rightarrow B$ is a surjective map with following property: for any point $y : B$ exists a neighborhood U_b for which a homeomorphism $f : p^{-1}(U_b) \rightarrow U_b \times F$ making the following diagram commute.

$$\begin{array}{ccc} p^{-1}(U_b) & \xrightarrow{f} & U_b \times F \\ p \downarrow & \swarrow pr_1 & \\ U_b & & \end{array}$$

Definition 10. (Cartesian Product of Family over B). Is a set F of sections of the bundle with elimination map $app : F \times B \rightarrow E$ such that

$$F \times B \xrightarrow{app} E \xrightarrow{pr_1} B \quad (1)$$

pr_1 is a product projection, so pr_1, app are morphisms of slice category Set/B . The universal mapping property of F : for all A and morphism $A \times B \rightarrow E$ in Set/B exists unique map $A \rightarrow F$ such that everything commute. So a category with all dependent products is necessarily a category with all pullbacks.

Definition 11 (Trivial Fiber Bundle). When total space E is cartesian product $\Sigma(B, F)$ and $p = pr_1$ then such bundle is called trivial $(F, \Sigma(B, F), pr_1, B)$.

Theorem 6 (Functions Preserve Paths). For a function $f : (x : A) \rightarrow B(x)$ there is an $ap_f : x =_A y \rightarrow f(x) =_{B(x)} f(y)$. This is called application of f to path or congruence property (for non-dependent case — *cong* function). This property behaves functorially as if paths are groupoid morphisms and types are objects.

Theorem 7 (Trivial Fiber Bundle equals Family of Sets). Inverse image (fiber) of fiber bundle $(F, B * F, pr_1, B)$ in point $y : B$ equals $F(y)$.

```
def Family (B : U) : U1 := B → U
def Fibration (B : U) : U1 := Σ (X : U), X → B

def encode-Pi (B : U) (F : B → U) (y : B)
  : fiber (Sigma B F) B (pr1 B F) y → F y
:= λ (x : fiber (Sigma B F) B (pr1 B F) y),
    subst B F x.1.1 y (<i> x.2 @ -i) x.1.2

def decode-Pi (B : U) (F : B → U) (y : B)
  : F y → fiber (Sigma B F) B (pr1 B F) y
:= λ (x : F y), ((y, x), idp B y)

def decode-encode-Pi (B : U) (F : B → U) (y : B) (x : F y)
  : Path (F y) (transp (<i> F (idp B y @ i)) 0 x) x
:= <j> transp (<i> F y) j x

def encode-decode-Pi (B : U) (F : B → U) (y : B)
  (x : fiber (Sigma B F) B (pr1 B F) y)
  : Path (fiber (Sigma B F) B (pr1 B F) y)
    ((y, encode-Pi B F y x), idp B y) x
:= <i> ( (x.2 @ i, transp (<j> F (x.2 @ i ∨ -j)) i x.1.2),
    <j> x.2 @ i ∧ j )

def Bundle=P (B : U) (F : B → U) (y : B)
  : PathP (<_> U) (fiber (Sigma B F) B (pr1 B F) y) (F y)
:= iso→Path (fiber (Sigma B F) B (pr1 B F) y) (F y)
  (encode-Pi B F y) (decode-Pi B F y)
  (decode-encode-Pi B F y) (encode-decode-Pi B F y)
```

2.2 Dependent Sum (Σ)

Σ -type is a space that contains dependent pairs where type of the second element depends on the value of the first element. As only one point of fiber domain present in every defined pair, Σ -type is also a dependent sum, where fiber base is a disjoint union.

Σ is a dependent sum type, the generalization of products. Σ type is a total space of fibration. Element of total space is formed as a pair of basepoint and fibration.

Spaces of dependent pairs are using in type theory to model cartesian products, disjoint sums, fiber bundles, vector spaces, telescopes, lenses, contexts, objects, algebras, \exists -type, etc.

Type-theoretical interpretation

Definition 12 (Σ -Formation). The dependent sum type is indexed over type A in the sense of coproduct or disjoint union, where only one fiber codomain $B(x)$ is present in pair.

$$\Sigma(A, B) : U =_{def} \prod_{A:U} \prod_{B:A \rightarrow U} \sum_{x:A} B(x).$$

def Sigma (A: U) (B: A \rightarrow U) : U := Σ (x: A), B(x)

Definition 13 (Σ -Introduction). The dependent pair constructor is a way to create indexed pair over type A in the sense of coproduct or disjoint union.

$$\text{pair} : \Sigma(A, B) =_{def} \prod_{A:U} \prod_{B:A \rightarrow U} \prod_{a:A} \prod_{b:B(a)} (a, b).$$

def pair (A: U) (B: A \rightarrow U) (a: A) (b: B a) : Sigma A B := (a, b)

Definition 14 (Σ -Elimination). The dependent projections $pr_1 : \Sigma(A, B) \rightarrow A$ and $pr_2 : \prod_{x:\Sigma(A, B)} B(pr_1(x))$ are pair deconstructors.

$$pr_1 : \prod_{A:U} \prod_{B:A \rightarrow U} \prod_{x:\Sigma(A, B)} A =_{def} .1 =_{def} (a, b) \mapsto a.$$

$$pr_2 : \prod_{A:U} \prod_{B:A \rightarrow U} \prod_{x:\Sigma(A, B)} B(x.1) =_{def} .2 =_{def} (a, b) \mapsto b.$$

def pr₁ (A: U) (B: A \rightarrow U) (x: Sigma A B) : A := x.1
def pr₂ (A: U) (B: A \rightarrow U) (x: Sigma A B) : B (pr₁ A B x) := x.2

Definition 15 (Σ -Induction). States that if predicate holds for two projections then predicate holds for total space.

```

def  $\Sigma$ -ind (A : U) (B : A  $\rightarrow$  U)
  (C :  $\Pi$  (s :  $\Sigma$  (x : A), B x), U)
  (g :  $\Pi$  (x : A) (y : B x), C (x, y))
  (p :  $\Sigma$  (x : A), B x)
  : C p := g p.1 p.2

```

Theorem 8 (Σ -Computation). $\text{def } \Sigma\text{-}\beta_1$ (A : U) (B : A \rightarrow U) (a : A) (b : B a) : Path A a (pr₁ A B (a, b)) := idp A a

```

def  $\Sigma\text{-}\beta_2$  (A : U) (B : A  $\rightarrow$  U) (a : A) (b : B a)
  : Path (B a) b (pr2 A B (a, b)) := idp (B a) b

```

Theorem 9 (Σ -Uniqueness). $\text{def } \Sigma\text{-}\eta$ (A : U) (B : A \rightarrow U) (p : Sigma A B) : Path (Sigma A B) p (pr₁ A B p, pr₂ A B p) := idp (Sigma A B) p

Categorical interpretation

Definition 16. (Dependent Sum). The dependent sum along the morphism $f : A \rightarrow B$ in category C is the left adjoint $\Sigma_f : C/A \rightarrow C/B$ of the base change functor.

Set-theoretical interpretation

Theorem 10. (Axiom of Choice). If for all $x : A$ there is $y : B$ such that $R(x, y)$, then there is a function $f : A \rightarrow B$ such that for all $x : A$ there is a witness of $R(x, f(x))$.

```

def ac (A B : U) (R : A  $\rightarrow$  B  $\rightarrow$  U)
  (g :  $\Pi$  (x : A),  $\Sigma$  (y : B), R x y)
  :  $\Sigma$  (f : A  $\rightarrow$  B),  $\Pi$  (x : A), R x (f x)
  := ( $\backslash$  (i : A), (g i).1,  $\backslash$  (j : A), (g j).2)

```

Theorem 11. (Total). If fiber over base implies another fiber over the same base then we can construct total space of section over that base with another fiber.

```

def total (A : U) (B C : A  $\rightarrow$  U)
  (f :  $\Pi$  (x : A), B x  $\rightarrow$  C x)
  (w :  $\Sigma$  (x : A), B x)
  :  $\Sigma$  (x : A), C x := (w.1, f (w.1) (w.2))

```

Theorem 12. (Path Between Sigmas). Path between two sigmas $t, u : \Sigma(A, B)$ could be decomposed to sigma of two paths $p : t_1 =_A u_1$ and $(t_2 =_{B(p @ i)} u_2)$.

```

def pathSig (A : U) (P : A  $\rightarrow$  U)
  (t u :  $\Sigma$  (x : A), P x) (p : PathP (<lt;_>A) t.1 u.1)
  : PathP (<lt;_>U) (PathP (<i> P (p @ i)) t.2 u.2)
  (PathP (<_>P u.1)
    (hcomp (P u.1) 0 ( $\lambda$ (k : I), []))
    (transp (<lt;_> P (p @ i)) 0 t.2)) u.2)

```

2.3 Path Space (Ξ)

The homotopy identity system defines a **Path** space indexed over type A with elements as functions from interval $[0, 1]$ to values of that path space $[0, 1] \rightarrow A$. HoTT book defines two induction principles for identity types: path induction and based path induction.

This ctt file reflects ¹CCHM cubicaltt model with connections. For ²ABCFHL yacctt model with variables please refer to ytt file. You may also want to read ³BCH, ⁴AFH. There is a ⁵PO paper about CCHM axiomatic in a topos.

Type-theoretical interpretation

Definition 17 (Path Formation).

$$\Xi : U =_{def} \prod_{A:U} \prod_{x,y:A} \mathbf{Path}_A(x, y).$$

```
def Path (A : U) (x y : A) : U
:= PathP (<_> A) x y

def Path' (A : U) (x y : A)
:=  $\Pi (i : I), A [\partial i] \multimap [(i = 0) \rightarrow x, (i = 1) \rightarrow y]$ 
```

Definition 18 (Path Introduction).

$$\mathbf{idp} : x \equiv_A x =_{def} \prod_{A:U} \prod_{x:A} [i]x.$$

```
def idp (A : U) (x : A) : Path A x x := <_> x
```

Returns a reflexivity path space for a given value of the type. The inhabitant of that path space is the lambda on the homotopy interval $[0, 1]$ that returns a constant value x . Written in syntax as $[i]x$.

Definition 19 (Path Application). You can apply face to path.

```
def at0 (A : U) (a b : A) (p : Path A a b) : A := p @ 0
def at1 (A : U) (a b : A) (p : Path A a b) : A := p @ 1
```

¹Cyril Cohen, Thierry Coquand, Simon Huber, Anders Mörtberg. Cubical Type Theory: a constructive interpretation of the univalence axiom. 2015. <https://5ht.co/cubicaltt.pdf>

²Carlo Angiuli, Brunerie, Coquand, Kuen-Bang Hou (Favonia), Robert Harper, Dan Licata. Cartesian Cubical Type Theory. 2017. <https://5ht.co/ccctt.pdf>

³Marc Bezem, Thierry Coquand, Simon Huber. A model of type theory in cubical sets. 2014. <http://www.cse.chalmers.se/~coquand/mod1.pdf>

⁴Carlo Angiuli, Kuen-Bang Hou (Favonia), Robert Harper. Cartesian Cubical Computational Type Theory: Constructive Reasoning with Paths and Equalities. 2018. <https://www.cs.cmu.edu/~cangiuli/papers/ccctt.pdf>

⁵Andrew Pitts, Ian Orton. Axioms for Modelling Cubical Type Theory in a Topos. 2016. <https://arxiv.org/pdf/1712.04864.pdf>

Definition 20 (Path Composition). Composition operation allows to build a new path by given to paths in a connected point.

$$\begin{array}{ccc} & a & \xrightarrow{comp} c \\ \lambda(i : I) \rightarrow a \uparrow & & \uparrow q \\ a & \xrightarrow{p @ i} & b \end{array}$$

```
def pcomp (A : U) (a b c : A) (p : Path A a b) (q : Path A b c)
  : Path A a c
:= <i> hcomp A (∂ i) (λ (j : I), [(i = 0) → a,
                                   (i = 1) → q @ j]) (p @ i)
```

Theorem 13 (Path Inversion).

```
def inv (A : U) (a b : A) (p : Path A a b) : Path A b a := <i> p @ -i
```

Definition 21 (Connections). Connections allows you to build square with given only one element of path: i) $\lambda (i, j : I) \rightarrow p @ \min(i, j)$; ii) $\lambda (i, j : I) \rightarrow p @ \max(i, j)$.

$$\begin{array}{ccc} & a & \xrightarrow{p} b \\ \lambda(i : I) \rightarrow a \uparrow & & \uparrow p \\ a & \xrightarrow{\lambda(i : I) \rightarrow a} & a \end{array} \quad \begin{array}{ccc} & b & \xrightarrow{\lambda(i : I) \rightarrow b} b \\ p \uparrow & & \uparrow \lambda(i : I) \rightarrow b \\ a & \xrightarrow{p} & b \end{array}$$

```
def meet (A : U) (a b : A) (p : Path A a b)
  : PathP (<x> Path A a (p @ x)) (<i>a) p
= <x y> p @ (x /\ y)
```

```
def join (A : U) (a b : A) (p : Path A a b)
  : PathP (<x> Path A (p @ x) b) p (<i>b)
= <y x> p @ (x \/ y)
```

Theorem 14 (Congruence). Is a map between values of one type to path space of another type by an encode function between types. Implemented as lambda defined on $[0, 1]$ that returns application of encode function to path application of the given path to lamda argument $\lambda(i : I), f(p @ i)$ for both cases.

$$ap : f(a) \equiv f(b) =_{def}$$

$$\prod_{A:U} \prod_{a,x:A} \prod_{B:A \rightarrow U} \prod_{f:\Pi(A,B)} \prod_{p:a \equiv_A x} [i]f(p @ i).$$

```

def ap (A B: U) (f: A → B) (a b: A) (p: Path A a b)
  : Path B (f a) (f b)

def apd (A: U) (a x: A) (B: A → U)
  (f: A → B a) (b: B a) (p: Path A a x)
  : Path (B a) (f a) (f x)

```

Theorem 15 (Generalized Transport Kan Operation). Transports a value of the left type to the value of the right type by a given path element of the path space between left and right types.

$$\text{transport} : A(0) \rightarrow A(1) =_{def}$$

$$\prod_{A:I \rightarrow U} \prod_{r:I} \lambda x, \mathbf{transp}([i]A(i), 0, x).$$

```

def transp' (A: U) (x y: A) (p : PathP (<_>A) x y) (i: I)
  := transp (<i> (\(_:A), A) (p @ i)) i x

def transp-U (A B: U) (p : PathP (<_>U) A B) (i: I)
  := transp (<i> (\(_:U), U) (p @ i)) i A

```

Definition 22. (Singleton).

```

def singl (A: U) (a: A): U := Σ (x: A), Ξ A a x

```

Theorem 16. (Singleton Instance).

```

def eta (A: U) (a: A): singl A a := (a, idp A a)

```

Theorem 17. (Singleton Contractability).

```

def contr (A : U) (a b : A) (p : Ξ A a b)
  : Ξ (singl A a) (eta A a) (b, p)
  := <i> (p @ i, <j> p @ i /\ j)

```

Theorem 18. (Path Elimination).

```

def subst (A : U) (P : A → U) (a b : A)
  (p : Ξ A a b) (e : P a) : P b
  := transp (<i> P (p @ i)) 0 e

def D (A : U) : U1
  := Π (x y : A), Path A x y → U

def J (A: U) (x: A) (C: D A) (d: C x x (idp A x))
  (y: A) (p: Ξ A x y) : C x y p
  := subst (singl A x) (\ (z: singl A x), C x (z.1) (z.2))
    (eta A x) (y, p) (contr A x y p) d

```

Theorem 19. (Path Computation).

```

def trans_comp (A : U) (a : A)
  :  $\Xi A a$  (transport A A (<i>A) a)
  := <j> transp (<_> A) -j a

def subst_comp (A: U) (P: A  $\rightarrow$  U) (a: A) (e: P a)
  :  $\Xi$  (P a) e (subst A P a a (idp A a) e)
  := trans_comp (P a) e

def J- $\beta$  (A : U) (a : A) (C : D A) (d: C a a (idp A a))
  :  $\Xi$  (C a a (idp A a)) d (J A a C d a (idp A a))
  := subst_comp (singl A a)
    (\ (z: singl A a), C a (z.1) (z.2)) (eta A a) d

```

Note that Path type has no Eta rule due to groupoid interpretation.

Groupoid interpretation

The groupoid interpretation of type theory is well known article by Martin Hofmann and Thomas Streicher, more specific interpretation of identity type as infinity groupoid.

Contexts

Speaking of type checker execution, we introduce context or dictionary with types and terms, from which we can derive typed variables. This chain could be implemented as nested sigma types (due to R.A.G.Seely) or list types (due to Voevodsky). Categorically dependent type theory is built upon categories of contexts.

Definition 23. (Empty Context).

$$\gamma_0 : \Gamma =_{def} \star.$$

Definition 24. (Context Comprehension).

$$\Gamma ; A =_{def} \sum_{\gamma:\Gamma} A(\gamma).$$

Definition 25. (Context Derivability).

$$\Gamma \vdash A =_{def} \prod_{\gamma:\Gamma} A(\gamma).$$

Definition 26. (Terms). Point in initial object of language AST inductive definition is called a term. If type theory or language is defined as an inductive type (AST) then the term is defined as its instance.

Definition 27. (Sorts). N-indexed set of universes $U_{n \in \mathbb{N}}$. Could have any number of elements which defines different type systems. All built-in types as long as user defined types are landed usually by default in U_0 universe. Sorts represented in type checker as a separate constructor.

Universes

Definition 28. (Axioms). The inclusion rules $U_i : U_j, i, j \in \mathbb{N}$, that define which universe is element of another given universe. You may attach any rules that joins i, j in some way. Axioms with sorts define universe hierarchy.

Definition 29. (Rules). The set of landings $U_i \rightarrow U_j : U_{\lambda(i,j), i,j \in \mathbb{N}}$, where $\lambda : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$. These rules define term dependence or how we land (in which universe) formation rules in definitions.

Definition 30. (Predicative hierarchy). If λ in Rules is an uncurried function $\max : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$ then such universe hierarchy is called predicative.

Definition 31. (Impredicative hierarchy). If λ in Rules is a second projection of a tuple $\text{snd} : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$ then such universe hierarchy is called impredicative.

Definition 32. (Definitional Equality). For any $U_i, i \in \mathbb{N}$ there is defined an equality between its members and between its instances. For all $x, y \in A$, there is defined a $x=y$. Definitional equality compares normalized term instances.

Definition 33. (SAR). The universum space is configured with a triple of: i) sorts, a set of universes $U_{n \in \mathbb{N}}$ indexed over set \mathbb{N} ; ii) axioms, a set of inclusions $U_i : U_j, i, j \in \mathbb{N}$; iii) rules of term dependence universe landing, a set of landings $U_i \rightarrow U_j : U_{\lambda(i,j), i,j \in \mathbb{N}}$, where λ could be function *max* (predicative) or *snd* (impredicative).

Example 1. (CoC). $\text{SAR} = \{\{\star, \square\}, \{\star : \square\}, \{i \rightarrow j : j; i, j \in \{\star, \square\}\}$. Terms live in universe \star , and types live in universe \square . In CoC $\lambda = \text{snd}$.

Example 2. (PTS^∞ , MLTT^∞).

$\text{SAR} = \{U_{i \in \mathbb{N}}, U_i : U_{j; i < j; i, j \in \mathbb{N}}, U_i \rightarrow U_j : U_{\lambda(i,j); i, j \in \mathbb{N}}\}$. Where U_i is a universe of i -level or i -category in categorical interpretation.

2.4 MLTT-73

Here is given formal model of type-theoretical interpretation of Martin-Löf Type Theory. It combines 4 Path rules (no eta), 5 Π rules, and 6 Σ rules (two elims). The proof is provided by direct embedding (internalizing) the model into the model of type checker which is even more powerful.

Definition 34. (MLTT-73). The MLTT as a Type is defined by taking all rules for Π , Σ and Path types into one Σ telescope or context.

```
def MLTT (A : U) : U1 :=
  Σ (Π-form : Π (B : A → U), U)
    (Π-ctor1 : Π (B : A → U), Π A B → Π A B)
    (Π-elim1 : Π (B : A → U), Π A B → Π A B)
    (Π-comp1 : Π (B : A → U) (a : A) (f : Π A B),
      ≡ (≡ (B a) (Π-elim1 B (Π-ctor1 B f) a) (f a)))
    (Π-comp2 : Π (B : A → U) (a : A) (f : Π A B),
      ≡ (Π A B) f (λ (x : A), f x))
    (Σ-form : Π (B : A → U), U)
    (Σ-ctor1 : Π (B : A → U) (a : A) (b : B a), Sigma A B)
    (Σ-elim1 : Π (B : A → U) (p : Sigma A B), A)
    (Σ-elim2 : Π (B : A → U) (p : Sigma A B), B (pr1 A B p))
    (Σ-comp1 : Π (B : A → U) (a : A) (b : B a),
      ≡ A a (Σ-elim1 B (Σ-ctor1 B a b)))
    (Σ-comp2 : Π (B : A → U) (a : A) (b : B a),
      ≡ (B a) b (Σ-elim2 B (a, b)))
    (Σ-comp3 : Π (B : A → U) (p : Sigma A B),
      ≡ (Sigma A B) p (pr1 A B p, pr2 A B p))
    (=form : Π (a : A), A → U)
    (=ctor1 : Π (a : A), Path A a a)
    (=elim1 : Π (a : A) (C : D A) (d : C a a (=ctor1 a))
      (y : A) (p : Path A a y), C a y p)
    (=comp1 : Π (a : A) (C : D A) (d : C a a (=ctor1 a)),
      ≡ (C a a (=ctor1 a)) d
      (=elim1 a C d a (=ctor1 a))), 1
```

Theorem 20. (Model Check). There is an instance of MLTT.

```
def internalizing (A : U)
  : MLTT A
:= ( Π A, Π-lambda A, Π-apply A, Π-β A, Π-η A,
    Sigma A, pair A, pr1 A, pr2 A, Σ-β1 A, Σ-β2 A, Σ-η A,
    Path A, idp A, J A, J-β A, ★
  )
```

The result of the work is a `mltt.ctt` file which can be runned using `cubicaltt`. Note that MLTT-73 internalization includes only eliminator and computational rule (without uniqueness rule) for identity system, as cubical Path spaces refute uniqueness of identity proofs.

Conclusions

This article presents a landmark achievement in type theory: the constructive internalization of Martin-Löf Type Theory (MLTT-73) within the **Per** language, a minimal type system equipped with cubical type theory primitives. By embedding MLTT-73’s core types — dependent function types (Π), dependent pair types (Σ), and identity types (Id, modeled as Path (Ξ) types in cubical syntax) — we have constructively verified all inference rules, including the pivotal J eliminator, using the cubical type checker [16].

This internalization, formalized in the `mltt.ctt` file and validated with `cubicaltt`, marks a significant advance in mechanized reasoning, as it provides a rigorous test of a type checker’s ability to fuse introduction and elimination rules through beta and eta equalities.

Language	U^n	Π	Σ	Id	Ξ	\mathbb{N}	0/1/2	W	Ind
System P_ω (CoC-88)		x							
MLTT-72		x	x						
Henk (ECC)	x	x							
Errett (LCCC/IPL)	x	x	x				x		
MLTT-73	x	x	x	x					
Per	x	x	x		x				
MLTT-75	x	x	x	x		x	x		
MLTT-80	x	x	x	x			x	x	
Anders (HTS)	x	x	x	x	x		x	x	
Frank (CoC+CIC)	x	x							x
Christine (Coq)	x	x	x	x					x
cubicaltt		x	x		x				x
Agda	x	x	x	x	x				x
Lean	x	x	x	x					x
NuPRL		x	x	x					x

The significance of this work lies in its constructive approach to the J eliminator, a cornerstone of MLTT-73’s identity type, which previous internalization attempts failed to derive constructively [3, 12]. By leveraging cubical type theory’s Path types and operations (e.g., connections, compositions), **Per** achieves a compact and robust framework for encoding MLTT-73, as demonstrated by the type-theoretical model presented herein. The article also elucidates MLTT-73’s versatility through logical, categorical, homotopical, and set-theoretical interpretations, offering a comprehensive landscape for researchers and newcomers to type theory.

The internalization of MLTT-73 in **Per** advances the mechanization of constructive mathematics by providing a verified foundation for type checkers. **Per**’s cubical framework ensures that all inference rules, except for Path types refuting UIP are derivable, fulfilling a core objective of constructive reasoning: verifiable mathematical proofs.

Література

- [1] Vladimir Voevodsky et al., *Homotopy Type Theory*, in *Univalent Foundations of Mathematics*, 2013.
- [2] Per Martin-Löf and Giovanni Sambin, *The Theory of Types*, in *Studies in Proof Theory*, 1972.
- [3] Per Martin-Löf, *An Intuitionistic Theory of Types: Predicative Part*, in *Studies in Logic and the Foundations of Mathematics*, vol. 80, pp. 73–118, 1975. doi:10.1016/S0049-237X(08)71945-1
- [4] Per Martin-Löf and Giovanni Sambin, *Intuitionistic Type Theory*, in *Studies in Proof Theory*, 1984.
- [5] Thierry Coquand and Gérard Huet, *The Calculus of Constructions*, in *Information and Computation*, pp. 95–120, 1988. doi:10.1016/0890-5401(88)90005-3
- [6] Martin Hofmann and Thomas Streicher, *The Groupoid Interpretation of Type Theory*, in *Venice Festschrift*, Oxford University Press, pp. 83–111, 1996.
- [7] Claudio Hermida and Bart Jacobs, *Fibrations with Indeterminates: Contextual and Functional Completeness for Polymorphic Lambda Calculi*, in *Mathematical Structures in Computer Science*, vol. 5, pp. 501–531, 1995.
- [8] Alexandre Buisse and Peter Dybjer, *The Interpretation of Intuitionistic Type Theory in Locally Cartesian Closed Categories – an Intuitionistic Perspective*, in *Electronic Notes in Theoretical Computer Science*, pp. 21–32, 2008. doi:10.1016/j.entcs.2008.10.003
- [9] Andreas Abel, Thierry Coquand, and Peter Dybjer, *On the Algebraic Foundation of Proof Assistants for Intuitionistic Type Theory*, in *Functional and Logic Programming*, Springer, Berlin, Heidelberg, pp. 3–13, 2008.
- [10] Pierre-Louis Curien et al., *Revisiting the Categorical Interpretation of Dependent Type Theory*, in *Theoretical Computer Science*, vol. 546, pp. 99–119, 2014. doi:10.1016/j.tcs.2014.03.003
- [11] Errett Bishop, *Foundations of Constructive Analysis*, 1967.
- [12] Bengt Nordström, Kent Petersson, and Jan M. Smith, *Programming in Martin-Löf’s Type Theory*, Oxford University Press, 1990.
- [13] Matthieu Sozeau and Nicolas Tabareau, *Internalizing Intensional Type Theory*, unpublished.
- [14] Martin Hofmann and Thomas Streicher, *The Groupoid Model Refutes Uniqueness of Identity Proofs*, in *Logic in Computer Science (LICS’94)*, IEEE, pp. 208–212, 1994.

- [15] Bart Jacobs, *Categorical Logic and Type Theory*, vol. 141, 1999.
- [16] Anders Mörtberg et al., *Cubical Type Theory: A Constructive Interpretation of the Univalence Axiom*, arXiv:1611.02108, 2017.
- [17] Simon Huber, *Cubical Interpretations of Type Theory*, Ph.D. thesis, Dept. of Computer Science and Engineering, University of Gothenburg, 2016.
- [18] Maksym Sokhatskyi and Pavlo Maslianko, *The Systems Engineering of Consistent Pure Language with Effect Type System for Certified Applications and Higher Languages*, in *Proc. 4th Int. Conf. Mathematical Models and Computational Techniques in Science and Engineering*, 2018. doi:10.1063/1.5045439