JAMES manual

Stef van Buuren

2020-03-05

Contents

1	Prerequisites	5
2	Introduction	7
3	JAMES data format	9
	3.1 Objective	9
	3.2 Generic object model	9
	3.3 BDS-elements	11
	3.4 Error checking	12
4	Growth charts in JAMES	15
	4.1 Chart naming conventions	15
5	Methods	19
6	D-score implementation	21
	6.1 Actions	21

4 CONTENTS

Prerequisites

This is very, very first minimal documentation of JAMES internals.

Introduction

Here's an introduction about JAMES

JAMES data format

3.1 Objective

This chapter describes the format of the input data accepted by JAMES. The specification

- closely follows the definition of the Basisdataset JGZ 3.25 (2018);
- defines data objects;
- defines the actions taken by JAMES in case of incorrect, missing or out-of-range data;
- defines the error messages for informing the client.

3.2 Generic object model

3.2.1 EPremDossier Class

3.2.1.1 Object model

EPremDossier	Instance	Class
->	Clientgegevens	EPremGroep
->	Contactmomenten	EPremContactmoment

3.2.1.2 Syntax C#

public class EPremDossier

3.2.1.3 Public properties

Name	Description	Required
Clientgegevens	Class with basic child data	Y
Contactmomenten	Class with data per visit	N
InstrumentCode	Integer identifying the instrument	Ignored
OrganisatieCode	Integer identifying the care organisation	Y
Referentie	String identifying the request	N

3.2.2 EPremGroep Class

3.2.2.1 Object model

EPremGroep	Instance	Class
->	Elementen	EPremElement
->	Groepen	EPremGroep

3.2.2.2 Syntax C#

public class EPremGroep

3.2.2.3 Public properties

Name	Description	Required
Elementen	Class with BDS-elements	Y
Groepen	Class with groups of BDS-elements	N

3.2.3 EPremElement Class

3.2.3.1 Syntax C#

public class EPremElement

3.2.3.2 Public properties

Name	Description	Required
Bdsnummer	Integer identifying the BDS-field	Y

Name	Description	Required
InternNummer	Integer identifying internal field	Ignored
Waarde	Value of the BDS-field	Y
Waardeomschrijving	Descriptive label for value	Ignored

3.2.4 EPremContactmoment Class

3.2.4.1 Object model

EPremContactmoment	Instance	Class
-> ->		EPremElement EPremGroep

3.2.4.2 Syntax C#

 $\verb"public class EPremContactmoment": EPremGroep"$

3.2.4.3 Public properties

Name	Description	Required
Elementen	Class with BDS-elements	Y
Groepen	Class with groups of BDS-elements	N
Tijdstip	Date of visit	Y

3.3 BDS-elements

BDS	Description	Value	Label	Required
19	Sex of child	"0"	Unknown	Y
		"1"	Male	
		"2"	Female	
		"3"	Not specified	
20	Date of birth	"yyyymmdd"	year-month-day	Y
62	Caretaker relation	"01"	biological father	N
		"02"	biological mother	
		"03"	male partner, stepfather	
		"04"	female partner, stepmother	
		"05"	adoptive father	
		"06"	adoptive mother	

BDS	Description	Value	Label	Required
		"07"	foster father	
		"08"	foster mother	
		"98"	other	
63	Caretaker date of birth	"yyyymmdd"	year-month-day	N
66	Caretaker education	"01"	no primary school	N
		"02"	primary school, special ed	
		"03"	VSO-MLK/IVBO/VMBO-LWOO	
		"04"	LBO/VBO/VMBO-BBL&KBL	
		"05"	MAVO/VMBO-GL&TL	
		"06"	MBO	
		"07"	HAVO/VWO	
		"08"	HBO/HTS/HEAO	
		"09"	WO	
		"98"	Other	
		"00"	Unknown	
71	Caretaker birth country	"dddd"	4-digit code, Table 34	N
82	Gestational age	"ddd"	in days	N
91	Smoking during pregnancy	"1"	yes	N
		"2"	no	
		"99"	unknown	
110	Birth weight	"dddd"	3-4 digits, grammes	N
235	Length/height	"dddd"	3-4 digits, millimeters	N
245	Body weight	"dddddd"	3-6 digits, grammes	N
252	Head circumference	"ddd"	2-3 digits, millimeters	N
238	Height biological mother	"dddd"	3-4 digits, millimeters	N
240	Height biological father	"dddd"	3-4 digits, millimeters	N
510	Passive smoking	"01"	No smoking in house	N
		"02"	Never with child	
		"03"	Not in last 7 days	
		"04"	Yes	

3.4 Error checking

Error checking of the JSON data occurs in three phases:

- 1. PHASE 1: Check whether the JSON data are valid JSON. The process terminates with an error message if the input JSON is not valid.
- 2. PHASE 2: Validate the JSON data against the JSON schema specification. The process terminates with an error if any required fields are missing. The process generates messages for data points that do not conform to the JSON schema, but continues.
- 3. PHASE 3: Check the range of the numeric data. The process generates

messages for out-of-range values, but continues using the specified values. The default JSON schema in phase 2 is the built-in JSON schema bds_schema_str.json, a data format implementing a version that accepts strings as values for BDS-elements.

Growth charts in JAMES

4.1 Chart naming conventions

The link https://groeidiagrammen.nl/ocpu/lib/james/www/ contains an interactive overview of the available growth charts. There are 342 different charts: for boys and girls, for preterms, for different age ranges, for specific ethnic groups, for height, weight, BMI, and so on. Each chart has a chart code, a character code identifying the design. This section explains the construction of the chart codes.

The GitHub repository https://github.com/stefvanbuuren/chartbox contains the chart libraries that are available to JAMES. The list_charts() function produces a tabular overview.

```
charts <- chartbox::list_charts()</pre>
dim(charts)
## [1] 394
charts[c(1, 22, 23, 300, 301, 340), ]
      chartgrp chartcode population
                                        sex design side language week
## 1
         n12010
                      HJAA
                                    HS
                                          male
                                                     A front
                                                                 dutch
## 22
         n12010
                      HMBH
                                    HS female
                                                         hgt
                                                                 dutch
## 23
         n12010
                      HMBR
                                    HS female
                                                     В
                                                         wfh
                                                                 dutch
                                                     hgt
## 300
        preterm
                  PMAHN28
                                  PT female
                                                             dutch
                                                                     28
## 301
                  PMAHN29
                                  PT female
                                                     hgt
                                                                     29
        preterm
                                                             dutch
## 340
       preterm
                  PMEAN32
                                  PT female
                                                  E front
                                                                     32
                                                             dutch
```

The chartbox package currently contains three chart groups: nl2010, preterm and who. Each group collects charts of a similar type.

Chart Group	Charts	Chart code	Description	Source
n12010	136	CCCC	Dutch children 0-21 years, including minorities	Talma et al. (2
preterm who		CCCCCNN CCCC	Dutch preterms, ga <= 36 weeks, 0-4 years WHO Child Growth Standards 0-4 years	Bocca-Tjeertes WHO

The chart code is an alpha-numeric code of four (for nl2010 and who) or seven (for preterm) that uniquely identifies each of the charts. The table below specifies the full coding schema used to construct the chart codes.

Position	Field	Value	Description
1	Population	N	Dutch
		${ m T}$	Turkish
		\mathbf{M}	Moroccan
		Η	Hindostan
		P	Preterm
		W	WHO
2	Sex	J	Male
		M	Female
3	Design	A	0-15 months
		В	0-4 years, WFH
		\mathbf{C}	1-21 years
		D	0-21 years
		\mathbf{E}	0-4 years, WFA
4	Side	A	A4, front
		В	A4, back
		\mathbf{C}	A4, back, no hdc
		Η	square, hgt
		O	square, hdc
		Q	square, bmi
		\mathbf{R}	square, wfh
		W	square, wgt
		X	A4, double sided
5	Language	N	Dutch
		\mathbf{E}	English
6-7	Week	25 - 36	Gestational age

For illustration, code NJAA references to Dutch (N), boys (J), 0-15 month (A), front side (A). Likewise, PMEAN33 codes for the chart of preterm (M), girls (M), 0-4 years (E), front side (A), Dutch language (N) born at 33 weeks of gestation (33).

Some forms hold multiple growth charts. For example, the NJAA chart is designed for A4 paper size (297mm \times 210mm) and contains three growth charts:

head circumference by age, length by age, and weight by age. Some others have no diagram, like NJAB with explanations. All square formats hold one growth chart. All of the square forms have equal sizes ($160 \text{mm} \times 160 \text{mm}$).

The following table lists the measures per design-form combination.

Design	Side	Measure	Description
A	A	hdc	Head circumference by age, 0-15 mo
		hgt	Length by age, 0-15 mo
		wgt	Weight by age, 0-15 mo
	В		
	$_{\mathrm{H}}$	hgt	Length by age, 0-15 mo
	O	hdc	Head circumference by age, 0-15 mo
	W	wgt	Weight by age, 0-15 mo
В	A	wfh	Weight for height, 0-4 yr
		hgt	Length by age, 0-4 yr
	В	hdc	Head circumference by age, 0-4 yr
	\mathbf{C}		
	$_{\mathrm{H}}$	hgt	Height by age, 0-4 yr
	O	hdc	Head circumference by age, 0-4 yr
	\mathbf{R}	wfh	Weight for height, 0-4 yr
	W	wgt	Weight by age, 0-4 yr
\mathbf{C}	A	wfh	Weight for height, 1-21 yr
		hgt	height by age, 1-21 yr
	В	bmi	BMI by age, 1-21 yr
		hdc	Head circumference by age, 1-21 yr
	\mathbf{C}	bmi	BMI by age, 1-21 yr
	$_{\mathrm{H}}$	hgt	Height by age, 1-21 yr
	O	hdc	Head circumference by age, 1-21 yr
	Q	bmi	Body mass index by age, 1-21 yr
	\mathbf{R}	wfh	Weight for height, 1-21 yr
\mathbf{E}	\mathbf{A}	wgt	Weight by age, 0-4 yr
		hgt	height by age, 0-4 yr
	В	hdc	Head circumference by age, 0-4 yr
	$_{\mathrm{H}}$	hgt	Height by age, 0-4 yr
	O	hdc	Head circumference by age, 0-4 yr
	W	wgt	Weight by age, 0-4 yr

Methods

We describe our methods in this chapter.

D-score implementation

This document describes the actions needed to implement the D-score into JAMES. The functionality of JAMES is distributed over multiple packages. This set of actions may be of interest when implementing new features.

6.1 Actions

Package	PR	Description
minihealth	03a32f1	Create milestones
		descriptions
dscore	f0013ce	Link BDS number to Van
		Wiechen milestones
dscore	6886854	Fine tuning of milestone
		labels
\min		Create the bds_lexicon
		object
\min	4893982	Add milestones to BDS
		validation JSON schema
\min	0069671	Add convert_ddi_gsed()
		to convert BDS-milestones
		into GSED items
minihealth	8ab1392	Add a new class
		individualDS for storing
		milestones, D-score and
_		DAZ
clopus	1182 cb0	Add Dutch and GCDG
		D-score references

Package	PR	Description
clopus	7bdbcd9	Construct age-shifted
		D-score references for
		preterms
clopus	ceab7f9	Import the D-score
		references into clopus
chartdesigner	6883190	Add chart constructor
		functions for D-score, both
		terms and pre-terms
chartdesigner	511f456	Extend internal
		$\mathtt{set.axes.design}()$ to
		D-score charts
chartdesigner	6582af 8	Extend to axes.locations
		object to D-score charts
chartdesigner	47e3cc3	Create dchart() function
		and extend its helper
		functions
chartdesigner	fbbc7c8	Function chartcode()
<u> </u>		factory, make one function
		for each chart code
chartcatalog	cc46788	Extend the chart naming
Ŭ.		system to D-score charts
chartcatalog	84aaded	Extend the lookup table
O .		ynames_lookup to handle
		new D-score charts
chartbox	aa31067	Extend chart box with all
		D-score charts
james	6412840	Add radio button for
J		D-score charts
minihealth	06a04c9	Calculate D-score and DAZ
chartplotter	4b58638	Skip the dsc field for
1		finding matches
minihealth	816be33	Add D-score and DAZ to
	0_0,000	class individualAN
donordata	77e01b4	Add milestones to SMOCC
	,,,,,,,,,,	donor data
donordata	ecb3413	Calculate D-score and DAZ
dollor dava	00.00110	for SMOCC data
donordata	3 fa 9 d4 d	Fit and store brokenstick
	3100 01 10	model for D-score on
		SMOCC data
donorloader	c22c446	Update internal data after
dollor loader	0220110	changes in donordata
jamesdocs	TBD	Document steps (this file)
Jamesaocs	100	Document steps (tills file)

6.1. ACTIONS 23

Package	PR	Description
donordata	94937e5	Saves the item scores to create JSON files
donordata	390adca	Save mapping between SMOCC and BDS coding scheme
donorloader	90ce41f	Make smocc_bds available to JAMES
minihealth	b9a4a23	Add two classes to store and convert to BDS number individual milestones data
jamestest	89dad46	Update the installed.cabinets object with the new individual milestones data

Bibliography

Bocca-Tjeertes, I., van Buuren, S., Bos, A., Kerstens, J., ten Vergert, E., and Reijneveld.S.A. (2012). Growth of preterm and fullterm children aged 0-4 years: Integrating median growth and variability in growth charts. *Journal of Pediatrics*, 161(3):460–465.

Talma, H., Schonbeck, Y., Bakker, B., Hirasing, R., and van Buuren, S. (2010). Groeidiagrammen 2010: Handleiding bij het meten en wegen van kinderen en het invullen van groeidiagrammen. TNO Kwaliteit van Leven, Leiden.