Sonic Insights Hybrid API (3.0.0)

Download OpenAPI specification: Download

A hybrid music intelligence API that combines Spotify user behaviour with a public discovery catalog. It computes a listening fingerprint, detects recent taste drift, supports explainable recommendations, and critiques its own generated insights.

Auth

User registration, login, and profile access.

Register a new user account

REQUEST BODY SCHEMA: application/json
required

`username` required	string (Username) [2 .. 50] characters
`email` required	string <email> (Email)
`password` required	string (Password) >= 8 characters

Responses

> **201** Successful Response

> **422** Validation Error

POST `/api/v1/auth/register`

Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "string",
    "email": "user@example.com",
    "password": "stringst"
}
```

Response samples

201 **422**

Content type
application/json

Copy

```
{
    "id": 0,
    "username": "string",
    "email": "string",
    "created_at": "2019-08-24T14:15:22Z"
}
```

Obtain access + refresh token pair

REQUEST BODY SCHEMA: application/x-www-form-urlencoded
required

grant_type >	Grant Type (string) or Grant Type (null) (Grant Type)
username required	string (Username)
password required	string <password> (Password)

`scope`	string (Scope) Default: `""`
`client_id` >	Client Id (string) or Client Id (null) (Client Id)
`client_secret` >	Client Secret (string) or Client Secret (null) <password> (Client Secret)

Responses

> **200** Successful Response

> **422** Validation Error

POST `/api/v1/auth/login`

Response samples

200 422

Content type
application/json

Copy

```
{
    "access_token": "string",
    "refresh_token": "string",
    "token_type": "bearer"
}
```

Exchange a refresh token for a new access + refresh token pair

Validates the refresh token, blacklists it immediately (rotation), and issues a fresh access + refresh token pair.

REQUEST BODY SCHEMA: application/json
required

refresh_token required	string (Refresh Token)

Responses

> **200** Successful Response

> **422** Validation Error

POST /api/v1/auth/refresh

Request samples

Payload

Content type
application/json

Copy

```
{
    "refresh_token": "string"
}
```

Response samples

200 422

Content type
application/json

Copy

```
{
    "access_token": "string",
    "refresh_token": "string",
    "token_type": "bearer"
}
```

Invalidate the current access token

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

POST `/api/v1/auth/logout`

Response samples

200

Content type
application/json

Copy

```
null
```

Get the current user's profile

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/auth/me

Response samples

200

Content type
application/json

Copy

```
{
    "id": 0,
    "username": "string",
    "email": "string",
    "created_at": "2019-08-24T14:15:22Z"
}
```

Ingestion

Import Spotify listening context and the public discovery catalog.

Start a Spotify import job

Runs a richer Spotify ingestion pipeline.

One request can fetch:

- top tracks for one window or all three Spotify windows
- recently played history
- saved-library tracks using pagination
- audio features for all unique imported tracks

Recently played items become real listening events. Top-track and saved-track imports can additionally synthesise plausible historical listening events so analytics endpoints remain useful even when Spotify only exposes affinity data.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

spotify_token required	string (Spotify Token)
time_range	string (Time Range) `^(short_term|medium_term|long_term|all)$` Default: `"all"`
include_recently_played	boolean (Include Recently Played) Default: `true`
include_saved_tracks	boolean (Include Saved Tracks) Default: `true`
saved_tracks_max_pages	integer (Saved Tracks Max Pages) [1 .. 20] Default: `5`
synthesise_history	boolean (Synthesise History) Default: `true`

Responses

> **202** Successful Response

> **422** Validation Error

POST /api/v1/imports/spotify

Request samples

Payload

Content type
application/json

Copy

```
{
  "spotify_token": "string",
  "time_range": "all",
  "include_recently_played": true,
  "include_saved_tracks": true,
```

```
    "saved_tracks_max_pages": 5,
    "synthesise_history": true
}
```

Response samples

202 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "id": "string",
    "user_id": 0,
    "status": "string",
    "source": "string",
    "time_range": "string",
    "tracks_found": 0,
    "tracks_imported": 0,
    "events_created": 0,
  - "errors": [
        null
    ],
    "started_at": "2019-08-24T14:15:22Z",
    "completed_at": "2019-08-24T14:15:22Z"
}
```

Check import job status

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

job_id required	string (Job Id)

Responses

> **200** Successful Response

> **422** Validation Error

GET /api/v1/imports/jobs/{job_id}

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "id": "string",
    "user_id": 0,
    "status": "string",
    "source": "string",
    "time_range": "string",
    "tracks_found": 0,
    "tracks_imported": 0,
    "events_created": 0,
  - "errors": [
        null
    ],
    "started_at": "2019-08-24T14:15:22Z",
    "completed_at": "2019-08-24T14:15:22Z"
}
```

List your recent import jobs

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/imports/jobs

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "id": "string",
      "user_id": 0,
      "status": "string",
      "source": "string",
      "time_range": "string",
      "tracks_found": 0,
      "tracks_imported": 0,
      "events_created": 0,
    + "errors": [ … ],
      "started_at": "2019-08-24T14:15:22Z",
      "completed_at": "2019-08-24T14:15:22Z"
   }
]
```

Import the public discovery catalog dataset

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

Any of CatalogImportRequest Body

`dataset_slug` string (Dataset Slug)
Default: `"ramithgajjala/ramith-top-songs"`

`file_path` string (File Path)
Default: `"ramith-top-songs.csv"`

Responses

> **201** Successful Response

> **422** Validation Error

POST `/api/v1/imports/catalog`

Request samples

Payload

Content type
application/json

Example
CatalogImportRequest

Copy

```
{
    "dataset_slug": "ramithgajjala/ramith-top-songs",
    "file_path": "ramith-top-songs.csv"
}
```

Response samples

201 **422**

Content type
application/json

Copy

```
{
    "status": "string",
    "dataset": "string",
    "imported_by": "string",
    "inserted": 0,
```

```
    "updated": 0,
    "total_rows": 0
}
```

Listening Events

Record and manage your listening history.

Record a new listening event

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`track_id` required	integer (Track Id)
`listened_at` >	Listened At (string) or Listened At (null) (Listened At)
`duration_listened_ms` >	Duration Listened Ms (integer) or Duration Listened Ms (null) (Duration Listened Ms)

Responses

> **201** Successful Response

> **422** Validation Error

POST `/api/v1/listening-events`

Request samples

Payload

Content type
application/json

Copy

```
{
    "track_id": 0,
    "listened_at": "2019-08-24T14:15:22Z",
    "duration_listened_ms": 0
}
```

Response samples

201 422

Content type
application/json

Copy

```
{
    "id": 0,
    "user_id": 0,
    "track_id": 0,
    "listened_at": "2019-08-24T14:15:22Z",
    "duration_listened_ms": 0,
    "source": "string"
}
```

List your listening events (paginated, filterable)

AUTHORIZATIONS: > *OAuth2PasswordBearer*

QUERY PARAMETERS

`offset`	integer (Offset) >= 0 Default: 0
`limit`	integer (Limit) [1 .. 100] Default: 20
`from` >	From (string) or From (null) (From)
`to` >	To (string) or To (null) (To)

Responses

> **200** Successful Response

> **422** Validation Error

GET /api/v1/listening-events

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "total": 0,
    "limit": 0,
    "offset": 0,
  - "items": [
      + { … }
    ]
}
```

Live stream of listening events via Server-Sent Events

Opens a persistent SSE connection that pushes a JSON event to the client every time a new listening event is recorded for the authenticated user. Also emits a heartbeat every 15 seconds to keep the connection alive. Compatible with MCP clients, Claude Desktop, and any EventSource-capable client.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

— **200** Successful Response

GET /api/v1/listening-events/stream

Get a single listening event

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

event_id required	integer (Event Id)

Responses

> **200** Successful Response

> **422** Validation Error

GET /api/v1/listening-events/{event_id}

Response samples

200 422

Content type
application/json

Copy

```
{
  "id": 0,
  "user_id": 0,
  "track_id": 0,
```

```
    "listened_at": "2019-08-24T14:15:22Z",
    "duration_listened_ms": 0,
    "source": "string"
}
```

Update a listening event

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`event_id` required	integer (Event Id)

REQUEST BODY SCHEMA: application/json
required

`listened_at` >	Listened At (string) or Listened At (null) (Listened At)
`duration_listened_ms` >	Duration Listened Ms (integer) or Duration Listened Ms (null) (Duration Listened Ms)

Responses

> **200** Successful Response

> **422** Validation Error

PATCH `/api/v1/listening-events/{event_id}`

Request samples

Payload

Content type
application/json

Copy

```
{
    "listened_at": "2019-08-24T14:15:22Z",
    "duration_listened_ms": 0
}
```

Response samples

200 422

Content type
application/json

Copy

```
{
    "id": 0,
    "user_id": 0,
    "track_id": 0,
    "listened_at": "2019-08-24T14:15:22Z",
    "duration_listened_ms": 0,
    "source": "string"
}
```

Delete a listening event

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

event_id required	integer (Event Id)

Responses

— **204** Successful Response

> **422** Validation Error

DELETE /api/v1/listening-events/{event_id}

Response samples

422

Content type
application/json

Copy Expand all Collapse all

```
{
 - "detail": [
     + { … }
   ]
}
```

Catalog

Browse and search the imported discovery catalog.

Search and filter the discovery catalog

AUTHORIZATIONS: > *OAuth2PasswordBearer*

QUERY PARAMETERS

q >	Q (string) or Q (null) (Q) Search by track name or artist (case-insensitive)
genre >	Genre (string) or Genre (null) (Genre) Filter by genre (e.g. pop, rock, hip hop)
min_energy >	Min Energy (number) or Min Energy (null) (Min Energy) Minimum energy value
max_energy >	Max Energy (number) or Max Energy (null) (Max Energy) Maximum energy value

`min_valence` >	Min Valence (number) or Min Valence (null) (Min Valence) Minimum valence (positivity)
`max_valence` >	Max Valence (number) or Max Valence (null) (Max Valence) Maximum valence (positivity)
`min_danceability` >	Min Danceability (number) or Min Danceability (null) (Min Danceability) Minimum danceability
`max_danceability` >	Max Danceability (number) or Max Danceability (null) (Max Danceability) Maximum danceability
`limit`	integer (Limit) [1 .. 100] Default: `20` Number of results to return
`offset`	integer (Offset) >= 0 Default: `0` Pagination offset

Responses

> **200** Successful Response

> **422** Validation Error

GET `/api/v1/catalog`

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "total": 0,
  "limit": 0,
  "offset": 0,
```

```
  - "items": [
      + { … }
    ]
}
```

Classify all catalog tracks into mood quadrants with deep statistics

Divides the entire catalog into four mood quadrants using the energy-valence plane: Happy (high energy + high valence), Angry (high energy + low valence), Calm (low energy + high valence), Sad (low energy + low valence). Returns per-quadrant statistics including track count, average audio features, and representative example tracks.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET `/api/v1/catalog/mood-map`

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "total_tracks": 0,
  - "quadrants": [
      + { … }
    ],
    "most_common_mood": "string",
    "description": "string"
```

```
}
```

Full statistical audio feature distribution across the entire catalog

Computes the complete statistical profile of every audio feature: mean, 25th percentile, 75th percentile, min, and max across all catalog tracks. Also returns a per-genre fingerprint for direct comparison between styles.

AUTHORIZATIONS: *OAuth2PasswordBearer*

Responses

200 Successful Response

GET `/api/v1/catalog/audio-dna`

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "total_tracks": 0,
  - "features": [
     + { … }
    ],
  - "genre_fingerprints": {
     + "property1": { … },
     + "property2": { … }
    },
    "insight": "string"
}
```

Genre breakdown of the imported catalog

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET `/api/v1/catalog/genres`

Response samples

200

Content type
application/json

Copy


```
null
```

Genre breakdown of the imported catalog

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET `/api/v1/catalog/genres`

Response samples

200

Content type
application/json

Copy

```
null
```

Natural language mood → ranked catalog recommendations

Parses a free-text mood description (e.g. 'rainy sunday afternoon') into audio feature targets using keyword matching, then ranks all matching catalog tracks by cosine similarity to those targets. Combines NLP intent parsing with 8-dimensional vector similarity search.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`description` required	string (Description) [3 .. 300] characters Natural language mood e.g. 'rainy sunday afternoon'
`limit`	integer (Limit) [1 .. 50] Default: `10`

genre > Genre (string) or Genre (null) (Genre)

Responses

> **200** Successful Response

> **422** Validation Error

POST /api/v1/catalog/recommend-by-mood

Request samples

Payload

Content type
application/json

Copy

```
{
    "description": "string",
    "limit": 10,
    "genre": "string"
}
```

Response samples

200 **422**

Content type
application/json

Copy Expand all Collapse all

```
{
    "description": "string",
    "interpreted_targets": { },
  - "matched_keywords": [
        "string"
    ],
    "total_candidates": 0,
```

```
  - "results": [
      + { … }
    ]
}
```

Get a single catalog track by ID

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`track_id` required	integer (Track Id)

Responses

> **200** Successful Response

> **422** Validation Error

GET `/api/v1/catalog/{track_id}`

Response samples

200 | 422

Content type
application/json

Copy

```
{
    "id": 0,
    "external_id": "string",
    "name": "string",
    "artist": "string",
    "album": "string",
    "genre": "string",
```

```
    "energy": 0,
    "valence": 0,
    "danceability": 0,
    "tempo": 0,
    "acousticness": 0,
    "instrumentalness": 0,
    "speechiness": 0,
    "liveness": 0,
    "source_dataset": "string",
    "created_at": "2019-08-24T14:15:22Z"
}
```

Find catalog tracks similar to a given track using cosine similarity

Computes cosine similarity across 8 audio features (energy, valence, danceability, tempo, acousticness, instrumentalness, speechiness, liveness) to find the closest matches to the seed track in the catalog.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`track_id` required	integer (Track Id)

QUERY PARAMETERS

`limit`	integer (Limit) [1 .. 50] Default: `10` Number of similar tracks to return
`same_genre`	boolean (Same Genre) Default: `false` Restrict results to the same genre

Responses

> **200** Successful Response

> **422** Validation Error

GET `/api/v1/catalog/{track_id}/similar`

Response samples

200 422

Content type
application/json

Copy

```
null
```

Feedback

Full CRUD over user feedback on catalog tracks.

Create feedback for a catalog track

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`catalog_track_id` required	integer (Catalog Track Id)
`rating` required	string (Rating) `^(like|dislike|save|skip)$`
`note` >	Note (string) or Note (null) (Note)

Responses

> **201** Successful Response

> **422** Validation Error

POST `/api/v1/feedback`

Request samples

Payload

Content type
application/json

Copy

```
{
    "catalog_track_id": 0,
    "rating": "string",
    "note": "string"
}
```

Response samples

201 **422**

Content type
application/json

Copy

```
{
    "id": 0,
    "user_id": 0,
    "catalog_track_id": 0,
    "rating": "string",
    "note": "string",
    "created_at": "2019-08-24T14:15:22Z",
    "updated_at": "2019-08-24T14:15:22Z"
}
```

List your feedback records

AUTHORIZATIONS: > *OAuth2PasswordBearer*

QUERY PARAMETERS

`rating` > Rating (string) or Rating (null) (Rating)

Responses

> **200** Successful Response

> **422** Validation Error

GET `/api/v1/feedback`

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
[
 - {
      "id": 0,
      "user_id": 0,
      "catalog_track_id": 0,
      "rating": "string",
      "note": "string",
      "created_at": "2019-08-24T14:15:22Z",
      "updated_at": "2019-08-24T14:15:22Z",
      "track_name": "string",
      "artist": "string",
      "genre": "string"
    }
]
```

Update a feedback record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`feedback_id` required	integer (Feedback Id)

REQUEST BODY SCHEMA: application/json
required

`rating` >	Rating (string) or Rating (null) (Rating)
`note` >	Note (string) or Note (null) (Note)

Responses

> **200** Successful Response

> **422** Validation Error

PATCH `/api/v1/feedback/{feedback_id}`

Request samples

Payload

Content type
application/json

Copy

```
{
    "rating": "string",
    "note": "string"
}
```

Response samples

200 **422**

Content type
application/json

Copy

```
{
    "id": 0,
    "user_id": 0,
    "catalog_track_id": 0,
    "rating": "string",
    "note": "string",
    "created_at": "2019-08-24T14:15:22Z",
    "updated_at": "2019-08-24T14:15:22Z"
}
```

Delete a feedback record

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`feedback_id` required	integer (Feedback Id)

Responses

> **200** Successful Response

> **422** Validation Error

DELETE `/api/v1/feedback/{feedback_id}`

Response samples

200 | 422

Content type
application/json

Copy

```
null
```

Analytics

Focused hybrid analytics including overview, fingerprint, highlights, and recent change detection.

High-level hybrid listening summary

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/analytics/overview

Response samples

200

Content type
application/json

Copy

```
{
    "user_id": 0,
    "total_events": 0,
    "unique_spotify_tracks": 0,
    "unique_catalog_feedback_tracks": 0,
    "avg_energy": 0,
    "avg_valence": 0,
    "dominant_mood": "string",
    "fingerprint_label": "string"
}
```

Build your listening fingerprint

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/analytics/fingerprint

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "fingerprint_label": "string",
  - "traits": {
        "avg_energy": 0,
        "avg_valence": 0,
        "avg_danceability": 0,
        "avg_tempo": 0,
        "novelty_ratio": 0,
        "diversity_score": 0,
        "dominant_mood": "string",
        "peak_hour": "string",
        "total_events": 0,
    + "top_artists": [ … ],
    + "top_genres": [ … ]
    },
    "explanation": "string",
  - "evidence": [
        { }
    ]
}
```

Explain recent taste drift

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/analytics/changes/recent

Response samples

200

Content type
application/json

Copy Expand all Collapse all


```
{
    "previous_window": "string",
    "recent_window": "string",
    "fingerprint_shift": "string",
    "summary": "string",
  - "metrics": [
      + { … }
    ],
  - "evidence": [
        { }
    ]
}
```

Compact analytics highlights

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **200** Successful Response

GET /api/v1/analytics/highlights

Response samples

200

Content type
application/json

Copy

```
{
    "top_artist": "string",
    "top_genre": "string",
    "novelty_ratio": 0,
    "diversity_score": 0,
    "peak_hour": "string",
    "dominant_mood": "string"
}
```

AI

Explainable hybrid recommendations, grounded insight generation, and critique.

Generate and store a hybrid listening insight

AUTHORIZATIONS: > *OAuth2PasswordBearer*

Responses

> **201** Successful Response

POST `/api/v1/ai/insights`

Response samples

201

Content type
application/json

Copy Expand all Collapse all


```
{
    "id": 0,
    "user_id": 0,
    "insight_type": "string",
    "title": "string",
    "insight_text": "string",
    "data_snapshot": { },
  - "evidence": [
        null
    ],
    "model_used": "string",
    "created_at": "2019-08-24T14:15:22Z"
}
```

Critique a generated insight for grounding and specificity

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

`insight_id` required	integer (Insight Id)

Responses

> **200** Successful Response

> **422** Validation Error

POST `/api/v1/ai/insights/{insight_id}/critique`

Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "insight_id": 0,
    "overall_verdict": "string",
  - "issues": [
      + { … }
    ],
    "improved_excerpt": "string",
    "grounding_score": 0
}
```

Return explainable hybrid recommendations grounded in your fingerprint

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`context` >	Context (string) or Context (null) (Context)
`strategy`	string (Strategy) `^(balanced|discovery|comfort)$` Default: `"balanced"`
`max_tracks`	integer (Max Tracks) [1 .. 20] Default: 5

Responses

> **200** Successful Response

> **422** Validation Error

POST /api/v1/ai/recommendations/explain

Request samples

Payload

Content type
application/json

Copy

```
{
    "context": "string",
    "strategy": "balanced",
    "max_tracks": 5
}
```

Response samples

200 **422**

Content type
application/json

Copy Expand all Collapse all

```
{
    "fingerprint_label": "string",
    "strategy": "string",
    "context": "string",
  - "recommendations": [
      + { … }
    ],
    "summary": "string"
}
```

Generate counterfactual recommendations for a scenario

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`scenario` required	string (Scenario) [5 .. 200] characters
`max_tracks`	integer (Max Tracks) [1 .. 20] Default: 5

Responses

> **200** Successful Response

> **422** Validation Error

POST `/api/v1/ai/recommendations/what-if`

Request samples

Payload

Content type
application/json

Copy

```
{
    "scenario": "string",
    "max_tracks": 5
}
```

Response samples

200 **422**

Content type
application/json

Copy Expand all Collapse all

```
{
    "fingerprint_label": "string",
    "strategy": "string",
    "context": "string",
```

```
  - "recommendations": [
      + { … }
    ],
    "summary": "string"
}
```

MCP

Model Context Protocol server — exposes Sonic Insights tools for AI client integration (Claude Desktop, Cursor, etc.).

List all available MCP tools and their input schemas

Responses

> **200** Successful Response

GET /api/v1/mcp/manifest

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
{
    "schema_version": "1.0",
    "name": "string",
    "description": "string",
```

```
  - "tools": [
      + { … }
    ]
}
```

Invoke a named MCP tool with arguments

Executes one of the registered Sonic Insights tools by name. Call GET /mcp/manifest first to see available tools and their parameters.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json
required

`tool` required	string (Tool)
`arguments` >	object (Arguments) Default: `{}`

Responses

> **200** Successful Response

> **422** Validation Error

POST `/api/v1/mcp/invoke`

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
    "tool": "string",
    "arguments": { }
}
```

Response samples

200 422

Content type
application/json

Copy

```
{
    "tool": "string",
    "success": true,
    "result": null,
    "error": "string"
}
```

System

Operational health endpoints.

API health check

Responses

> **200** Successful Response

GET /health

Response samples

200

Content type
application/json

Copy

```
null
```

Detailed system health with database statistics

Responses

> **200** Successful Response

GET /health/detailed

Response samples

200

Content type
application/json

Copy

```
null
```