Harbor Chimney Sweeps

CHIMNEY INSPECTION REPORT

Chimney 1: The unit should be inspected at least once a year by a qualified technician.

Chimney 1: Keep the area around the equipment clear of debris and stored items.

Chimney 1: Refer to the table below for recommended settings in each season.

Chimney 1: If the indicator light flashes, turn off power and wait thirty seconds.

Chimney 1: Clean the filter screen with warm water and a soft brush.

Chimney 1: Do not use abrasive cleaners on the stainless surfaces.

Chimney 1: Record each service visit so the history is available later.

Chimney 1: Normal operating noise includes a soft hum and occasional clicks.

Chimney 1: Contact a licensed professional for any electrical repair.

Chimney 1: Replace worn gaskets before they start to leak.

Harbor Chimney Sweeps

Chimney 2: The unit should be inspected at least once a year by a qualified technician.

Chimney 2: Keep the area around the equipment clear of debris and stored items.

Chimney 2: Refer to the table below for recommended settings in each season.

Chimney 2: If the indicator light flashes, turn off power and wait thirty seconds.

Chimney 2: Clean the filter screen with warm water and a soft brush.

Chimney 2: Do not use abrasive cleaners on the stainless surfaces.

Chimney 2: Record each service visit so the history is available later.

Chimney 2: Normal operating noise includes a soft hum and occasional clicks.

Chimney 2: Contact a licensed professional for any electrical repair.

Chimney 2: Replace worn gaskets before they start to leak.

Harbor Chimney Sweeps

Chimney 3: The unit should be inspected at least once a year by a qualified technician.

Chimney 3: Keep the area around the equipment clear of debris and stored items.

Chimney 3: Refer to the table below for recommended settings in each season.

Chimney 3: If the indicator light flashes, turn off power and wait thirty seconds.

Chimney 3: Clean the filter screen with warm water and a soft brush.

Chimney 3: Do not use abrasive cleaners on the stainless surfaces.

Chimney 3: Record each service visit so the history is available later.

Chimney 3: Normal operating noise includes a soft hum and occasional clicks.

Chimney 3: Contact a licensed professional for any electrical repair.

Chimney 3: Replace worn gaskets before they start to leak.

Thank you for your business!

Received from owner for gutter cleaning, paid in full.

Receipt: The unit should be inspected at least once a year by a qualified technician.

Receipt: Keep the area around the equipment clear of debris and stored items.

Receipt: Refer to the table below for recommended settings in each season.

Receipt: If the indicator light flashes, turn off power and wait thirty seconds.

Receipt: Clean the filter screen with warm water and a soft brush.

Receipt: Do not use abrasive cleaners on the stainless surfaces.

LiftRight 3000 Garage Door Opener
OWNERS MANUAL
Opener: The unit should be inspected at least once a year by a qualified technician.
Opener: Keep the area around the equipment clear of debris and stored items.
Opener: Refer to the table below for recommended settings in each season.
Opener: If the indicator light flashes, turn off power and wait thirty seconds.
Opener: Clean the filter screen with warm water and a soft brush.
Opener: Do not use abrasive cleaners on the stainless surfaces.
Opener: Record each service visit so the history is available later.
Opener: Normal operating noise includes a soft hum and occasional clicks.
Opener: Contact a licensed professional for any electrical repair.
Opener: Replace worn gaskets before they start to leak.

LiftRight 3000 Garage Door Opener

Opener: The unit should be inspected at least once a year by a qualified technician.

Opener: Keep the area around the equipment clear of debris and stored items.

Opener: Refer to the table below for recommended settings in each season.

Opener: If the indicator light flashes, turn off power and wait thirty seconds.

Opener: Clean the filter screen with warm water and a soft brush.

Opener: Do not use abrasive cleaners on the stainless surfaces.

Opener: Record each service visit so the history is available later.

Opener: Normal operating noise includes a soft hum and occasional clicks.

Opener: Contact a licensed professional for any electrical repair.

Opener: Replace worn gaskets before they start to leak.

Coastal Bluffs Homeowners Association
(760) 555-0101 | www.coastalbluffs.example
January 5, 2024
HOA letter: The unit should be inspected at least once a year by a qualified technician.
HOA letter: Keep the area around the equipment clear of debris and stored items.
HOA letter: Refer to the table below for recommended settings in each season.
HOA letter: If the indicator light flashes, turn off power and wait thirty seconds.
HOA letter: Clean the filter screen with warm water and a soft brush.
HOA letter: Do not use abrasive cleaners on the stainless surfaces.
HOA letter: Record each service visit so the history is available later.
HOA letter: Normal operating noise includes a soft hum and occasional clicks.
HOA letter: Contact a licensed professional for any electrical repair.

Coastal Bluffs Homeowners Association
(760) 555-0101 | www.coastalbluffs.example
February 9, 2024
HOA letter: The unit should be inspected at least once a year by a qualified technician.
HOA letter: Keep the area around the equipment clear of debris and stored items.
HOA letter: Refer to the table below for recommended settings in each season.
HOA letter: If the indicator light flashes, turn off power and wait thirty seconds.
HOA letter: Clean the filter screen with warm water and a soft brush.
HOA letter: Do not use abrasive cleaners on the stainless surfaces.
HOA letter: Record each service visit so the history is available later.
HOA letter: Normal operating noise includes a soft hum and occasional clicks.
HOA letter: Contact a licensed professional for any electrical repair.

Hi neighbours,

About the shared fence repair

Fence: The unit should be inspected at least once a year by a qualified technician.

Fence: Keep the area around the equipment clear of debris and stored items.

Fence: Refer to the table below for recommended settings in each season.

Fence: If the indicator light flashes, turn off power and wait thirty seconds.

Fence: Clean the filter screen with warm water and a soft brush.

Fence: Do not use abrasive cleaners on the stainless surfaces.

Fence: Record each service visit so the history is available later.

Fence: Normal operating noise includes a soft hum and occasional clicks.

Thanks, Pat

Panel schedule, main service

Circuit: The unit should be inspected at least once a year by a qualified technician.

Circuit: Keep the area around the equipment clear of debris and stored items.

Circuit: Refer to the table below for recommended settings in each season.

Circuit: If the indicator light flashes, turn off power and wait thirty seconds.

Circuit: Clean the filter screen with warm water and a soft brush.

Circuit: Do not use abrasive cleaners on the stainless surfaces.

Circuit: Record each service visit so the history is available later.

Circuit: Normal operating noise includes a soft hum and occasional clicks.

Circuit: Contact a licensed professional for any electrical repair.

Circuit: Replace worn gaskets before they start to leak.

Circuit: The drain line must slope continuously toward the outlet.

Circuit: Allow the system to run a full cycle after any adjustment.

Panel schedule, sub panel

Circuit: The unit should be inspected at least once a year by a qualified technician.

Circuit: Keep the area around the equipment clear of debris and stored items.

Circuit: Refer to the table below for recommended settings in each season.

Circuit: If the indicator light flashes, turn off power and wait thirty seconds.

Circuit: Clean the filter screen with warm water and a soft brush.

Circuit: Do not use abrasive cleaners on the stainless surfaces.

Circuit: Record each service visit so the history is available later.

Circuit: Normal operating noise includes a soft hum and occasional clicks.

Circuit: Contact a licensed professional for any electrical repair.

Circuit: Replace worn gaskets before they start to leak.

Circuit: The drain line must slope continuously toward the outlet.

Circuit: Allow the system to run a full cycle after any adjustment.

Voltek Breakers Inc.

Product data sheet

Spec: The unit should be inspected at least once a year by a qualified technician.

Spec: Keep the area around the equipment clear of debris and stored items.

Spec: Refer to the table below for recommended settings in each season.

Spec: If the indicator light flashes, turn off power and wait thirty seconds.

Spec: Clean the filter screen with warm water and a soft brush.

Spec: Do not use abrasive cleaners on the stainless surfaces.

Spec: Record each service visit so the history is available later.

Spec: Normal operating noise includes a soft hum and occasional clicks.

Spec: Contact a licensed professional for any electrical repair.

Spec: Replace worn gaskets before they start to leak.