

1. Description

1.1. Project

Project Name	BlackPill-BMP
Board Name	custom
Generated with:	STM32CubeMX 6.6.1
Date	11/06/2022


1.2. MCU

MCU Series	STM32F4
MCU Line	STM32F411
MCU name	STM32F411CEUx
MCU Package	UFQFPN48
MCU Pin number	48

1.3. Core(s) information

Core(s)	Arm Cortex-M4

2. Pinout Configuration




3. Pins Configuration

Pin Number	Pin Name	Pin Type	Alternate	Label
UFQFPN48	(function after		Function(s)	
·	reset)		,	
1	VBAT	Power		
2	PC13-ANTI_TAMP *	I/O	GPIO_Output	LEDS
5	PH0 - OSC_IN	I/O	RCC_OSC_IN	
6	PH1 - OSC_OUT	I/O	RCC_OSC_OUT	
7	NRST	Reset		
8	VSSA	Power		
9	VDDA	Power		
10	PA0-WKUP	I/O	ADC1_IN0	VREF_2
11	PA1 *	I/O	GPIO_Output	JRST
12	PA2	I/O	USART2_TX	JTXD
13	PA3	I/O	USART2_RX	JRXD
14	PA4 *	I/O	GPIO_Output	JTEST
15	PA5	I/O	SPI1_SCK	JTCK
16	PA6	I/O	SPI1_MISO	JTDO
17	PA7	I/O	SPI1_MOSI	JTDI
20	PB2 *	I/O	GPIO_Input	BOOT1
22	VCAP1	Power		
23	VSS	Power		
24	VDD	Power		
25	PB12 *	I/O	GPIO_Output	JENA
26	PB13	I/O	SPI2_SCK	SBW_CLK
27	PB14	I/O	SPI2_MISO	SBW_IN
28	PB15	I/O	SPI2_MOSI	SBW_OUT
29	PA8	I/O	TIM1_CH1	JTCK_IN
30	PA9	I/O	TIM1_CH2	SBW_DIR
31	PA10	I/O	TIM1_CH3	JTMS
32	PA11	I/O	USB_OTG_FS_DM	
33	PA12	I/O	USB_OTG_FS_DP	
34	PA13	I/O	SYS_JTMS-SWDIO	
35	VSS	Power		
36	VDD	Power		
37	PA14	I/O	SYS_JTCK-SWCLK	
38	PA15	I/O	SYS_JTDI	
39	PB3	I/O	SYS_JTDO-SWO	
42	PB6	I/O	USART1_TX	GDB_TX
43	PB7	I/O	USART1_RX	GDB_RX

Pin Number UFQFPN48	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
44	воото	Boot		
45	PB8	I/O	TIM10_CH1	PWM_VT
47	VSS	Power		
48	VDD	Power		

^{*} The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	BlackPill-BMP
Project Folder	P:\github.com\glossy-msp430\Hardware\BlackPill-BMP\CubeMX
Toolchain / IDE	EWARM V8.50
Firmware Package Name and Version	STM32Cube FW_F4 V1.27.1
Application Structure	Advanced
Generate Under Root	No
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy all used libraries into the project folder
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_DMA_Init	DMA
4	MX_ADC1_Init	ADC1
5	MX_SPI2_Init	SPI2
6	MX_USART2_UART_Init	USART2
7	MX_USB_OTG_FS_PCD_Init	USB_OTG_FS
8	MX_SPI1_Init	SPI1
9	MX_TIM1_Init	TIM1
10	MX_TIM10_Init	TIM10
11	MX_USART1_UART_Init	USART1

Rank	Function Name	Peripheral Instance Name
12	MX_TIM2_Init	TIM2

6. Power Consumption Calculator report

6.1. Microcontroller Selection

Series	STM32F4
Line	STM32F411
MCU	STM32F411CEUx
Datasheet	DS10314_Rev6

6.2. Parameter Selection

Temperature	25
Vdd	1.7

6.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


6.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	1.7	1.7
Voltage Source	Battery	Battery
Range	Scale1-High	No Scale
Fetch Type	SRAM	n/a
CPU Frequency	100 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator_LPLV Flash- PwrDwn
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	12.7 mA	9 μΑ
Duration	0.1 ms	0.9 ms
DMIPS	125.0	0.0
Ta Max	104.31	105
Category	In DS Table	In DS Table

6.5. Results

Sequence Time	1 ms	Average Current	1.28 mA
Battery Life	3 months, 19	Average DMIPS	125.0 DMIPS
	days, 6 hours		

6.6. Chart



7. Peripherals and Middlewares Configuration

7.1. ADC1 mode: IN0

7.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC_Settings:

Clock Prescaler PCLK2 divided by 6 *

Resolution 12 bits (15 ADC Clock cycles)

Data Alignment Right alignment

Scan Conversion Mode Disabled
Continuous Conversion Mode Disabled
Discontinuous Conversion Mode Disabled
DMA Continuous Requests Disabled

End Of Conversion Selection EOC flag at the end of single channel conversion

ADC_Regular_ConversionMode:

Number Of Conversion 1

External Trigger Conversion Source Regular Conversion launched by software

External Trigger Conversion Edge None
Rank 1

Channel Channel 0
Sampling Time 3 Cycles

ADC_Injected_ConversionMode:

Number Of Conversions 0

WatchDog:

Enable Analog WatchDog Mode false

7.2. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

7.2.1. Parameter Settings:

System Parameters:

VDD voltage (V) 3.3
Instruction Cache Enabled
Prefetch Buffer Enabled
Data Cache Enabled

Flash Latency(WS) 3 WS (4 CPU cycle)

RCC Parameters:

HSI Calibration Value 16

TIM Prescaler Selection Disabled
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000

Power Parameters:

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

7.3. SPI1

Mode: Full-Duplex Master

7.3.1. Parameter Settings:

Basic Parameters:

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

Clock Parameters:

Prescaler (for Baud Rate) 2

Baud Rate 48.0 MBits/s *

Clock Polarity (CPOL) Low
Clock Phase (CPHA) 1 Edge

Advanced Parameters:

CRC Calculation Disabled NSS Signal Type Software

7.4. SPI2

Mode: Full-Duplex Master

7.4.1. Parameter Settings:

Basic Parameters:

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

Clock Parameters:

Prescaler (for Baud Rate)

Baud Rate 24.0 MBits/s *

Clock Polarity (CPOL) Low

Clock Phase (CPHA) 1 Edge

Advanced Parameters:

CRC Calculation Disabled
NSS Signal Type Software

7.5. SYS

Debug: JTAG (4 pins)

Timebase Source: SysTick

7.6. TIM1

Slave Mode: External Clock Mode 1

Trigger Source: TI1FP1

Channel2: Output Compare CH2 Channel3: Output Compare CH3

mode: One Pulse Mode7.6.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 0
Counter Mode Up
Counter Period (AutoReload Register - 16 bits value) 65535
Internal Clock Division (CKD) No Division

Repetition Counter (RCR - 8 bits value) 0
auto-reload preload Disable
Slave Mode Controller ETR mode 1

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

Break And Dead Time management - BRK Configuration:

BRK State Disable
BRK Polarity High

Break And Dead Time management - Output Configuration:

Automatic Output State Disable

Off State Selection for Run Mode (OSSR) Disable

Off State Selection for Idle Mode (OSSI) Disable

Lock Configuration Off

Trigger:

Trigger Polarity Rising Edge

Trigger Filter (4 bits value) 0

Output Compare Channel 2:

Mode Frozen (used for Timing base)

Pulse (16 bits value) 0

Output compare preload Disable
CH Polarity High
CH Idle State Reset

Output Compare Channel 3:

Mode Frozen (used for Timing base)

Pulse (16 bits value) 0

Output compare preload Disable
CH Polarity High
CH Idle State Reset

7.7. TIM2

Channel3: Output Compare No Output

7.7.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 0

Counter Mode Up

Counter Period (AutoReload Register - 32 bits value) 4294967295
Internal Clock Division (CKD) No Division
auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)

Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

Output Compare No Output Channel 3:

Mode Frozen (used for Timing base)

Pulse (32 bits value) 0

Output compare preload Disable

CH Polarity High

7.8. TIM10

mode: Activated

Channel1: PWM Generation CH1

7.8.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 0
Counter Mode Up
Counter Period (AutoReload Register - 16 bits value) 65535
Internal Clock Division (CKD) No Division auto-reload preload Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable

Fast Mode Disable

CH Polarity High

7.9. USART1

Mode: Asynchronous

7.9.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.10. USART2

Mode: Asynchronous

7.10.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples

7.11. USB_OTG_FS

Mode: Device_Only

7.11.1. Parameter Settings:

Speed Device Full Speed 12MBit/s

Low powerDisabledLink Power ManagementDisabledVBUS sensingDisabledSignal start of frameDisabled

* User modified value

8. System Configuration

8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PA0-WKUP	ADC1_IN0	Analog mode	No pull-up and no pull-down	n/a	VREF_2
RCC	PH0 - OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
	PH1 - OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	
SPI1	PA5	SPI1_SCK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	JTCK
	PA6	SPI1_MISO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	JTDO
	PA7	SPI1_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	Very High	JTDI
SPI2	PB13	SPI2_SCK	Alternate Function Push Pull	No pull-up and no pull-down	Very High	SBW_CLK
	PB14	SPI2_MISO	Alternate Function Push Pull	No pull-up and no pull-down	Very High	SBW_IN
	PB15	SPI2_MOSI	Alternate Function Push Pull	No pull-up and no pull-down	Very High	SBW_OUT
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	
	PA15	SYS_JTDI	n/a	n/a	n/a	
	PB3	SYS_JTDO- SWO	n/a	n/a	n/a	
TIM1	PA8	TIM1_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	JTCK_IN
	PA9	TIM1_CH2	Alternate Function Push Pull	No pull-up and no pull-down	Low	SBW_DIR
	PA10	TIM1_CH3	Alternate Function Push Pull	No pull-up and no pull-down	Low	JTMS
TIM10	PB8	TIM10_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	PWM_VT
USART1	PB6	USART1_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	GDB_TX
	PB7	USART1_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	GDB_RX
USART2	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	JTXD
	PA3	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	JRXD

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
USB_OTG_ FS	PA11	USB_OTG_FS_ DM	Alternate Function Push Pull	No pull-up and no pull-down	* Very High *	
	PA12	USB_OTG_FS_ DP	Alternate Function Push Pull	No pull-up and no pull-down	Very High	
GPIO	PC13- ANTI_TAMP	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LEDS
	PA1	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	JRST
	PA4	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	JTEST
	PB2	GPIO_Input	Input mode	No pull-up and no pull-down	n/a	BOOT1
	PB12	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	JENA

8.2. DMA configuration

DMA request	Stream	Direction	Priority
TIM1_CH3	DMA2_Stream6	Peripheral To Memory	Very High *
TIM2_CH3/UP	DMA1_Stream1	Peripheral To Memory	Low
SPI1_RX	DMA2_Stream0	Peripheral To Memory	Medium *
SPI1_TX	DMA2_Stream2	Memory To Peripheral	Low

TIM1_CH3: DMA2_Stream6 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *
Peripheral Data Width: Word *
Memory Data Width: Word *

TIM2_CH3/UP: DMA1_Stream1 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *
Peripheral Data Width: Word
Memory Data Width: Word

SPI1_RX: DMA2_Stream0 DMA request Settings:

Mode: Normal
Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *
Peripheral Data Width: Byte

Peripheral Data Width: Byte Memory Data Width: Byte

SPI1_TX: DMA2_Stream2 DMA request Settings:

Mode: Normal

Use fifo: Disable
Peripheral Increment: Disable
Memory Increment: Enable *

Peripheral Data Width: Byte
Memory Data Width: Byte

8.3. NVIC configuration

8.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
Memory management fault	true	0	0
Pre-fetch fault, memory access fault	true	0	0
Undefined instruction or illegal state	true	0	0
System service call via SWI instruction	true	0	0
Debug monitor	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	15	0
DMA1 stream1 global interrupt	true	0	0
DMA2 stream0 global interrupt	true	0	0
DMA2 stream2 global interrupt	true	0	0
DMA2 stream6 global interrupt	true	0	0
PVD interrupt through EXTI line 16		unused	
Flash global interrupt		unused	
RCC global interrupt		unused	
ADC1 global interrupt		unused	
TIM1 break interrupt and TIM9 global interrupt		unused	
TIM1 update interrupt and TIM10 global interrupt	unused		
TIM1 trigger and commutation interrupts and TIM11 global interrupt	unused		
TIM1 capture compare interrupt	unused		
TIM2 global interrupt	unused		
SPI1 global interrupt	unused		
SPI2 global interrupt	unused		
USART1 global interrupt	unused		
USART2 global interrupt	unused		
USB On The Go FS global interrupt	unused		
FPU global interrupt	unused		

8.3.2. NVIC Code generation

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Pre-fetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true
DMA1 stream1 global interrupt	false	true	true
DMA2 stream0 global interrupt	false	true	true
DMA2 stream2 global interrupt	false	true	true
DMA2 stream6 global interrupt	false	true	true

^{*} User modified value

9. System Views

9.1. Category view

9.1.1. Current



10. Docs & Resources

Type Link

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Training Material https://www.st.com/resource/en/sales_guide/sg_sc2154.pdf

Flyers https://www.st.com/resource/en/flyer/flnucleolrwan.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32f4x1.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Product https://www.st.com/resource/en/certification_document/stm32_authenticat

Certifications ion_can.pdf

Application Notes https://www.st.com/resource/en/application_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-

recommendations-and-package-information-for-leadfree-ecopack-mcus-

and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-get-the-

best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2867-oscillator-

design-guide-for-stm8afals-stm32-mcus-and-mpus-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4031-using-the-stm32f2-stm32f4-and-stm32f7-series-dma-controller-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-stm32-

- microcontroller-random-number-generation-validation-using-the-nist-statistical-test-suite-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4488-getting-started-with-stm32f4xxxx-mcu-hardware-development-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4616-migrating-from-stm32f401-and-stm32f411-lines-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4646-peripheral-interconnections-on-stm32f401-and-stm32f411-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cube-firmware-examples-for-stm32f4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4838-managing-

- memory-protection-unit-in-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4850-stm32-mcusspreadspectrum-clock-generation-principles-properties-andimplementation-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4879-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4904-migration-of-microcontroller-applications-from-stm32f1-series-to-stm32f4-access-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5073-receiving-spdif-audio-stream-with-the-stm32f4f7h7-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guide-

for related Tools freertos-guide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in for related Tools _truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog

for related Tools rammer_in_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard

for related Tools _shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio

for related Tools __migration_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio

for related Tools n_in_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2656-stm32f10xxx-

for related Tools Icd-glass-driver-firmware-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3078-stm32-

for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application note/an3174-implementing-

for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3241-qvga-tftlcd-

for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3307-guidelines-for-for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-

for related Tools compatibility-guidelines-for-stm32-microcontroller-applications-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3965-

for related Tools stm32f40xstm32f41x-inapplication-programming-using-the-usart-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3969-eeprom-

for related Tools emulation-in-stm32f40xstm32f41x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3990-upgrading-

for related Tools stm32f4discovery-board-firmware-using-a-usb-key-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3997-audio-playback-

for related Tools and-recording-using-the-stm32f4discovery-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3998-pdm-audio-

for related Tools software-decoding-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4044-floating-point-

for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4187-using-the-crc-

for related Tools peripheral-in-the-stm32-family-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4365-using-stm32f4-

for related Tools mcu-power-modes-with-best-dynamic-efficiency-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4457-implementing-for related Tools an-emulated-uart-on-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4499-stm32-for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4502-stm32-for related Tools smbuspmbus-embedded-software-expansion-for-stm32cube-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4515-using-batch-for related Tools acquisition-mode-bam-to-maximize-power-efficiency-on-stm32f410-

& Software stm32f411-stm32f412-stm32f413-microcontroller-lines-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4666-parallel-for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4678-full-duplex-spifor related Tools emulation-for-stm32f4-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4701-proprietary-for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4739-stm32cube-for related Tools firmware-examples-for-stm32f4-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4759-using-the-

for related Tools hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-

& Software stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-

for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5464-position-control-

for related Tools of-a-threephase-permanent-magnet-motor-using-xcubemcsdk-or-

& Software xcubemcsdkful-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Design Notes & https://www.st.com/resource/en/design_tip/dt0088-fir-filter-design-by-

Tips sampling-windowing-and-modulating-the-sinc-function-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0089-the-goertzel-algorithm-

Tips to-compute-individual-terms-of-the-discrete-fourier-transform-dft-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0091-lattice-wave-digital-

Tips filter-design-and-automatic-c-code-generation-stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0092-lattice-wave-digital-

Tips filter-test-and-performance-verification-stmicroelectronics.pdf

Device Option https://www.st.com/resource/en/device option list/opl stm32f411 512k.zi

Lists

Errata Sheets https://www.st.com/resource/en/errata_sheet/es0287-stm32f411xc-and-

stm32f411xe-device-limitations-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00115249.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0214-stm32-Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference_manual/rm0383-

Manuals stm32f411xce-advanced-armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn0516-overview-of-the-

& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf