

'UPRITE' AUTOMATIC LADDER-LEVELLER

FITTING INSTRUCTIONS

- A. For parallel-sill ladders up to 380 mm (15 in) O.D., fit ladder retaining brackets as shown in Figure 1.

Ladders wider than 380 mm: fit as in Figure 2.

Extra wide ladders: Figure 3.

Tighten U-clamps securely, but do not over-tighten brackets.



- B. Place ladder in horizontal position, using four bolts supplied, attach 'UPRITE' to ladder brackets. Before tightening bolts, make sure centre of leveler and ladder are in line, and base of both rails are forced against top plane of leveler.
- C. Your 'UPRITE' ladder-leveler is now ready for use. Simply place in position, check that bubble in spirit-level is central, and use.
- D. TO REPOSITION. Raise ladder slightly, leaving feet in contact with ground surface, adjust angle until bubble is in central position, lower ladder.

Once fitted with an 'UPRITE' your ladder can be used with confidence on level, sloping, uneven, hard or soft surfaces.

NOTE: Slip-on bumper disc feet available for soft ground.

The unique automatic locking device incorporated in the 'UPRITE', ensures the utmost safety at all times.

Simplicity of design and durable materials give 'UPRITE' a long and virtually maintenance-free life.

Non-slip feet add to safety and allow use on damage-prone surfaces, such as polished floors, vinyl, carpets, etc.

With the fitting of an 'UPRITE' ladder-leveler you have eliminated a large percentage of danger usually associated with the use of ladders, with the addition of reasonable cost, your ladder can always be a safe, speedy and trusty tool.

SAFETY HINTS. Never place base of ladder too close or too far away from building; an angle of approximately 15 degrees is appropriate.

Always remove obstacles (stones, gravel, etc.) from area where ladder is to be used.

If using against opening, check that opening is free enough to withstand the weight of both ladder and operator.

When working on roof, spread ladder three rungs above edge of building.

Never use a ladder on soft ground, such as garden beds or freshly-filled trenches without 'UPRITE'. Super feet fitted.

PATENT NUMBERS

* Australia 517,861; * U.S.A. 4,047,722; * U.K. 2,187,317. Patent 50,000 taken pending.

GOVERNMENT AUTHORIZATION

Noted and approved for use in the industry by the Department of Labour and Industry, Victoria. Approval Classification 284/177.

Division of Industrial Research, A.B.C. V.V. December 1976

PRINTED IN T.A.P.A.N.