

WEEK 05 · TAILWIND CSS

THE PAGE WRITTEN IN CLASSES

Same CSS. Different place to put it. And one real argument.

WHERE WE ARE

You can build any layout. You have also written 480 lines to do it once.

AFTER TODAY YOU CAN

Write the same page with no stylesheet, and say what every class emits.

WHAT THIS UNLOCKS

Every page from here, including the project. And a component you define once.

THIS IS WHAT YOU SHIPPED LAST WEEK

[a notification card, and its stylesheet, measured](#) [↶ reload](#) [open ↷](#)

WRITTEN BY HAND — THE WAY WEEK 4 TAUGHT

! **Certificate expires in 6 days**
Renew it before Friday or the gateway starts refusing connections.

rules in the stylesheet	15
...matching nothing on this page	8
class names invented	11
rules that escalated	7
!important	1
worst specificity (a,b,c)	1,2,0

8 of 15 authored rules (53%) match nothing on this page.
The browser found them just now, by running `querySelectorAll` on every selector.

Dead:
`.notice--compact`
`.notice--compact .notice__icon`
`.notice--compact .notice__title`

THE SAME CARD, IN UTILITIES

! **Certificate expires in 6 days**
Renew it before Friday or the gateway starts refusing connections.

rules in the stylesheet	0 — there is no stylesheet
...matching nothing on this page	0
class names invented	0
rules that escalated	0
!important	0
highest specificity possible	0,1,0

► **HANDS-ON** [demos/01-why-utilities/](#) — left column only. Ask the room how many of those rules still do something. **DO NOT SCROLL RIGHT YET.**

FOUR COSTS, AND YOU PAID ALL OF THEM

DEAD RULES

Over half the stylesheet matches nothing on the page. Nobody deleted them, and nobody was careless — you cannot prove a selector is unused by reading it.

INVENTED NAMES

Eleven of them.

`.notice__meta--compact` is not a design decision. It is bookkeeping you have to remember.

THE SPECIFICITY RATCHET

Three rules fighting over one colour. To change it you cannot write a rule — you have to write one that **wins**. And the next person has to beat yours.

And the fourth: two files, and your attention moving between them all day.

THE RATCHET, IN THE FILE YOU WROTE

```
1  /* January */
2  .notice__title { color: #0f172a; }
3
4  /* February – the panel needed a darker one */
5  .panel .notice__title { color: #0f172a; }
6
7  /* March – the alert panel needed red */
8  #alerts .panel .notice__title { color: #7f1d1d; }
```

Every step is reasonable. The stylesheet is now un-editable and nobody did anything wrong.

THE SAME CARD, WITH NO STYLESHEET AT ALL

```
1 <div class="flex items-start gap-3 rounded-xl border border-slate-300 bg-white p-4">
2   <div class="grid h-8 w-8 flex-none place-items-center rounded-full bg-blue-100">!</div>
3   <div class="min-w-0">
4     <p class="mb-0.5 font-semibold">Certificate expires in 6 days</p>
5     <p class="text-sm text-slate-600">Renew it before Friday.</p>
6   </div>
7 </div>
```

DEAD RULES: STRUCTURALLY ZERO

Not "fewer". There is no stylesheet, so there is nothing that **can** die.

NAMES INVENTED: ZERO

Nothing to remember, nothing to defend in review, nothing to rename.

SPECIFICITY: 0,1,0. ALWAYS.

Every utility is exactly one class. There is nothing to escalate.

AND NOW THE BILL

The markup is three times longer, and it reads worse.

SAY THIS OUT LOUD

Before a student says it for you. It is true and it does not go away.

ACT 5 PAYS IT

Honestly, with the arguments the people who dislike this system actually make.

ACT 6 FIXES IT

Not by shortening the markup. By having one of it.

WHAT IS ACTUALLY BEING CLAIMED

What it is

A fixed set of single-purpose classes, generated from your own design tokens.

Key trait

The styling lives where the markup lives, so a component is one thing in one place instead of two things in two files.

Use it for

Anything you are building rather than theming. It is the wrong tool for a stylesheet you ship to other people's pages.

Tips

It is not faster to type. It is cheaper to **delete** — and deleting is what you spend a codebase's life doing.

Nothing here is new CSS. Every class you will see today emits a declaration you already wrote, in a file you already deleted.

What changes is **where the decision lives** — and that is the only thing worth arguing about.

MISCONCEPTION 1

“THIS IS JUST INLINE STYLES WITH EXTRA STEPS.”

It is a fair objection, it is the first thing everyone says, and it deserves a real answer rather than a slogan.

ASK BOTH OF THEM TO DO FOUR THINGS

a style attribute and a utility, side by side↻ reloadopen ↗

narrow the frame

dark

add an overriding class

viewport is >= md (48rem)

style="..."

utilities

Deploy

Deploy

asked to...	style=""	utilities	measured right now
change on hover	no	yes	a style attribute has no :hover to hang a value on
change at a breakpoint	no	yes	a style attribute has no @media
change in dark mode	no	yes	same reason – no @media
be overridden by a later class	no	yes	the attribute is (1,0,0,0) – it beats every selector you can write
hold a value computed at run time	yes	no	THE one thing the attribute is genuinely for – utilities are a fixed set

right now:

```
style="..." button    background rgb(24, 45, 242) · padding 8px 16px
utility button        background rgb(24, 45, 242) · padding 8px 32px
```

and here is what those utility classes actually ARE. Read out of document.styleSheets – this is the browser answering, not a lookup table:

► **HANDS-ON** [demos/02-not-inline-styles/](#) — press the buttons in order: **HOVER · NARROW · DARK · OVERRIDE**. Say nothing while you do it.

BECAUSE A CLASS CAN CARRY A CONDITION. AN ATTRIBUTE CANNOT.

```
1 @media (hover: hover) {  
2   .hover\:bg-brand-700:hover { background-color: ... } }  
3  
4 @media (width >= 48rem) {  
5   .md\:px-8 { padding-inline: ... } }  
6  
7 @media (prefers-color-scheme: dark) {  
8   .dark\:bg-brand-300 { background-color: ... } }
```

An attribute is a value. These are conditions.



WHAT A STYLE ATTRIBUTE IS GENUINELY FOR

A VALUE COMPUTED AT RUN TIME

A progress bar at 63%. A tooltip at the cursor. A number that did not exist when the page was written. Utilities are a fixed set generated from the source.

THAT IS THE WHOLE LIST

And it is worth saying, because a rebuttal with a boundary is stronger than one without. You will use it in week 9.

AND IT NEVER FIGHTS THE CSS YOU DO WRITE

```
1 @layer theme, base, components, utilities; /* Tailwind, first thing */
2
3 @layer base { h2 { font-size: 1.5rem } } /* all of it: LAYERED */
4
5 h2 { font-size: 13px } /* yours is not – and it wins */
```

A layered rule loses to an unlayered one whatever the order. Your CSS beats the reset with no `!important`.



LIVE CODING · 6 MINUTES

ONE CARD, TRANSLATED IN FRONT OF YOU

- 1 Open last week's `.kpi` rule. Read it out loud, declaration by declaration.
- 2 Write the class for each one. Delete the CSS line you just replaced.
- 3 When the rule is empty, delete the rule. Then delete the file.
- 4 Reload. Nothing changed on screen.

Do not look anything up. Guess out loud, get one wrong, and fix it in front of them.

MISCONCEPTION 2

“SO I HAVE TO MEMORISE A FEW HUNDRED CLASS NAMES.”

No. You have to know CSS, and you already do.

A student who memorises is stuck the first time they meet a class they have not seen — and that happens tomorrow.

ASK THE BROWSER INSTEAD

CSS in, utility out – by measurement, not by table

UTILITY → CSS

a class, exactly as you would write it in the markup

p-4

p-4 md:px-8 hover:bg-brand-700 dark:bg-slate-900 flex gap-4 rounded-xl text-huge

```
.p-4 {  
  padding: calc(var(--spacing) * 4);  
}
```

...and that is all it is. One class, one rule.

applied to a real element, live:

specimen

reload open

CSS → UTILITY

a declaration, straight out of last week's stylesheet

padding: 1rem;

padding: 1rem; display: flex; gap: 1rem; justify-content: space-between;

font-weight: 600; padding: 13px; max-width: 62ch;

you asked for:
padding-top: 16px
padding-right: 16px
padding-bottom: 16px
padding-left: 16px

these classes resolve to exactly that:
p-4

Checked by MEASURING, not by looking up a table: each one was applied to a real element and its computed value compared with yours. That is why the answer is trustworthy even for a property nobody anticipated.

► **HANDS-ON** `demos/03-translator/` — start with the **RIGHT** box. `padding: 1rem`, then `display: flex`, then `justify-content: space-between`. Stop before the fourth.

THE WHOLE TRANSLATION, BY PROPERTY FAMILY

BOX

`padding` → `p-*` · `px-*` · `py-*` · `pt-*`
`margin` → `m-*` · `mx-auto`
`border-radius` → `rounded-*`

LAYOUT

`display:flex` → `flex`
`grid-template-columns` → `grid-cols-*`
`gap` → `gap-*` · `gap-x-*`

ALIGNMENT

`justify-content` → `justify-*`
`align-items` → `items-*`
`align-self` → `self-*`

TYPE

`font-size` → `text-sm` · `text-lg`
`font-weight` → `font-semibold`
`text-decoration` → `underline` ·
`no-underline`

COLOUR

`color` → `text-*`
`background` → `bg-*`
`border-color` → `border-*`

THE ONE TRAP

`text-*` means **both** size and colour. `text-sm` is a size; `text-slate-600` is a colour. The value decides.

THE SCALES ARE THE PRODUCT. THE SHORT NAMES ARE A SIDE EFFECT.

spacing, type and colour, drawn at their real sizes

↻ reload

open ↗

SPACING — EVERY STEP IS --SPACING TIMES A WHOLE NUMBER

w-0.5	2px	
w-1	4px	
w-1.5	6px	
w-2	8px	
w-3	12px	
w-[13px]	13px	
w-4	16px	
w-5	20px	
w-6	24px	
w-8	32px	
w-10	40px	
w-12	48px	
w-16	64px	
w-20	80px	
w-24	96px	

TYPE

text-xs	12px	Renew the certificate
text-sm	14px	Renew the certificate
text-base	16px	Renew the certificate

► **HANDS-ON** [demos/04-scale/](#) — cover the readout. Ask: **WHICH ONE DOES NOT BELONG?** Then wait.

ONE NUMBER MOVES THE WHOLE PAGE

```
1 @theme {  
2   --spacing: 0.25rem;  
3 }
```

p-4 is not “sixteen pixels”. It is **four units**, and the unit is one line.

What it is

A single multiplier behind every padding, margin, gap, width and height.

Key trait

Change it and everything moves together, staying in proportion.

Use it for

Denser layouts, a bigger touch target, a design that felt cramped.

Tip

This is week 2's token argument with a system on top. Same idea, more reach.

@theme IS tokens.css WITH A SECOND JOB

WEEK 2 — TOKENS.CSS

```
:root {  
  --color-accent: hsl(234 89% 52%);  
}  
  
.brand { color: var(--color-accent) }
```

WEEK 5 — THE SAME VALUES

```
@theme {  
  --color-brand-500: hsl(234 89% 52%);  
}  
  
/* and now: text-brand-500,  
   bg-brand-500, border-brand-500 ... */
```

A **@theme** entry is a custom property,
and also generates a family of classes.

WEEK 4'S RULE, NOW IMPOSSIBLE TO GET BACKWARDS

which breakpoints match, at any width you like

reload open

frame width 1400px sm md lg xl 2xl

Requests
1.42M

Latency
86ms

Errors
0.31%

WHICH BREAKPOINTS MATCH, RIGHT NOW

sm:	≥ 40rem (640px)	matches – not used in this markup
md:	≥ 48rem (768px)	matches
lg:	≥ 64rem (1024px)	matches – not used in this markup
	≥ 80rem	

► **HANDS-ON** [demos/05-responsive/](#) — start at 1400 and drag **DOWN**, slowly. Stop at exactly 768 and ask what happens at 767.

YOU WROTE THIS LAST WEEK. IT IS THE SAME RULE.

WEEK 4 — BY HAND

```
.kpis {  
  display: grid;  
  grid-template-columns: 1fr;  
}  
  
@media (min-width: 48rem) {  
  .kpis {  
    grid-template-columns: repeat(3, 1fr);  
  }  
}
```

WEEK 5 — AND IT GENERATES EXACTLY THAT

```
<section class="grid grid-cols-1  
             md:grid-cols-3">
```

Nine lines and an invented class name become one attribute. The **breakpoint did not move** and the CSS is identical — you can read it back out of the browser and check.

THERE IS NO `max-*` BY DEFAULT, AND THAT IS A DECISION

A MAX-WIDTH QUERY

States what a thing **stops** being.
Every one has to be undone by the next size up — which is the tangle CA4 made you untangle.

A PREFIX

Only ever **adds**. Four of them can match at once and none of them fights. Mobile-first is not a discipline here; it is the shape of the tool.

THE ESCAPE HATCH EXISTS

`max-md:` is real, because a system with no escape hatch is one you abandon. It is still the wrong default. **Remember that it exists.**

“You don't always need media queries — the system replaces most of them.” — *this course, lesson 6, about a different framework. It was true then and it is true now.*

FIVE STATES, AND NO JAVASCRIPT IN ANY OF THEM

hover · focus-visible · active · group-hover · peer

reload open

hover: idle

point at me

```
@media (hover: hover)
.hover\:bg-brand-700:hover {
  background-color: var(--color-brand-700);
}
```

Notice the media query. This is why hover never sticks on a phone.

focus-visible: idle

reach me with Tab

```
.focus-visible\:outline-brand-500:focus-visible
{
  outline-color: var(--color-brand-500);
}
```

The one you cannot demonstrate with a mouse, and the one always graded.

active: idle

hold the button down

```
.active\:bg-brand-700:active {
  background-color: var(--color-brand-700);
}
```

Lasts exactly as long as the mouse button is down. Rarely enough on its own.

group-hover: idle

Gateway
hover anywhere on the card — this line changes

```
@media (hover: hover)
.group-hover\:text-brand-500:is(:where(.group):hover *) {
  color: var(--color-brand-500);
}
```

Parent hovered, child styled. Zero JavaScript — read the selector.

peer-checked: idle

☐ email me when a deploy fails

```
.peer-checked\:text-brand-500:is(:where(.peer):checked ~ *) {
  color: var(--color-brand-500);
}
```

► **HANDS-ON** [demos/06-variants/](#) — do the first three with the mouse, then **PUT THE MOUSE DOWN** and reach the fourth with Tab.

READ THE SELECTOR AND THE MAGIC EVAPORATES

```
1 /* group-hover:text-brand-500 */  
2 .group-hover\:text-brand-500:is(:where(.group):hover *) { ... }  
3  
4 /* peer-checked:text-brand-500 */  
5 .peer-checked\:text-brand-500:is(:where(.peer):checked ~ *) { ... }
```

“INSIDE A HOVERED `.group`”

A descendant combinator and a pseudo-class. Week 2 taught both.

“A LATER SIBLING OF A CHECKED `.peer`”

The `~` combinator — which is why the checkbox must come **first** in the markup. CSS cannot look backwards.

LIVE CODING · 6 MINUTES

ONE LINK, FOUR STATES, IN THE BROWSER

- 1 A plain nav link. Add `hover: .` Show it.
- 2 Add `focus-visible: .` Show it **with Tab**, not the mouse.
- 3 Add `dark: .` Flip the OS setting live and let them watch.
- 4 Now delete the focus one and Tab again. Put it back.

Step 4 is the point. Ten seconds without a focus ring is worth more than a slide about accessibility.

BOTH RAMPS, ON SCREEN AT ONCE

the same card, two ramps, contrast computed live

↺ reload

open ↗

LIGHT RAMP

GATEWAY

Certificate expires in 6 days

Renew it before Friday or the gateway starts refusing connections.

Renew now

DARK RAMP

GATEWAY

Certificate expires in 6 days

Renew it before Friday or the gateway starts refusing connections.

Renew now

every colour in both cards, resolved from the rendered page – and what week 2 called it

@theme token	week 2 (tokens.css)	light	dark
--color-page	--color-bg	☐ rgb(255, 255, 255)	☒ rgb(16, 20, 30)
--color-surface	--color-surface	☐ rgb(248, 249, 252)	☒ rgb(25, 30, 42)
--color-edge	--color-border	☐ rgb(199, 205, 219)	☒ rgb(63, 71, 90)
--color-ink	--color-text	☒ rgb(15, 23, 41)	☐ rgb(242, 245, 248)
--color-text-muted	--color-text-muted	☒ rgb(88, 98, 124)	☐ rgb(182, 188, 205)

► **HANDS-ON** demos/07-dark/ — say nothing and ask **“WHAT CHANGED?”** Give it fifteen seconds.

A DARK RAMP IS A SECOND SET OF DECISIONS, NOT AN INVERSION

WHAT PEOPLE EXPECT

Flip the background, flip the text, ship it.

WHAT ACTUALLY HAPPENS

`brand-500` on near-black is about **3:1**. Legal for a border, illegal for a word.

WHAT YOU DO

A lighter cut of the same colour.
4.5:1 in both ramps, independently.

And no toggle: `dark:` is a media query on a preference the user already set.

MISCONCEPTION 4

SQUARE BRACKETS: A TEST, NOT A TABOO

three legitimate uses and one smell, audited

↶ reload

open ↷

The test, and it is mechanical:

Would you want a *second* element to have this exact value?

yes → it is a decision. Give it a name in @theme.

no → it is a one-off. Brackets are the right answer.

And then: is it already on the scale, or within one step of it? If so you are overriding a system that was working, and that is the smell.

CORRECT A SIZE SOMEBODY ELSE DECIDED

A leaderboard slot is 728x90 because the ad network says so. Nobody on this team chose it, nobody will reuse it, and rounding it to the scale would break the thing. Brackets, no apology.

728 x 90

```
class="w-[728px] h-[90px] ..."
```

measured 728 x 90 — exactly the number the ad network specified.

Nobody would want a *SECOND* element at 728x90, so there is nothing to name.

The test says brackets, and the test is right.

► **HANDS-ON** demos/08-arbitrary/ — third panel first, and do not explain it. Ask: **HOW MANY COLOURS ARE IN THIS ROW?**

THE TEST, AND IT IS ONE QUESTION

Would you want a second element to have this exact value?

NO → BRACKETS

A 728×90 ad slot. A `mask-image` used once in a career. Nobody chose it and nobody will reuse it.

YES → `@theme`

It is a decision. Give it a name, and it becomes a first-class utility.

ALREADY ON THE SCALE → THE SMELL

`p-[13px]` when `p-3` exists. You are overriding a system that was working, one pixel at a time.

THE HONEST COSTS — AND I WROTE THESE BEFORE TAILWIND

CLASS BLOAT

“Many classes in HTML can make the code messy.”

OVER-RELIANCE

“Over-reliance can limit learning of native CSS.”

SEPARATION

“You want clean separation between structure and styling.”

– THIS COURSE, LESSON 6, ABOUT BOOTSTRAP. EVERY ONE OF THEM APPLIES HERE.

AND THE ARITHMETIC TRANSFERS UNCHANGED

LESSON 6, BOOTSTRAP

```
<div class="row">
  <div class="col-lg-3">...</div>
  <div class="col-lg-6">...</div>
  <div class="col-lg-3">...</div>
</div>
```

WEEK 5, AND CA5'S SHELL

```
<div class="grid md:grid-cols-12">
  <nav class="md:col-span-4 xl:col-span-2">
  <main class="md:col-span-8 xl:col-span-7">
  <aside class="md:col-span-12 xl:col-span-3">
</div>
```

Twelve columns, because twelve divides by 2, 3, 4 and 6. Every design tool in the industry speaks it.

MISCONCEPTION 5

"CLASS SOUP IS JUST WHAT THIS LOOKS LIKE."

six copies of one button, and what happened to them

↶ reload

open ↷

TODAY SIX COPIES

The same button, typed out six times. Find the odd ones out by eye before you read the audit.



```
<button class="cursor-pointer rounded-lg bg-brand-500  
px-5 py-2 text-sm font-semibold text-white  
hover:bg-brand-700">Renew</button>
```

...and five more, each typed out again

6 buttons, meant to be identical.
distinct renderings: 2
carrying a hover rule: 5 of 6
renders differently: Scale
has no hover state: Roll back

Two of the six have already drifted, and neither drift was a decision.
One has px-4 where the rest have px-5 – four pixels, invisible in a row.

THIS WEEK ONE SOURCE

The button is defined once, on `components.html`, and every use is a copy of *that* — by hand, no build step. That is what CA5 asks for. *On this page* the six are generated from one string, so that the demo has a single source too; the discipline is the same and the audit cannot tell them apart, which is the point.



`components.html` – the ONE definition:

```
<!-- button / primary -->  
<button class="cursor-pointer rounded-lg  
bg-brand-500 px-5 py-2 text-sm font-semibold  
text-white hover:bg-brand-700">Label</button>
```

everywhere else: copy that line.
changed your mind? change it there, then re-copy.

6 buttons, meant to be identical.
distinct renderings: 1
carrying a hover rule: 6 of 6

WEEK 9 ONE FUNCTION

Read this one; do not write it yet. It needs template literals and functions, which is week 7, and the render pattern it belongs to is week 9. It is here so you know the ladder has a top.



```
const BUTTON =  
  'cursor-pointer rounded-lg bg-brand-500 ' +  
  'px-5 py-2 text-sm font-semibold text-white ' +  
  'hover:bg-brand-700';  
  
const button = (label) =>  
  `<button type="button" class="${BUTTON}">${label}</button>`;  
  
LABELS.map(button).join('')
```

6 buttons, meant to be identical.
distinct renderings: 1
carrying a hover rule: 6 of 6

One rendering, and now it is not a discipline – it is

► **HANDS-ON** `demos/09-extraction/` — panel one. Ask the room to find the odd button **BY EYE** before reading the audit.

THE LADDER HAS THREE RUNGS, AND YOU ARE ON THE SECOND

SIX COPIES

Today, if you do nothing. Two of them have already drifted.

ONE DEFINITION, COPIED

`components.html`. One place a component is defined, one place to change it. **This is CA5, and it is graded by measurement.**

ONE FUNCTION

Week 9. Then copying stops being a step anybody can forget — and markup can be produced from **data**.

```
const BUTTON = 'cursor-pointer rounded-lg bg-brand-500 px-5 py-2 font-semibold text-white';  
const button = (label) => `
```

**Read that. Do not write it — it needs
template literals, which is week 7.**

MISCONCEPTION 3

“@apply SOLVES THIS.”

the same four measurements, on an @apply stylesheet

↺ reload

open ↗

THE SAME BUTTONS, WRITTEN WITH @APPLY

Renew Delete Archive

and the same two buttons again, inside .panel — which is a real wrapper in a real page and not a trick:

Renew Delete Archive

```
.btn { @apply cursor-pointer rounded-lg bg-brand-500 px-5 py-2 _ }  
.btn-danger { @apply bg-red-600; }  
  
.panel .btn { @apply bg-brand-500; } /* written later, by someone else */
```

the Delete button, measured in both rows:
outside .panel oklch(0.577 0.245 27.325)
inside .panel oklch(0.577 0.245 27.325)

they agree — only because .panel .btn.btn-danger was written to win the fight that .panel .btn started. Delete that one line and the Delete button turns brand-blue inside panels and nowhere else.

Utilities cannot do this to you. `bg-red-600` is one class at (0,1,0) and it

► **HANDS-ON** demos/10-apply-trap/ — write `.btn { @apply ... }` on the board first. Ask whether it beats six copies.

AND THE ONE PLACE IT IS RIGHT

WHEN YOU DO NOT OWN THE MARKUP

A base rule for every `<a>` in prose. A `::selection` colour. A third-party widget you cannot put a class on.

A HANDFUL OF RULES, IN A BASE LAYER

That is the whole legitimate use. If you want it everywhere, what you want is a **component**.

Which is why `@apply` is forbidden in CA5: it would let you avoid the thing the assignment is about.

THE FIVE THINGS PEOPLE GET WRONG

1. "IT'S INLINE STYLES"

A class carries conditions. An attribute carries a value.

2. MEMORISING THE CLASS NAMES

Know the CSS underneath and you are never stuck. Ask the browser.

3. @apply EVERYWHERE

It hands back every cost act 1 measured. One legitimate use, in a base layer.

4. IGNORING THE SCALE

`p-[13px]` · when `p-3` exists.

Rhythm is a property of the set.

5. CLASS SOUP WITH NO COMPONENT

Six copies drift within a fortnight.

Define once, copy from there.

THREE QUESTIONS BEFORE YOU GO

- 1 Name two things a utility class can do that `style=""` cannot, and say **why**.
- 2 You need `padding: 13px`. What are the three honest answers, and which is right nine times in ten?
- 3 You have the same button in six places. Why is `@apply` not the fix?

THIS WEEK

CLASS ASSIGNMENT 5

Rebuild the week-4 dashboard with no stylesheet, plus a component set with dark mode.

New this week: Claude generated three versions of one design. One of them does not do what its explanation claims. Find it, fix it, and write down why you rejected the other one.

THE AI POLICY MOVED

Tutor → Assistant. Claude may generate code now. You are answerable for every line you keep — and that is a graded row, not a disclaimer.

BEFORE NEXT WEEK

Install **Tailwind CSS IntelliSense** in VS Code. A misspelled class produces no rule and no error — it is the one real failure mode here.

Next week: UX, accessibility, and your project topic gets locked.