A Manufacturer-Agnostic Automation Framework for SPM

Nick Sullivan Molina

McGill University

Outline


1 Justification

2 Introduction to afspm


3 Design Particulars

SPM Basics

- An atomically-sharp tip is scanned above a surface measuring properties.
 - Allows spatial imaging, spectroscopic analysis, sample manipulation.
- Usable on various surfaces, only require relatively flat sample ($\sim 5 \mu m$).



Typical AFM Configuration, Tom Toyosaki, Wikimedia Commons.



Schematics of AFM topographic image forming, Tom Toyosaki, Wikimedia Commons.

Challenges and Automation

Challenges and Automation

Challenges for Wider Adoption

- Preparing, running, and analyzing requires significant domain knowledge.
- 2 Running an experiment requires constant user attention.
- 3 Statistical understanding is limited by the researcher's decisions.

Challenges and Automation

Challenges for Wider Adoption

- Preparing, running, and analyzing requires significant domain knowledge.
- 2 Running an experiment requires constant user attention.
- 3 Statistical understanding is limited by the researcher's decisions.

Automation Prior Art.

- Conditioning of the tip for proper surface characterization.
- Structure classification, for where to scan next.
- Bayesian/Active Learning for statistical decision making.

A Remaining Limitation


Many SPM systems allow custom scripts to run an experiment. But:

- Scripts written for a **specific** SPM system **cannot be re-used** on others.
- While **decoupling** is possible, it is **rarely** a **priority** for researchers.

A Remaining Limitation

Many SPM systems allow custom scripts to run an experiment. But:


- Scripts written for a **specific** SPM system **cannot be re-used** on others.
- While **decoupling** is possible, it is **rarely** a **priority** for researchers.



A Remaining Limitation

Many SPM systems allow custom scripts to run an experiment. But:

- Scripts written for a **specific** SPM system **cannot be re-used** on others.
- While decoupling is possible, it is rarely a priority for researchers.



Code reuse is rare.

Goals

To facilitate **code sharing** and **reusability** of developed automation.

Goals

To facilitate code sharing and reusability of developed automation.

Scope

Concerned with the **choices** a researcher would perform **during** an experiment.

Goals

To facilitate **code sharing** and **reusability** of developed automation.


Scope

Concerned with the choices a researcher would perform during an experiment.


Design Characteristics

- Standalone components that each 'do one thing and do it well' (nodes).
- They communicate over 'pipes' via generic schemas.
- It is easy to **split up** components among **different** computing **devices**.

Principal Components




Principal Components



Any experiment must contain:


- Microscope Translator: translates between afspm-generic and microscope-specific.
- Microscope Scheduler: mediates control between components and translator and caches data.

Scripting with / without afspm




Code Reuse in SPM Scripting

Scripting with / without afspm




Code Reuse in SPM Scripting




Approach Taken by afspm

Communication Protocol



Generic schemas sent between network sockets held by components.

Communication Protocol




Generic schemas sent between network sockets held by components.

Serialization / Deserialization

Translates data structures into a format that can be stored/communicated.

Google Protocol Buffers: avoids schema violations, extra error handling.

Communication Protocol



Generic schemas sent between network sockets held by components.

Serialization / Deserialization


Translates data structures into a format that can be stored/communicated. Google Protocol Buffers: avoids schema violations, extra error handling.

Data Transmission Protocol


Handles sending of data between 'sockets' via common 'nodes'.

ZeroMQ: abstracts away transports used, handles common roadblocks.

Example



Example



- ROI Analyzer reviews scans for interesting regions.
- **Experiment** switches between scanning a large region or a suggested ROI.
- **Tip Detector** evaluates the state of the tip, logs problem if deemed poor.
- Visualizer visualizes what is being scanned.

Our publisher-subscriber, control-request world

We subscribe to events published by the SPM and request actions of it.

Our publisher-subscriber, control-request world

We subscribe to events published by the SPM and request actions of it.

Publisher-Subscriber Path

- The SPM **publishes** messages types when its 'state' changes.
- Components may **subscribe** to only messages of interest.
- Messages may be **cached** by the Scheduler, to send to new components.

Our publisher-subscriber, control-request world

We subscribe to events published by the SPM and request actions of it.


Publisher-Subscriber Path

- The SPM **publishes** messages types when its 'state' changes.
- Components may **subscribe** to only messages of interest.
- Messages may be **cached** by the Scheduler, to send to new components.

Control Path

- Components send requests to the SPM and receive responses.
- The Scheduler routes control to the SPM (one component at a time).
- Components not in control may flag **problems** control is dropped.
 - A user may manually fix a problem and unflag the problem.
 - A component that **fixes** a flagged problem can grab control.

afspm: Detailed View



Publisher-Subscriber Path

```
message DataAspects {
    optional Size2u shape = 1;
    optional string units = 2;
}

message SpatialAspects {
    optional Rect2d roi = 1;
    optional string units = 2;
}

message ScanParameters2d {
    optional SpatialAspects spatial = 1;
    optional DataAspects data = 2;
}
```

2D Scan Parameters Schema

```
message Scan2d {
    optional ScanParameters2d params = 1;
    optional google.protobuf.Timestamp timestamp = 2;
    optional string channel = 3;
    optional string filename = 5;
    repeated double values = 4;
}
```

2D Scan Schema

Publisher-Subscriber Path

```
message DataAspects {
   optional Size2u shape = 1;
   optional string units = 2;
}
message SpatialAspects {
   optional Rect2d roi = 1;
   optional string units = 2;
}
message ScanParameters2d {
   optional SpatialAspects spatial = 1;
   optional DataAspects data = 2;
}
```

message Scan2d {
 optional ScanParameters2d params = 1;
 optional google.protobuf.Timestamp timestamp = 2;
 optional string channel = 3;
 optional string filename = 5;
 repeated double values = 4;
}

2D Scan Schema

2D Scan Parameters Schema

 Frame 1
 'Scan2d'

 Frame 2
 Scan2d Data

Envelope
Serialized Data Structure

Message Format

Control Path

Control Request Schema

Control Response Schema

Control Path

```
enum ControlRequest {
  REQ_UNDEFINED = 0;
  REQ_START_SCAN = 1;  // [...]
  REQ_REQUEST_CTRL = 4;  // [...]
  REQ_ADD_EXP_PRELM = 6;  // [...]
  REQ_SET_CONTROL_MODE = 8;
}
```

Control Request Schema

```
enum ExperimentProblem {
   EP_NONE = 0;
   EP_TIP_SHAPE_CHANGED = 1;
   EP_DEVICE_MALFUNCTION = 2;
   EP_FEEDBACK_NON_OPTIMAL = 3;
}
```

Experiment Problem Schema

Control Response Schema

```
enum ControlMode {
  CM_UNDEFINED = 0;
  CM_MANUAL = 1;
  CM_AUTOMATED = 2;
  CM_PROBLEM = 3;
}
```

Control Mode Schema

Control Path

Control Request Schema

```
enum ExperimentProblem {
EP_NONE = 0;
EP_TIP_SHAPE_CHANGED = 1;
EP_DEVICE_MALFUNCTION = 2;
EP_FEEDBACK_NON_OPTIMAL = 3;
}
```

Experiment Problem Schema

```
Frame 1 REQ_REQUEST_CTRL

Frame 2 EP_TIP_SHAPE_CHANGED
```

Control Response Schema

```
enum ControlMode {
  CM_UNDEFINED = 0;
  CM_MANUAL = 1;
  CM_AUTOMATED = 2;
  CM_PROBLEM = 3;
}
```

Control Mode Schema

```
Command Request Enum
Serialized Data Structure(s)
```

Message Format

Design Particulars

Spawning, Monitoring, and the Config File

An experiment defined via a config file, with components spawned as needed.

Spawning, Monitoring, and the Config File

An experiment defined via a config file, with components spawned as needed.

Spawning

- Each component is instantiated as a child process (independent memory).
 - One crashed component does not crash all.
- We can spawn different components on different computers.
 - The 'spawn' command allows indication of which components to spawn.

Spawning, Monitoring, and the Config File

An experiment defined via a config file, with components spawned as needed.

Spawning

- Each component is instantiated as a child process (independent memory).
 - One crashed component does not crash all.
- We can spawn different components on different computers.
 - The 'spawn' command allows indication of which components to spawn.

Monitoring

- The parent process monitors spawned components for heartbeats.
- If a process has not 'beat' in a timeframe, it is killed and respawned.
- Then the caching logic chosen is important must be able to run.

Sample Config File

```
# --- URLs --- #
pub_url = "tcp://127.0.0.1:9000"
psc_url = "tcp://127.0.0.1:9001"

server_url = "tcp://127.0.0.1:6666"
router_url = "tcp://127.0.0.1:6667"
# [...]
exp_scan_res = [256, 256]
# [...]
```

```
f ..... PubSub ..... f
[translator_pub]
class = 'afspm.io.pubsub.publisher.Publisher'
url = 'pub_url'
f [...]
[experiment_sub]
class = 'afspm.io.pubsub.subscriber.Subscriber'
sub_url = 'psc_url'
f [...]
```

General Variables

Intermediary Classes

```
[translator]
component = true
class = 'afspm.components.microscope.translators.gxsm.translator.GxsmTranslator'
publisher = 'translator_pub'
control_server = 'translator_server'
# [...]
```

Config Components

We defined a 'basis' set of schemas we believe are standard. But this is quite arbitrary! Here are ways you can expand upon them.

We defined a 'basis' set of schemas we believe are standard. But this is quite arbitrary! Here are ways you can expand upon them.

Operating Modes

- Defined as an SPM config describing cantilever control during a scan.
- We assume experiment has scan and spectroscopy modes configured.
- Can change by providing op. mode id and <key:value> params map.

We defined a 'basis' set of schemas we believe are standard. But this is quite arbitrary! Here are ways you can expand upon them.

Operating Modes

- Defined as an SPM config describing cantilever control during a scan.
- We assume experiment has scan and spectroscopy modes configured.
- Can change by providing op. mode id and <key:value> params map.

Actions

- Many manufacturers provide some automation tasks (e.g. approach tip).
- Can send these by providing action id and <key:value> params map.

We defined a 'basis' set of schemas we believe are standard. But this is quite arbitrary! Here are ways you can expand upon them.

Operating Modes

- Defined as an SPM config describing cantilever control during a scan.
- We assume experiment has scan and spectroscopy modes configured.
- Can change by providing op. mode id and <key:value> params map.

Actions

- Many manufacturers provide some automation tasks (e.g. approach tip).
- Can send these by providing **action** id and <key:value> **params** map.

Custom Messages

■ Any user may create custom messages or expand existing ones.

The End

Let us know what you think and help us make it better.

afspm on github