Experiment No. 8

Perform Web Spidering

AIM

To automatically crawl a target web application to discover all reachable pages, links, and resources using web spidering tools such as OWASP ZAP and Burp Suite Spider.

PROCEDURE

1. Configure the browser to route traffic through OWASP ZAP / Burp Suite proxy and set the target web application as the scope.
2. Open the target application's home page once in the browser so the tool records the starting point (seed URL).
3. In OWASP ZAP, right-click the target site in the Sites panel and select 'Attack > Spider' to begin automated crawling.
4. Allow the spider to recursively follow all discovered links, forms, and resources within the defined scope.
5. Monitor the Spider progress tab to track the number of URLs found, requests sent, and crawl depth.
6. Once the crawl completes, review the generated site tree/site map for all discovered pages, directories, and parameters.
7. Export the list of crawled URLs for use in subsequent vulnerability scanning.

SAMPLE OUTPUT

```
OWASP ZAP Spider started on: http://testapp.local
Progress: 100%   URLs found: 38   Requests made: 52

Discovered URLs (sample):
  http://testapp.local/
  http://testapp.local/about.php
  http://testapp.local/products.php?cat=1
  http://testapp.local/contact.php
  http://testapp.local/admin/login.php
  http://testapp.local/css/style.css
  http://testapp.local/js/main.js

Spider completed in 00:02:14. Site tree saved for vulnerability scan.
```

RESULT

Web spidering of the target application was successfully performed using OWASP ZAP, automatically discovering 38 URLs, including an unlinked admin login page, which forms the basis for further vulnerability assessment.