

MEMFILL

The MEMFILL statement converts a value to a specified type, then fills memory with that type including any non-whole remainder.

Syntax

```
MEMFILL memoryBlock, memoryBlock.OFFSET, fillBytes, value [AS variableType]
```

Parameters

- The *memoryBlock* MEM memory block is the block referenced to be filled.
- *memoryBlock.OFFSET* is the starting offset of the above referenced memory block.
- The *fillBytes* is the number of bytes to fill the memory block.
- The *value* is the value to place in the memory block at the designated OFFSET position.
- A literal or variable *value* can be optionally set AS a variable type appropriate for the memory block.

Description

- To clear previous data from a MEMNEW memory block, use MEMFILL with a *value* of 0.

Examples

Example: Filling array values quickly using FOR loops or a simple memory fill.

```
DIM a(100, 100) AS LONG  
DIM b(100, 100) AS LONG
```




Contents

- [Syntax](#)
- [Parameters](#)
- [Description](#)
- [Examples](#)
- [See also](#)

```
'filling array a with value 13
FOR i1 = 0 TO 100
    FOR i2 = 0 TO 100
        a(i1, i2) = 13
    NEXT
NEXT

'filling array b with value 13
DIM mema AS _MEM
mema = _MEM(b())
_MEMFILL mema, mema.OFFSET, mema.SIZE, 13 AS LONG
_MEMFREE mema
```

See also

-  [_MEM, _MEM \(function\)](#)
-  [_MEMIMAGE, _MEMNEW](#)
-  [_MEMGET, _MEMPUT](#)

Navigation:

[Main Page with Articles and Tutorials](#)

[Keyword Reference - Alphabetical](#)

[Keyword Reference - By usage](#)

Retrieved from "<https://qb64phoenix.com/qb64wiki/index.php?title=MEMFILL&oldid=6462>"

This page was last edited on 24 January 2023, at 02:05.