# Laboratory Session #03

Distributed Systems Programming

Daniele Bringhenti, Riccardo Sisto



### Socket API



- The **Socket API** represents the de-facto standard API for **accessing network** services provided by Internet layers 4-3-2.
- The main features of the Socket API are:
  - 1) procedural API
  - 2) **general** procedures rather than specific for a single protocol stack
    - > TCP/IP is a particular case
  - 3) **designed** with **TCP/IP** in mind
    - asymmetric connection model
    - > stream-oriented connections without message delimiters

Sockets used for TCP/IP are called **stream** sockets.

2 Laboratory Session #03

## Topics of the Laboratory Session



Laboratory Session #03 covers the following activities:



Implementation of a TCP/IP socket **server** application (in Java), which can perform **image conversion** 



Implementation of a TCP/IP socket **client** application (in Java), which requests an image conversion

#### Converter Service



#### Main characteristics of the *Converter* service:

- concurrent TCP server, listening to the TCP port number 2001;
- the server can establish TCP connections with multiple clients, and each request is managed by a different thread;
- it performs the media type conversion of image files;
- the media types supported are three: PNG, JPEG, and GIF.

#### Implementation tips:

- reuse the code for image conversion from Lab02;
- the ExecutorService framework provided by the JDK may simplify the execution of tasks in asynchronous mode.

4 Laboratory Session #03

### ConversionRequest client




#### Main characteristics of the *ConversionRequest* client:

- it interacts with the Converter service to perform the conversion of an image file;
- it **receives** three parameters from the **command line**:
  - 1) the **original** media type of the image file;
  - 2) the **target** media type to which the image file must be converted;
  - 3) the **path** of the image file in the local file system of the *ConversionRequest* client.
    - the path is relative to the ./image folder (where . is the current client directory)

### The Protocol: Messages exchanged on the TCP Connection






6 Laboratory Session #03 D. Bringhenti, R.Sisto

### The Protocol: Request from the client



#### The client sends to the server:

- three ASCII characters representing the original media type of the image file that must be converted ("PNG", "JPG" or "GIF");
- three ASCII characters representing the target media type for the conversion;
- a 4-byte 2's complement integer number in network byte order, representing the length in bytes of the image file;
- the bytes of the image file.




7 Laboratory Session #03 D. Bringhenti, R.Sisto

### The Protocol: Response from the server (I)



If there are no issues in receiving the client's message or in converting the image file, the server sends to the client:

- the ASCII character '0' representing the **successful outcome** of the operations;
- a 4-byte 2's complement integer number in network byte order, representing the length in bytes of the converted image file;
- the bytes of the converted image file.




### The Protocol: Response from the server (II)



If there are <u>issues</u> in receiving the client's message or in converting the image file, the server sends to the client:

- an ASCII character representing a number greater than 0 in case of unsuccessful outcome ('1' for a wrong request, '2' for internal error of the server);
- a 4-byte integer number in network byte order, representing the length in bytes of a string describing the error that occurred;
- the **bytes** of an ASCII string describing the error that occurred.



9 Laboratory Session #03 D. Bringhenti, R.Sisto

## Final tips



- Both the client and the server should use timeouts when waiting for input from the peer, in order to avoid deadlocks.
- Tips for testing the implementation:
  - try the conversion of files of different types;
  - try a conversion with a file of large size (e.g., 10MB) and check the efficiency;
  - run more clients concurrently and check how execution time varies;
  - test interoperability against the reference client and server;
  - try your client and server under erroneous conditions and fix any robustness problems.

10 Laboratory Session #03



# Thanks for your attention!

D. Bringhenti, R. Sisto daniele.bringhenti@polito.it riccardo.sisto@polito.it



